

## Matplotlib & Seaborn - 1

### Session Objectives:

- Understand what data visualization is and why it matters
- Use Matplotlib to plot different types of charts
- Customize plots with markers, colors, linewidth, and line styles
- Integrate Matplotlib with NumPy and Pandas
- Understand why Seaborn is important in visualization
- Recognize common Seaborn plot types

```
# Concatenate : pd.concat() -> Append Queries [Union / Union All]
# Stack [Axis = 0]
combined_df = pd.concat([customers,products],axis = 0) # Prefer to use Identical Table [Sales2015/16/17]
combined_df
```

0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male		1.0	Trailsway	Road	San Diego	Calif.
1	2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male		0.0	Trailsway	Road	El Paso	Tex.
2	3	Bambi	Westrip	bwestrip2@symantec.com	Female		4057.0	Arkansas	Circle	San Antonio	Tenn.
3	4	Roarke	Pankettman	rpankettman3@wiley.com	Male		74.0	Debs	Point	Memphis	Tenne.
4	5	Mikaela	Althorpe	malthorpe4@51.la	Male		0.0	2nd	Drive	Baltimore	Mary.
...	...	...	...	...	...	...	...	...	...	...	...
55	56	NaN	NaN		NaN	NaN	NaN	NaN	NaN	NaN	NaN

```
# Merging [Merge Query] [Joins] 'on' constraints -> [P.K , F.K] [how = 'inner','left','right']
inner_merge_df = pd.merge(customers,products,on='id',how='inner')
inner_merge_df
```

0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male		1.0	Trailsway	Road	San Diego	Calif.
1	2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male		0.0	Trailsway	Road	El Paso	Tex.
2	3	Bambi	Westrip	bwestrip2@symantec.com	Female		4057.0	Arkansas	Circle	San Antonio	Tenn.
3	4	Roarke	Pankettman	rpankettman3@wiley.com	Male		74.0	Debs	Point	Memphis	Tenne.
4	5	Mikaela	Althorpe	malthorpe4@51.la	Male		0.0	2nd	Drive	Baltimore	Mary.

```
left_merge_df = pd.merge(customers,products,on='id',how='left')
left_merge_df
```

	<b>id</b>	<b>first_name</b>	<b>last_name</b>		<b>email</b>	<b>gender</b>	<b>street_number</b>	<b>street_address</b>	<b>street_suffix</b>	
<b>0</b>	1	Romain	Southcott		rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road	San Diego
<b>1</b>	2	Cosimo	Molyneaux		cmolyneaux1@wiley.com	Male	0.0	Trailsway	Road	El Paso
<b>2</b>	3	Bambi	Westrip		bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle	San Antonio
<b>3</b>	4	Roarke	Pankettman		rpankettman3@wiley.com	Male	74.0	Debs	Point	Memphis

```
right_merge_df = pd.merge(customers,products,on='id',how='right') # Inner Join
right_merge_df
```

	<b>id</b>	<b>first_name</b>	<b>last_name</b>		<b>email</b>	<b>gender</b>	<b>street_number</b>	<b>street_address</b>	<b>street_suffix</b>	<b>city</b>
<b>0</b>	1	Romain	Southcott		rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road	San Diego
<b>1</b>	2	Cosimo	Molyneaux		cmolyneaux1@wiley.com	Male	0.0	Trailsway	Road	El Paso
<b>2</b>	3	Bambi	Westrip		bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle	San Antonio
<b>3</b>	4	Roarke	Pankettman		rpankettman3@wiley.com	Male	74.0	Debs	Point	Memphis
<b>4</b>	5	Mikaela	Althorpe		malthorpe4@51.la	Male	0.0	2nd	Drive	Baltimore

```
right_merge_df = pd.merge(customers,purchases,on='id',how='right')
right_merge_df
```

	<b>id</b>	<b>first_name</b>	<b>last_name</b>		<b>email</b>	<b>gender</b>	<b>street_number</b>	<b>street_address</b>	<b>street_suffix</b>	<b>city</b>
<b>0</b>	1	Romain	Southcott	rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road	San Diego	California
<b>1</b>	2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male	0.0	Trailsway	Road	El Paso	Texas
<b>2</b>	3	Bambi	Westrip	bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle	San Antonio	Texas
<b>3</b>	4	Roarke	Pankettman	rpankettman3@wiley.com	Male	74.0	Debs	Point	Memphis	Tennessee
<b>4</b>	5	Mikaela	Althorpe	malthorpe4@51.la	Male	0.0	2nd	Drive	Baltimore	Maryland
...	...	...	...	...	...	...	...	...	...	...
<b>5995</b>	5996	NaN	NaN		NaN	NaN	NaN	NaN	NaN	NaN
<b>5996</b>	5997	NaN	NaN		NaN	NaN	NaN	NaN	NaN	NaN
<b>5997</b>	5998	NaN	NaN		NaN	NaN	NaN	NaN	NaN	NaN
<b>5998</b>	5999	NaN	NaN		NaN	NaN	NaN	NaN	NaN	NaN
<b>5999</b>	6000	NaN	NaN		NaN	NaN	NaN	NaN	NaN	NaN

6000 rows × 16 columns

```
# Overlapping Columns Handles with Suffixes
Customer = pd.DataFrame(
    {
        'id' : [1,2,3],
        'name' : ['Shyam', 'Deepak', 'Rajat'],
        'product' : ['Book', 'Pen', 'NoteBook']
    }
)
Product = pd.DataFrame(
    {
        'id' : [2,3,4],
        'product' : ['Pen', 'NoteBook', 'Pencil'],
        'amount' : [10,25,15]
    }
)
Customer

```

	<b>id</b>	<b>name</b>	<b>product</b>
<b>0</b>	1	Shyam	Book
<b>1</b>	2	Deepak	Pen
<b>2</b>	3	Rajat	NoteBook

```
Product
```

	<b>id</b>	<b>product</b>	<b>amount</b>
<b>0</b>	2	Pen	10
<b>1</b>	3	NoteBook	25
<b>2</b>	4	Pencil	15

```
merge_df = pd.merge(Customer,Product,on='id',how='inner',suffixes=('_cust','_prod'))
merge_df
```

	<b>id</b>	<b>name</b>	<b>product_cust</b>	<b>product_prod</b>	<b>amount</b>
<b>0</b>	2	Deepak	Pen	Pen	10
<b>1</b>	3	Rajat	NoteBook	NoteBook	25

```
merge_df = pd.merge(Customer,Product,on='id',how='left',suffixes=('_cust','_prod'))
merge_df
```

	<b>id</b>	<b>name</b>	<b>product_cust</b>	<b>product_prod</b>	<b>amount</b>
<b>0</b>	1	Shyam	Book	NaN	NaN
<b>1</b>	2	Deepak	Pen	Pen	10.0
<b>2</b>	3	Rajat	NoteBook	NoteBook	25.0

```
merge_df = pd.merge(Customer,Product,on='id',how='right',suffixes=('_cust','_prod'))
merge_df
```

	<b>id</b>	<b>name</b>	<b>product_cust</b>	<b>product_prod</b>	<b>amount</b>
<b>0</b>	2	Deepak	Pen	Pen	10
<b>1</b>	3	Rajat	NoteBook	NoteBook	25
<b>2</b>	4	NaN	NaN	Pencil	15

```
# suffixes Default _x , _y
merge_df = pd.merge(Customer,Product,on='id',how='inner')
merge_df
```

	<b>id</b>	<b>name</b>	<b>product_x</b>	<b>product_y</b>	<b>amount</b>
<b>0</b>	2	Deepak	Pen	Pen	10
<b>1</b>	3	Rajat	NoteBook	NoteBook	25

```
# set_index
customers = customers.set_index('id')
customers.head()
```

	<b>first_name</b>	<b>last_name</b>		<b>email</b>	<b>gender</b>	<b>street_number</b>	<b>street_address</b>	<b>street_suffix</b>		<b>city</b>	<b>state</b>
<b>id</b>											
<b>1</b>	Romain	Southcott	rsouthcott0@clickbank.net	Male		1.0	Trailsway	Road	San Diego	California	
<b>2</b>	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male		0.0	Trailsway	Road	El Paso	Texas	
<b>3</b>	Bambi	Westrip	bwestrip2@symantec.com	Female		4057.0	Arkansas	Circle	San Antonio	Texas	
<b>4</b>	Roarke	Pankettman	rpankettman3@wiley.com	Male		74.0	Debs	Point	Memphis	Tennessee	
<b>5</b>	Mikaela	Althorpe	malthorpe4@51.la	Male		0.0	2nd	Drive	Baltimore	Maryland	

```
purchases = purchases.set_index('id')
purchases.head()
```

	<b>purch_date</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>
<b>1</b>	2019-01-03	823	27	12	568.92
<b>2</b>	2019-01-03	606	28	14	395.36

```
# Joining with Index
joined_df = customers.join(purchases)
joined_df
```

	first_name	last_name		email	gender	street_number	street_address	street_suffix	city
	id								
1	Romain	Southcott		rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road	San Diego
2	Cosimo	Molyneaux		cmolyneaux1@wiley.com	Male	0.0	Trailsway	Road	El Paso
3	Bambi	Westrip		bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle	San Antonio
4	Roarke	Pankettman		rpankettman3@wiley.com	Male	74.0	Debs	Point	Memphis
5	Mikaela	Althorpe		malthorpe4@51.la	Male	0.0	2nd	Drive	Baltimore
...	...	...		...	...	...	...	...	...
996	Merrili	Alman		malmanrn@cornell.edu	Female	0.0	Thompson	Way	Reading
997	Winonah	Heckle		whecklero@fc2.com	Female	701.0	Rowland	Hill	Indianapolis
998	Tobit	Birt		Unknown	Male	2.0	Basil	Road	Waterbury
999	Issiah	Standbrooke	istandbrookerq@yellowpages.com		Male	0.0	Kenwood	Drive	Savannah
1000	Elmore	Malpas		Unknown	Male	205.0	Farwell	Park	Atlanta

1000 rows × 15 columns

```
customers = customers.reset_index()
customers.head()
```

	index	id	first_name	last_name		email	gender	street_number	street_address	street_suffix	city
	0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road	San Diego	...
0	0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road	San Diego	...
1	1	2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male	0.0	Trailsway	Road	El Paso	...
2	2	3	Bambi	Westrip	bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle	San Antonio	...
3	3	4	Roarke	Pankettman	rpankettman3@wiley.com	Male	74.0	Debs	Point	Memphis	...
4	4	5	Mikaela	Althorpe	malthorpe4@51.la	Male	0.0	2nd	Drive	Baltimore	...

```
customers = customers.drop('index',axis = 1)
customers
```

	id	first_name	last_name		email	gender	street_number	street_address	street_suffix
	0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road
0	1	Romain	Southcott		rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road
1	2	Cosimo	Molyneaux		cmolyneaux1@wiley.com	Male	0.0	Trailsway	Road
2	3	Bambi	Westrip		bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle
3	4	Roarke	Pankettman		rpankettman3@wiley.com	Male	74.0	Debs	Point

```
purchases = purchases.reset_index()
purchases.head()
```

	<b>id</b>	<b>purch_date</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>
0	1	2019-01-03	823	27	12	568.92
1	2	2019-01-03	606	28	14	395.36
2	3	2019-01-03	955	9	17	510.17
3	4	2019-01-03	577	19	3	68.49
4	5	2019-01-03	429	8	18	759.42

```
# Joining with Index
joined_df = customers.set_index('id').join(purchases.set_index('id'))
joined_df
```

	<b>first_name</b>	<b>last_name</b>	<b>email</b>	<b>gender</b>	<b>street_number</b>	<b>street_address</b>	<b>street_suffix</b>	<b>city</b>	<b>state</b>
	<b>id</b>								
1	Romain	Southcott	rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road	San Diego	California
2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male	0.0	Trailsway	Road	El Paso	Texas
3	Bambi	Westrip	bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle	San Antonio	Texas
4	Roarke	Pankettman	rpankettman3@wiley.com	Male	74.0	Debs	Point	Memphis	Tennessee
5	Mikaela	Althorpe	malthorpe4@51.la	Male	0.0	2nd	Drive	Baltimore	Maryland
...	...	...	...	...	...	...	...	...	...
996	Merrili	Alman	malmanrn@cornell.edu	Female	0.0	Thompson	Way	Readii	...

```
customers.head()
```

	<b>id</b>	<b>first_name</b>	<b>last_name</b>	<b>email</b>	<b>gender</b>	<b>street_number</b>	<b>street_address</b>	<b>street_suffix</b>	<b>city</b>	<b>state</b>
	<b>id</b>									
0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male	1.0	Trailsway	Road	San Diego	California
1	2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male	0.0	Trailsway	Road	El Paso	Texas
2	3	Bambi	Westrip	bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle	San Antonio	Texas
3	4	Roarke	Pankettman	rpankettman3@wiley.com	Male	74.0	Debs	Point	Memphis	Tennessee
4	5	Mikaela	Althorpe	malthorpe4@51.la	Male	0.0	2nd	Drive	Baltimore	Maryland

```
# Drop_duplicates
unique_customers = customers.drop_duplicates(subset = 'first_name')
unique_customers
```

	<b>id</b>	<b>first_name</b>	<b>last_name</b>		<b>email</b>	<b>gender</b>	<b>street_number</b>	<b>street_address</b>	<b>street_suffix</b>	<b>city</b>
0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male		1.0	Trailsway	Road	San Diego
1	2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male		0.0	Trailsway	Road	El Paso
2	3	Bambi	Westrip	bwestrip2@symantec.com	Female		4057.0	Arkansas	Circle	San Antonio
3	4	Roarke	Pankettman	rpankettman3@wiley.com	Male		74.0	Debs	Point	Memphis
4	5	Mikaela	Althorpe	malthorpe4@51.la	Male		0.0	2nd	Drive	Baltimore
...	...	...	...	...	...	...	...	...	...	...
994	995	Brana	Dixon	bdixonrm@myspace.com	Female		97.0	Truax	Avenue	Maple Plain
995	996	Merrili	Alman	malmanrn@cornell.edu	Female		0.0	Thompson	Way	Reading P
996	997	Winonah	Heckle	whecklero@fc2.com	Female		701.0	Rowland	Hill	Indianapolis
997	998	Tobit	Birt		Unknown	Male	2.0	Basil	Road	Waterbury
999	1000	Elmore	Malpas		Unknown	Male	205.0	Farwell	Park	Atlanta

932 rows × 11 columns

```
# Drop_duplicates
unique_customers = customers.drop_duplicates(subset = 'last_name')
unique_customers
```

	<b>id</b>	<b>first_name</b>	<b>last_name</b>		<b>email</b>	<b>gender</b>	<b>street_number</b>	<b>street_address</b>	<b>street_suffix</b>	<b>city</b>
0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male		1.0	Trailsway	Road	San I
1	2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male		0.0	Trailsway	Road	El
2	3	Bambi	Westrip	bwestrip2@symantec.com	Female		4057.0	Arkansas	Circle	An
3	4	Roarke	Pankettman	rpankettman3@wiley.com	Male		74.0	Debs	Point	Mer
4	5	Mikaela	Althorpe	malthorpe4@51.la	Male		0.0	2nd	Drive	Balti
...	...	...	...	...	...	...	...	...	...	...
995	996	Merrili	Alman	malmanrn@cornell.edu	Female		0.0	Thompson	Way	Rea
996	997	Winonah	Heckle	whecklero@fc2.com	Female		701.0	Rowland	Hill	Indiana
997	998	Tobit	Birt		Unknown	Male	2.0	Basil	Road	Wate
998	999	Issiah	Standbrooke	istandbrookerq@yellowpages.com	Male		0.0	Kenwood	Drive	Sava
999	1000	Elmore	Malpas		Unknown	Male	205.0	Farwell	Park	Al

93 rows × 11 columns

0	1	Romain	Southcott	rsouthcott0@clickbank.net	Male	1.0	Trailway	Road	Sai
1	2	Cosimo	Molyneaux	cmolyneaux1@wiley.com	Male	0.0	Trailway	Road	
2	3	Bambi	Westrip	bwestrip2@symantec.com	Female	4057.0	Arkansas	Circle	
3	4	Roarke	Pankettman	rpankettman3@wiley.com	Male	74.0	Debs	Point	M
4	5	Mikaela	Althorpe	malthorpe4@51.la	Male	0.0	2nd	Drive	Ba
...	...	...	...	...	...	...	...	...	...
995	996	Merrili	Alman	malmanrn@cornell.edu	Female	0.0	Thompson	Way	F
996	997	Winonah	Heckle	whecklero@fc2.com	Female	701.0	Rowland	Hill	India
...	...	...	...	...	...	...	...	...	...

```
customers['first_name'].nunique()
```

```
932
```

```
customers['first_name'].value_counts().head(7)
```

first_name	count
Berty	4
Leland	3
Abel	3
Gunther	2
Silvain	2
Corry	2
Obediah	2

Name: count, dtype: int64

```
dropna(axis = 0) -> If at any cell a NaN Value exist -> Removes the complete row  

dropna(axis = 1) -> If at any cell a NaN Value exist -> Removes the complete column
```

```
# .interpolate() - [Linear , Polynomial , degree 2] = [0 2 4 _ 8 10 _ 14 _ 18]  

data = {  

    'index' : range(1,11), # [1,2,3....10]  

    'cost' : [100,200,150,None,250,None,350,None,450,600]  

}  

df = pd.DataFrame(data)  

df
```

	index	cost
0	1	100.0
1	2	200.0
2	3	150.0
3	4	NaN
4	5	250.0
5	6	NaN
6	7	350.0
7	8	NaN
8	9	450.0
9	10	600.0

	index	cost
0	1	100.0
1	2	200.0
2	3	150.0
3	4	250.0
4	5	350.0
5	6	450.0
6	7	600.0

	index
0	1
1	2
2	3
3	4
4	5
5	6
6	7
7	8
8	9
9	10

	index	cost
0	1	100.0
1	2	200.0
2	3	150.0
3	4	200.0
4	5	250.0
5	6	300.0
6	7	350.0
7	8	400.0
8	9	450.0
9	10	600.0

```
# .interpolate() - [Linear , Polynomial , degree 2] = [0 2 4 _ 8 10 _ 14 _ 18]
data = {
    'index' : range(1,11), # [1,2,3....10]
    'cost' : [100,200,150,None,250,None,350,None,450,600]
}
df = pd.DataFrame(data)
df['cost'] = df['cost'].interpolate(method = 'polynomial' , order = 2)
df
```

	index	cost
0	1	100.000000
1	2	200.000000
2	3	150.000000
3	4	175.893566
4	5	250.000000
5	6	306.989674
6	7	350.000000
7	8	382.168388
8	9	450.000000
9	10	600.000000

```
# Data Aggregations + GroupBy [SQL]
products['cost'].aggregate('max')
99.54

products['cost'].aggregate('mean')
55.15616666666664

products['cost'].aggregate('median')
57.78

products['cost'].aggregate('sum')
3309.37

products['cost'].aggregate(['max','min','sum','count','mean','median','std','var'])
```

	max	99.540000
	min	6.360000
	sum	3309.370000
	count	60.000000
	mean	55.156167
	median	57.780000
	std	27.552204
	var	759.123963
Name:	cost	dtype: float64

```
purchases['amount'].aggregate(['max','min','sum','count','mean','median','std','var']).round(2)
```

```
max      20.00
min      1.00
sum    63457.00
count   6000.00
mean     10.58
median    11.00
std       5.77
var      33.28
Name: amount, dtype: float64
```

```
purchases['paid'].aggregate(['max','min','sum','count','mean','median','std','var'])
```

```
max      1.990800e+03
min      3.630000e+00
sum    3.293228e+06
count   6.000000e+03
mean     5.488714e+02
median    4.227000e+02
std      4.442372e+02
var      1.973467e+05
Name: paid, dtype: float64
```

```
# GroupBY
company_cost_analysis = products.groupby('company')['cost'].sum().reset_index() # Series -> DataFrame
company_cost_analysis
```

	company	cost
0	Aibox	56.33
1	Babbleopia	63.98
2	Brainsphere	22.83
3	Browsezoom	82.10
4	Cogibox	102.27
5	Digitube	8.55
6	Dynabox	99.40
7	Dynazzy	85.74
8	Eare	87.39

```
type(company_cost_analysis)
```

```
pandas.core.frame.DataFrame
```

```
company_cost_analysis.sort_values(by = 'cost' , ascending = False).head(7)
```

	company	cost
19	Livepath	188.21
37	Skinder	159.85
34	Realcube	150.74
25	Ntag	121.17
40	Thoughtstorm	107.11
4	Cogibox	102.27
44	Vitz	100.84

```
products.groupby('company')['cost'].sum().nlargest(7).reset_index()
```

	company	cost
0	Livepath	188.21
1	Skinder	159.85
2	Realcube	150.74
3	Ntag	121.17
4	Thoughtstorm	107.11
5	Cogibox	102.27
6	Vitz	100.84

```
products.groupby('company')['cost'].sum().nsmallest(7).reset_index()
```

	company	cost
0	Skipfire	6.36
1	Digitube	8.55
2	Oloo	13.83
3	Quatz	13.83
4	Zoombox	16.27
5	Twitterworks	19.90
6	Zazio	20.53

```
# sort_values(by = ['col1','col2'] , ascending = [True,False] )
customers.sort_values(by = 'state' , ascending = False).head()
```

me	last_name		email	gender	street_number	street_address	street_suffix	city	state	postcode
ick	Gowthrop		Unknown	Male	0.0	Almo	Avenue	Springfield	Wisconsin	45505
etta	Leftwich	aleftwichdb@cafepress.com	Female		25.0	Vermont	Road	Milwaukee	Wisconsin	53234
erty	Meert	bmeertjr@hatena.ne.jp	Male		0.0	Lakeland	Drive	Milwaukee	Wisconsin	53215
Elle	Coultish	ecoultish8n@techcrunch.com	Female		88.0	Westerfield	Pass	Milwaukee	Wisconsin	53234
Julie	Gadault	pgadaultql@posterous.com	Female		2061.0	Aberg	Street	Milwaukee	Wisconsin	53285

```
products.sort_values(by='cost', ascending = False) # High to Low
```

	<b>id</b>	<b>product</b>	<b>cost</b>	<b>company</b>
33	34	Muffin Hinge Container 6	99.54	Skyble
13	14	Cookies Oatmeal Raisin	99.40	Dynabox
5	6	Wine - White, Riesling, Semi - Dry	99.22	Livepath
51	52	Soup - Knorr, Country Bean	98.74	Eimbee
34	35	Pie Box - Cello Window 2.5	95.68	Linkbuzz
31	32	Container Clear 8 Oz	92.33	Muxo
20	21	Bagel - Whole White Sesame	90.48	Realcube
9	10	Sambuca - Ramazzotti	88.99	Livepath
41	42	Sauce - Demi Glace	87.51	Wordware

```
purchases.sort_values(by = ['amount','paid'] , ascending = False).head(10) # Both Columns [High to Low]
```

	<b>id</b>	<b>purch_date</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>
211	212	2019-01-06		918	34	20 1990.8
2279	2280	2019-03-13		685	34	20 1990.8
4846	4847	2019-05-13		993	34	20 1990.8
2924	2925	2019-03-24		619	14	20 1988.0
3222	3223	2019-03-27		747	14	20 1988.0
4148	4149	2019-04-21		139	14	20 1988.0
697	698	2019-04-04		969	6	20 1984.4

```
purchases.sort_values(by = ['amount','paid'] , ascending = [False,True])  
# amount -> Descending , paid - Ascending
```

	<b>id</b>	<b>purch_date</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>
2422	2423	2019-03-16		690	1	20 63.60
5254	5255	2019-05-22		652	1	20 101.80
3388	3389	2019-03-29		155	1	20 127.20
3849	3850	2019-04-16		759	1	20 127.20
5849	5850	2019-06-17		113	1	20 127.20
...	...	...		...	...	...
5061	5062	2019-05-18		540	52	1 98.74
331	332	2019-02-05		418	6	1 99.22
5771	5772	2019-06-15		138	14	1 99.40
1301	1302	2019-07-06		450	34	1 99.54
5070	5071	2019-05-18		317	34	1 99.54

6000 rows x 6 columns

```
purchases.sort_values(by = ['amount','paid'] , ascending = [True,False])
# amount -> Ascending , paid - Descending
```

	<b>id</b>	<b>purch_date</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>
1301	1302	2019-07-06		450	34	1 99.54
5070	5071	2019-05-18		317	34	1 99.54
5771	5772	2019-06-15		138	14	1 99.40
331	332	2019-02-05		418	6	1 99.22
641	642	2019-03-06		519	52	1 98.74
...	...	...		...	...	...
3388	3389	2019-03-29		155	1	20 127.20
3849	3850	2019-04-16		759	1	20 127.20
5849	5850	2019-06-17		113	1	20 127.20
5254	5255	2019-05-22		652	1	20 101.80
2422	2423	2019-03-16		690	1	20 63.60

6000 rows × 6 columns

```
# calculated columns [DAX] (row context , filtering)
# Add Column [Power Query Editor] [Date column -> Extract [Year,month,days]]
purchases['year'] = purchases['purch_date'].dt.year
purchases['month'] = purchases['purch_date'].dt.month
purchases['item_price'] = purchases['paid'] / purchases['amount']
purchases
```

	<b>id</b>	<b>purch_date</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>	<b>year</b>	<b>month</b>	<b>item_price</b>
0	1	2019-01-03		823	27	12 568.92	2019	1	47.41
1	2	2019-01-03		606	28	14 395.36	2019	1	28.24
2	3	2019-01-03		955	9	17 510.17	2019	1	30.01
3	4	2019-01-03		577	19	3 68.49	2019	1	22.83
4	5	2019-01-03		429	8	18 759.42	2019	1	42.19
...	...	...		...	...	...	...	...	...
5995	5996	2019-06-20		893	33	5 411.10	2019	6	82.22
5996	5997	2019-06-20		566	23	11 178.97	2019	6	16.27
5997	5998	2019-06-20		114	19	9 205.47	2019	6	22.83
5998	5999	2019-06-20		404	11	20 429.40	2019	6	21.47
5999	6000	2019-06-20		88	57	4 274.52	2019	6	68.63

6000 rows × 9 columns

```
# argsort() in numpy -> idxmax()
products.idxmax()
```

<b>id</b>	59
<b>product</b>	5
<b>cost</b>	33
<b>company</b>	22
<b>dtype:</b>	int64

```

products.idxmax()['product'] # 5
5

products.loc[products.idxmax()['product']]

id                               6
product    Wine - White, Riesling, Semi - Dry
cost           99.22
company          Livepath
Name: 5, dtype: object

products.iloc[products.idxmax()['product']]

id                               6
product    Wine - White, Riesling, Semi - Dry
cost           99.22
company          Livepath
Name: 5, dtype: object

products.loc[[products.idxmax()['product']]] # DataFrame

  id      product   cost company
5  6  Wine - White, Riesling, Semi - Dry  99.22  Livepath

products.loc[[5]]

  id      product   cost company
5  6  Wine - White, Riesling, Semi - Dry  99.22  Livepath

```

```

products.loc[[products.idxmax()['cost']]] # DataFrame

  id      product   cost company
33 34  Muffin Hinge Container 6  99.54  Skyble

products.loc[[products.idxmax()['company']]] # DataFrame

  id      product   cost company
22 23  Puree - Blackcurrant 16.27  Zoombox

products.loc[5] # Series

id                               6
product    Wine - White, Riesling, Semi - Dry
cost           99.22
company          Livepath
Name: 5, dtype: object

products.loc[[5]] # DataFrame

  id      product   cost company
5  6  Wine - White, Riesling, Semi - Dry  99.22  Livepath

```

```
# Group BY + Aggregations
sorted_product = products.sort_values(by = ['cost'] , ascending = False)
sorted_product
```

	<b>id</b>	<b>product</b>	<b>cost</b>	<b>company</b>
33	34	Muffin Hinge Container 6	99.54	Skyble
13	14	Cookies Oatmeal Raisin	99.40	Dynabox
5	6	Wine - White, Riesling, Semi - Dry	99.22	Livepath
51	52	Soup - Knorr, Country Bean	98.74	Eimbee
34	35	Pie Box - Cello Window 2.5	95.68	Linkbuzz
31	32	Container Clear 8 Oz	92.33	Muxo
20	21	Bagel - Whole White Sesame	90.48	Realcube
9	10	Sambuca - Ramazzotti	88.99	Livepath
41	42	Sauce - Demi Glace	87.51	Wordware

```
sorted_product.groupby(['company'])['cost'].mean() # Series
```

company	cost
Aibox	56.330000
Babbleopia	63.980000
Brainsphere	22.830000
Browsezoom	41.050000
Cogibox	51.135000

```
sorted_product.groupby(['company'])['cost'].mean().reset_index() # DataFrame
```

	<b>company</b>	<b>cost</b>
0	Aibox	56.330000
1	Babbleopia	63.980000
2	Brainsphere	22.830000
3	Browsezoom	41.050000
4	Cogibox	51.135000
5	Digitube	8.550000
6	Dynabox	99.400000
7	Dynazzy	85.740000
8	Eare	87.390000

```
sorted_product.groupby(['company'])['cost'].mean().reset_index().sort_values(by = 'cost' , ascending = False)
```

	<b>company</b>	<b>cost</b>
39	Skyble	99.540000
6	Dynabox	99.400000
11	Eimbee	98.740000
18	Linkbuzz	95.680000

```
sorted_product.groupby(['company'])['cost'].mean().nlargest(10)
```

```
company
Skyble    99.540
Dynabox   99.400
Eimbee    98.740
Linkbuzz  95.680
Livepath  94.105
Muxo      92.330
Wordware  87.510
Eare      87.390
Trunyx    87.050
Dynazzy   85.740
Name: cost, dtype: float64
```

```
# Trend-Axis
purchases.set_index('purch_date')
```


	<b>id</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>	<b>year</b>	<b>month</b>	<b>item_price</b>
<b>purch_date</b>								
<b>2019-01-03</b>	1	823	27	12	568.92	2019	1	47.41
<b>2019-01-03</b>	2	606	28	14	395.36	2019	1	28.24
<b>2019-01-03</b>	3	955	9	17	510.17	2019	1	30.01
<b>2019-01-03</b>	4	577	19	3	68.49	2019	1	22.83
<b>2019-01-03</b>	5	429	8	18	759.42	2019	1	42.19
...	...	...	...	...	...	...	...	...
<b>2019-06-20</b>	5996	893	33	5	411.10	2019	6	82.22
<b>2019-06-20</b>	5997	566	23	11	178.97	2019	6	16.27

```
purchases.groupby('month')[['paid','amount']].sum()
```

	<b>paid</b>	<b>amount</b>
<b>month</b>		
<b>1</b>	139986.42	2643
<b>2</b>	83532.80	1713
<b>3</b>	890751.05	16752
<b>4</b>	715885.30	14268
<b>5</b>	550416.29	10537
<b>6</b>	271329.22	5457
<b>7</b>	112608.31	2063
<b>8</b>	118668.27	2291
<b>9</b>	94420.38	1962
<b>10</b>	92266.35	1695
<b>11</b>	111315.89	2044
<b>12</b>	112047.84	2032

```
purchases.groupby('month')[['paid','amount']].sum().plot.scatter('paid','amount')
```

```
<Axes: xlabel='paid', ylabel='amount'>
```



```
# .isin() -> In 'Membership Operators' [Boolean Results]  
company_list = ['Ntag','Skipfire','Vitz','Realcube','Zoombox']  
products[products['company'].isin(company_list)]
```

	<b>id</b>	<b>product</b>	<b>cost</b>	<b>company</b>
0	1	Liners - Baking Cups	6.36	Skipfire
2	3	Bar Bran Honey Nut	65.40	Ntag
14	15	Cookies Oatmeal Raisin	14.13	Vitz
15	16	Sausage - Chorizo	55.45	Vitz
20	21	Bagel - Whole White Sesame	90.48	Realcube
21	22	Scotch - Queen Anne	60.26	Realcube
22	23	Puree - Blackcurrant	16.27	Zoombox
23	24	Bread - Bagels, Plain	31.26	Vitz
30	31	Wine - Carmenere Casillero Del	55.77	Ntag

# .between() [Inclusive][Continuous Column] purchases[purchases['amount'].between(11,20)]										
	<b>id</b>	<b>purch_date</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>	<b>year</b>	<b>month</b>	<b>item_price</b>	
0	1	2019-01-03	823	27	12	568.92	2019	1	47.41	
1	2	2019-01-03	606	28	14	395.36	2019	1	28.24	
2	3	2019-01-03	955	9	17	510.17	2019	1	30.01	
4	5	2019-01-03	429	8	18	759.42	2019	1	42.19	
5	6	2019-01-03	275	36	18	176.76	2019	1	9.82	
...	...	...	...	...	...	...	...	...	...	...
5990	5991	2019-06-20	632	2	15	1286.10	2019	6	85.74	
5992	5993	2019-06-20	159	18	17	957.61	2019	6	56.33	
5994	5995	2019-06-20	840	23	18	292.86	2019	6	16.27	
5996	5997	2019-06-20	566	23	11	178.97	2019	6	16.27	
5998	5999	2019-06-20	404	11	20	429.40	2019	6	21.47	

3023 rows × 9 columns


# .between() [Inclusive][Continuous Column] # DatesBetween purchases[purchases['purch_date'].between('01-01-2019','31-03-2019')]										
	<b>id</b>	<b>purch_date</b>	<b>customer_num</b>	<b>product_num</b>	<b>amount</b>	<b>paid</b>	<b>year</b>	<b>month</b>	<b>item_price</b>	
0	1	2019-01-03	823	27	12	568.92	2019	1	47.41	
1	2	2019-01-03	606	28	14	395.36	2019	1	28.24	
2	3	2019-01-03	955	9	17	510.17	2019	1	30.01	
3	4	2019-01-03	577	19	3	68.49	2019	1	22.83	
4	5	2019-01-03	429	8	18	759.42	2019	1	42.19	
...	...	...	...	...	...	...	...	...	...	...
3633	3634	2019-03-31	128	56	17	279.14	2019	3	16.42	
3634	3635	2019-03-31	145	3	6	392.40	2019	3	65.40	
3635	3636	2019-03-31	224	25	8	589.60	2019	3	73.70	
3636	3637	2019-03-31	260	28	4	108.44	2019	3	27.11	
3637	3638	2019-03-31	846	42	16	1400.16	2019	3	87.51	

2010 rows × 9 columns

## pandas.pivot\_table #

```
pandas.pivot_table(data, values=None, index=None, columns=None,  
aggfunc='mean', fill_value=None, margins=False, dropna=True,  
margins_name='All', observed=True, sort=True,  
**kwargs)
```

[\[source\]](#)



## pandas.melt #

```
pandas.melt(frame, id_vars=None, value_vars=None, var_name=None,  
value_name='value', col_level=None, ignore_index=True) \[source\]
```

Unpivot a DataFrame from wide to long format, optionally leaving identifiers set.

```

# Pivot Table
data = {
    'Region' : ['North', 'East', 'East', 'West', 'West', 'North', 'East', 'East', 'West', 'North'],
    'Products' : ['Bikes', 'Clothings', 'Accessories', 'Components', 'Bikes', 'Clothings',
                  'Accessories', 'Components', 'Clothings', 'Accessories'],
    'Revenue' : [2000, 1000, 1500, 1000, 2500, 5000, 1500, 2000, 1000, 7000]
}
df = pd.DataFrame(data)
df

```

	Region	Products	Revenue
0	North	Bikes	2000
1	East	Clothings	1000
2	East	Accessories	1500
3	West	Components	1000
4	West	Bikes	2500
5	North	Clothings	5000
6	East	Accessories	1500
7	East	Components	2000
8	West	Clothings	1000
9	North	Accessories	7000

```

pivot_table = df.pivot_table(
    values='Revenue',
    index='Region',
    columns='Products',
    aggfunc = 'sum'
)
pivot_table

```

	Products	Accessories	Bikes	Clothings	Components
Region					
East	3000.0	NaN	1000.0	2000.0	
North	7000.0	2000.0	5000.0		NaN
West		NaN	2500.0	1000.0	1000.0

```

pivot_table = df.pivot_table(
    values='Revenue',
    index='Region',
    columns='Products',
    aggfunc = 'sum',
    fill_value = 0
)
pivot_table

```

Products	Accessories	Bikes	Clothings	Components
Region	East	North	West	
<b>Accessories</b>	3000	0	1000	2000
<b>Bikes</b>	7000	2000	5000	0
<b>Clothings</b>	0	2500	1000	1000
<b>Components</b>				

```
pivot_table = df.pivot_table(  
    values='Revenue',  
    index= 'Products',  
    columns='Region',  
    aggfunc = 'sum',  
    fill_value = 0  
)  
pivot_table
```

Region	East		North	West
Products	Accessories	Bikes	Clothings	Components
<b>Accessories</b>	3000	7000	0	
<b>Bikes</b>	0	2000	2500	
<b>Clothings</b>	1000	5000	1000	
<b>Components</b>	2000	0	1000	

```
filter_pivot = pivot_table[pivot_table.sum(axis=1) >= 7000]  
filter_pivot
```

Region	East	North	West
Products	Accessories	Bikes	Clothings
<b>Accessories</b>	3000	7000	0
<b>Clothings</b>	1000	5000	1000

```
# Observe the caller()  
pivot_table = pd.pivot_table(  
    data = df,  
    values='Revenue',  
    index='Region',  
    columns='Products',  
    aggfunc = 'sum',  
    fill_value = 0  
)  
pivot_table
```

Products	Accessories	Bikes	Clothings	Components
Region	East	North	West	
<b>Accessories</b>	3000	0	1000	2000
<b>Bikes</b>	7000	2000	5000	0
<b>Clothings</b>	0	2500	1000	1000
<b>Components</b>				

```
# Observe the caller()
pivot_table = pd.pivot_table(
    data = df,
    values='Revenue',
    index=['Region','Products'],
    aggfunc = 'sum',
)
pivot_table
```

### Revenue

Region	Products	Revenue
East	Accessories	3000
	Clothings	1000
	Components	2000
North	Accessories	7000
	Bikes	2000
	Clothings	5000
West	Bikes	2500
	Clothings	1000
	Components	1000

```
# Performing Pivot Table with Multiple Aggregations
pivot_table = pd.pivot_table(
    data = df,
    values='Revenue',
    index=['Region','Products'],
    aggfunc = [ 'sum','mean','median','max','min'],
)
pivot_table
```

	sum	mean	median	max	min
	Revenue	Revenue	Revenue	Revenue	Revenue

Region	Products	sum	mean	median	max	min
East	Accessories	3000	1500.0	1500.0	1500	1500
	Clothings	1000	1000.0	1000.0	1000	1000
	Components	2000	2000.0	2000.0	2000	2000
North	Accessories	7000	7000.0	7000.0	7000	7000
	Bikes	2000	2000.0	2000.0	2000	2000
	Clothings	5000	5000.0	5000.0	5000	5000
West	Bikes	2500	2500.0	2500.0	2500	2500
	Clothings	1000	1000.0	1000.0	1000	1000
	Components	1000	1000.0	1000.0	1000	1000

```

products_pivot = pd.pivot_table(
    data = products,
    values=['cost','id'],
    index=['company'],
    aggfunc = {'cost':'sum','id':'count'}
)
products_pivot

```

cost id

company		
<b>Aibox</b>	56.33	1
<b>Babbleopia</b>	63.98	1
<b>Brainsphere</b>	22.83	1
<b>Browserzoom</b>	82.10	2
<b>Cogibox</b>	102.27	2
<b>Digitube</b>	8.55	1
<b>Dynabox</b>	99.40	1
<b>Dynazzy</b>	85.74	1

```
type(products_pivot)
```

pandas.core.frame.DataFrame

```
products_pivot.sort_values(by = 'id' , ascending = False).head(7)
```

cost id

company		
<b>Skinder</b>	159.85	3
<b>Vitz</b>	100.84	3
<b>Ntag</b>	121.17	2
<b>Browserzoom</b>	82.10	2
<b>Cogibox</b>	102.27	2
<b>Livepath</b>	188.21	2
<b>Realcube</b>	150.74	2

```
# CrossTab
```

```
# Regions VS Products [Frequency]
```

```

data = {
    'Region' : ['North','East','East','West','West','North','East','East','West','North'],
    'Products' : ['Bikes','Clothings','Accessories','Components','Bikes','Clothings',
                 'Accessories','Components','Clothings','Accessories'],
    'Revenue' : [2000,1000,1500,1000,2500,5000,1500,2000,1000,7000]
}
df = pd.DataFrame(data)
df

```

	Region	Products	Revenue
0	North	Bikes	2000
1	East	Clothings	1000
2	East	Accessories	1500
3	West	Components	1000
4	West	Bikes	2500
5	North	Clothings	5000
6	East	Accessories	1500
7	East	Components	2000
8	West	Clothings	1000
9	North	Accessories	7000

```
# CrossTab
cross_tab = pd.crosstab(df['Region'],df['Products'])
cross_tab
```

	Products	Accessories	Bikes	Clothings	Components
Region					
East	2	0	1	1	
North	1	1	1	0	
West	0	1	1	1	

```
# Pivot Table -> 'Unpivot' Table
data = {
    'Region' : ['North','East','West'],
    'Bikes' : [2000,1500,1000],
    'Components' : [200,500,700],
    'Accessories' : [250,300,100],
    'Clothings' : [100,700,900]
}
df = pd.DataFrame(data)
df
```

	Region	Bikes	Components	Accessories	Clothings
0	North	2000	200	250	100
1	East	1500	500	300	700
2	West	1000	700	100	900

```
# Melting the .df -> to have more extended rows
# Unpivot Table
melted_df = pd.melt(
    df,
    id_vars='Region',
    value_vars=['Bikes','Components','Accessories','Clothings'],
    var_name='Products',
    value_name= 'Total Sales',
)
melted_df
```

	Region	Products	Total Sales
0	North	Bikes	2000
1	East	Bikes	1500
2	West	Bikes	1000
3	North	Components	200
4	East	Components	500
5	West	Components	700
6	North	Accessories	250
7	East	Accessories	300
8	West	Accessories	100
9	North	Clothings	100
10	East	Clothings	700
11	West	Clothings	900

