



PRODUCT DATA SHEET

PRODUCT	: FERMAID™ AF	
VERSION No.	: 1.1	DATE: 01-04-2018

Introduction:

Fermaid™ AF is a user friendly, Polydimethylsiloxane based product.

In the present scenario, where the distilleries are compelled to work under best of efficiencies due to competitive atmosphere in the industries, new technologies are most sought after.

Fermaid™ AF enables distilleries to increase the fermentation capacity by at least 10 % without any infrastructure investments.

Benefits:

- Increased fermentation capacity by 10% by reduced fermentation head space.
- Highly recommended for process intensification

Application Conditions:

- Fermaid™ AF is a very stable product that performs best under normal wort fermentation conditions of pH 3.5- 6.5 & temperatures of 10-100°C.
- Fermaid™ AF is effective at concentrations of 3-5 g per HL wort.
- Fermaid™ AF may be added in the fermentation tank. It should be added along with the feeding of seed into the fermentation tank. It may be added in the media used for scaling up the yeast culture. We strongly recommend this product to be used in the recycled yeast cultures.

Storage Conditions and Packaging:

Fermaid™ AF MUST BE STORED at temp. $25\pm 5^{\circ}\text{C}$ and $35\pm 5\%$ humid conditions

It is best used before 12 months from the date of manufacturing.

Fermaid™ AF is available in 25 kg HDPE drums.

All our products, conform to the standard FSSR, 2011 (The food safety and standard regulation, 2011 as amended by regulations, 2016)

FSSAI LICENSE NUMBER - 10015043001372

The information contained herein is true and accurate to the best of our knowledge and is offered in good faith. Recommendations are to be optimized at every stage since the conditions and method of use, are specific and beyond our control.