



PRODUCT DATA SHEET

PRODUCT	: SOLUBAID G	
VERSION No.	: 3.0	DATE: 01-12-2016

Introduction:

There is great emphasis on improving Grain Liquification efficiencies in the present scenario of the alcohol industry, which is looking at portable alcohol from varied grades & types of grains.

Solub Aid G improves the solubilization of starch at high temperature efficiencies.

Solub Aid G is a high temperature stable endo-amylase derived from a selected strain of Bacillus licheniformis. It is an extracellular enzyme which randomly hydrolyses alpha-1,4 bonds in amylose and amylopectins. Thus help in rapid reduction in wort viscosity & complete stabilization of grain starch.

Solub Aid G is a brown coloured liquid with specific gravity of 1.10 to 1.2gms/ml, which is water soluble.

Application Conditions:

•Optimum Parameter for jet cooking system using Solub Aid G is:

a) Slurry Preparation:

- i) Solub Aid G @:0.6-0.80kg per ton dry starch.
- ii) Free calcium: 70ppm.
- iii) pH: 6-7 %
- iv) DS: 20-30%.

b) Primary Liquefaction:

- i)Temperature:104-107 0C(219-225 0F)
- ii)Retention time:5 min
- iii) Flow rate as per the jet cooker specification.
- iv)Slurry pressure:50-70 psi
- v) Back pressure: 10-20 psi.

C) Secondary Liquefaction:

i) pH = 5.5 -7.5

ii) Iodine Staining: Light purple Brown.

iii) DE% = 16 – 20 in 90-120min

iv) % DS = 20-25%.

v) Temperature 900C-960C

Storage Conditions and Packaging:

SOLUB AID G MUST BE STORED at temp. 25±5°C and 35±5% humid conditions

It is best if used before 12months from date of manufacturing.

It is available in 25 kg HDPE cans.

All our products, conform to the standard FSSR, 2011 (The food safety and standard regulation, 2011 as amended by regulations, 2016)

The information contained herein is true and accurate to the best of our knowledge and is offered in good faith. Recommendations are to be optimized at every stage since the conditions and method of use, are specific and beyond our control.