



PRODUCT DATA SHEET

PRODUCT	:	FLOCAID® W
VERSION No.	:	1.0
		DATE: 29-11-2024

Introduction:

FlocAid® W promotes wine fining that accelerates the settling of the yeast cells, colloids, and tannins to the bottom of the wine tank. It provides a solution to reduce process costs, time and improves the quality of the wine.

Benefits:

- **FlocAid® W** can replace bentonite, gelatin and Poly Vinyl Pyrrolidone for fining of wine thus saving costs substantially.
- **FlocAid® W** helps in better compact sediment formation. Thus reduces the carryover of the cell and cell debris, and boosts filtration efficiencies and increases wine recovery.
- Reduces wine fining time by 66% thus improving productivity.
- It does not affect the sensory characteristics of the wine.

Application Conditions:

1. The recommended dose of **FlocAid® W** for wine fining is between 1.5-3.0 g/HL. 0.5 % w/v solution of FlocAid® W is prepared using distilled water or water with low hardness and temperature of 6-12 °C using agitator.
2. The following precautions must be taken to achieve the optimum performance:
 - a. The FlocAid® W solution must be used between 6-12 °C. No other ingredients should be added to the FlocAid® W.
 - b. We recommend the optimization of **FlocAid® W** on regular intervals. The procedure is available on request. The optimum addition rate will vary from one wine type to another.

Storage Conditions & Packaging:

FlocAid® W can remain stable for 12 months if stored at temp. 25±5°C and 35±5% humid conditions
It is available in 25kg packaging.

All our products, conform to the standard FSSR, 2011 (The food safety and standard regulation, 2011 as amended by regulations, 2016)

FSSAI LICENSE NUMBER - 10015043001372