

MIT WORLD PEACE UNIVERSITY

Computer Networks  
Second Year B. Tech, Semester 3

---

---

TCP SOCKET PROGRAMMING

---

---

PRACTICAL REPORT  
ASSIGNMENT 8

Prepared By  
Krishnaraj Thadesar  
Cyber Security and Forensics  
Batch A1, PA 20  
November 29, 2022

# Contents

<b>1</b>	<b>Aim and Objectives</b>	<b>1</b>
<b>2</b>	<b>Problem Statement</b>	<b>1</b>
<b>3</b>	<b>Platform</b>	<b>1</b>
<b>4</b>	<b>Code</b>	<b>1</b>
<b>5</b>	<b>Output</b>	<b>4</b>

## 1 Aim and Objectives

To understand Concept of TCP Socket programming.

## 2 Problem Statement

Write a C Program to implement TCP Socket Programming, and simulate a Chat Application using it.

## 3 Platform

**Operating System:** Arch Linux x86-64

**IDEs or Text Editors Used:** Visual Studio Code

**Programs Used:** Cisco Packet Tracer v6.0.1

## 4 Code

```
1 #include <stdio.h>
2 #include <netdb.h>
3 #include <netinet/in.h>
4 #include <stdlib.h>
5 #include <string.h>
6 #include <sys/socket.h>
7 #include <sys/types.h>
8 #include <unistd.h> // read(), write(), close()
9 #define MAX 80
10 #define PORT 8080
11 #define SA struct sockaddr
12
13 // Function designed for chat between client and server.
14 void func(int connfd)
15 {
16     char buff[MAX];
17     int n;
18     // infinite loop for chat
19     for (;;)
20     {
21         bzero(buff, MAX);
22
23         // read the message from client and copy it in buffer
24         read(connfd, buff, sizeof(buff));
25         // print buffer which contains the client contents
26         printf("From client: %s\t To client : ", buff);
27         bzero(buff, MAX);
28         n = 0;
29         // copy server message in the buffer
30         while ((buff[n++] = getchar()) != '\n')
31             ;
32
33         // and send that buffer to client
34         write(connfd, buff, sizeof(buff));
35
36         // if msg contains "Exit" then server exit and chat ended.
```

```
37     if (strcmp("exit", buff, 4) == 0)
38     {
39         printf("Server Exit...\n");
40         break;
41     }
42 }
43 }
44
45 // Driver function
46 int main()
47 {
48     int sockfd, connfd, len;
49     struct sockaddr_in servaddr, cli;
50
51     // socket create and verification
52     sockfd = socket(AF_INET, SOCK_STREAM, 0);
53     if (sockfd == -1)
54     {
55         printf("socket creation failed...\n");
56         exit(0);
57     }
58     else
59         printf("Socket successfully created..\n");
60     bzero(&servaddr, sizeof(servaddr));
61
62     // assign IP, PORT
63     servaddr.sin_family = AF_INET;
64     servaddr.sin_addr.s_addr = htonl(INADDR_ANY);
65     servaddr.sin_port = htons(PORT);
66
67     // Binding newly created socket to given IP and verification
68     if ((bind(sockfd, (SA *)&servaddr, sizeof(servaddr))) != 0)
69     {
70         printf("socket bind failed...\n");
71         exit(0);
72     }
73     else
74         printf("Socket successfully binded..\n");
75
76     // Now server is ready to listen and verification
77     if ((listen(sockfd, 5)) != 0)
78     {
79         printf("Listen failed...\n");
80         exit(0);
81     }
82     else
83         printf("Server listening..\n");
84     len = sizeof(cli);
85
86     // Accept the data packet from client and verification
87     connfd = accept(sockfd, (SA *)&cli, &len);
88     if (connfd < 0)
89     {
90         printf("server accept failed...\n");
91         exit(0);
92     }
93     else
94         printf("server accept the client...\n");
95 }
```

```
96 // Function for chatting between client and server
97 func(connfd);
98
99 // After chatting close the socket
100 close(sockfd);
101 }
```

Listing 1: Server

```
1 #include <arpa/inet.h> // inet_addr()
2 #include <netdb.h>
3 #include <stdio.h>
4 #include <stdlib.h>
5 #include <string.h>
6 #include <strings.h> // bzero()
7 #include <sys/socket.h>
8 #include <unistd.h> // read(), write(), close()
9 #define MAX 80
10 #define PORT 8080
11 #define SA struct sockaddr
12 void func(int sockfd)
13 {
14     char buff[MAX];
15     int n;
16     for (;;)
17     {
18         bzero(buff, sizeof(buff));
19         printf("Enter the string : ");
20         n = 0;
21         while ((buff[n++] = getchar()) != '\n')
22             ;
23         write(sockfd, buff, sizeof(buff));
24         bzero(buff, sizeof(buff));
25         read(sockfd, buff, sizeof(buff));
26         printf("From Server : %s", buff);
27         if ((strcmp(buff, "exit", 4)) == 0)
28         {
29             printf("Client Exit...\n");
30             break;
31         }
32     }
33 }
34
35 int main()
36 {
37     int sockfd, connfd;
38     struct sockaddr_in servaddr, cli;
39
40     // socket create and verification
41     sockfd = socket(AF_INET, SOCK_STREAM, 0);
42     if (sockfd == -1)
43     {
44         printf("socket creation failed...\n");
45         exit(0);
46     }
47     else
48         printf("Socket successfully created..\n");
49     bzero(&servaddr, sizeof(servaddr));
50 }
```

```
51 // assign IP, PORT
52 servaddr.sin_family = AF_INET;
53 servaddr.sin_addr.s_addr = inet_addr("127.0.0.1");
54 servaddr.sin_port = htons(PORT);
55
56 // connect the client socket to server socket
57 if (connect(sockfd, (SA *)&servaddr, sizeof(servaddr)) != 0)
58 {
59     printf("connection with the server failed...\n");
60     exit(0);
61 }
62 else
63     printf("connected to the server..\n");
64
65 // function for chat
66 func(sockfd);
67
68 // close the socket
69 close(sockfd);
70 }
```

Listing 2: Client

## 5 Output

SERVER

```
Socket successfully created..
Socket successfully binded..
Server listening..
server accept the client...
From client: something
    To client : hello bro
From client: hii
    To client : how are you?
From client: im doing good
    To client : me 2
From client: byee
    To client : byee
From client: exit
    To client : exit
Server Exit...
```

CLIENT

```
Socket successfully created..
connected to the server..
Enter the string : something
From Server : hello bro
Enter the string : hii
From Server : how are you?
```

```
Enter the string : im doing good
From Server : me 2
Enter the string : byee
From Server : byee
Enter the string : exit
From Server : exit
Client Exit...
```