

MIT WORLD PEACE UNIVERSITY

Computer Networks
Second Year B. Tech, Semester 3

CONFIGURATION OF A VIRTUAL LAN

PRACTICAL REPORT

Prepared By

Krishnaraj Thadesar
Cyber Security and Forensics
Batch A1, PA 20

November 20, 2022

Contents

1 Aim and Objectives

To Design and configure a virtual LAN using Packet Tracer and To understand the concept of VLAN and implement it using packet tracer.

2 Devices

2.1 Devices Used

1. 1 Generic Switch
2. 2 Switch 2960 with 24 LAN Ports
3. 6 Generic PCs
4. 4 Laptops

2.2 Device Info and IP Addresses

Subnet Mask: 255.255.255.0

| Name | Type | IP |
|---------|----------------|---------------|
| PC0 | PC | 192.168.10.1 |
| PC1 | PC | 192.168.10.2 |
| PC2 | PC | 192.168.10.3 |
| PC3 | PC | 192.168.10.4 |
| PC4 | PC | 192.168.10.5 |
| PC5 | PC | 192.168.10.6 |
| Laptop0 | Laptop | 192.168.10.7 |
| Laptop1 | Laptop | 192.168.10.8 |
| Laptop2 | Laptop | 192.168.10.9 |
| Laptop3 | Laptop | 192.168.10.10 |
| Switch0 | 2950-24 Switch | None |
| Switch1 | 2950-24 Switch | None |
| Switch2 | Generic Switch | None |

3 Cables

1. Straight LAN Cable to connect unlike Devices
2. Crossover LAN Cable to connect like Devices

4 Procedure to Configure LAN

1. All 3 switches are connected with each other using crossover cables, as they are similar.
2. 4 PCs are connected to The first Switch
3. 4 Laptops are connected to the Second switch

4. 2 More computers are connected to another Switch.
5. Check the connection by opening the command prompt, and entering the commands `ipconfig`, and pinging the other computers.

5 Commands

1. `ipconfig`:

In Windows, `ipconfig` is a console application designed to run from the Windows command prompt. This utility allows you to get the IP address information of a Windows computer. It also allows some control over your network adapters, IP addresses (DHCP-assigned specifically), even your DNS cache. `Ipconfig` replaced the older `winipcfg` utility.

2. `ping <ip addr>`:

The `ping` command is a Command Prompt command used to test the ability of the source computer to reach a specified destination computer. It's a simple way to verify that a computer can communicate with another computer or network device.

The `ping` command operates by sending Internet Control Message Protocol (ICMP) Echo Request messages to the destination computer and waiting for a response. The two major pieces of information that the `ping` command provides are how many of those responses are returned and how long it takes for them to return.

6 Platform

Operating System: Arch Linux x86-64

IDEs or Text Editors Used: Visual Studio Code

Programs Used: Cisco Packet Tracer v6.0.1

7 Output

```
1 FastEthernet0 Connection:(default port)
2
3 Link-local IPv6 Address.....: FE80::201:C9FF:FEE6:3985
4 IP Address.....: 192.168.1.1
5 Subnet Mask.....: 255.255.255.0
6 Default Gateway.....: 0.0.0.0
7
8 PC>ping 192.168.1.2
9
10 Pinging 192.168.1.2 with 32 bytes of data:
11
12 Reply from 192.168.1.2: bytes=32 time=1ms TTL=128
13 Reply from 192.168.1.2: bytes=32 time=17ms TTL=128
14 Reply from 192.168.1.2: bytes=32 time=0ms TTL=128
15 Reply from 192.168.1.2: bytes=32 time=0ms TTL=128
16
17 Ping statistics for 192.168.1.2:
18   Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
19   Approximate round trip times in milli-seconds:
20     Minimum = 0ms, Maximum = 17ms, Average = 4ms
```

8 Connection Screenshot

Screenshots/Assignment_2_screenshot.png

9 Conclusion

A local area network was successfully created, deployed and tested on a simulator. The concept behind the Local area network was understood in detail. The various types of cables used to connect the devices were also used and explained. Commands to test computers on a network were also executed successfully. Various computers can be connected with each other and communicate seamlessly with the help of switches, Network Interface Cards, Computers and Straight as well as twisted Ethernet Cables. in a local area network.