

MIT WORLD PEACE UNIVERSITY

Object Oriented Programming with Java and C++
Second Year B. Tech, Semester 1

UNDERSTANDING AND IMPLEMENTATION OF
EXCEPTION HANDLING CONCEPTS IN C++ AND
JAVA.

PRACTICAL REPORT

Prepared By

Krishnaraj Thadesar
Cyber Security and Forensics
Batch A2, PA 20

October 6, 2022

Contents

1	Aim and Objectives	1
2	Problem Statements	1
2.1	Problem 1 in C++	1
2.2	Problem 2 in Java	1
2.3	Problem 3 in Java	2
2.4	Problem 4 in Java	2
3	Theory	2
3.1	Exception Handling	2
3.2	Try Throw Catch Block	2
3.3	Catch All	2
3.4	Rethrowing Exceptions	2
4	Platform	2
5	Input	2
6	Output	3
7	Code	3
7.1	C++ Implementation of Problem A	3
7.1.1	C++ Output	5
7.2	Java Implementation of Problem B	6
7.2.1	Java Output	7
7.3	Java Implementation of Problem C	8
7.3.1	Java Output	9
7.4	Java Implementation of Problem D	9
7.4.1	Java Output	11
8	Conclusion	12
9	FAQs	13

1 Aim and Objectives

Implementation and Understanding of Exception handling in Java and C++, and to learn and use the exception handling mechanisms with try and catch blocks.

2 Problem Statements

2.1 Problem 1 in C++

Define a class Employee consisting following:

Data Members

1. Employee ID
2. Name of Employee
3. Age
4. Income
5. City
6. Vehicle

Member Functions

1. To assign initial values.
2. To display.

Accept Employee ID, Name, Age, Income, City and Vehicle from the user. Create an exception to check the following conditions and throw an exception if the condition does not meet.

- Employee age between 18 and 55
- Employee income between Rs. 50,000 - Rs. 1,00,000 per month
- Employee staying in Pune/ Mumbai/ Bangalore / Chennai
- Employee having 4-wheeler

2.2 Problem 2 in Java

Implement the program to handle the arithmetic exception, `ArrayIndexOutOfBoundsException`. The user enters the two numbers: `n1`, `n2`. The division of `n1` and `n2` is displayed. If `n1`, `n2` are not integers then program will throw number format exception. If `n2` is zero the program will throw Arithmetic exception.

2.3 Problem 3 in Java

Validate the employee record with custom exception Create a class employee with attributes eid, name, age and department. Initialize values through parameterized constructor. If age of employee is not in between 25 and 60 then generate user-defined exception "AgeNotWithinRangeException". If name contains numbers or special symbols raise exception "NameNotValidException". Define the two exception classes.

2.4 Problem 4 in Java

Write a menu-driven program for banking system which accept the personal data for Customer(cid, cname, amount). Implement the user-defined/standard exceptions, wherever required to handle the following situations:

1. Account should be created with minimum amount of 1000 Rs.
2. For withdrawal of amount, if withdrawal Amount is greater than the Amount in the Account.
3. Customer Id should be between 1 and 20 only.
4. Entered amount should be positive.

3 Theory

3.1 Exception Handling

3.2 Try Throw Catch Block

3.3 Catch All

3.4 Rethrowing Exceptions

4 Platform

Operating System: Arch Linux x86-64

IDEs or Text Editors Used: Visual Studio Code

Compilers : g++ and gcc on linux for C++, and javac, with JDK 18.0.2 for Java

5 Input

For C++

1. Number of Each Type of Employee
2. Name, Age, Address City, and Salary of Each Employee

For Java

1. The Side of the Square
2. The Radius of the Circle
3. The Length and Breadth of the Rectangle.

6 Output

For C++

1. General Information about Each Employee
2. The Weekly, hourly and commisioned Salary for Respective Employees.

For Java

1. The Area of the Shapes
2. The Location of the Hill Stations
3. The Reason the Hill stations are Famous for.

7 Code

7.1 C++ Implementation of Problem A

```
1 #include <iostream>
2 #include <string.h>
3 using namespace std;
4
5 class Employee
6 {
7 public:
8     int emp_id, age, income;
9     string name, city;
10    bool has_vehicle, data_entered_correctly;
11
12    Employee()
13    {
14        emp_id = 1;
15        age = 30;
16        income = 10000;
17        name = "William";
18        city = "Pune";
19        has_vehicle = true;
20        cout << "The default values are: " << endl;
21        data_entered_correctly = true;
22        display();
23    }
24
25    int accept()
26    {
27
28        cout << "Enter the information of the new Employee : " << endl;
29        cout << "Enter the Employee ID: " << endl;
30        cin >> emp_id;
31        cout << "Enter the Employee Name: " << endl;
32        cin >> name;
33        age:
34        cout << "Enter the Employee Age: " << endl;
35        try
36        {
```

```
37         cin >> age;
38         if (age <= 18 || age >= 55)
39         {
40             throw age;
41         }
42     }
43     catch (int e)
44     {
45         cout << "Exception Caught!, Age is not in the valid limit. " << endl;
46         data_entered_correctly = false;
47         goto age;
48     }
49 salary:
50     cout << "Enter the Employee basic Salary: " << endl;
51     try
52     {
53         cin >> income;
54         if (income <= 50000 || income >= 100000)
55         {
56             throw 'a';
57         }
58     }
59     catch (char e)
60     {
61         cout << "Exception Caught!, Income is not in the valid limit. " <<
endl;
62         data_entered_correctly = false;
63         goto salary;
64     }
65 city:
66     cout << "Enter the Employee Address City: " << endl;
67     try
68     {
69         cin >> city;
70         if (city != "Mumbai" && city != "Pune" && city != "Bangalore")
71         {
72             throw 1.1;
73         }
74     }
75     catch (double e)
76     {
77         cout << "Exception Caught!, City Entered Incorrectly " << endl;
78         data_entered_correctly = false;
79         goto city;
80     }
81 vehicle:
82     cout << "Does the Employee have a vehicle? (Y, N) " << endl;
83     try
84     {
85         char inp;
86         cin >> inp;
87         if (inp != 'Y')
88         {
89             throw has_vehicle;
90         }
91     }
92     catch (bool e)
93     {
94         cout << "Exception Caught!, You must have a vehicle!" << endl;
```

```
95         data_entered_correctly = false;
96         goto vehicle;
97     }
98     data_entered_correctly = true;
99     return 0;
100 }
101
102 void display()
103 {
104     if (data_entered_correctly)
105     {
106         cout << "Employee ID is : " << emp_id << endl;
107         cout << "Employee Name: " << name << endl;
108         cout << "Employee Age: " << age << endl;
109         cout << "Employee Income : " << income << endl;
110         cout << "Employee Address City: " << city << endl;
111         cout << "Does Employee have a vehicle? : " << has_vehicle << endl;
112     }
113     else
114     {
115         cout << "You didnt enter the Data Correctly" << endl;
116     }
117 }
118 };
119
120 int main()
121 {
122     cout << "Welcome to Assignment 4: Error Safe Employee Data Input Program" <<
endl;
123     Employee obj;
124     obj.accept();
125     obj.display();
126     if (!obj.data_entered_correctly)
127     {
128         cout << "Please Try again";
129     }
130     else
131     {
132         cout << "You have entered the data correctly! " << endl;
133     }
134     return 0;
135 }
```

Listing 1: Main.Cpp

7.1.1 C++ Output

```
1 Welcome to Assignment 4: Error Safe Employee Data Input Program
2 The default values are:
3 Employee ID is : 1
4 Employee Name: William
5 Employee Age: 30
6 Employee Income : 10000
7 Employee Address City: Pune
8 Does Employee have a vehicle? : 1
9 Enter the information of the new Employee :
10 Enter the Employee ID:
11 1
12 Enter the Employee Name:
```

```
13 Mike
14 Enter the Employee Age:
15 400
16 Exception Caught!, Age is not in the valid limit.
17 Enter the Employee Age:
18 2000
19 Exception Caught!, Age is not in the valid limit.
20 Enter the Employee Age:
21 40
22 Enter the Employee basic Salary:
23 1
24 Exception Caught!, Income is not in the valid limit.
25 Enter the Employee basic Salary:
26 5000
27 Exception Caught!, Income is not in the valid limit.
28 Enter the Employee basic Salary:
29 100000
30 Exception Caught!, Income is not in the valid limit.
31 Enter the Employee basic Salary:
32 60000
33 Enter the Employee Address City:
34 Mumbai
35 Does the Employee have a vehicle? (Y, N)
36 n
37 Exception Caught!, You must have a vehicle!
38 Does the Employee have a vehicle? (Y, N)
39 Y
40 Employee ID is : 1
41 Employee Name: Mike
42 Employee Age: 40
43 Employee Income : 60000
44 Employee Address City: Mumbai
45 Does Employee have a vehicle? : 1
46 You have entered the data correctly!
```

Listing 2: Output for Problem 1

7.2 Java Implementation of Problem B

```
1 package assignment_4;
2
3 import java.util.InputMismatchException;
4 import java.util.Scanner;
5
6 // Implement the program to handle the arithmetic exception, ArrayIndexOutOfBoundsException
7 // The user enters the two numbers: n1, n2. The division of n1 and n2 is displayed
8 // . If n1, n2
9 // are not integers then program will throw number format exception. If n2 is zero
10 // the
11 // program will throw Arithmetic exception.
12
13 // class NumberFormatException extends Exception
14 // {
15 //     public NumberFormatException(String s)
16 //     {
17 //         super(s);
18 //     }
19 }
```



```
18 //      @Override
19 //      public String getMessage()
20 //      {
21 //          return "What is this";
22 //      }
23 // }
24
25 public class Division {
26     int n1;
27     int n2;
28     int ans;
29     Scanner input = new Scanner(System.in);
30
31     void accept() {
32         System.out.println("Enter the Numbers that you want to divide. ");
33         try {
34             n1 = input.nextInt();
35             n2 = input.nextInt();
36         } catch (InputMismatchException e) {
37             System.out.println("Number Format Exception, the format you entered
38 does not match. ");
39         }
40
41     int divide() {
42         try {
43             ans = n1 / n2;
44         } catch (ArithmeticException e) {
45             System.out.println("Exception Caught! Cant divide by Zero!");
46         }
47         return ans;
48     }
49 }
50 }
```

Listing 3: Full Time Employee.java

7.2.1 Java Output

```
1
2 Enter the Employee ID:
3 1001
4 Enter the Employee Name
5 William
6 Enter the Employee Age:
7 1
8 Age not within range
9 Age is not within the correct range.
10
11
12 Enter the Employee ID:
13 1
14 Enter the Employee Name
15 William
16 Enter the Employee Age:
17 35
18 Enter the Employee Department:
19 Sales
20 Employee ID is : 1
```

```
21 Employee Name: William
22 Employee Age: 35
23 Employee Department: Sales
```

Listing 4: Output for Problem 2

7.3 Java Implementation of Problem C

```
1 package assignment_4;
2
3 import java.util.Scanner;
4
5 // Validate the employee record with custom exception
6 // Create a class employee with attributes eid, name, age and department.
7 // Initialize values through parameterized constructor. If age of employee is not
  in between
8 // 25 and 60 then generate user-defined exception "AgeNotWithinRangeException". If
9 // name contains numbers or special symbols raise exception "NameNotValidException
  ".
10 // Define the two exception classes.
11
12 class AgeNotWithinRangeException extends Exception {
13     public AgeNotWithinRangeException(int s) {
14         // super(s);
15         System.out.println("Age not within range");
16     }
17
18     @Override
19     public String getMessage() {
20         return "Incorrect Age!";
21     }
22 }
23
24 class NameNotValidException extends Exception {
25     public NameNotValidException(String s) {
26         // super(s);
27     }
28 }
29
30 public class Employee {
31     Scanner input = new Scanner(System.in);
32     int e_id, age;
33     String name, department;
34
35     int accept() {
36         String specialCharactersString = "1234567890!@#%&*()'+,-./:;<=>?[]^_`{|}";
37
38         try {
39             System.out.println("Enter the Employee ID: ");
40             e_id = input.nextInt();
41             System.out.println("Enter the Employee Name");
42             name = input.next();
43
44             for (int i = 0; i < name.length(); i++) {
45                 char ch = name.charAt(i);
46                 if (specialCharactersString.contains(Character.toString(ch))) {
47                     System.out.println(name + " contains special character");
48                     throw new NameNotValidException(name);
49                 }
50             }
51         } catch (NameNotValidException e) {
52             System.out.println(e.getMessage());
53         }
54     }
55 }
```

```
49     }
50     System.out.println("Enter the Employee Age: ");
51     age = input.nextInt();
52     if (age > 60 || age < 25) {
53         throw new AgeNotWithinRangeException(age);
54     }
55     System.out.println("Enter the Employee Department: ");
56     department = input.next();
57
58     } catch (AgeNotWithinRangeException e) {
59         System.out.println("Age is not within the correct range.");
60         return -1;
61     } catch (NameNotValidException e) {
62         System.out.println("Name not Valid");
63         return -1;
64     }
65     return 0;
66 }
67
68 void display() {
69     System.out.println("Employee ID is : " + e_id);
70     System.out.println("Employee Name: " + name);
71     System.out.println("Employee Age: " + age);
72     System.out.println("Employee Department: " + department);
73 }
74
75 }
```

Listing 5: HillStation

7.3.1 Java Output

```
1
2 Enter the Employee ID:
3 1001
4 Enter the Employee Name
5 William
6 Enter the Employee Age:
7 1
8 Age not within range
9 Age is not within the correct range.
10
11
12 Enter the Employee ID:
13 1
14 Enter the Employee Name
15 William
16 Enter the Employee Age:
17 35
18 Enter the Employee Department:
19 Sales
20 Employee ID is : 1
21 Employee Name: William
22 Employee Age: 35
23 Employee Department: Sales
```

Listing 6: Output for Problem 3

7.4 Java Implementation of Problem D

```
1 package assignment_4;
2
3 import java.util.*;
4
5 public class Bank {
6     public int minimum_sal;
7     public int withdrawal_amt;
8     public int amount;
9     public int c_id;
10    Scanner input = new Scanner(System.in);
11
12    public int accept() {
13        System.out.println("Enter the customer id: ");
14        try {
15            c_id = input.nextInt();
16            if (c_id > 20 || c_id < 0) {
17                throw new Exception("wrong cust id");
18            }
19        } catch (Exception e) {
20            System.out.println("Wrong customer id");
21            return 0;
22        }
23
24        System.out.println("Enter the Amount in your Account: ");
25        try {
26            amount = input.nextInt();
27            if (amount < 1000) {
28                throw new Exception("Amount less than mimimum");
29            }
30        } catch (Exception e) {
31            System.out.println("Mimimum amount cant be less than 1000. ");
32            return 0;
33        }
34
35        System.out.println("Enter the Withdrawal Amount: ");
36        try {
37            withdrawal_amt = input.nextInt();
38            if (withdrawal_amt > amount) {
39                throw new Exception("Withdrawal amount more than amount. ");
40            } else {
41                amount -= withdrawal_amt;
42            }
43        } catch (Exception e) {
44            System.out.println("Withdrawal Amount more than amount in bank. ");
45            return 0;
46        }
47
48        return 1;
49    }
50
51    public void display() {
52        System.out.println("\n\nThe Customer ID is: ");
53        System.out.println(c_id);
54        System.out.println("The Amount in the Bank Before Withdrawing was: ");
55        System.out.println(amount + withdrawal_amt);
56        System.out.println("The Withdrawal Amount is: ");
57        System.out.println(withdrawal_amt);
58        System.out.println("The Amount Remaining in Bank is: ");
59        System.out.println(amount);
```

```
60     }  
61 }
```

Listing 7: HillStation

```
1 package assignment_4;  
2  
3 public class Main {  
4  
5     public static void program_3() {  
6         Bank obj = new Bank();  
7         if (obj.accept() == 1) {  
8             System.out.println("Data entered Correctly!");  
9             obj.display();  
10        } else {  
11            System.out.println("Data entered Incorrectly!");  
12        }  
13    }  
14  
15    public static void program_2() {  
16        Division d = new Division();  
17        d.accept();  
18        System.out.println("Dividing the inputs: ");  
19        System.out.println(d.divide());  
20    }  
21  
22  
23    public static void program_1() {  
24  
25        Employee obj = new Employee();  
26        if (obj.accept() >= 0) {  
27            obj.display();  
28        }  
29    }  
30  
31    public static void main(String args[]) {  
32  
33        // program_1();  
34        program_2();  
35        program_3();  
36    }  
37 }  
38 }
```

Listing 8: HillStation

7.4.1 Java Output

```
1 Enter the customer id:  
2 1001  
3 Wrong customer id  
4 Data entered Incorrectly!  
5  
6 Enter the customer id:  
7 1  
8 Enter the Amount in your Account:  
9 5000  
10 Enter the Withdrawal Amount:  
11 3000
```

```
12 Data entered Correctly!
13
14
15 The Customer ID is:
16 1
17 The Amount in the Bank Before Withdrawing was:
18 5000
19 The Withdrawal Amount is:
20 3000
21 The Amount Remaining in Bank is:
22 2000
23 krishnaraj@
```

Listing 9: Main.java

8 Conclusion

Thus, learned to use polymorphism and implemented solution of the given problem statement using C++ and Java.

9 FAQs

1. Why do we use Exception Handling mechanism?

Exception handling is the process of responding to unwanted or unexpected events when a computer program runs. Exception handling deals with these events to avoid the program or system crashing, and without this process, exceptions would disrupt the normal operation of a program.

- (a) It helps you avoid the program from crashing
- (b) It helps you set the program control in a more detailed manner
- (c) It helps you manually stop the program safely according to your wish.

```
// Psudo code for exception handling
int a;
try
{
    cin>> a;
    cout<<33/a; // if a is 0, Exception is thrown, program crashes.
}
catch DivisionByZeroException as e
{
    cout<<"cant divide by zero;
}
```

2. Is it possible to use multiple catch for single throw? Explain?

Yes, it is possible to use multiple catch statements for a single throw statement in both C++ and Java. C++ try and catch block works in a specific way, where the throw keyword throws an exception with an integer, or an exception. You can then write multiple catch statements just below the try block.

In Java, you can throw instances of the Exception class, or throw any of the pre defined exceptions in java.

Example

```
1      int a;
2      try
3      {
4          cin>> a;
5          if(a == 0)
6          {
7              throw a; // int is being thrown.
8          }
9          else{
10             cout<<33/a;
11             throw 'a'; // character is being thrown.
12         }
13     }
14     catch (int a)
15     {
16         cout<<"cant divide by zero;
17     }
18     catch (char a)
```

```
19 {
20     cout<<"A is not zero";
21 }
22
1
2     try {
3         withdrawal_amt = input.nextInt();
4         if (withdrawal_amt > amount) {
5             throw new Exception("Withdrawal amount more than amount. ");
6         } else {
7             new_amount = withdrawal_amt / amount;
8             amount -= withdrawal_amt;
9         }
10    } catch (Exception e) {
11        System.out.println("Withdrawal Amount more than amount in bank. ")
12    ;
13        return 0;
14    } catch (DivisionByZeroException d)
15    {
16        System.out.println(d);
17    }
```

3. What is Exception Specification?

An exception specification is a contract between the function and the rest of the program. It is a guarantee that the function will not throw any exception not listed in its exception specification.

```
1     void f1(void) throw(int) {
2         printf_s("About to throw 1\n");
3         if (1)
4             throw 1;
5     }
6
1     void function_name() throw(Exception)
2     {
3         if (error)
4         {
5             throw Exception("Error");
6         }
7     }
8
```

4. What is Re-throwing Exception?

If a catch block cannot handle the exception that it was designed to handle, then you can rethrow that exception from that catch block. It causes the original exception to be rethrown.

Because the exception has already been caught at the scope in which the rethrow expression occurs, it is rethrown out to the next dynamically enclosing try block. Therefore, it cannot be handled by catch blocks at the scope in which the rethrow expression occurred. Any catch blocks for the dynamically enclosing try block have an opportunity to catch the exception.

```
1     void f() {
2         try {
3             cout << "In try block of f()" << endl;
4             cout << "Throwing exception of type E1" << endl;
```



```
5      E1 myException;  
6      throw myException;  
7  }  
8  catch (E2& e) {  
9      cout << "In handler of f(), catch (E2& e)" << endl;  
10     cout << "Exception: " << e.message << endl;  
11     throw;  
12 }  
13 catch (E1& e) {  
14     cout << "In handler of f(), catch (E1& e)" << endl;  
15     cout << "Exception: " << e.message << endl;  
16     throw;  
17 }  
18 }  
19  
20
```

5. Explain use of finally keyword in java.

Java finally block is a block used to execute important code such as closing the connection, etc.

Java finally block is always executed whether an exception is handled or not. Therefore, it contains all the necessary statements that need to be printed regardless of the exception occurs or not.

The finally block follows the try-catch block.

```
1  class TestFinallyBlock {  
2      public static void main(String args[]){  
3          try{  
4              //below code do not throw any exception  
5              int data=25/5;  
6              System.out.println(data);  
7          }  
8          //catch won't be executed  
9          catch(NullPointerException e){  
10             System.out.println(e);  
11         }  
12         //executed regardless of exception occurred or not  
13         finally {  
14             System.out.println("finally block is always executed");  
15         }  
16     }  
17 }
```