Tel: +86-18157453060 | Email: info@volcanomotor.com

one-stop partner for motors & motor drives designing and manufacturing



Home About Us Products Solutions News FAQ Contact Us Feedback

Home > Products > Motor power-Brushless Motor > 5 HP Brushless DC Motor



251mm 48V 4000W 2580rpm Hall Sensor With Controller BLDC Motor

Model Number:	VOL-BL400C48
Туре:	Brushless DC Motor
Output Power:	4KW
DC Voltage:	48V
Speed Range:	2580 RPM
Poles:	4P, 6P, 8P

Detailed information

Brand Name:	Volcano Electric	Model Number:	VOL-BL400C48	Type:	Brushless DC Motor		
Output Power:	4000W	DC Voltage:	48V	Speed Range:	2580 RPM		
Controller:	Customized, Optional	Braker:	Optional	Insulation Class:	Class B/F/H		
Enclosure:	IP44/IP54	Poles:	4P, 6P, 8P	Wire:	100% copper		
Current:	58.82A	Sensor:	Hall sensor, Optional	Certification:	CE,UL,ROHS		
Housing:	Aluminum frame	Efficiency:	up to 87				
Duty:	S1 (continuous)	Place of Origin:	Zhejiang, China (Mainland)	Standard:	IEC/NEMA		
Application:	Boat, Car, EV, Fan, Home Appliance, Traction Motor, Pump, bus A/C systems ,Other						


Product Description

Volcano electric BLDC Motor 48V, 4000W, 2580RPM, IP54 duty continues, along with hall sensor, controller. The gross weight of the motor is 16kgs. Motor efficiency is 87% and under rated power of 4000W, the motor gives round 12.3N.m torque value. Rotation of this motor is CW and CCW. Mounting method of this motor is B14, we also equipped a junk box for this motor in consideration of the current larger than 100A. For the safety issues. This motor is applied in EV market for electric tricycle.

Volcano electric provide lost of motors in EV application and sold all over words which all give us a good reputation. Our motor come out with high efficiency, economic cost as small size as possible. We accept OEM and customized design.

If you have interesting for this motor, please feel free to contact us by info@volcanomotor.com

Configuration



*CAN MAKE ACCORDING TO YOUR REQUIRMENT

Brushless motor list

Motor type	Output	Voltage	Load	Speed	Rated Torque	Poles	Efficiency	Noise
	KW	V	A	RPM	N.m		%	dB
VOL-BL020C24	0.2	24	10.7	1500	1.27	8	89	62
VOL-BL090C24	0.9	24	44.6	2600	3.31	8	84	60
VOL-BL100C30	1	30	43	1200	7.96	8	88	60
VOL-BL120C24	1.2	24	64.5	2300	4.98	8	89	60
VOL-BL120C36	1.2	36	39.7	2270	5.05	8	84	60
VOL-BL125C24	1.25	24	62	3200	3.73	8	84	60
VOL-BL130C36	1.3	36	40.12	3200	3.88	8	90	60
VOL-BL150C24	1.5	24	73.5	2590	5.53	8	85	61
VOL-BL400C48	4	48	107	2580	14.81	8	89	61
VOL-BL150C48	1.5	48	40.3	1800	7.96	8	90	61.5
VOL-BL100C48	1	48	26.9	2500	3.82	8	84.7	61.5

Advantages of Brushless DC motor:

- Lower Maintainance and longer lifetime no brush and commutator erosion
- Lower noise the elimination of brush contact
- Higher power to weight ratio
- Higher efficiency (in general higher than 90%)
- Lower temperature rise more efficient heat dissipation due to winding construction
- Simple structure
- Reduction of EMI

For customized DC Motors, please contact our technician, Ordinary, we have to know the following information to get a professional proposal:

- Brushed or Brushless Customer preference
- Output power (W) Horsepower/watts/torque rated at full load speed

- Voltage (V) i.e 12v DC 220v AC
- Motor speed (RPM) Revolutions per minute of the shaft at full load Voltage
- Application e.g. traction, airconditioning, etc.
- Duty Most motors are rated continuous. Some applications however may use motors designed for intermittent duty
- Configuration/Frame Our products are according to IEC standard, we also can customize the flange and shaft according to the customer drawing
- **Controller function** e.g. forward/reverse, variable speed, acceleration profile, etc.

Previous 251mm 72V 4KW Hall Sensor BLDC Motor With Controller

Next 48V 90% Efficiency 1500W Hall Sensor EV Motor With Brake

You may like:





DC Motor Manufacturer & Supplier in China Email: info@volcanomotor.com | Tel: 86-18157453060

About Us Products Solutions Contact Us

Copyright © Ningbo volcanic electric co.,LTD

Feedback

Search