Tel: +86-18157453060 | Email: info@volcanomotor.com one-stop partner for motors & motor drives designing and manufacturing



Home About Us Products Solutions News FAQ Contact Us Feedback

 ${\sf Home} \, \geq \, {\sf Products} \, \geq \, {\sf Motor \ power-Brushless \ Motor}$ 



## **M7 Brushless DC Motor**


Model Number:	BLDCM7
Туре:	Brushless DC Motor
Output Power:	1KW-15KW
DC Voltage:	24V,36V,48V,78V,120V,180V250
Speed Range:	1200-4500 RPM
Poles:	4P, 6P, 8P

Detailed information

## **Quick Details**

uick Details								
Brand Name:	Volcano Electric	Model Number:	BLDCM7	Туре:	Brushless DC Motor			
Output Power:	1KW-15KW	DC Voltage:	24V,36V,48V,78V,120V,180 V250V,300V	Speed Range:	1200-4500 RPM			
Controller:	Customized, Optional	Braker:	Optional	Insulation Class:	Class B/F/H			
Enclosure:	IP44/IP54	Poles:	4P, 6P, 8P	Wire:	100% copper			
Housing:	Aluminum	SHAFT:	25MM AND 38MM, customized	Flange:	180MM, customized			
Efficiency:	IE 4.0							
Duty:	S1 (continuous)	Place of Origin:	Zhejiang, China (Mainland)	Standard:	confirm to IEC international standard			
Application:	Boat, Car, Electric Bicycle, Fan, Home Appliance, Traction Motor, Solar Pump DC systems, bus A/C systems ,Other							

## Configuration



## \*CAN MAKE ACCORDING TO YOUR REQUIRMENT

Motor type	Output	Voltage	Load	Speed	Rated Torque	Poles	Efficiency	Noise
	KW	V	А	RPM	N.m		%	dB
BLDC3.0S-M7	0.9	48	67.6	2650	10.81	8	92.5	61
BLDC4.0M-M7	1.2	48	90.6	2580	14.81	8	92	62
BLDC5.0L-M7	1.5	72	85.6	3680	14.27	8	89.2	63

For customized DC Motors, please contact our technician, Ordinary, we have to know the following information to get a professional proposal:

- Brushed or Brushless Customer preference
- Output power (W) Horsepower/watts/torque rated at full load speed
- Voltage (V) i.e 12v DC ...... 220v AC
- Motor speed (RPM) Revolutions per minute of the shaft at full load Voltage
- Application e.g. traction, airconditioning, etc.
- Duty Most motors are rated continuous. Some applications however may use motors designed for intermittent duty
- Configuration/Frame Our products are according to IEC standard, we also can customize the flange and shaft according to the customer drawing
- Controller function e.g. forward/reverse, variable speed, acceleration profile, etc.

Previous DC126 Brushed Motor

Next M6 Brushless DC Motor

You may like:





DC Motor Manufacturer & Supplier in China Email: info@volcanomotor.com | Tel: 86-18157453060

About Us

Products

Solutions

Contact Us

Feedback

Search

Copyright © Ningbo volcanic electric co.,LTD