

Shreeinsul Cloth & tape

Shreeinsul Cloth/Tape are woven from Superior Quality ceramic fiber yarn and reinforced with Fiberglass/SS wire. Cloth and Tapes have high temperature resistance. These cloths contain specific quantum of organic carrier which helps to establish physical formation of products which charred out at 400°C. The continuous with stand temperature of the cloth & Tape is 1000°C. and also available in vermiculate coated



Standard Dimension

Cloths - 10000 mm Length x 1000 mm width x 3mm - 6mm Thickness

Tape - 25 mtrs : Length
25 mm, 50mm, 75mm, 100mm : Width
3 mm - 6mm : Thickness

Density (Kg/m3) - 400 - 600

Applications

Metalic Textile	Non Metalic
• Coke oven door seal preventing gas leakage	• Insulation between anode buss and box
• Between refractory and door jamb.	• Asbestos free and ideal replacement for asbestos
• Piping insulation	• Furnace doors and radiant tube seals
• Hot top seal	• Blast furnace stove expansion joint
• Coke oven ascension pipe seal, preventing fume	• Welding curtains
• Turbine insulation - Ceramic pads and make a jacket	
• Emission on exhaust collection system	

Grade	1260° C
Density (Kg/m3)	400 - 600
LOI (%)	< 20
Chemical Composition	1260° C
SiO2%	49-58%
Al2O3%	39-43%
ZrO2%	0-7%
Fe2O3%	Max 0.1%