

Hands-Free: a robot augmented reality teleoperation system

Cristina Nuzzi*, Stefano Ghidini, Roberto Pagani, Simone Pasinetti and Giovanna Sansoni

Abstract—This electronic document is a live template. The various components of your paper [title, text, heads, etc.] are already defined on the style sheet, as illustrated by the portions given in this document.

I. INTRODUCTION

Despite advances in robotic perception are increasing autonomous capabilities, the human intelligence is still considered a necessity in unstructured or not predictable environments. Typical scenarios concern the detection of random shape objects, manipulation, or custom robot motion. In such context, human and robots must achieve mutual human-robot interaction (HRI) [1].

HRI can be both physical (pHRI) or not, depending on the assigned task. For example, when the robot is constrained in a dangerous environment or must handle hazardous materials, pHRI is not recommended. In this cases, robot teleoperation may be necessary. A teleoperation system concerns with the exploration and exploitation of spaces which do not allow user presence, thus, the operator acts by remotely move the robot [2]. A plenty of human-machine interfaces for teleoperation have been developed considering a mechanical interface, this includes exoskeleton [3] or gloves [4]. Such systems are particularly helpful to achieve bilateral teleoperation [5], where they can transmit or reflect back to the user reaction forces from the task being performed. In this case, a high perception with complete haptic feedback [6] is required. Other interfaces includes mouse, switchbox, keyboard, touch-screen and joystick, which is usually a better control device than others because the operators can identify better with the task [7]. Electromyography (EMG) is widely used to implement teleoperation systems by mean of muscular activity signals [8], [9]. However, as reminded recently in [10], EMG could be affected by difficulties in processing EMG signals for amplitude and spectral analysis, reducing their efficiency for many applications. Moreover, all the interfaces described still act by contact, hindering the movement of the operator or cause him to act through unnatural movements.

Therefore, if bilater interaction is not required, a vision-based interface is preferable. A vision-based interface does not require physical contact with external devices such as

cables, connectors and objects outside of the user working area. This grants a more natural and intuitive interaction, which is reflected on the task performance: as shown in [11], the accuracy of object gripping tasks is improved by mean of a contactless vision-based robot teleoperation method, while in [12] a stereo vision system improved the performance of a mobile robot teleoperation application.

Furthermore, if a vision-interface is integrated with virtual and augmented reality techniques, it translates in a greater level of immersion for the user. Such techniques are used to enhance the feedback information; in fact, the operator feels like being physically present in the remote environment, enhancing the immersion level. The notion of immersion is one of the most important reasons for using virtual and augmented reality [7]. An augmented reality system for teleoperation based on the Leap Motion (LM) controller is presented in [13]. For its application domain, the LM controller is considered an accurate sensor [14], however it is limited to a relatively small measuring distance if compared with other sensors. In this sense, the LM controller introduces spatial constraints that clash with the previously stated concept of the high level user immersion.

For these reasons, we present a novel robot augmented reality teleoperation system that exploits RGB cameras, which provide greater measuring distance if compared with the LM controller. A ROS-based framework has been developed to provide hand tracking and hand-gesture recognition features, exploiting the OpenPose software [15], [16] based on the Deep Learning framework Caffe [17]. This, in combination with the ease of availability of an RGB camera, lead the framework to be strongly open-source oriented and highly replicable on all the ROS-based platform. The proposed system includes: neural network for hand–gesture recognition (Section III), a rigorous procedure for robot workspace calibration and a mapping policy between the coordinate system of the user and the robot (Section III). Different experiments were performed on a *Sawyer (Rethink Robotics)* industrial collaborative robot to evaluate repeatability and accuracy of the proposed system. Section IV reports the results.

II. WORKSPACE CALIBRATION AND MAPPING

Our set-up is composed of two workspaces: the *user workspace* and the *robot workspace*. Cartesian points in the user workspace, which can be reached by the user hand and are correctly viewed by the camera, correspond to precise robot end-effector Cartesian points in the robot workspace. To obtain a mapping between the hand positions and the

This work was not supported by any organization.

Cristina Nuzzi, Roberto Pagani, Simone Pasinetti and Giovanna Sansoni are members of the Department of Mechanical and Industrial Engineering at University of Brescia, Via Branze 38, 25123 Brescia, Italy.

Stefano Ghidini is a member of the STIIMA-CNR, Via Alfonso Corti 12, 20133 Milan, Italy. He is also a member of the Department of Mechanical and Industrial Engineering at University of Brescia, Via Branze 38, 25123 Brescia, Italy.

* Corresponding author, e-mail: c.nuzzi@unibs.it

robot end-effector positions, it is necessary to perform a set of calibration procedures described in the following sections.

A. User Workspace Calibration

In the user workspace an RGB camera is used to recognize the hand skeleton in real-time. Therefore, it is necessary to properly calibrate the camera with respect to the user-defined reference system. This procedure is called *camera calibration*, and can be easily realized following standard procedures, such as the one detailed in [18]. To correctly map a point $\mathbf{S} = (u, v)$ in the image to its corresponding real world coordinate point $\mathbf{P} = (x, y, z)$ it is necessary to use homogeneous coordinates and apply the following Equation:

$$s \begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \mathbf{K} [\mathbf{R}|\mathbf{t}] \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} \quad (1)$$

In the equation above, the scalar $s \in \mathbb{R}$ is the scale factor of the image, $\mathbf{K} \in \mathbb{R}^{3 \times 3}$ is the camera matrix containing the intrinsic parameters of the camera such as focal length and optical center, $[\mathbf{R}|\mathbf{t}] \in \mathbb{R}^{4 \times 3}$ is the rigid transformation matrix containing the extrinsic parameters for rotation ($\mathbf{R} \in \mathbb{R}^{3 \times 3}$) and translation ($\mathbf{t} \in \mathbb{R}^3$) of the camera reference frame C with respect to the calibration master reference frame H .

To obtain matrix \mathbf{K} it is necessary to perform a calibration procedure. A well-performed calibration procedure allows to obtain a satisfactory estimation of the camera parameters. To correctly map image points to the corresponding real world coordinates, the rigid transformation matrix must be estimated with respect to the user-defined reference system of the calibration master. Thus, if reference system H changes or the camera C moves, it is necessary to estimate again the correct rigid transformation matrix.

Images acquired by the camera are processed, then the hand skeleton joints coordinates are calculated. By using Equation 1 for each frame, it is possible to obtain the real world coordinates of the hand skeleton joints in real time (Fig. 1).

Fig. 1. Scheme of the user workspace, where the camera reference system C and the user-defined reference system H are calibrated to find the correspondence between image points and real world coordinates.

B. Robot Workspace Calibration

The robot workspace refers to the space in which the robot moves (purple square of Fig. 2) with respect to the user workspace (green square of Fig. 1). In this case, the user hand real-world position in reference system H is mapped to the new reference system W . The mapping between reference system H and reference system W is obtained easily if the two workspaces have the same dimension (matrix $[\mathbf{R}|\mathbf{t}]$ is the identity matrix) or if one workspace is a scaled version of the other one (matrix $[\mathbf{R}|\mathbf{t}]$ is the identity matrix multiplied by the scale factor).

To correctly move the robot in a cartesian position of reference system W , it is necessary to perform a calibration

Fig. 2. Scheme of the robot workspace, where the second user-defined reference system W and the robot reference system R are calibrated to find the correspondence between the workspace positions and the end-effector joint coordinates.

between reference system W and the robot reference system R . This procedure has been carried out experimentally by moving the robot (using its manual guidance mode) in a set of 13 Cartesian positions of reference system W (Fig. xx). The robot correct positioning on top of each calibration position has been assured by using a 3D-printed centering tool (Fig. xx). The tool must be centered manually on each calibration marker and secured in place, then the robot end effector can be moved on it and carefully positioned inside the purposely made circular cavity of the tool. When the positioning is complete, the robot coordinates (both in the Cartesian space and in the Joints space) corresponding to that particular marker (of which the positioning is known with respect to reference system W) can be extracted using ROS or the robot proprietary software.

When a satisfactory number of calibration positions (in our case, 13) has been acquired, it is possible to estimate the rigid transformation matrix between workspaces W and R , following the formula:

III. HAND-GESTURE RECOGNITION

The proposed teleoperation method is based on the recognition of the user hands skeleton.

Each frame acquired by the RGB camera (in our set-up, a Kinect v2 camera) is processed by the software, which leverages the OpenPose hand skeleton recognition network to predict the hand skeleton, following the details of [15]. The gesture recognition procedure is based on the position of the reference keypoint (red keypoint 0 in Fig. xx) and on the position of the four knuckles keypoints (yellow keypoints 5, 9, 13, 17 in Fig. xx). According to the knuckles and the thumb (x, y) keypoints positions (from keypoint 1 to 4), the orientation of the hand can be hypotized as upright, left oriented, right oriented, or upside down (Fig. xx). This allows the software to recognize the gestures regardless of the orientation of the hand.

Using the fingers keypoints Euclidean distances, it is possible to recognize if a certain finger is opened or closed: for example, if keypoints from 6 to 8 are detected both (i) close to each other and (ii) close to their corresponding knuckle keypoint 5, the index finger is detected as closed. Using this logic, we defined two gestures used to carry out basic teleoperation tasks: the **open hand** gesture and the **index** gesture.

Considering the calibration procedure detailed in Section II, a certain position P_H of user workspace H corresponds to a certain robot end-effector position P_W in workspace W . Hence, to move the robot end-effector in position P_W , users must:

- 1) place their hand in position P_H (corresponding to position P_W), using the real-time visualization of the software as guidance (Fig. xx a);

- 2) perform the open hand gesture to allow the coordinate extraction (Fig. xx b);
- 3) perform the index gesture, carefully pointing the index finger to position P_H (Fig. xx c).

It is worth noting that, since the hand skeleton is obtained by a neural network which estimates the joints coordinates frame per frame, their position in consecutive frames may vary. Therefore, our software extracts N different P_H coordinates from N consecutive index gestures recognized in consecutive frames. The average coordinates are extracted to reduce positioning errors introduced by the hand skeleton recognition network. The higher the value of N , the higher the error reduction, at the cost of a higher delay before the final P_H coordinates are extracted. In our set-up, we set $N = 7$. After a position P_H is obtained, the corresponding robot position P_R is calculated and the robot is moved there using ROS. To perform a new robot movement, the procedure in Fig. xx must be repeated from the start.

IV. EXPERIMENTAL EVALUATION

A reliable teleoperation system is obtained if the robot correctly moves to the desired position with a low positioning error. In the case of our set-up, the positioning error is obtained considering the whole procedure carried out to move the robot end-effector to a certain position corresponding to the real world position of the index finger:

- 1) place the index finger to a certain position P_1 ;
- 2) calculate the average of the consecutive index finger positions estimated by the neural network. The obtained position is P_2 , which corresponds to $P_1 + E_1$, where E_1 is the positioning error between the two positions;
- 3) transform P_2 to P_3 according to the mapping between the user horizontal workspace H and the vertical workspace W . If the two workspaces have the same dimension except for a scale factor, no errors are introduced in this step, otherwise an error E_S is added;
- 4) transform P_3 to P_4 according to the rigid transformation between the vertical workspace W and the robot workspace R . P_4 corresponds to $P_3 + E_2$, where E_2 is the positioning error due to the rigid transformation;
- 5) move the robot to P_4 .

Hence, we obtained that $P_4 = P_1 + E_1 + E_S + E_2$. Considering this formula, and that in our set-up E_S can be assumed equal to zero (because we kept workspace H and workspace W dimensions except for the scaling factor), we designed two experiments to assess if the positioning error obtained depends (i) on the estimation of the hand skeleton (E_1), or (ii) on the robot calibration (E_2).

A. Evaluation of the skeleton estimation error

The positioning error due to the estimation of the hand skeleton joints made by OpenPose neural network has been evaluated considering the theoretical position of the index in the image T and the index joint position in the image A calculated by the software (Fig. xx).

B. Evaluation of the robot positioning error

In our set-up, reference system H is placed horizontally with the camera mounted still at a 1m distance (Fig. xx). Reference system W , however, has been placed vertically on a glass pane (Fig. xx). To reliably assess the positioning of the robot end-effector, a red laser has been mounted on the end effector (laser name bla bla) (Fig. xx). When the robot is moved to a certain theoretical position T , the laser will point to its actual positioning A . To correctly visualize and measure the robot workspace and the laser positioning, an RGB camera (camera serial name) has been mounted behind the glass pane. A measuring software has been developed using LabVIEW to measure the distance between the theoretical position T (calculated as the barycenter of the black dot of the experimental master as in Fig. xx) and the actual positioning A (red dot in the image as in Fig. xx).

We moved the robot using the proposed system in xx theoretical positions. To do that, we used the Cartesian positions corresponding to the circular markers barycenters (theoretical positions) to move the robot using ROS. Hence, this procedure avoids considering the hand skeleton estimation errors.

V. FIGURES AND TABLES

TABLE I
AN EXAMPLE OF A TABLE

One	Two
Three	Four

VI. CONCLUSIONS

Conclusioni sul progetto/esperimenti ottenuti. Problematiche incontrate e come sono state risolte. Future developments.

REFERENCES

- [1] H. A. Yanco and J. L. Drury, "A Taxonomy for Human-Robot Interaction," *Engineering*, p. 9, 2002.
- [2] J. Vertut and P. C. Coeffet, *Robot Technology; vol. 3A Teleoperation and Robotics Evolution and Development*. 1986.
- [3] J. Rebelo, T. Sednaoui, E. B. Den Exter, T. Krueger, and A. Schiele, "Bilateral robot teleoperation: A wearable arm exoskeleton featuring an intuitive user interface," *IEEE Robot. Autom. Mag.*, vol. 21, no. 4, pp. 62–69, 2014.
- [4] X. Lv, M. Zhang, F. Cui, and X. Zhang, "Teleoperation of robot based on virtual reality," *Proc. - 16th Int. Conf. Artif. Real. Telexistence - Work. ICAT 2006*, pp. 400–403, 2006.
- [5] P. F. Hokayem and M. W. Spong, "Bilateral teleoperation: An historical survey," *Automatica*, vol. 42, no. 12, pp. 2035–2057, 2006.
- [6] C. Glover, B. Russell, A. White, M. Miller, and A. Stoytchev, "An effective and intuitive control interface for remote robot teleoperation with complete haptic feedback," *Proc. 2009 Emerg. Technol. Conf. (ETC)*, Ames, IA, USA, 2009.
- [7] R. Boboc, H. Moga, and D. TALAB, "A Review of Current Applications in Teleoperation of Mobile Robots," *Bull. Transilv. Univ. Brasov Ser. I Eng. Sci.*, vol. 5, no. 54, pp. 9–16, 2012.
- [8] J. Vogel, C. Castellini, and P. van der Smagt, "EMG-based teleoperation and manipulation with the DLR LWR-III," pp. 672–678, 2011.
- [9] H. F. Hassan, S. J. Abou-Loukh, and I. K. Ibraheem, "Teleoperated robotic arm movement using electromyography signal with wearable Myo armband," *J. King Saud Univ. - Eng. Sci.*, no. xxxx, 2019.

- [10] L. Roveda, S. Haghshenas, A. Prini, T. Dinon, N. Pedrocchi, F. Braghin, and L. M. Tosatti, "Fuzzy Impedance Control for Enhancing Capabilities of Humans in Onerous Tasks Execution," in *2018 15th Int. Conf. Ubiquitous Robot. UR 2018*, pp. 406–411, Institute of Electrical and Electronics Engineers Inc., aug 2018.
- [11] J. Kofman, X. Wu, T. Luu, and S. Verma, "Teleoperation of a robot manipulator using a vision-based human-robot interface," *IEEE Trans. Ind. Electron.*, vol. 52, no. 5, pp. 1206–1219, 2005.
- [12] S. Livatino, G. Muscato, and F. Privitera, "Stereo viewing and virtual reality technologies in mobile robot teleguide," *IEEE Trans. Robot.*, vol. 25, no. 6, pp. 1343–1355, 2009.
- [13] L. Peppoloni, F. Brizzi, C. A. Avizzano, and E. Ruffaldi, "Immersive ROS-integrated framework for robot teleoperation," *2015 IEEE Symp. 3D User Interfaces, 3DUI 2015 - Proc.*, pp. 177–178, 2015.
- [14] H. Hedayati, M. Walker, and D. Szafir, "Improving Collocated Robot Teleoperation with Augmented Reality," *ACM/IEEE Int. Conf. Human-Robot Interact.*, pp. 78–86, 2018.
- [15] T. Simon, H. Joo, I. Matthews, and Y. Sheikh, "Hand keypoint detection in single images using multiview bootstrapping," in *CVPR*, 2017.
- [16] Z. Cao, G. Hidalgo, T. Simon, S.-E. Wei, and Y. Sheikh, "OpenPose: realtime multi-person 2D pose estimation using Part Affinity Fields," in *arXiv preprint arXiv:1812.08008*, 2018.
- [17] Y. Jia, E. Shelhamer, J. Donahue, S. Karayev, J. Long, R. Girshick, S. Guadarrama, and T. Darrell, "Caffe: Convolutional architecture for fast feature embedding," *arXiv preprint arXiv:1408.5093*, 2014.
- [18] J.-Y. Bouguet, "Camera calibration toolbox for matlab," 2001.