

Polymorphism

Polymorphism, Override and Overload Methods



SoftUni Team
Technical Trainers



SoftUni



Software University

<https://softuni.bg>

Table of Contents

- Polymorphism
- The **is** Keyword
- The **as** Keyword
- Compile-time Polymorphism
 - Overload Methods
- Runtime Polymorphism
 - Override Methods

sli.do

#csharp-advanced

ANIMAL




A dark blue circle containing the word 'ANIMAL' at the top. Below it are two white line-art icons: a dog's head on the left and a cat's head on the right. Two white lines connect 'ANIMAL' to each icon, one on the left and one on the right. The background features a light gray network of circles and lines.

Polymorphism

What is Polimorphism?

- From the Greek



- This is something similar to a word having several different meanings depending on the context
- Polymorphism is often referred to as the third pillar of object-oriented programming, after encapsulation and inheritance



Polymorphism in OOP

- Ability of an **object** to take on **many forms**

```
public interface IAnimal {}  
public abstract class Mammal {}  
public class Person : Mammal, IAnimal {}
```

Person **IS-A** Person

Person **IS-AN** Animal

Person **IS-AN** Object

Person **IS-A** Mammal



Variable Type and Data Type

- **Variables Type** is the compile-time type of the variable
- **Data Type** is the actual runtime type of the variable
- If you need an **object method** you need to **cast it or override it**

```
public class Person : Mammal, IAnimal {}  
object objPerson = new Person();  
IAnimal person   = new Person();  
Mammal mammal    = new Person();  
Person person    = new Person();
```

Variable Type

Data Type

- Runtime check if an **object** is an **instance** of a specific **class**

```
public class Person : Mammal, IAnimal {}  
IAnimal person = new Person();  
Mammal personOne = new Person();  
Person personTwo = new Person();  
if (person is Person)  
{  
    ((Person)person).getSalary();  
}
```

Check object type of person

Cast to object
type and use its
methods

- Type pattern - tests whether an expression can be converted to a specified type and casts it to a variable of that type

```
public class Person : Mammal, IAnimal {}  
Mammal personOne = new Person();  
Person personTwo = new Person();  
if (personOne is Person person)  
{  
    person.GetSalary();  
}
```

Checks if object is of type person and casts it

Uses its methods

- When performing pattern matching with the constant pattern, **is** tests whether an expression equals a specified constant
- Checking for **null** can be performed using the constant pattern

```
int i = 0;
int min = 0, max = 10;
while(true)
{
    Console.WriteLine($"i is {i}");
    i++;
    if(i is max or min) break;
}
```

- A pattern match with the **var pattern** always succeeds

```
Enumerable.Range(0, 100).Where(  
    x => x % 10 is var r && r >= 1 && r <= 3)
```

- The value of `expr` is always assigned to a local variable named `varname`
- **varname** is a variable of the same type as **expr**
- Note that if **expr** is null, the **is** expression still is true and assigns null to **varname**

Anytime you find yourself writing code of the form "if the object is of type T1, then do something, but if it's of type T2, then do something else", **slap yourself**.

From *Effective C++*, by Scott Meyers

- You can use the as operator to perform certain types of conversions between compatible reference types

```
public class Person : Mammal, IAnimal {}
```

```
IAnimal person = new Person();
```

```
Mammal personOne = new Person();
```

```
Person personTwo;
```

```
personTwo = personOne as Person;
```

```
if (personTwo != null) {
```

```
    // Do something specific for Person
```

```
}
```

Convert Mammal to Person

Check if conversion is successful

Types of Polymorphism

■ Runtime

```
public class Shape {}  
public class Circle : Shape {}  
public static void Main()  
{  
    Shape shape = new Circle();  
    shape.Draw();  
}
```

■ Compile-time

```
public static void Main()  
{  
    int Sum(int a, int b, int c)  
    double Sum(double a, double b)  
}
```



- Also known as **Static Polymorphism**

```
public static void Main()  
{  
    static int MyMethod(int a, int b) {}  
    static double MyMethod(double a, double b) { ... }  
}
```

Method
overloading

- Argument lists could differ in:
 - Number of parameters
 - Data type of parameters
 - Order of parameters

Problem: MathOperation

MathOperation

```
+Add(int, int): int  
+Add(double, double, double): double  
+Add(decimal, decimal, decimal): decimal
```



```
MathOperations mo = new MathOperations();  
Console.WriteLine(mo.Add(2, 3));  
Console.WriteLine(mo.Add(2.2, 3.3, 5.5));  
Console.WriteLine(mo.Add(2.2m, 3.3m, 4.4m));
```

Check your solution here: <https://judge.softuni.org/Contests/Practice/Index/1503#0>

Solution: MathOperation

```
public int Add(int a, int b)
{
    return a + b;
}
public double Add(double a, double b, double c)
{
    return a + b + c;
}
public decimal Add(decimal a, decimal b, decimal c)
{
    return a + b + c;
}
```

Rules for Overloading a Method

- Name should be the same
- **Signature** must be different
 - **Number** of arguments
 - **Type** of arguments
 - **Order** of arguments
- Return type is not a part of its signature
- Overloading can take place in the **same class** or in its **sub-classes**
- Constructors can be **overloaded**

- Has two distinct aspects:
- At run time, objects of a **derived class** may be treated as objects of **a base class in** places, such as method parameters and collections or arrays
 - When this occurs, the **object's declared type** is no longer identical to **its run-time type**

- Base classes may define and implement **virtual methods**
 - Derived classes can override
 - They provide **their own definition and implementation**
- At run-time, the CLR looks up the run-time type of the object and invokes that override of the virtual method

Runtime Polymorphism (1)

- Also known as **Dynamic Polymorphism**

```
public class Rectangle {  
    public virtual double Area() {  
        return this.a * this.b;  
    }  
}  
  
public class Square : Rectangle {  
    public override double Area() {  
        return this.a * this.a;  
    }  
}
```

Method
overriding


Runtime Polymorphism (2)

- Usage of **override** method

```
public static void Main()  
{  
    Rectangle rect = new Rectangle(3.0, 4.0);  
    Rectangle square = new Square(4.0);  
  
    Console.WriteLine(rect.Area()); // 12.0  
    Console.WriteLine(square.Area()); // 16.0  
}
```

Method
overriding

Problem: Animals



Check your solution here: <https://judge.softuni.org/Contests/Practice/Index/1503#1>

Solution: Animals (1)

```
public abstract class Animal {  
    // Create Constructor  
    public string Name { get; private set; }  
    public string FavouriteFood { get; private set; }  
    public virtual string ExplainSelf() {  
        return string.Format(  
            "I am {0} and my favourite food is {1}",  
            this.Name,  
            this.FavouriteFood);  
    }  
}
```


Solution: Animals (2)

```
public class Dog : Animal
{
    public Dog(string name, string favouriteFood)
        : base(name, favouriteFood) { }
    public override string ExplainSelf()
    {
        return base.ExplainSelf() +
            Environment.NewLine +
            "BARK";
    }
}
```

Solution: Animals (3)

```
public class Cat : Animal
{
    public Cat(string name, string favouriteFood)
        : base(name, favouriteFood) { }
    public override string ExplainSelf()
    {
        return base.ExplainSelf() +
            Environment.NewLine +
            "MEOW";
    }
}
```

Rules for Overriding Method


- **Overriding** must take place in any sub-classes
- The overriding method and the base must have the **same return type** and the **same signature**
- Base method must have the **virtual** keyword
- Overriding method must have the **abstract** or **override** keyword
- **Private and static** methods **cannot** be overridden
- **Virtual** members can use **base keyword** to call the **base class**

- Virtual members **remain virtual indefinitely**
- A derived class can stop virtual inheritance by declaring an override as **sealed**
 - Sealed methods can be replaced by derived classes by using the **new** keyword
- The **override** modifier extends the base class virtual method
 - The **new** modifier hides an accessible base class method

- Polymorphism - **Definition** and **Types**
- **is** Keyword
- **as** Keyword
- Overload Methods
- Override Methods



Questions?



SoftUni Diamond Partners

**SUPER
HOSTING
.BG**



**Coca-Cola HBC
Bulgaria**

 **Flutter**TM
International

INDEAVR
Serving the high achievers



AMBITIONED

 **DRAFT
KINGS**

 **SOFTWARE
GROUP**



BOSCH

 **Postbank**
Решения за твоето утре

 **PHAR
VISION**



SmartIT

DXC
TECHNOLOGY

createX

- Software University – High-Quality Education, Profession and Job for Software Developers

- softuni.bg, about.softuni.bg

- Software University Foundation

- softuni.foundation

- Software University @ Facebook

- facebook.com/SoftwareUniversity

- Software University Forums

- forum.softuni.bg



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://about.softuni.bg>
- © Software University – <https://softuni.bg>

