

Network Compliance Report

Generated 2026-09-26 17:56 UTC

Scan ID	1ea86857-fd31-44fe-bc3a-fc567c140b4e
File	cisco_ios__CTRL-001_PASS.cfg
Uploaded	2026-09-26T10:17:09.530605+00:00
Vendor	Cisco IOS
Hostname	-
Model	-
Serial number	-
OS version	-

Compliance summary

PASS	FAIL	MISSING	REVIEW	N/A	Compliant
19	0	0	1	0	95.0%

Framework coverage

Framework	Controls cited	PASS	FAIL	MISSING	REVIEW
CIS	20	19	0	0	1
DISA STIG	20	19	0	0	1
ISO 27001	20	19	0	0	1
NIST 800-53	20	19	0	0	1

Findings

Control	State	Sev.	Expected	Observed	Evidence
CTRL-001 SSH must be restricted to version 2	PASS	high	2	-	L2: ip ssh version 2

CTRL-002 Telnet must be disabled for device management	PASS	high	False	-	L24: transport input ssh
CTRL-003 HTTP (unencrypted) management interface must be disabled	PASS	high	False	no	L3: no ip http server
CTRL-004 HTTPS must be enabled for web-based device management	PASS	high	True	-	L4: ip http secure-server
CTRL-005 Administrative sessions must time out after a maximum of 10 minutes of inactivity	PASS	medium	10	-	L25: exec-timeout 10 0
CTRL-006 AAA (Authentication, Authorization, and Accounting) must be enabled for device management	PASS	high	True	-	L5: aaa new-model
CTRL-007 A strong password policy (complexity, minimum length, encryption) must be enforced	PASS	high	True	-	L6: security passwords min-length 8
CTRL-008 Failed login attempts must be limited and result in a lockout period	PASS	medium	3	-	L7: login block-for 120 attempts 3 within 60
CTRL-009 System event logging must be enabled	PASS	medium	True	-	L8: logging on

CTRL-010 Logs must be forwarded to a remote syslog host	PASS	medium	True	-	L9: logging host 10.0.0.5
CTRL-011 NTP must be configured with a valid time source	PASS	low	True	-	L10: ntp server 10.0.0.10
CTRL-012 NTP must use authentication keys to validate time sources	PASS	medium	True	-	L11: ntp authenticate
CTRL-013 SNMP must be secured (SNMPv3 only, no default/weak community strings, ACL-restricted)	PASS	high	True	group	L12: snmp-server group ADMIN v3 priv
CTRL-014 Unused physical/logical ports and interfaces must be administratively disabled	PASS	medium	True	-	L21: shutdown
CTRL-015 Management access must be restricted by an access control list	PASS	high	True	-	L26: access-class MGMT_ACL in
CTRL-016 Dynamic routing protocol neighbor authentication must be enabled where the protocol is used	PASS	high	True	-	L19: ip ospf authentication message-digest
CTRL-017 Administrative access must be restricted to authorized sources/roles	REVIEW	high	True	-	L26: access-class MGMT_ACL in

CTRL-018 A security/legal warning banner must be configured for administrative access	PASS	low	True	-	L13: banner login ^C Authorized access only ^C
CTRL-019 Weak cryptographic algorithms/keys must be disabled; strong ciphers, key lengths, and hashing must be enforced	PASS	high	True	mac	L14: ip ssh server algorithm mac hmac-sha2-256
CTRL-020 Insecure/clear-text management protocols must be disabled in favor of encrypted equivalents	PASS	high	True	no	L15: no ip finger

Remediation preview

Conflict checking and before/after simulation are **Phase 8 future work** and are not included here. These commands are unverified against dependency, connectivity or management-path conflicts -- review before applying to a live device.

No remediable FAIL/MISSING findings, or no remediation rules defined for this vendor.