



4. Introducing jQuery Filters and Selectors

Client-Side Web Programming

2023/2024

José Socuéllamos

Index

1. Introducing jQuery
2. Downloading jQuery
3. Hello World
4. Selecting Elements
5. Basic Filters
6. Advanced Filters
7. Using JS variables in jQuery selectors



1.- Introducing jQuery

“There are only two kind of languages: the ones people complain about and the ones nobody uses”

Bjarne Stroustrup – C++ Designer

- Some JS libraries out there: Ajax, Prototype, Node.js, jQuery, etc...



1.- Introducing jQuery

- jQuery is used by 73% of the Top Million websites.
- It was created in 2006 to simplify the client-side scripting.

“WRITE LESS, DO MORE”


```
var checkedValue;
var elements = document.getElementsByTagName('input');
for (let i = 0; i < elements.length; i++) {
  if (elements[i].type === 'radio' &&
      elements[i].name === 'radio-group' &&
      elements[i].checked) {
    checkedValue = elements[i].value;
    break;
  }
}
```




1.- Introducing jQuery

- jQuery is used by 73% of the Top Million websites.
- It was created in 2006 to simplify the client-side scripting.

“WRITE LESS, DO MORE”



```
var checkedValue:  
var elements = document.getElementsByTagName('input');  
for (let i = 0; i < elements.length; i++) {  
    if (elements[i].type === 'radio' &&  
        elements[i].name === 'radio-group' &&  
        elements[i].checked) {  
        checkedValue = elements[i].value;  
        break;  
    }  
}
```



```
var checkedValue =  
    jQuery('input:radio[name="radio-group"]:checked').val();
```

<https://api.jquery.com/>



2.- Downloading jQuery

- Download jQuery from the official website ([jQuery.com/download](https://jquery.com/download)).
 - Uncompressed file: best used during development or debugging.
 - ★ Compressed file (min): saves bandwidth and improves performance in production.
- Save it in your local machine and link it from your webpage.

```
<!DOCTYPE html>
<head>
  <meta charset="UTF-8">
  <title>jQuery Hello World DAW</title>
  <script type="text/javascript" src="js/jquery-3.7.1.min.js"></script>
</head>
<body>

</body>
</html>
```



2.- Linking jQuery

- Include jQuery from a CDN (Content Delivery Network).
 - For example, Google, Microsoft...

```
<!DOCTYPE html>
<head>
  <meta charset="UTF-8">
  <title>jQuery Hello World DAW</title>
  <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.7.1/jquery.min.js"></script>
  <script src="https://ajax.aspnetcdn.com/ajax/jquery/jquery-3.7.1.min.js"></script>
</head>
<body>

</body>
</html>
```



3.- Hello World

- In JavaScript we use the `window.onload` event to wrap all of our code.

```
window.onload = function () {  
    alert("The web page is loaded!!!")  
}
```

- The `onload` event is triggered when all the content of the page has been loaded (including images).



3.- Hello World

- In jQuery we will write all of our code inside a `document.ready` event.

```
$(document).ready(function () {  
    alert("The web page is loaded!!!");  
});
```

```
$(function () {  
    alert("The web page is loaded!!!");  
});
```

- This will prevent any jQuery code from running before the document is finished loading (is ready).
- It will also allow us to have our JavaScript code before the body of our document, in the head section.



3.- Hello World

- If our jQuery code is in an external file, we can also load it asynchronously by adding the `defer` attribute in the *script* tag.
- The script will load in the background and run once the DOM is complete.
- We can use this attribute to load jQuery too.

```
<script src="jquery/3.7.1/jquery.min.js" defer></script>  
<script src="resources/js/mycode.js" defer></script>
```



4.- Selecting Elements

- Selectors allows us to get content from the document and manipulate it.
- They are used to "find" (or select) HTML elements based on their name, id, classes, types, attributes, values of attributes....
- They return a jQuery object with multiple functions and properties to interact with.
- We have several selectors in jQuery:
 - Simple
 - Composite
 - Filters

<http://api.jquery.com/category/selectors/>



4.- Selecting Elements

- Basic selectors are based on the CSS syntax and work basically the same way.

Selector	Description	Example
tag	Gets the elements with the specified HTML tag	<code>\$("div");</code>
#id	Gets the element with the specified id	<code>\$("#myimg");</code>
.class	Gets the elements with the specified class name	<code>\$(".myclass");</code>
tag.class	Gets the elements with the specified HTML tag and class	<code>\$("ul.customclass");</code>
tag#id.class	Gets the elements with the specified HTML tag, id and class	<code>\$("form#input1.myclass");</code>
*	Gets all elements in the page	<code>\$("*");</code>

- We can check the selection with `.length`

```
if ($('#div.foo').length) { ... }
```

4.- Selecting Elements

- Composite selectors allow to get objects by its hierarchy and combination.
- Some of them are:

Selector	Description	Example
E, F, G...	Gets all the specified elements	<code>\$("p, ul.b");</code>
E>F...	Gets all F elements that are direct children of E	<code>\$("ul.customclass>li>a");</code>
E F	Gets all F elements that are descendants of E	<code>\$("table td")</code>
E+F	Gets all F elements that are immediately preceded by sibling E	<code>\$("p+div")</code>
E~F	Gets all F elements preceded by any sibling E	<code>\$("p~div")</code>
.class1.class2	Gets the elements with class1 and class2	<code>\$(".a.b");</code>



5.- Basic Filters

- Filters keep the simplicity of selecting elements in jQuery and are used to polish the results of a selector.
- There are many types of filters, but these are some of the basic ones:

Filter	Description	Example
:first	Gets the first element	<code>\$("#div:first");</code> <code>\$("#ul li:first"); //first ul first li</code>
:last	Gets the last element	<code>\$("#div:last");</code>
:even // :odd	Gets the even/odd elements	<code>\$("#div:even");</code> <code>\$("#div:odd");</code>
:eq(n)//:gt(n)//:lt(n)	Gets the elements equal, greater or lower than the specified index (starts at 0)	<code>\$("#div:eq(3)");</code> <code>\$("#div:gt(6)");</code> <code>\$("#div:lt(4)");</code>
:not(selector)	All the elements but the ones that meet the provided selector	<code>\$("#div:not(div:eq(2))");</code>



6.- Advanced Filters

- Attribute filters
 - They allow us to refine the results gathered by the selector using the attributes of the element.
 - Attribute selectors are extremely powerful and allow you to select elements based on their attributes.
 - You can easily recognize these selectors because they're wrapped with square brackets (for example, [selector]).
 - They can be very slow.



6.- Advanced Filters

- Attribute filters
 - We can have multiple filters working as an AND. [filter][filter]

Filter	Description	Example
[attributeName]	Get element that contain a specified attribute	<code>\$("form[method]");</code>
[attributeName=value]	Get the element with the given attribute and with the given value. You can also use !=.	<code>\$("div[id='container']");</code>
[attributeName^=value]	Get the element with the given attribute and with the value beginning with the given value. You can also use !^	<code>\$("div[id^='container']");</code>
[attributeName\$=value]	Get the element with the given attribute and with the value finishing with the given value. You can also use !\$	<code>\$("a[href\$='.pdf']");</code>
[attributeName*=value]	Get the element with the given attribute and with the value containing the given value. You can also use !*	<code>\$("a[href*='jquery.com']");</code>



6.- Advanced Filters

- Content filters
 - They allow us to refine the results gathered by the selector using the content of the element.

Filter	Description	Example
:contains(text)	Gets elements that contains the specified text	<code>\$("div:contains('my house')");</code>
:empty	Gets all elements that are empty.	<code>\$("div:empty");</code>
:has(selector)	Gets all elements that contain the specified selector.	<code>\$("div:has(p[class=a])");</code>
:parent	Gets all elements that are a parent of another element (containing at least one element)	<code>\$("div:parent");</code>



6.- Advanced Filters

- Type filters
 - They allow us to refine the results gathered by the selector using the type of the element.

Filter	Description	Example
:header	All header elements <h1>, <h2> ...	<code>\$(":header")</code>
:animated	All elements that are in the progress of an animation	<code>\$(":animated")</code>



6.- Advanced Filters

- Visibility filters
 - They allow us to refine the results gathered by the selector depending if the elements are visible or not.

Filter	Description	Example
:visible	Get the visible elements	<code>\$("div:visible");</code>
:hidden	Get the hidden elements	<code>\$("div:hidden");</code>

- What's a hidden element?
 - Set to `display:none`
 - Form elements with `type="hidden"`
 - Width and height set to 0
 - A hidden parent element (this also hides child elements)
 - Note: It will not work on elements with `visibility:hidden`.



6.- Advanced Filters

- Child filters
 - They allow us to refine the results gathered by the selector considering its relationship with their parents.

Filter	Description	Example
:nth-child(index)	The element at the specified index	<code>\$("div p:nth-child(2)");</code>
:nth-child(even) :nth-child(odd)	Even/odd elements	<code>\$("div p:nth-child(even)");</code> <code>\$("div p:nth-child(odd)");</code>
:first-child :last-child	Get first/last child of a element	<code>\$("div p:first-child");</code> <code>\$("div p:last-child");</code>
:only-child	Get the child without siblings	<code>\$("div p:only-child");</code>



6.- Advanced Filters

- Form filters
 - Very similar to the previous filters, but useful to find specific elements in a form.

Filter	Description	Example
:button	Gets all button elements and input elements with type="button"	\$(":button");
:checkbox	Gets all input elements with type="checkbox"	\$(":checkbox")
:file	Gets all input elements with type="file"	\$(":file")
:image	Gets all input elements with type="image"	\$(":image")
:input	Gets all form elements (input, select, textarea, button)	\$(":input")
:password	Gets all input elements with type="password"	\$(":password")
:radio	Gets all input elements with type="radio"	\$(":radio")
:reset // :submit	Gets all elements with type="reset" // type="submit" (buttons and inputs)	\$(":reset") \$(":submit")
:text	Gets all input elements with type="text" or without a type specified (type="text" is the default)	\$(":text")

\$("input[type='button']");
.
.
.



6.- Advanced Filters

- Form filters

- Very similar to the previous filters, but useful to find specific elements in a form.

Filter	Description	Example
:checked	Gets all checked input elements (checkboxes, radio and options of select)	<code>\$(":checked")</code>
:disabled	Gets all disabled input elements	<code>\$(":disabled")</code>
:enabled	Gets all enabled input elements	<code>\$(":enabled")</code>
:focus	Gets the element that has the focus at the time the selector is run	<code>\$(":focus")</code>
:selected	Gets all selected options in a select element	<code>\$(":selected")</code>

- Very similar to the previous filters, but useful to find specific elements in a form.



7.- Using JS variables in jQuery selectors

- We can use JavaScript variables as a parameter in a jQuery selector.

```
var par = prompt("Enter the paragraph number");  
console.log($("#pe:eq(" + par + ")"));
```

- Using the “+” symbol we can concatenate the selector with the variable, inserting it in the right place.

```
var cla = prompt("Enter the class name");  
console.log($(". " + cla));
```

