

Instalar mysql

```
admin1@admin1:~$ sudo apt install mysql-server
Leyendo lista de paquetes... Hecho
Creando árbol de dependencias... Hecho
Leyendo la información de estado... Hecho
Se instalarán los siguientes paquetes adicionales:
libecj-fast-perl libecj-perl libevent-threaded-2.1-7t64 libfexi-bin
```

Cuando la instalación esté completa, debes ejecutar un archivo de comandos de seguridad que viene preinstalado con MySQL, éste removerá algunos parámetros peligrosos, así como asegurará el acceso a tu base de datos. Ejecuta el archivo interactivo de comandos mediante:

```
admin1@admin1:~$ sudo mysql_secure_installation
```

Securing the MySQL server deployment.

Connecting to MySQL using a blank password.

VALIDATE PASSWORD COMPONENT can be used to test passwords and improve security. It checks the strength of password and allows the users to set only those passwords which are secure enough. Would you like to setup VALIDATE PASSWORD component?

Press y|Y for Yes, any other key for No: y

There are three levels of password validation policy:

LOW Length >= 8
MEDIUM Length >= 8, numeric, mixed case, and special characters
STRONG Length >= 8, numeric, mixed case, special characters and dictionary file

Please enter 0 = LOW, 1 = MEDIUM and 2 = STRONG: 1

Skipping password set for root as authentication with auth_socket is used by default.

If you would like to use password authentication instead, this can be done with the "ALTER_USER" command.

See <https://dev.mysql.com/doc/refman/8.0/en/alter-user.html#alter-user-password-management> for more information.

By default, a MySQL installation has an anonymous user, allowing anyone to log into MySQL without having to have a user account created for them. This is intended only for testing, and to make the installation go a bit smoother. You should remove them before moving into a production environment.

Remove anonymous users? (Press y|Y for Yes, any other key for No) : n

... skipping.

Normally, root should only be allowed to connect from 'localhost'. This ensures that someone cannot guess at the root password from the network.

Disallow root login remotely? (Press y|Y for Yes, any other key for No) : n

```
... skipping.  
By default, MySQL comes with a database named 'test' that  
anyone can access. This is also intended only for testing,  
and should be removed before moving into a production  
environment.  
  
Remove test database and access to it? (Press y|Y for Yes, any other key for  
No) : n  
  
... skipping.  
Reloading the privilege tables will ensure that all changes  
made so far will take effect immediately.  
  
Reload privilege tables now? (Press y|Y for Yes, any other key for No) : n  
  
... skipping.  
All done!  
admin1@admin1:~$
```