MythX

REPORT 636A62F24170E1001A54724F

Created	Tue Nov 08 2022 14:08:50 GMT+0000 (Coordinated Universal Time)
Number of analyses	1
User	62b1a8425ec4948f52c83856

REPORT SUMMARY

Analyses ID	Main source file	Detected vulnerabilities
a0c978d0-0e18-4916-8e5b-fc2f28e15774	ppyc.sol	13

Analysis a0c978d0-0e18-4916-8e5b-fc2f28e15774 MythX

Started	Tue Nov 08 2022 14:08:58 GMT+0000 (Coordinated Universal Time)
Finished	Tue Nov 08 2022 14:24:00 GMT+0000 (Coordinated Universal Time)
Mode	Standard
Client Tool	Remythx
Main Source File	Ppyc.Sol

DETECTED VULNERABILITIES

HIGH	MEDIUM	LOW
0	0	13

ISSUES

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file
ppyc.sol
Locations

```
6  // OpenZeppelin Contracts (last updated v4.7.0) (utils/Strings.sol)
7
8  pragma solidity ^0.8.0;
9
10 /**
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.1"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file
ppyc.sol
Locations

```
84 // OpenZeppelin Contracts (last updated v4.7.0) (utils/Address.sol)
85
86 pragma solidity ^0.8.1;
87
88 /**
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
309 // OpenZeppelin Contracts (last updated v4.6.0) (token/ERC721/IERC721Receiver.sol)
310
311 pragma solidity ^0.8.0;
312
313 /**
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
339 // OpenZeppelin Contracts v4.4.1 (utils/introspection/IERC165.sol)
340
341 pragma solidity ^0.8.0;
342
343 /**
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
367 // OpenZeppelin Contracts v4.4.1 (utils/introspection/ERC165.sol)
368
369 pragma solidity ^0.8.0;
370
371
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
398 // OpenZeppelin Contracts (last updated v4.7.0) (token/ERC721/IERC721.sol)
399
400 pragma solidity ^0.8.0;
401
402
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
543 // OpenZeppelin Contracts (last updated v4.5.0) (token/ERC721/extensions/IERC721Enumerable.sol)
544
545 pragma solidity ^0.8.0;
546
547
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
574 // OpenZeppelin Contracts v4.4.1 (token/ERC721/extensions/IERC721Metadata.sol)
575
576 pragma solidity ^0.8.0;
577
578
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
603 // OpenZeppelin Contracts v4.4.1 (security/ReentrancyGuard.sol)
604
605 pragma solidity ^0.8.0;
606
607 /**
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
669 // OpenZeppelin Contracts v4.4.1 (utils/Context.sol)
670
671 pragma solidity ^0.8.0;
672
673 /**
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
695
696
697 pragma solidity ^0.8.0;
698
699
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
1254 // OpenZeppelin Contracts (last updated v4.7.0) (access/Ownable.sol)
1255
1256 pragma solidity ^0.8.0;
1257
1258
```

LOW

SWC-103

A floating pragma is set.

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source file

ppyc.sol

Locations

```
1338
1339
1340 pragma solidity ^0.8.0;
1341
1342
```