

项目方案及报价

PROPOSAL

24,000 瓶/小时 PET 热灌装饮料生产线

24,000BPH PET Hot fill Beverage Production Line

供货范围 Scope of Supply: 24,000BPH PET Hot Fill Production Line

报价单号 Quotation No.: TIQ-26-160327-06

制作人 Quoted By: Ken Lin

电话 Tel: +86 18688875952

邮箱 Email: kentillylin@tech-long.com



TECH-LONG PACKAGING MACHINERY CO., LTD

Dated: 27 March 2026

一、项目介绍 Project Introduction

项目名称： 24,000 瓶/小时 PET 热灌装生产线(250ml)

Project: 24,000BPH PET hot fill production line (250ml)

以下数据需与客户协商后选择 To be discussed and confirmed with client for following information:

一、包装容器及规格 Packing Container & Specifications				
包装容器 Packing Type	形状/Shape	灌装容量 (ml) Filling Volume	瓶盖类型 Cap Type	瓶口类型 Neck Finish
PET 瓶	圆形瓶 Round Shape	250ml	塑料平盖 Plastic Cap	28mm PCO 1881
二、吹瓶方式 Blowing Type				
吹瓶机类型 Blowing Machine	吹瓶容量 Bottle Volume	模具类型 Mold Material	除尘装置 De-dusting System	瓶子检测 Inspection System
PET 热瓶	250ml	不锈钢 Stainless steel	静电离子除尘 Static Dust Removing	破瓶检测 Defected bottle inspection
三、灌装方式 Filling Type				
灌装产品种类 Filling Products	产品特性 Product Feature	灌装温度 Filling Temp.	灌装方式 Filling Method	其他配置 Others
功能饮料 Energy drinks	pH<7 显酸性	72-85°C	机械阀重力灌装	选择一项。
四、产品标签及方式 Label				
贴标机类型 Labeler Type	标签材质 Label Material	贴标方式 Label Method		
套标机	PET/PVC	套标方式 Sleeving label		
五、包装材料及方式 Packing Material & Packing Format				
包装材料 Packing Material	包装方式 Packing format	包装材料 Packing Material	包装方式 Packing format	
膜包 Shrinkable film	400ml: 4x6; 4x3			

二、设备分项报价及商务条款

Equipment Price List & Business Terms

I、24,000BPH (250ml) equipment list as followings:

Item	Equipment	描述	Description	数量 QTY (SET)	单价 Unit Price (USD)	总价 Amount (USD)
第一部分：30 吨一级 RO 水处理系统 Part 1: 30TPH RO water treatment system						
1、	预处理系统:	预处理：原水进水→消毒剂添加→15T 原水箱→原水泵组→多介质过滤器→活性炭过滤器→精滤器 5um→UV Raw water intake → disinfectant Dosing → 15T raw water tank → raw water pump → iron/manganese removal filter→ multi-media filter → activated carbon filter → scale inhibitor addition → 5µm fine filtration → UV				
1.1	原水箱进水管 Raw water tank inlet pipe	含气动或电动蝶阀，DN25 ~ DN100， 食品卫生级管道、弯头、三通、活接等 连接件及固定支撑等。	Including pneumatic or electric butterfly valves DN25-100 food-grade piping components such as elbows, tees, unions, and fixed supports.	1	1300.00	1300.00
1.2	消毒剂投加 Disinfectant Dosing	含计量泵，自动控制，配套 100L 锥底 加药桶。含底架	Includes a metering pump, automatic control system, and a 100L conical-bottom dosing drum. Comes with a base frame.	1	350.00	350.00

1.3	原水箱 Raw water tank	φ2200*3660 (直段) , 15T, 锥底卫生型设计, 材质 304, 内外焊缝采用抛光处理; 含爬梯、围拢、护栏、取样阀; 双重保护液位控制、呼吸器、CIP 清洗装置, 水箱曝气装置等。	φ2200*3660 (straight section), 15T, conical bottom sanitary design, Material: 304; Both internal and external welds are polished; Features include ladder, enclosure, guardrails, sampling valve, dual protection level control, breather, CIP cleaning system, and tank aeration device	1	6100.00	6100.00
1.4	原水泵组 Raw water Pump set	两台水泵, Q=45m³/h, H=30m, 恒压供水, 带变频器, 流量计, 压力检测, 流量检测 材质: 304	Two pumps (Q=45m³/h, H=30m) with constant pressure water supply, equipped with frequency converter, flow meter, and pressure/dynamic flow detection. Material: 304	1	5150.00	5150.00
1.5	多介质过滤器 Multi-Media Filter	2 倍反洗流量, DN2200*1800 (直段高度), 网罩式下布水器, 配套进出检修人孔、出料口等标准配件。不含滤料 材质: 304	2 times backwash flow, DN1600*1800 (straight section height), mesh-type lower water distributor, with standard accessories such as inlet and outlet manholes, discharge ports. Filter media not included. Material: 304	1	9200.00	9200.00

1.6	活性炭过滤器 Activated Carbon Filter	2 倍反洗流量, DN2200*2250 (直段高度), 网罩式下布水器, 配套进出检修人孔、出料口, 温度计等标准配件。含蒸汽截止阀, 含减压阀, 疏水阀。不含滤料 材质: 304	2 times backwash flow, DN2200*2250 (straight section height), mesh-type lower water distributor, with standard accessories such as inlet and outlet manholes, discharge ports, thermometers. Including steam stop valve, pressure reducing valve, steam trap. Filter media not included Material: 304	1	9650.00	9650.00
1.7	阻垢剂投加 Scale Inhibitor Dosing	含计量泵, 自动控制, 配套 100L 锥底加药桶。含底架	including a metering pump, automatic control system, and a 100L conical-bottom dosing drum. Comes with a base frame.	1	Included	0.00
1.8	5um 精滤器 5µm Filter	插翅+防泄设计、方便更换滤芯及清洗罐体, 含大通量 5um 滤芯, 与滤器配套防泄漏, 纳污能力强, 进出口压力检测, 取样阀	Including high-flow 5µm filter element, anti-leakage matching with the filter, strong dirt-holding capacity, inlet and outlet pressure detection, sampling valve,	1	2200.00	2200.00
1.9	紫外杀菌系统 UV sterilizer	1 套低压 UV 装置 Q=43m³/hr, 40MJ, 316L 材质 品牌: 乐富易得/华仕威	1 set of low-pressure UV equipment with Q=43m³/hr, 40MJ, material of 316L	1	6400.00	6400.00
2、	RO 膜过滤系统: RO Membrane Filtration System	一级高压泵→一级 RO 系统→纯水箱 First-Stage High-Pressure Pump → First-Stage RO System → Pure Water Tank				

2.1	一级 RO 系统 First-Stage RO System	产能 30m³/hr, 65-70%回收率 RO 高压泵, 304 材质, Q=43m³/h, H=130m 品牌: 南泵 变频器, 30KW, IC2 系列变频控制器 配带数字控制面板 品牌: Danfoss/汇川 30 支 RO 膜元件: AG8040F400, 美国进口膜片, 有卫生许可批件。品牌: GE/同等 PH 检测仪表, 1 ~ 14, 现场显示带远传, 在触摸屏上在线显示, 计量精准 品牌: GF/同等 电导率检测仪表 1000us/cm, 现场显示带远传, 在触摸屏上在线显示, 计量精准	Capacity: Q = 30m³/hr, 65-70% recovery rate, RO high-pressure pump, 304 stainless steel, Q=43m³/h, H=130m, Brand: CNP Inverter, 30KW, IC2 series frequency converter with digital control panel. Brand: Danfoss/Inovance RO membrane elements: AG8040F400, imported brand from the United States with health permit approval. Brand: GE/Equivalent PH detection instrument, 1-14, with on-site display and remote transmission, featuring real-time online display on touchscreen for precise measurement The conductivity detection instrument has a measurement range of 1000 µS/cm, featuring on-site display with remote transmission capability and real-time online display on the touchscreen.	1	35300.00	35300.00
2.2	20T 纯水箱 20T Pure Water Tank	φ2200*4880 (直段), 锥底卫生型设计, 内外焊缝采用抛光处理, 含爬梯、围拢、护栏、取样阀, 双重保护液位控制、除菌呼吸器、防止真空阀、CIP 清	φ2200*3660 (straight section), conical bottom sanitary design, Both internal and external welds are polished. Equipped with ladder, enclosure, guardrails, sampling valve, dual protection level control, bacteria-free respirator,	1	7100.00	7100.00

		洗装置等。	vacuum prevention valve, CIP cleaning device, etc			
3.	前处理外送供水 Water supply system	调配水外送泵/辅助水泵→UV 灯→调配用水点/辅助用水点(出墙 1 米) Blending water via external pump/auxiliary water pump → UV lamp → distribution point/auxiliary water point				
3.1	调配水外送泵 Blending water delivery pump	离心泵, 304 材质, Q=30m³/h, H=35m 品牌: 南泵 卫生型压力表, 316L 材质, DN32 卡盘接口, 0~1.0MPa 品牌: BLD/YD 变频器, 5.5KW, IC2 系列变频控制器 配带数字控制面板 品牌: Danfoss/汇川	Centrifugal pump, 304 stainless steel, Q=30m³/h, H=35m, Brand: CNP Hygienic pressure gauge, 316L material, DN32 flange, 0~1.0MPa, brand:BLD/YD Inverter, 5.5KW, IC2 series frequency converter with digital control panel,Brand: Danfoss/Inovance	1	4000.00	4000.00
3.2	辅助水泵 Auxiliary water pump	离心泵, 304 材质, Q=5m³/h, H=40m 品牌: 南泵 卫生型压力表, 316L 材质, DN32 卡盘接口, 0~1.0MPa 品牌: BLD/YD 变频器, 1.1KW, IC2 系列变频控制器 配带数字控制面板 品牌: Danfoss/汇川	Centrifugal pump, 304 stainless steel, Q=5m³/h, H=40m, Brand: CNP Hygienic pressure gauge, 316L material, DN32 flange, 0~1.0MPa, brand:BLD/YD Inverter, 1.1KW, IC2 series frequency converter with digital control panel,Brand: Danfoss/Inovance	1	1000.00	1000.00

3.3	紫外杀菌系统 UV Sterilization System	低压 UV 装置, Q=45m³/hr, 40MJ, DN32 ~ DN80, 配套手动控制阀门、三通、活接、弯头、支架及连接件, 管道过滤器	Low-pressure UV device, Q = 40m³/hr, 45MJ, DN32 - DN80, with manual control valves, tees, unions, elbows, brackets, and connecting components, pipeline filter	1	6400.00	6400.00
4、	膜 CIP 系统: Membrane CIP System	CIP 水箱 (PE) → CIP 泵 → 管道过滤器 → CIP 清洗点 → 回 CIP 水箱 CIP Tank (PE) → CIP Pump → Pipeline Filter → CIP Cleaning Point → Return to CIP Tank				
4.1	CIP 水箱 CIP Tank	1000L 锥底 PE 水箱, 整体框架设计, 配套药剂投加泵, 自动控制	1000L conical-bottom PE tank, integral frame design, with chemical dosing pump, automatic control	1	700.00	700.00
4.2	膜 CIP 泵 CIP Pump	Q=24m³/h, H=35m, 恒压供水, 带变频器, 压力检测, 流量检测, 管道过滤器 DN25 ~ DN65, 进出水蝶阀、单向阀、管道、弯头、三通、活接等连接件及固定支撑	Q = 24m³/h, H = 35m, constant pressure water supply, with frequency converter, pressure detection, flow detection, pipeline filter DN25 - DN65, inlet and outlet butterfly valves, check valves, pipes, elbows, tees, unions, and other connecting components and fixed supports	1	1500.00	1500.00

5	管道系统 Pipeline System	预处理系统采用 SS316L 材质，其余使用 SS304 材质， 焊接采用单面焊双面成型工艺，整体管路系统无丝口连接，（最终按照客户确定的用水点平面布置图确定）	The pre-treatment system is made of SS316L material, and the rest is made of SS304 material.Welding adopts single-sided welding and double-sided forming process, and the overall pipeline system has no threaded connection. (Finally determined according to the water point layout plan confirmed by the customer)	1	17500.00	17500.00
6.	电气控制系统 Electrical Control System	整体水处理采用中央集成控制方式，设备自动化控制程度高，PLC、扩展模块采用德国 Siemens 品牌，空气开关、中间继电器、交流接触器、指示灯、三档开关等均采用 Schneider/同等品牌，电缆线采用广东南缆/珠江品牌；标准 304 控制电柜，不锈钢线槽。	The overall water treatment adopts a central integrated control method, with a high degree of equipment automation control. PLC and expansion modules are of German Siemens brand. Air switches, intermediate relays, AC contactors, indicator lights, three-speed switches, etc. are of Schneider/equivalent brand. Cable wires are of Guangdong Nanlan/Pearl River brand; standard 304 control cabinet, stainless steel wire trough	1	12500.00	12500.00
Total Price of Part 1: Water Treatment System (USD) 第一部分：水处理系统					126,350.00	
第二部分：前调配系统； 产能：15 吨/小时 Part 2: Blending System ; Capacity: 15TPH						
1.	CIP 系统 CIP System	3 个 CIP 罐（热水/酸/碱），容积 4000L， 双层罐，锥底卫生型设计，内胆材质	✓ 3 CIP tanks (hot water/acid/alkali), with a capacity of 4000L, double-layered design, conical bottom sanitary type,	1	55,000.00	55,000.00

		SS304,壁厚 3mm, 外套材质 SS304,壁厚 2mm, 内外焊缝采用抛光处理, 含爬梯护栏 容积 4000L, 单层罐, 锥底卫生型设计, 内胆材质 SS304,筒体 3mm, 内外焊缝采用抛光处理, 含爬梯护栏 2 个单层浓酸碱罐,材质 SS316L, 容积 50L, 立式储罐, 平顶锥底 2 台 CIP 泵 材质 304 15T,36M,4KW (变频控制) 品牌: 溧阳四方/利百加 2 套蒸汽阀组 (含管式换热器, 截止阀, 减压阀, 疏水阀等) 2 台气动隔膜泵 (酸/碱) P1 品牌: 威尔顿 2 套电导率检测, 流量开关 品牌:	inner tank material SS304, wall thickness 3mm, outer tank material SS304, wall thickness 2mm, inner and outer welds polished, including ladder guardrail ✓ 1 CIP tank (recycling), capacity 4000L, single-layer tank, conical bottom sanitary design, inner liner material SS304, cylinder wall 3mm, inner and outer welds polished, includes ladder guardrail ✓ 2 single-layer concentrated acid and alkali tanks, made of SS316L material, with a capacity of 50L, vertical storage tanks, flat-top and conical bottom ✓ 2 CIP pumps, made of 304 stainless steel, with specifications: 15T,36M, and 4KW (inverter control) ✓ 2 sets of steam valve assemblies (including tubular heat exchangers, globe valves, pressure-reducing valves, steam traps, etc.) ✓ 2 pneumatic diaphragm pumps (acid/alkali) ✓ 2 sets of conductivity detection, flow switch,brand:SELI/E+H/WIKA ✓ 2 vortex flow meters, 2 temperature sensors, with transmitters, and with		
--	--	---	--	--	--

		SELI/E+H/WIKA 2 台涡街流量计, 2 台温度传感器, 带变送器, 带模拟量和脉冲信号 4 套管道过滤器, 304 材质, DN50	analog and pulse signals ✓ 4 sets of 304 stainless steel pipeline filters, DN50			
2.	热水系统 Hot Water system	1 个热水罐, 容积 8000L, 双层罐, 锥底卫生型设计, 封头、内胆材质 SS304, 壁厚 3mm, 外套材质 SS304, 壁厚 2mm, 内外焊缝采用抛光处理, 含爬梯护栏 1 台热水循环外送泵 材质 304 15T,36M,4KW (变频控制) 1 套蒸汽阀组 (含管式换热器, 截止阀, 减压阀, 疏水阀等) 2 套温度传感器, 带变送器, 带模拟量和脉冲信号 1 台涡轮流量计, 带变送器, 带模拟量	✓ 1 hot water tank, capacity 8000L, double-layered tank with conical bottom sanitary design, head and inner tank material SS304, wall thickness 3mm, outer tank material SS304, wall thickness 2mm, inner and outer welds polished, includes ladder guardrail ✓ 1 water tank, capacity 300L, single-layer tank, conical bottom sanitary design, head and cylinder material SS304, wall thickness 2mm ✓ 1 hot water circulation pump, material: 304 stainless steel, 15T,36M,4KW (inverter control) ✓ 1 set of steam valve assembly (including tubular heat exchanger, globe valve, pressure reducing valve, steam trap, etc.) ✓ 2 sets of temperature sensors, with transmitters, providing both analog and pulse signals ✓ 1 turbine flowmeter with transmitter,	1	26,500.00	26,500.00

		和脉冲信号	providing both analog and pulse signals			
3.	溶糖系统 Sugar Dissolving system	①1 个储糖罐，容积 6000L，单罐，锥底卫生型设计，封头、内胆材质 SS304，壁厚 3mm，内外焊缝采用抛光处理，含（LS TI 等）含爬梯护栏（带搅拌） ②1 个溶糖罐，3000L，双层罐，锥底卫生型设计，封头、内胆材质 SS304 罐体壁厚 3mm，外套材质 SS304 罐体壁厚 2mm，内外焊缝采用抛光处理，含爬梯护栏（带搅拌） ③1 台溶糖自吸泵 材质 304 20T,24M,7.5KW 1 台糖浆储存外送泵,材质 304 20T,40M,5.5KW（变频控制） ④1 台糖冷却板式换热器，SS316L 材质 2 段式，15T/H 85℃-45℃-25℃ ⑤1 套蒸汽阀组（含管式换热器，截止	✓ 1 sugar storage tank with a capacity of 6000L, single-tank design featuring a conical bottom and hygienic construction. The head and inner tank are made of SS304 material with 3mm wall thickness. Both internal and external welds are polished. Includes (LS TI, etc.) ladder guardrails (with stirring function). ✓ 1 sugar dissolution tank, 3000L, double-layered tank, conical bottom sanitary design, head and inner tank material SS304, tank wall thickness 3mm, outer tank material SS304, tank wall thickness 2mm, inner and outer welds polished, includes ladder guardrail (with stirring) ✓ 1 self-priming sugar dissolution pump (material: 304 stainless steel, 20T,24M,7.5KW) 1 syrup storage and delivery pump (material: 304 stainless steel, 20T,40M,5.5KW) ✓ 1 unit of sugar cooling plate heat exchanger, SS316L material, 2-stage design, 15T/H capacity, operating temperature range: 85℃-45℃-25℃ ✓ 1 set of steam valve assembly (including tubular heat exchanger, globe valve,	1	38,000.00	38,000.00

		阀, 减压阀, 疏水阀等) ⑥2 套袋式过滤器, 2 套管道过滤器, 304 材质	pressure reducing valve, steam trap, etc.) ✓ 2 bag-house filters, 2 pipeline filters, 304 stainless steel			
4.	辅料系统 Auxiliary Material System	①1 个果汁还原罐, 容积 2000L, 单层 罐, 304 材质, 锥底卫生型设计, 封头、 罐体壁厚 3mm, 内外焊缝采用抛光处 理 (带搅拌) ②2 台快速混合机, 容积 2000L, 单层, 316L 材质, 带减速机 ③1 台辅料外送泵 材质 316L 15T,36M,4KW (变频控制) 1 台果汁 气动隔膜泵, P4 10T/H 1 台 CIP 回 流泵, 304 材质, 20T,24M,7.5KW ④2 套管道过滤器, 316L 材质	✓ 1 juice reduction tank, capacity 2000L, single-layer tank, 304 stainless steel material, conical bottom with hygienic design, head and tank wall thickness 3mm, internal and external welds polished (with stirring) ✓ 2 rapid mixers, 2000L capacity, single-layer design, 316L material, with reducer ✓ 1 auxiliary material delivery pump, material 316L 15T,36M,4KW (frequency conversion control); 1 fruit juice pneumatic diaphragm pump, P4 10T/H; 1 CIP reflux pump, 304 stainless steel, 20T,24M,7.5KW ✓ 2 sets of pipeline filters, 316L material	1	42,000.00	42,000.00
5.	调配系统 Blending System	①3 个调配罐, 容积 12000L, 316L 材 质, 单层罐, 锥底卫生型设计, 封头、 内胆材质 SS304 罐体壁厚 3mm, 内外 焊缝采用抛光处理, 含调配平台 (带搅	✓ ① Three blending tanks with a total capacity of 12,000L, constructed from 316L stainless steel, featuring single-layer design and conical bottom for hygienic operation. The heads and inner tanks are made of SS304 material with 3mm wall	1	95,000.00	95,000.00

		拌), 含(称重 LS TI 等) 含托利多称重模块 ②1 台调配外送泵 材质 316L 15T,36M,4KW (变频控制) 1 台 CIP 回流泵, 304 材质, 20T,24M,7.5KW ③2 套袋式过滤器, 316L 材质 ④1 台涡街流量计, 带变送器, 带模拟量和脉冲信号 品牌: KRONE/E+H/RKS/同等 ⑤1 台涡轮流量计, 带变送器, 带模拟量和脉冲信号	thickness, and both internal and external welds are polished. Each tank includes a blending platform (with stirring function), weighing equipment (LS TI, etc.), and a Torido weighing module. ✓ ② One blending and delivery pump (316L,15T,36M,4KW, frequency-controlled), one CIP reflux pump (304 material, 20T,24M,7.5KW) ✓ ③ Two sets of bag filters, 316L, ✓ ④1 vortex flowmeter with transmitter, supporting both analog and pulse signals (Brand: KRONE/E+H/RKS/Equivalent) ✓ ⑤1 turbine flowmeter with transmitter, supporting both analog and pulse signals			
6.	(RO 水) 板式杀菌机 (RO Water) Plate Sterilizer	5T/H 普通标准机 进水温度: 20--35°C; 杀菌温度: 121°C ; 出水温度: 45°C; 保持时间: 30S	✓ 5T/H standard machine; Inlet water temperature: 20--35°C; Sterilization temperature: 121°C; Outlet water temperature: 45°C; Holding time: 30S	1	35,000.00	35,000.00
7.	(产品) 杀菌机 (Product) Sterilizer	1、产能 12T/H 2、杀菌温度 130-142°C 可调, 罐装温度 85-90°C 可调, 保持时间 5S/15S/30S	✓ 1. Production capacity: 12 tons/hour. ✓ 2. Sterilization temperature: adjustable (130-142°C). Filling temperature: adjustable (85-90°C). Holding time: adjustable (5S/15S/30S).		135,000.00	135,000.00

		可调 3、2 台 12T 物料泵 材质 316L 4、1 台 25T 热水泵 材质 304 品牌：南泵/同等 5 套蒸汽阀组（含管式换热器，截止阀，减压阀，疏水阀等）品牌：瑞克/同等	✓ 3. Two 12-ton material pumps (material: 316L) ✓ 4. One 25-ton hot water pump (material: 304, brand: CNP) ✓ 5. Five sets of steam valve assemblies (including tubular heat exchangers, globe valves, pressure-reducing valves, and drain valves) , brand: Ruike/Equivalent).			
8.	前调配管道系统 Pre-Blending Pipeline System	与产品管道材质为 904L，阀门材质为 316L，CIP 管道为 304， 焊接采用单面焊双面成型工艺，整体管路系统无丝口连接，含卫生型取样阀、卫生型压力表，现场管路系统架空处理。	✓ Pipes in contact with products are made of 904L, valves are made of 316L, CIP pipes are made of 304; ✓ welding adopts single-side welding and double-side forming process; the overall pipeline system has no threaded connections; including sanitary sampling valves, sanitary pressure gauges; on-site pipeline system is overhead-mounted	1	18,000.00	18,000.00
9.	电气控制系统与 电气调试 Electrical Control System and Electrical Commissioning	整体前调配采用中央集成控制方式，设备自动化控制程度高， PLC、扩展模块采用德国 Siemens 品牌，空气开关、中间继电器、交流接触器、指示灯、三档开关等均采用 Schneider/同等品牌， 电缆线采用广东南缆/珠江品牌；标准	✓ The overall pre-blending adopts centralized integrated control mode with high equipment automation control level; ✓ PLC and expansion modules are of Siemens brand (Germany); air switches, intermediate relays, AC contactors, indicator lights, three-position switches,	1	26500.00	26500.00

		304 控制电柜, 不锈钢线槽	etc. are of Schneider/equivalent brand; ✓ cables are of Guangdong Nanlan/Pearl River brand; standard 304 control cabinet, stainless steel wire trough			
第二部分：前调配系统价格总计 (USD) : Total Price of Part 2: Blending System (USD) :						471,000.00

第三部分： 饮料生产线设备 Part3: Beverage Production Line Equipment						
序 列 号	设备名称	中文描述	英文文描述	数量	单价(USD)	合计(USD)
I. 吹灌旋一体机系统: BLOWER-FILLER-CAPPER COMBI BLOCK SYSTEM						
1.	瓶胚翻斗机 Preform Tipper	-用于将瓶胚从储存框装入瓶胚料斗 -瓶胚铁笼尺寸: 1.0x1.2x1.0M	-Used to load preforms from storage crates into the preform hopper - Preform iron cage size: 1.0x1.2x1.0M	1set	13,000.00	13,000.00
2.	瓶胚料斗 Preform Hopper	料斗不锈钢 304 材质; 出坯方式: 皮带输送	Material: 304 stainless steel; Preform discharge method: Belt conveyor	1set	Included	0.00
3.	瓶胚输送机构	皮带式瓶坯提升机, 坯道设计: 密封防尘;	Belt-type preform elevator; Preform	1set	Included	0.00

	Preform Conveying Mechanism	国产电机	track design: Sealed and dust-proof; Domestic motor			
4.	理胚机及下坯机构 Preform Orientator & Loading Mechanism	带坯道回送装置; 封闭型结构	Equipped with preform track return device; Enclosed structure	1set	Included	0.00
5.	吹瓶机 型号: CPX14 产能: 24,000BPH (<500ml) Blow Molding Machine Model: CPX14 Capacity:24,000 BPH (<500ml)	吹瓶机: 14 腔吹瓶机, 烤箱: ✓ 颈部冷却系统, 用于保护颈部, 避免在加热过程中发生变形 ✓ 进口品牌加热灯管 吹瓶主机: ✓ 静电除尘装置 ✓ 伺服电机拉伸-B&R/施耐德 ✓ SEITZ 吹气阀 ✓ 集中中央润滑系统 ✓ 自动控制比例阀 ✓ 冷却水温度监控系统	Blow Molding Machine: 14-cavity Oven: ✓ Neck cooling system: Used to protect the neck and avoid deformation during heating ✓ Imported brand heating lamp Blow Molding Main Machine: ✓ Electrostatic dust removal device ✓ Servo motor stretching - B&R/Schneider ✓ SEITZ blowing valve ✓ Centralized lubrication system ✓ Automatic control proportional valve	1set	774,000.00	774,000.00

		✓ 破瓶检测剔除系统 ✓ 配置回收利用高压气系统 电气控制系统 ✓ MADLER/SEW 电机；带丹佛斯变频器 ✓ PLC 和控制系统：西门子 ✓ 带联锁的安全防护装置 ✓ 带空调的机柜，用于温度控制 ✓ 带 UPS 保护的控制系统 ✓ 配备一套标准备件	✓ Cooling water temperature monitoring system Broken bottle detection and rejection system ✓ High-pressure air recycling system Electrical Control System: ✓ MADLER/SEW motor; Equipped with Danfoss inverter ✓ PLC and control system: Siemens ✓ Safety protection device with interlock ✓ Cabinet with air conditioner for temperature control ✓ Control system with UPS protection ✓ with one set of standard spare parts			
6.	模具#1 -250ML 模具 Mold #1- 250ML Mold	✓ 材质：不锈钢 383ESR ✓ 含一套试验模具	✓ Material: 383ESR stainless steel ✓ Including one set of test molds	15sets	2,200.00	33,000.00

7.	灌装-封盖一体机 Filling & Capping Monoblock 型号: TBFC-SD-JX-6020G.36	主机部分 ✓ 灌装-封盖一体机 ✓ 60 头灌装机及 20 头旋盖机 ✓ 带液位控制系统的热灌装阀，机械式灌装阀 ✓ 所有与产品接触的阀件为 AISI316/SS304 材质 ✓ -带 CIP 假杯装置 ✓ -自带一套瓶型更换件 ✓ -PLC 控制系统，西门子系统 ✓ -自动集中润滑系统 ✓ 达意隆标准旋盖机 ✓ 配置万级洁净顶罩 电器部分	Main Machine Part: ✓ Filling & capping monoblock system ✓ 80-head filler and 30-head capper ✓ Hot filling valve with liquid level control system, mechanical filling valve ✓ All valve parts in contact with products: AISI316/SS304 material ✓ Equipped with CIP dummy cup device ✓ Included one set of bottle type change parts ✓ PLC control system: Siemens ✓ Automatic centralized lubrication system ✓ Tech-long standard capping head ✓ Equipped with dust-proof top cover	1set	310,000.00	310,000.00
----	--	--	--	------	------------	-------------------

		✓ -SEW 电机及丹佛斯变频器 ✓ -UPS 保护系统用于 PLC 控制系统	Electrical Part: ✓ SEW motor and Danfoss inverter ✓ UPS protection system for PLC control system			
8.	送盖机构+理盖机 Cap Feeding Mechanism + Cap Orientator Model: DCT-06	型号:DCT-06 ✓ 皮带式上盖机带盖斗 ✓ -斜斗式理盖机 ✓ -适用于 28MM 盖子	✓ Belt-type cap elevator with cap hopper ✓ Inclined hopper type cap orientator ✓ Suitable for 28MM caps	1set	9,000.00	9,000.00
9.	盖清洗消毒装置 型号: DGX-08 Cap Cleaning & Sterilization Device Model: DGX-08	✓ 两段清洗-第一段药水冲洗; 第二段成品水清洗 ✓ 包括其他关联配置	✓ Two-stage cleaning: First stage with chemical solution rinsing; Second stage with finished water rinsing ✓ Including other associated configurations	1set	25,000.00	25,000.00
II. 吹瓶机辅助单元 Blow Molding Machine Auxiliary Units						

10.	冷水机 Chiller	✓ 水冷式 ✓ 用于吹瓶机的加温机冷却 ✓ (不含冷却塔及其与冷水机之间的连接管路)	✓ Water-cooled type ✓ Used for cooling the heater of the blow molding machine ✓ (Excluding cooling tower and connecting pipelines between the cooling tower and chiller)	1set	9,500.00	9,500.00
11.	模具温度控制设备 Mold Temperature Control Equipment	✓ 油加热方式 ✓ 温度控制系统用于吹瓶机模具的温度控制使用	✓ Oil heating method ✓ Temperature control system for mold temperature control of the blow molding machine	2sets	12,000.00	24,000.00
12.	空瓶成像检测 Empty Bottle Inspection	✓ 瓶底中心度、颈部瓶口/密封表面、颈部瓶口椭圆度	Inspects bottle bottom centering, neck mouth/sealing surface, and neck mouth ovality	1set	25,000.00	25,000.00
13.	加温机排风风罩 (可选项) Heater Exhaust Hood (Optional)	不锈钢材质; 带轴流风机	Material: Stainless steel; Equipped with axial flow fan	1set	Purchased by Customer	0.00
III. 后段包装设备 Down stream Packaging Machines						
14.	全自动套标机	✓ B&R 贝加莱控制系统	✓ With B&R control system	1sets	146,000.00	146,000.00

	型号: HP-500X <u>Automatic Sleeving machine</u> ✓ Model: HP-500X	✓ B&R 贝加莱伺服电机 ✓ 单头套标主机, 包括标签机构、单瓶分装机制及一套圆形瓶更换装置 ✓ 收缩炉: 组合蒸汽收缩炉 ✓ 强化玻璃视窗设计; 内外双层炉体及独立排风阀门设计 ✓ 不停机地面标签解卷机 ✓ 含 1 套瓶型更换件	✓ Including labeling agencies, single bottle distributing mechanism, and one set round bottle replacement ✓ steam shrinking stove ✓ Design of strengthened glass window; double-layer furnace body and independent exhaust valve ✓ Non-stop ground label unwinder ✓ Including 1 set of bottle type change parts			
--	---	---	---	--	--	--

15.	膜包机 型号: MB45 Film Wrapping Machine Model: MB45	✓ 触摸屏: 汇川 ✓ 控制系统: 汇川 ✓ 伺服电机: 与控制系统相匹配 ✓ 变频器: 汇川 ✓ 气动原件: FESTO/Airtac ✓ 传感器: SICK 西克 ✓ 包装格式: 4x6; 4x3 (适用于两种包装规格)	✓ Touch screen: Inovance ✓ Control system: Inovance ✓ Servo motor: Matching the control system ✓ Inverter: Inovance ✓ Pneumatic components: FESTO/Airtac ✓ Sensor: SICK ✓ Packaging formats: 4x6; 4x3 (suitable for two packaging specifications)	1set	105,000.00	105,000.00
16.	倒瓶杀菌链 Bottle Inversion Sterilization Chain	✓ SEW 电机, 达意隆标配链板, ✓ 30 秒杀菌工艺, 适用于 24000BPH 生产线	✓ Motor: SEW; Chain plate: Tech-Long standard ✓ Sterilization process: 30 seconds; ✓ Suitable for 24,000 BPH production line	1set	54,000.00	54,000.00

17.	冷却隧道 Cooling Tunnel	✓ 五段设计, 包括杀菌段, 冷却段, 各种泵类, 管道, 链板, 冷却水喷淋, SEW 电机, 不锈钢排水管路 ✓ 产能: 24,000BPH **不含冷却隧道所需的冷却塔及泵体及管道	✓ Five-section design, including sterilization section, cooling section, various pumps, pipelines, chain plates, cooling water spray, SEW motor, stainless steel drainage pipeline ✓ Capacity: 24,000 BPH **Excluding cooling tower, pump body and pipelines	1set	145,000.00	145,000.00
18.	实瓶输送链 Filled Bottle Conveyor	✓ 带 SEW IE3 电机及优质国产高分子链板, 厚度 8.7MM ✓ 含变速箱, 电机, 变频器; ✓ 电线槽, 不锈钢接水盘, 缓冲平台, 不锈钢排水管路, 单排链, 弯链, 多排链等 ✓ 根据布局图而定	✓ Equipped with SEW IE3 motor and high-quality domestic polymer chain plate (thickness: 8.7MM) ✓ Including gearbox, motor, inverter ✓ Cable tray, stainless steel water receiving tray, buffer platform, stainless steel drainage pipeline, single-row chain, curved chain, multi-row chain, etc. ✓ Determined according to the	1set 800m	304,000.00	304,000.00

			layout drawing			
19.	膜包输送 Pack Conveyor	✓ -滚珠输送链 - (膜包后段) ✓ -带 SEW 电机, 传感器、电线等 ✓ -直链; 弯链及相关装置 ✓ 根据布局图而定	✓ Ball conveyor chain - (post film wrapping section) ✓ Equipped with SEW motor, sensor, cable, etc. ✓ Straight chain; curved chain and related devices ✓ Determined according to the layout drawing	1set 30m	45,000.00	45,000.00
20.	整线输送链电器控制系统 Electrical Control System for Whole-Line Conveyor	✓ 不锈钢控制柜; ✓ 主要电气品牌: 西门子 PLC, 触摸屏/丹佛斯变频器/施耐德低压电器/西克或劳易测光电检测等	✓ Stainless steel control cabinet ✓ Main electrical brands: Siemens PLC, touch screen / Danfoss inverter / Schneider low-voltage electrical / SICK or Leuze photoelectric detection, etc.	1set	28,000.00	28,000.00

21.	密封式风干装置 Air Drying Device	✓ 可视门窗、304 不锈钢机架 ✓ 配高压静音吹风机 7.5KW, 柔性吹嘴 设计可随意调节瓶身局部位吹干	✓ Visible door and window, 304 stainless steel frame ✓ Equipped with 7.5KW high-pressure mute air blower; Flexible air nozzle design for adjustable local drying of bottle body	2sets	8,000.00	16,000.00
22.	灯检箱 Light Inspection Box	人工检测灯检箱	Manual checking station	1set	500.00	500.00
23.	输送线润滑系统 Conveyor Lubrication System	✓ 国产品牌干润滑系统	✓ Domestic brand, Dry lubrication system	1set	13,000.00	13,000.00
24.	打码机 Coding Machine	✓ 喷墨打码机/激光打码机	✓ Inkjet coding machine / Laser coding machine	1set	By Customer	0.00

25.	码垛机-低位码垛机 型号: BMD-40B Palletizer - Low-bay Palletizer Model: BMD-40B	✓ SEW 电机, AirTAC 气动元件 ✓ 空跺板仓板机构>12 个可储存量带缺跺板警报功能 ✓ 层隔板功能 ✓ 层隔板储存功能带缺层隔板报警功能 ✓ 电柜带空调配置 ✓ 跺 板 尺 寸 : 1100mmX1200mmX150mm ✓ 滚筒式码垛输送链	✓ Motor: SEW; Pneumatic components: AirTAC ✓ Empty pallet magazine mechanism: Capacity >12 pallets, with pallet shortage alarm function ✓ Layer separator function ✓ Layer separator storage function with layer separator shortage alarm function ✓ Control cabinet with air conditioner ✓ Pallet size: 1100mmX1200mmX150mm ✓ Roller-type palletizing conveyor chain	1set	145,000.00	145,000.00
-----	---	---	--	------	------------	------------

26.	在线膜缠绕机 型号: R1800FZ-PL Film Wrapping Machine Model: R1800FZ-P	✓ 悬臂式膜缠绕机 ✓ 预拉伸可达 300% ✓	✓ Cantilever-type film wrapping machine ✓ Pre-stretching ratio up to 300%	1set	26,200.00	26,200.00
IV. 公用能源设备 Utility Equipment						
27.	动力柜 Power Cabinet	动力柜及空气开关装置 Power cabinet and air switch device		1set	by Customer	0.00
28.	高压空压机 High-Pressure Compressor Air	-40 公斤压力, 排气量: xxx(根据瓶型设备再推荐合适排气量的机型) -带冷干机, 过滤系统, 缓冲罐, 冷却塔 Pressure: 40 bar; Air displacement: xxx (Suitable model to be recommended based on bottle type equipment) - Equipped with refrigerated dryer, filtration system, buffer tank, cooling tower		1set	by Customer	0.00
29.	低压空压机 Low-Pressure Air	600M3/H		1set	by Customer	0.00

	Compressor				
30.	锅炉 Boiler		1set	by Customer	0.00
V. 包装, 运输及调试 Packaging, Transportation & Commissioning					
1.	出口包装费用(标准陆运和海运包装及熏蒸): Export packaging cost (Standard land and sea transportation packaging & fumigation)		1set	30,000.00	30,000.00
2.	出口运输方式: 出货前 30 天由买卖双方另行确定 (2x40FR+13x40HQ) Export Transportation Method: To be determined separately by both parties 30 days before shipment (2x40FR+13x40HQ)		1set	Excluded	Excluded
3.	服务总价 Total Service Price	12 名技术人员 60 天人工费 (超出部分另算) 仅适用于 1 次服务; 保修期内 1 次回访服务 卸货/安装工作的监督 在客户现场的机械电气安装 借助当地工厂人工和进行安装监督、调试和产线启动; 验收试验和操作员培训	1set	151,000.00	151,000.00

		仅适用于 1 种瓶子的调试 包括验收, 2 天验收运行, 1 个确认瓶每天 8 小时, 生产效率达到≥90%。 Labor cost for 10 technicians for 60 days (Additional charges apply for any excess). Applicable to 1 time service only; one return visit service within the warranty period. Supervision of unloading/installation work. On-site mechanical and electrical installation at the customer's premises. Installation supervision, commissioning, and production line startup with the assistance of local factory labor. Acceptance testing and operator training. Applicable only to the commissioning of 1-confirmed bottles. Including acceptance: 2-day acceptance operation, one confirmed bottle type, 8 hours per day, with production efficiency reaching ≥90%.			
4.	差旅费用 Travelling costs	所有差旅费用, 包括机票、签证、当地住宿、餐饮、当地交通、保险费。 All travel expenses, including air tickets, visas, local accommodation, meals, local transportation, and insurance.	1set	0.00	0.00

第三部分：饮料生产设备及服务费用总价： (USD)	2,431,200.00
Part3: Beverage Production Line Equipment	
总价 (USD)	3,028,550.00

S/N	设备名称	数量	供货备注	单价(USD)	合计(USD)
1.	第一部分：30 吨水处理系统总价： Part 1: 30TPH RO water treatment system	1	达意隆	126,350.00	126,350.00
2.	第二部分：前调配系统价格总计价 Part 2: Blending System	1	达意隆	471,000.00	471,000.00
3.	第三部分：饮料生产设备及服务费用总价 Part3: Beverage Production Line Equipment	1	达意隆	2,431,200.00	2,431,200.00
项目总价 (USD) : EXW :					3,028,550.00
优惠后总价 After Discount(USD):					2,580,000.00

Terms and Conditions:

A. Payment Terms :

- 30% payment by T/T with confirmed purchase upon receipt of invoice.
- 60% Payment upon after FAT but before shipment.
- 10% Payment after commissioning and acceptance.

B.Warranty 质保期

1) Unless otherwise stated, the warranty period shall be 12 months calculated from the date of acceptance or started max 18 Months after B/L date, whichever comes first. 除非另作说明, 保修期为 12 个月, 从验收合格之日起算, 或从提单日期起算最多 18 个月, 以先到者为准。

2) The Manufacturer warrants to the Buyer that, after the issue of the Technical Acceptance Certificate, the Equipment (subject to these conditions) has been manufactured to satisfy the Contract's technical requirement, using materials conforming with International standards, except otherwise provided by Manufacturer with prior notification to Buyer during production, and with workmanship of good quality. In any case for a period of one (1) year, effective from the date of Technical Acceptance Certificate or else from the actual beginning of the Saleable Production (but not later than six (6) months, depending on whichever occurs first), the Manufacturer will remedy at its own costs any defect of the Equipment imputable to defective material, workmanship or design (with the exception of those designs delivered or anyway requested by the Buyer and for which the Manufacturer has disclaimed its responsibility in writing). No other warranty obligation shall be at the charge of the Manufacturer. Common wear parts and consumables are excluded from the warranty.

制造商向买方保证在签署技术验收报告后, 制造商提供的设备是符合本合同技术条款, 采用符合国际标准材料 (制造方在生产过程中提前通知买方的除外) 和高质量的工艺。任何条件下, 从签署技术验收报告之日起或自设备可实际进行可供销售的产品生产之日 (但不超过发货后的 6 个月, 以最早达到的时间为准) 起 1 年内, 制造商应免费对因不合格的材料, 工艺或设计 (由买方要求的设计及制造商已明确以书面形式向买方说明的设计除外) 造成的设备缺陷进行补救。除此以外制造商无任何免费的质量保证责任。常见的易损件及耗材不包括在制造商的质量保证责任中。

3) During the warranty period, the Manufacturer will maintain or provide a turn-around solution within a reasonable period time, any reproducible malfunctions

of the software embedded in or bundled with the Equipment (if any) in accordance with detailed provisions of the conditions.

在质保期内，制造商应在合理的时间内以本合同条款中的详细约定对设备嵌入或配套的软件的任何重复性故障进行修正或提供完整的解决方案。

4) The above warranties shall not apply to defects or damages arising from any of the following reasons: improper use, bad maintenance, modification without the written consent of the Manufacturer, repairs non-correctly carried out by the Buyer, non-compliance with operating manual and the directions for use, faulty replacement materials, normal wear and tear, exposure to conditions outside the range of the environmental specifications, or chemical, electronic or electrical influences which were not contemplated in the Technical Conditions of the Contract. Motors, the electrics and pneumatic components, as well as ancillary equipments and material and all the parts not produced by the Manufacturer are warranted to the same extent as that of the suppliers of these equipments.

以上质量保证不适用于因以下原因造成的任何故障或损失：如不正确的使用，疏于维护，未经制造商书面同意的改造，买方人员进行的不正确维修，任何不符合制造商提供的操作说明或指引的使用，不正确的更换材料，正常磨损，超过设备的环境设定的使用，或任何不符合本合同技术条款的化学及电子，电气的影响因素。电机、电器、气动元件、材料以及非制造商生产的零配件及辅助设备由相关元件或设备的原始供应商负责保修。

5) The above warranty shall constitute the only warranty and sole remedy of the Buyer and the sole liability of Manufacturer; The warranties of this paragraph are in lieu of all other warranties, expressed or implied the implied warranties of merchant ability and fitness for a particular purpose and all other warranties, representation and conditions, express or implied by statute, trade usage or otherwise are excluded and shall not be applied to the equipment delivered, except for warranties which by law cannot be excluded or limited.

以上质量保证是由制造商对买方的唯一质量保证及补救措施和制造商的唯一责任所构成。本条款中所列明的质量保证应代替任何其它明示或暗示的适销性、适用于特定用途的保证及其它所有以陈述或条件，法律明示或默示的或贸易惯例所构成的或对制造商提供设备无法使用的保证。法律规定或限定的质量保证除外。

6) The following items are excluded from the Warranty: normal wearing and consumable parts. 下列事项不在保修范围内：正常的磨损和易耗件。

《设备验收标准与技术指标》

"Equipment Acceptance Criteria and Technical specifications"

一、验收测试方法

I . Acceptance test method

1、验收测试时间为安装调试完成，设备正常生产后。

1. The acceptance test time is after the installation and commissioning are completed and the equipment is in normal production.

2、验收测试由买卖双方共同派员参加。

2. Both parties send engineers to participate the acceptance test together.

3、验收测试，时间为 2 天，每天连续生产 8 小时。

3. The acceptance test lasts 2 days, takes continuous production for 8 hours a day.

二、生产线设备验收标准:

II . Production line equipment acceptance standards:

1、整线生产效率≥90%。

1. The production efficiency of the whole line is $\geq 90\%$.

A. 设计产能： **36000** 瓶/小时（ **400 ml** 瓶型） （连续 **3** 天 **1** 个班次的平均值）为判断依据；

Designed production capacity: 36000bottles/hour (400 ml bottle type) (average of 1 shifts in 2 consecutive days) as the basis for judgment;

B. 进行效率测试时，因原液、容器、生产物料、其他能耗配备装置等非我司提供设备、物料不良引起的生产线停机时间，应在 8 小时测试时间内扣除；During the efficiency test, the downtime of the production line caused by raw liquid, containers, production materials and other energy-consuming equipments, the pool materials, which are not provided by our company, should be deducted within the 8-hour test period;

C. 计算方法 Calculation method:

D.

$$\begin{aligned} \text{生产效率} & \text{Production efficiency} \\ &= \frac{\text{8 小时总产量} \text{8 hours total output}}{(\text{8} - \text{非我司设备引起的停机时间}) \times \text{设计产能}} \times 100\% \\ &= \frac{\text{8 hours total output}}{(\text{8} - \text{Downtime not caused by our equipment}) \times \text{Design capacity}} \times 100\% \end{aligned}$$

注：公式中设计产能单位为：瓶/小时。

Note: The design capacity unit in the formula is: bottles/hour.

2、废品率≤3%。（不包含厂方所提供的原材料质量问题）。

The rejection rate≤3%. (Not including the quality of raw materials provided by the manufacturer).

注：废品率包括：产品液位或者容量、重量（测量方法按照灌装定量方式定）超出合同允许误差，损瓶、损盖，歪盖及漏盖。

Note: The rejection rate includes: product level or capacity, weight (measurement method is determined according to the filling quantitative method) exceeding the allowable error of the contract, damaged bottles, damaged caps, crooked caps and missed caps.

C. Lead time

6 months on receipt of down payment and confirmed technical requests.

D. Quotation Validity

If no change for technical requests, the validity of this quotation only 30days.

E. Remarks

Delivery place: Appointed Port

Full bottle conveyor: Multi-lance conveyor will be calculated into single lance.

The required utilities should be supplied to appointed connection for equipments, such as water/chilled water, electricity, compressed air etc.