The Kronos Fusion Triple Product: Maximizing $nT\tau_E$ in a High-Field Spherical Tokamak

Table of Contents

The Kronos Fusion Triple Product: Maximizing $nT\tau E$ in a High-Field Spherical Tokamak *1*

Introduction 2

The Fusion Triple Product and Lawson Criterion 2

Kronos S.M.A.R.T. Tokamak Architecture Overview 3

Maximizing Plasma Pressure: High Magnetic Fields and High-β Shaping 4

Magnetic Pitch Gradient Control and Confinement Optimization 6

Comparative Performance Metrics and Electrical Gain (Q_e) 8

Materials and Engineering Constraints at 30 Tesla Fields 11

Conclusion 14

References 17

Introduction

Fusion power systems are fundamentally constrained by the **Lawson triple product** – the product of plasma ion density n, temperature T, and energy confinement time τ_E. This figure of merit must exceed a threshold (on the order of 3×10^{21} keV·s·m^{-3} for the conventional deuterium–tritium (D–T) fuel) to achieve net energy gain[1]. Advanced **aneutronic** fusion fuels such as deuterium–helium-3 (D–^{3}He) and proton–boron-11 (p–^{11}B) demand even higher triple products – one to two orders of magnitude above D–T – due to their higher optimal temperatures and radiation losses[2]. The **Kronos S.M.A.R.T. tokamak** (Superconducting, Minimum-Aspect-Ratio Tokamak) is a next-generation fusion reactor explicitly designed to meet these extreme conditions. It leverages a compact **spherical tokamak** geometry, **ultra-high magnetic fields**, and a suite of novel control and materials innovations to push $nT\tau_E$ into the aneutronic regime while directly converting much of the fusion energy into electricity. In doing so, Kronos aims to deliver the highest electric power density of any fusion architecture[3], far surpassing the net electrical gain (**Q_e**) of conventional D–T machines like ITER or ARC. This whitepaper provides a rigorous analysis of the triple product in Kronos, detailing how its design optimizes each term – density, temperature, and confinement – via **magnetic pitch control**, **high-beta spherical plasma shaping**, and **30+ tesla HTS magnets**. We derive the relevant scaling laws and performance metrics, compare against existing D–T systems, and present simulation-backed data on how Kronos achieves superior confinement and energy conversion in aneutronic operation.

The Fusion Triple Product and Lawson Criterion

In magnetic confinement fusion, the triple product $nT\tau_E$ encapsulates the core physics requirements for ignition or high gain. It derives from the Lawson criterion, which dictates that a plasma must maintain a sufficient density of fuel ions n at a high temperature T for a long enough energy confinement time τ_E to produce more fusion energy than is lost. For D–T fuel (the easiest to ignite), this breakeven condition is approximately $nT\tau_E \gtrsim 3 \times 10^{21}$ keV·s·m^{-3}[1]. Aneutronic fuels demand substantially more: for example, D–^{3}He requires on the order of 10^{22} keV·s·m^{-3} and p–^{11}B on the order of 10^{23-24} keV·s·m^{-3}[2]. These higher requirements stem from less favorable reaction cross-sections at lower temperatures and greater energy losses (e.g. bremsstrahlung radiation) at the extreme temperatures (50–200 keV) needed for D–^{3}He and p–^{11}B[4]. Table 1 summarizes these target triple product levels for key fuels.

Table 1 – Lawson Triple Product Targets for Fusion Fuels[2]
- **D–T:** $T \approx 10 - 15$ keV, target $nT\tau_E \sim 3 \times 10^{21}$ keV·s·m^{-3} (80% of fusion energy in neutrons).
- **D–^{3}He:** $T \approx 50 - 100$ keV, target $nT\tau_E \sim 1 - 3 \times 10^{22}$ keV·s·m^{-3} (most energy in charged particles).
- **p–^{11}B:** $T \approx 150 - 200$ keV, target $nT\tau_E \sim 3 \times 10^{23} - 10^{24}$ keV·s·m^{-3} (aneutronic, but very high radiation losses)[2].

Achieving a given triple product can be approached in different ways (e.g. lower density and very good confinement, or very high density with short confinement as in inertial fusion). Magnetic tokamaks operate in the low-density, long-confinement regime. For instance, ITER and ARC (both D–T tokamaks) are designed for $n \sim 10^{20}$ m^{-3}, $T \sim 10 - 20$ keV, and $\tau_E \sim 0.5 - 1$ s, giving $nT\tau_E \approx 3 \times 10^{21}$ keV·s·m^{-3}[5] – just at the D–T breakeven yardstick. In contrast, an aneutronic reactor like Kronos must sustain perhaps $n \sim$ few $\times 10^{20}$ m^{-3} at $T \sim 50 - 100$ keV with τ_E of order 0.3–0.5 s to approach 10^{22} keV·s·m^{-3} for D–^{3}He burn, and push even further for p–^{11}B conditions[6][7]. These figures are daunting, but Kronos was

conceived to meet them by **raising each factor of the triple product beyond what conventional designs allow**. Crucially, Kronos also emphasizes that **it is not enough to satisfy the physics threshold – one must efficiently convert the fusion energy to electricity**. In a traditional D–T tokamak, even a achieved triple product yields only ~35% of fusion energy as electricity (the rest lost as heat)[8]. Aneutronic systems like Kronos, by capturing charged fusion products directly as electric current, can in principle achieve 60–70% energy conversion[9][10]. This essentially **doubles** the effective electrical gain for a given plasma performance[10][11]. A plasma achieving $nT\tau_E \approx 10^{22}$ keV·s·m^{-3} with 65% direct conversion can yield as much net electric power as a D–T plasma at 3×10^{21} keV·s·m^{-3} running on a 35% efficient steam cycle[11]. In summary, the triple product sets the **physics** requirement, but the **economic viability** is determined by how that fusion energy is harnessed[12]. Kronos's design philosophy is to pursue the high $nT\tau_E$ needed for aneutronic fuels **and** to integrate high-efficiency energy conversion, thereby achieving an unprecedented electric power density per cubic meter of plasma[13].

Kronos S.M.A.R.T. Tokamak Architecture Overview

Kronos Fusion Energy's S.M.A.R.T. reactor is a compact, high-field spherical tokamak tailored for aneutronic D–^{3}He and p–^{11}B fusion. "S.M.A.R.T." denotes *Superconducting, Minimum-Aspect-Ratio Tokamak*[14] – in other words, a spherical tokamak (aspect ratio $A \approx 2$) employing high-temperature superconducting (HTS) magnets. Table 2 summarizes key design parameters for Kronos alongside a conventional tokamak:

Table 2 – Key Design Parameters: Kronos vs. Conventional Tokamak
- **Major radius R:** ~2.0 m for Kronos (very compact), vs. ~6 m in ITER-scale devices[15].
- **Minor radius a:** ~1.0 m (elongated cross-section) for Kronos[15].
- **Aspect ratio $A = R/a$:** ~2 (spherical tokamak) for Kronos, vs. ~3 in ARC, ~>3 in ITER.
- **Elongation κ:** >2.5 in Kronos (highly elongated plasma)[15].
- **Triangularity δ:** negative ($\delta < 0$, i.e. inverted-D shape) in Kronos[16] for stability, vs. positive in standard tokamaks.
- **Toroidal field B_T:** ~30 T at the magnets (on-axis field ~10 T), using REBCO HTS coils (much higher than ITER's ~5–6 T on-axis)[17].
- **Plasma beta $\beta = 2\mu_0 p/B^2$:** target ~30–40% in Kronos[18], vs. ~2–5% in ITER (low-β large aspect ratio).
- **Pulse/Operation:** Steady-state **non-pulsed** operation in Kronos (fully superconducting, high-bootstrap fraction), vs. pulsed or limited pulse in many traditional designs.
- **Fuel cycle:** D–^{3}He startup, transitioning to p–^{11}B (via intermediate p–^{6}Li reactions to breed ^{3}He in situ) – fully aneutronic cycle[19]. No tritium breeding blankets needed (only lithium blankets for ^{3}He breeding and shielding).
- **Energy conversion:** Direct energy conversion (DEC) built into first wall (electrostatic collectors, thermionic converters, etc.) achieving >60% direct electrical efficiency[20][21], vs. thermal conversion (~35%) in conventional designs.
- **Neutron load:** <1% of a D–T machine's neutron flux[22] – dramatically reducing activation and allowing simpler maintenance and licensing.

In essence, Kronos is a **high-β, high-field spherical tokamak** with advanced shape control and materials. Its mission is to realize aneutronic fusion in a device far smaller than ITER or ARC, by taking advantage of physics scaling that favor high field and by avoiding the neutron-related engineering burdens

of D–T. Kronos's steady-state operation is enabled by strong intrinsic plasma current drive (a large bootstrap current fraction at high beta) and external heating/current-drive systems, rather than relying on a central solenoid. Indeed, Kronos's ignition strategy accepts a higher required temperature (~50 keV) and provides substantial external heating power to reach it[23][24], trading "easier" D–T ignition for a **far superior overall power plant** with aneutronic output[25][24]. Once ignited, a projected plasma gain of $Q \approx 40$ (fusion power ~40× input power) is achieved, meaning only a few percent of the reactor's electric output must be fed back into plasma heating[24]. The majority of the fusion energy emerges in charged particles (α particles, protons) rather than neutrons[19], and Kronos is engineered to capture over 60% of that energy *in situ* as electricity[20][21]. The net effect is that Kronos can produce **net electric power** with a smaller plasma performance margin than a D–T machine – yet it also pushes that plasma performance to unprecedented levels to burn the advanced fuels.

To support 30 T magnetic fields and long lifetime, Kronos employs a **materials-first design philosophy**[26]. Rare-earth barium copper oxide (REBCO) HTS tapes are used in the toroidal and poloidal field coils, leveraging their ability to carry critical current at high fields. These HTS magnets are robustly supported by a structure of high-strength alloys (e.g. MP35N, an Ni-Co-Cr-Mo superalloy) and high-modulus carbon-fiber composites to withstand the enormous Lorentz forces without excessive strain[27][28]. Advanced plasma-facing materials (ultra-refractory ceramics, graphene composites, high-entropy alloys) are integrated to handle the intense thermal and particle flux in an aneutronic plasma[29][19]. In the sections that follow, we detail how each aspect of the Kronos design – magnetic field, plasma shaping, pitch control, direct conversion, and materials – contributes to maximizing the triple product $nT\tau_E$ and the net electrical gain.

Maximizing Plasma Pressure: High Magnetic Fields and High-β Shaping

A hallmark of Kronos is its **ultra-high magnetic field strength**, on the order of 30 teslas in the toroidal field coils. Fusion performance benefits superlinearly from increasing the magnetic field. At fixed plasma beta (ratio of plasma pressure to magnetic pressure), a stronger field allows a higher absolute pressure (since $p \approx \beta B^2/2\mu_0$). Moreover, energy confinement in tokamaks empirically improves with higher field (and machine size) in most scaling laws. As a result, the **fusion power density** in a tokamak roughly scales as $P_f \sim \beta^2 B^4 V$, where V is the plasma volume[30]. This scaling can be understood in a simplified way: fusion reaction rate $\propto n^2\langle\sigma v\rangle \sim n^2T^2$ (for Maxwellian plasma in the 10–100 keV range), while $nT \sim \beta B^2$ (for a given β) and higher field also tends to allow higher T before magnetohydrodynamic limits. Thus P_f per volume grows roughly with B^4 if β is held ~constant[30]. **Kronos simultaneously pushes B and β to unprecedented levels**, enabling reactor-level power output in a device only ~1/5 to 1/10 the volume of ITER or similar D–T machines[31].



Figure 1: Spherical tokamak geometry and support structure in service of performance. Kronos's compact spherical architecture (aspect ratio ~2) with an inverted-D plasma shape (negative triangularity) allows very high plasma pressure (β ~ 30–40%) without disruptive edge instabilities. The diagram highlights key design features: a ceramic central bucking cylinder and ice-powered cryogenic pistons that preload the structure to handle Lorentz forces, slight helical pitch of TF coils to spread stress, and a divertor repositioned at larger radius for better heat handling. The result is enhanced confinement and stability at extreme fields. The fusion performance scales strongly with these parameters (roughly $P_f \propto \beta^2 B^4 V$), enabling Kronos to achieve multi-fold higher power density than conventional tokamaks of much larger size[30][32].

Achieving **β ≈ 30–40%** in a stable manner is critical to Kronos. Spherical tokamaks inherently operate at higher β than conventional aspect ratios; for example, experiments have exceeded 30% β in spherical plasmas, whereas ITER is limited to a few percent. Kronos's plasma shaping further augments this. The **negative triangularity** cross-section (inverted D-shape) has been shown to improve stability and avoid large edge instabilities (ELMs) even at high pressure[33]. By combining the spherical tokamak's high-β capability and negative triangularity's stabilizing effect, Kronos can sustain a high pressure without transient disruptions[34][35]. The target volume-averaged plasma pressure is on the order of 4–6 MPa (at 30 T field) – several times higher pressure density than ITER. This directly multiplies the fusion reaction rate and thus the triple product (since nT is higher for a given temperature).

High β also means a large fraction of the plasma current is self-driven by the plasma pressure gradient (bootstrap current). Kronos's configuration is expected to be largely self-driven, reducing the need for external current drive and allowing steady operation. The design includes a close-fitting, low-activation conducting wall and active feedback coils just behind the blanket to provide passive and active stability for the high-β plasma[36]. In essence, **Kronos's compact, high-field approach "bends" the standard tokamak scaling in its favor** – instead of a huge device to reach high triple product, it uses extreme field and optimized shape to get high pressure and confinement in a small volume. The cost is an engineering one: extraordinary magnet and structural stresses. We address below how advanced materials make that feasible. The payoff is clear in comparative metrics: Kronos's plasma (D–^{3}He mode) at $nT\tau_E \sim 10^{22}$ keV·s·m^{-3} and ~65% conversion efficiency can yield on the order of 100–200 MWh$_e$ per cubic meter, whereas an ARC/ITER-class D–T plasma (~3×10^{21}, 35% eff) would net only ~10–20 MWh$_e$/m^3[17][37]. Pushing both **B** and **β** to the limit gives Kronos an inherent advantage in potential power density.

Magnetic Pitch Gradient Control and Confinement Optimization

While high field and pressure set the stage, achieving a long **energy confinement time** τ_E and minimizing losses are equally important for maximizing the triple product. Kronos employs an innovative **magnetic pitch gradient optimization strategy** to control particle orbits and heat transport. Unlike a conventional tokamak where field lines twist purely as a result of plasma current, Kronos **pre-shapes and dynamically tunes** the field-line pitch (the helical winding angle of field lines around the torus) using a combination of specially wound coils and current profile control[38][39]. By tailoring the **spatial gradient of field-line pitch (q-profile)**, Kronos can improve confinement of high-energy fusion products and guide them either to remain trapped or to escape along desired paths for energy extraction.

1. Helically Wound Toroidal Field Coils: Kronos's toroidal field (TF) magnets are each built with a slight **helical twist (~3–5°)** instead of being perfectly vertical rings[40][41]. This means the TF coils themselves provide a small amount of rotational transform (like a torsatron or stellarator) even before plasma current flows. The effect is twofold: it **distributes magnetic loads** more evenly (reducing hot spots in the coil stress) and it **"pre-twists" the field lines** to supplement the plasma-generated twist[42][41]. Past experiments (e.g. Proto-CIRCUS) showed that tilted coils can produce net rotational transform and even reduce toroidal field ripple[43]. In Kronos, the modest ~5° twist is enough to introduce a continuous gentle shear in the confining field, effectively seeding a favorable q-profile. This external twist means the plasma doesn't rely solely on its own current for field-line twisting, which in turn relaxes constraints on current density and allows more freedom in shaping the safety factor $q(r)$.

2. Plasma Current Profile Shaping: On the plasma side, Kronos actively controls the distribution of its toroidal plasma current to sculpt the **q-profile** (safety factor profile) during operation. High-powered neutral beam injection (NBI) and radio-frequency (RF) current drive are used not just for heating but to drive current in specific regions of the plasma[44][45]. By adjusting beam deposition and RF waves, operators can make the current profile more peaked or more broad. This in turn changes the **magnetic shear** (radial gradient of q). Higher shear in certain regions can stabilize turbulence and MHD modes. Kronos's inherently low aspect ratio and strong shaping already give naturally high edge shear[15]. The negative triangularity shape further redistributes current such that the inner leg of the plasma has a safer q-profile. Through a combination of early induction (for initial profile) and sustained non-inductive drive, Kronos can maintain an optimized q(r) throughout the pulse[46][47]. This dynamic q-profile control – an approach demonstrated in advanced tokamak experiments – means Kronos can fine-tune confinement (by suppressing deleterious instabilities) on the fly.

3. Auxiliary "Bucking" Mirror Coils: Encircling the plasma at the top and bottom, Kronos has special superconducting coils known as **mirror coils** or bucking coils[48][49]. These are part of the poloidal field system and can be powered to locally bump the magnetic field strength at the axial ends of the plasma – analogous to the mirrors in a magnetic mirror trap. By increasing the field at the ends, these coils create a **mirror ratio** that reflects charged particles back toward the core. In effect, the mirror coils **cap the ends** of the flux tube with higher field, forcing field lines to bend more sharply as they exit the plasma and thus increasing their pitch angle near the ends[49][50]. By adjusting the current in these bucking coils, operators can **tune the end-field-line pitch in real time**[50][51]. A higher mirror coil current produces a stronger "mirror" (tightening confinement of fast particles), whereas lowering the mirror field allows field lines to straighten out and let particles escape along those paths. This capability is unique to Kronos: it acts like an electromagnetic lens or valve that can confine **or** extract fast particles as needed[51][52]. Importantly, the mirror coils are made of the same REBCO conductor and housed in robust ceramic-supported structures so they can handle the ~4 T mirror fields they produce without damage[53].

4. Synergistic Pitch Profile Control: The combination of a pre-twisted TF coil set, actively shaped plasma current, and tunable mirror coils gives Kronos fine-grained control over the **magnetic shear and field-line pitch** from the plasma core to the edge[53][54]. The result is a strongly sheared magnetic configuration that has multiple benefits: it **"corrals" high-energy particle orbits**, suppresses certain transport modes, and guides particle trajectories in desirable ways. Specifically, a high pitch gradient near the edge acts to **pinch drift orbits away from the wall** – if a fast ion drifts outward, it encounters regions of different field-line twist, which alter its path and tend to send it back inward before it can reach the wall[55][56]. This reduces **orbit losses**, especially on the inboard side of the tokamak where field symmetry is hardest to maintain. Likewise, by tailoring pitch at the plasma ends, Kronos can ensure that most fusion-born ions **do not free-stream out** into wall structures, unless intentionally permitted.

Minimizing Ripple and Fast-Ion Losses: Toroidal field **ripple** – the small variations in field strength from the discrete TF coil gaps – can induce losses of fast ions, particularly in spherical tokamaks which often have fewer coils. Kronos mitigates this by using a relatively **high number of TF coils** (the exact number is proprietary, but likely on the order of 16 or more) and possibly adding ferritic inserts to smooth the field[57][58]. Studies indicate that with 16 coils, a spherical tokamak can keep ripple below ~1%, limiting prompt alpha particle losses to ~2–5%[59][60]. Kronos likely follows this approach so that inherent ripple losses are negligible. Furthermore, the **negative triangularity shaping** provides more clearance on the

inner leg – the plasma is shifted such that the closest approach to the inner wall is not at the midplane, giving fast ions extra "breathing room" and reducing their chances of hitting the wall[61]. The **helical TF coil twist** also helps by smearing out the ripple patterns poloidally: as a particle makes many toroidal transits, the ripple phase is averaged out, effectively smoothing the field non-uniformity[62][63]. Finally, the mirror coils can be fine-tuned to compensate any residual ripple by creating small counter-fields on the inner side[64]. In summary, Kronos tackles one of the thorniest issues in compact tokamaks – fast ion containment – through a combination of symmetry (many coils, symmetric design) and active control (pitch shaping and mirror fields). The design goal is to keep **alpha losses below ~5%** of fusion alphas[65], which is on par with large devices like ITER. **"The mirror coils frame the plasma like parentheses, ensuring order at the edge"**, one Kronos document poetically notes[66] – meaning they keep what must be confined *inside* and eject what should be extracted *along controlled channels*[66].

Fast Particle Confinement and Direct Conversion: The ultimate aim of pitch optimization is not only to confine fusion α-particles and protons for plasma heating but also to **redirect them for energy conversion**. In aneutronic fusion, >95% of the fusion energy is carried by charged particles and X-rays[67]. If all those fast ions simply thermalize in the plasma or dump into walls, the benefit of aneutronic fuel is lost. Kronos's pitch control strategy ensures that the majority of energetic fusion products **remain in closed orbits long enough to either slow down in the plasma (contributing to self-heating)** or to be **guided into special exhaust channels for direct energy capture**[68][69]. For example, by slightly reducing the mirror field at a particular flux tube, Kronos can preferentially stream some α-particles out along that path to a waiting **direct converter** plate, while still confining the bulk of them. High-energy protons (14.7 MeV from D–^{3}He, or 3 MeV from p–^{6}Li reactions) can similarly be siphoned to direct converters. This **balance between confinement and extraction** is crucial. Kronos's control system, augmented by AI, continuously tweaks the mirror coil currents and other actuators to maintain the optimal distribution – enough fast particles kept in the plasma to sustain the burn, but not so many that their energy is wasted as heat when it could be extracted as electricity. The integrated **digital twin** of the reactor plays a key role here, running in parallel to predict plasma behavior and adjust settings in real-time[70][71]. With >99.99% accuracy predictive models, the digital twin can foresee drops in edge shear or incipient orbit losses and command, for instance, a 2% increase in mirror coil current or a 5 kA tweak in core current drive to counteract it[72][73]. This autonomous feedback ensures no important parameter drifts far from its setpoint[74]. The result is a plasma that is always nudged toward optimum performance, maximizing confinement time τ_E. In effect, Kronos's **magnetic pitch gradient optimization** is a multifaceted approach that **raises the effective confinement of energy and particles**, directly boosting $nT\tau_E$, while simultaneously enabling **direct energy conversion** of the charged particle energy. This is a distinguishing innovation that sets Kronos apart from previous tokamaks.

Comparative Performance Metrics and Electrical Gain (Q_e)

A key claim of Kronos Fusion Energy is that their S.M.A.R.T. reactor will **outperform existing D–T systems on net electric output**, even if the raw triple product values are of the same order of magnitude. Table 3 compares the plasma performance and expected energy output of Kronos versus several other fusion programs (data drawn from technical assessments):

Table 3 – Comparative Plasma Performance and Energy Output[75][37][76]

Company	Approach	Fuel	Target Timeline	Key Risks	Kronos Comparative Advantage
Commonwealth Fusion Systems (CFS)	Compact tokamak (SPARC → ARC) using REBCO HTS magnets	D–T	Early 2030s	• Heavy 14 MeV neutron flux → magnet degradation & embrittlement • Tritium scarcity (< 25 kg/yr) + costly breeding blankets • Full nuclear licensing & decommissioning burden • High O&M and insurance costs	• **Aneutronic fuels (^{3}He/^{6}Li/D)** eliminate tritium and neutron damage • **Non-nuclear classification** → fast, low-cost deployment • **Extended magnet life > 20 yrs** • **Lower CAPEX/OPEX** via simplified systems
Helion Energy	Pulsed field-reversed configuration (FRC) with magnetic compression	D–^{3}He hybrid	Demo 2028	• Cyclic fatigue from high-frequency pulsing • Synchronization and coil timing errors • ^{3}He scarcity & D–D side-reaction variability • Efficiency limited by piston recovery	• **Steady-state operation** (no fatigue) • **Closed toroidal confinement** = geometric stability • **Continuous DEC 70–90 % efficiency** • **In-situ ^{3}He breeding** from Li-6
TAE Technologies	Beam-driven FRC with neutral-beam injection	p–B^{11}	Mid-2030s	• > 1 billion °C temperature requirement • High bremsstrahlung X-ray losses (Z = 5) • Beam-target inefficiency & poor scaling • Thermal efficiency < 40 %	• **Mixed D–^{3}He–^{6}Li fuel** burns at ~150–200 MK • **Negative triangularity SMART geometry** enhances stability • **Direct electric conversion** (no turbines) • **Lower radiation loss profile**
Zap Energy	Sheared-flow stabilized Z-pinch	D (R&D); D–T planned for plant	~2030	• Linear geometry → Rayleigh–Taylor & sausage instabilities • Scaling density × confinement unproven • Neutron activation from D–D • Electrode erosion & wall damage	• **Toroidal SMART design** eliminates linear instabilities • **Aneutronic blend** cuts neutron flux • **30 + T REBCO magnets** maintain stability • **Replaceable first wall** extends lifetime
General Fusion	Magnetized-target fusion (MTF) with liquid-metal piston liner	D–T	Early 2030s	• Hundreds of synchronized pistons → mechanical asymmetry risk • Molten-metal contamination & activation • Complex maintenance and waste handling • Pulsed cycle < 40 % efficiency	• **No moving parts or fluids** → high reliability • **All-electromagnetic confinement** • **Direct energy conversion (DEC)** doubles efficiency • **Modular factory-built systems** for mass deployment

---

Kronos's performance is notable in both the normalized triple product and the net electricity metrics. In D–^{3}He mode, Kronos is designed for $nT\tau_E$ on the order of 1–3×10^{22}, about 4–8× the D–T Lawson criterion[6]. ARC and ITER operate near the 3×10^{21} level, but because 80% of their fusion energy is in neutrons (requiring thermal conversion at ~35% efficiency), their net electric output per volume is relatively low (tens of MWh$_e$/m^3)[77][78]. Kronos, recovering ~65% of energy directly, can achieve dozens to hundreds of MWh$_e$/m^3[17][18]. Helion's pulsed approach reaches a respectable effective triple product (~1×10^{22}) but only in millisecond bursts[81], and its inductive recapture yields maybe 50% electrical efficiency. TAE and similar p–^{11}B concepts tout very high theoretical $nT\tau$ requirements (10^{34} in cgs units) but face daunting physics (temperatures >10^9 K and high bremsstrahlung losses)[82].

Several qualitative points emerge from this comparison:

- **Kronos vs. Conventional D–T (ITER/ARC):** Kronos's **plasma Q (fusion gain)** is expected to be on par or higher (Q_plasma ~40 for Kronos vs. Q≈10–30 for ITER/ARC)[24], but critically, Kronos's **electrical Q_e** is far superior. With direct conversion, a Q≈40 plasma can yield Q_e ≈ 24–26 (60–65% of fusion power to electricity), whereas ITER's Q≈10 would only be Q_e ≈ 3.5 (35% of 10) if it were a reactor[10][11]. In practical terms, **1 m^3 of Kronos plasma could generate on the order of 100–200 MWh of electricity per run**, while 1 m^3 of ITER plasma would generate perhaps 10 MWh[17][78]. This is a 10× advantage in power density. Additionally, Kronos's steady-state operation at high capacity factor (>90% uptime)[83] means it delivers power continuously, unlike ITER which will have long downtimes and pulsed operation constraints.

- **Kronos vs. Other Aneutronic Concepts:** Private fusion ventures like TAE Technologies (field-reversed configuration with p–^{11}B) and Marvel Fusion (laser-driven p–^{11}B) often cite extremely high target triple products (≳10^{23}) because p–^{11}B requires it[84]. However, **having a high $nT\tau$ "on paper" is not the**

same as producing useful electricity. TAE's and Marvel's approaches operate in a regime of 150–400 keV ion energy where bremsstrahlung X-ray losses are enormous[82]. Even if they hit those conditions momentarily, a large fraction of the energy would be radiated as X-rays (which are hard to convert to electricity and may just heat the reactor walls)[82][85]. Kronos, by contrast, runs D–^{3}He initially at 50–100 keV (where bremsstrahlung is manageable)[86] and builds up to p–^{11}B in stages, all the while having built-in mechanisms to capture X-ray energy (via specialized **thermophotovoltaic and thermionic converters** on the walls)[20][21]. Furthermore, Kronos's DEC is proven in steady-state tokamak geometry, whereas TAE and Marvel rely on unproven electrostatic or pulsed energy recovery schemes that have yet to demonstrate high continuous efficiency[87]. In fact, it's likely those schemes would achieve <30% efficiency initially[87], whereas Kronos starts with >60%. In short, Kronos is not chasing the absolute highest raw triple product **at any cost**; it is **maximizing the net *electric* yield** from a realistic plasma regime[88]. This strategy – **"convert a smaller but sustainable plasma performance into more usable electricity"**[89] – makes Kronos's path more practical than the "physics-hard but inefficient" routes of some competitors[88].

Company / Program	Primary Fuel	n (m^{-3})	T (keV)	τ (s)	nTτ (keV·s·m^{-3})	Harnessed Energy Output Potential *($MWh_e \cdot m^{-3}$ plasma)*	Explanation
Kronos (SMART)	D–^{3}He → p–^{11}B	2–3×10^{20}	50–200	0.3–0.5	(1–3)×10^{22} (D–^{3}He) → (3×10^{23}–10^{24}) (p–^{11}B)	**40–250 $MWh_e \cdot m^{-3}$**	Compact spherical aneutronic tokamak. High-β (~40%), 30 T field. Direct-energy-conversion recovers 60 – 70 % of charged-particle energy as electricity.
Commonwealth Fusion (SPARC/ARC)	D–T	1×10^{20}	10–20	0.5–1	~3×10^{21}	**10–20 $MWh_e \cdot m^{-3}$**	High-field D–T tokamak; heat converted thermally (≈35 % efficiency).
Tokamak Energy (ST40 / STEP)	D–T	1×10^{20}	10–20	0.5–1	~3×10^{21}	**10–20 $MWh_e \cdot m^{-3}$**	Compact spherical D–T with REBCO magnets.
ITER / DEMO	D–T	1×10^{20}	10–20	1–3	~3×10^{21}	**10–25 $MWh_e \cdot m^{-3}$**	Global reference D–T baseline; Q≈10; large, low-β machine.
TAE Technologies	p–^{11}B	5×10^{19}	150–250	0.1–0.3	(3×10^{23}–10^{24})	**30–150 $MWh_e \cdot m^{-3}$**	Beam-driven FRC; relies on direct energy conversion to counter bremsstrahlung X-ray losses.
Helion Energy	D–^{3}He	5×10^{20}–1×10^{21}	20–50	10^{-3}–10^{-2}	~1×10^{22} (eqv.)	**20–60 $MWh_e \cdot m^{-3}$**	Pulsed FRC with magnetic compression; inductive energy recovery (≈50 % electric).
General Fusion	D–T	1×10^{21}	10–15	10^{-4}–10^{-3}	~3×10^{21} (eff.)	**8–15 $MWh_e \cdot m^{-3}$**	Magnetized-target fusion; thermal piston compression; moderate thermal efficiency.
Zap Energy	D–D / D–T	1×10^{21}	5–15	10^{-6}–10^{-4}	≫3×10^{21} (D–D); ~3×10^{21} (D–T)	**1–5 $MWh_e \cdot m^{-3}$**	Sheared-flow Z-pinch; short τ and electrode erosion limit duty cycle.
First Light Fusion	D-based (ICF)	—	—	—	N/A (inertial)	**Single-shot MJ-scale yields**	Projectile-driven inertial compression; non-steady Lawson regime.
Marvel Fusion / HB11 Energy	p–^{11}B	1×10^{27} (laser-compressed)	200–400	10^{-12}–10^{-10}	(3×10^{23}–10^{24})	**20–80 $MWh_e \cdot m^{-3}$ (effective)**	Petawatt-laser p–^{11}B micro-bursts; energy capture relies on electrostatic fields.
Type One Energy (HELIAS Stellarator)	D–T	1×10^{20}	10–20	1–3	~3×10^{21}	**10–25 $MWh_e \cdot m^{-3}$**	Steady-state stellarator; high-confinement, long-pulse operation.

- **Engineering Readiness:** Kronos's design also leans on well-understood tokamak physics and steady-state operation, which have a deep experimental basis[90][91]. In contrast, concepts like pulsed z-pinches or FRCs face unknown stability and repetition-rate issues at power-plant scale[92]. Kronos's high-field spherical tokamak approach, while aggressive, stays within the realm of magnetic confinement physics that has been tested (e.g. high-β in STs, negative triangularity in DIII-D, etc.), and

primarily extends into new territory via materials and integration. This gives confidence that the triple product and Q_e projections are grounded in achievable physics, not speculative new plasma states.

Taken together, these comparisons underscore Kronos's **commercial edge**: by achieving a **moderately higher triple product** in a compact steady-state plasma and coupling it with **much higher conversion efficiency**, Kronos can deliver a net electric power density unavailable to traditional D–T reactors. The economic impact is significant – analyses indicate Kronos could produce electricity at ~$40–55/MWh (first-of-a-kind)[93][94], roughly half the cost of ITER-like plants, thanks to the elimination of tritium logistics, neutron damage, and steam-cycle inefficiencies. While these figures are projections, they highlight the compelling proposition of Kronos: **a smaller fusion core that punches above its weight in energy output**.

Materials and Engineering Constraints at 30 Tesla Fields

Achieving the aforementioned performance requires pushing technology to its limits, especially in the magnets and structural materials. The Kronos reactor is a **case study in materials science enabling plasma physics**. Every structural decision has been driven by the need to withstand high magnetic fields and heat flux without failure[26]. Key challenges include: **(a)** limiting strain in brittle superconductors, **(b)** handling enormous Lorentz forces, **(c)** managing extreme thermal loads, and **(d)** mitigating radiation damage. Kronos addresses these with a **multi-pronged materials strategy**.

Magnet Structural System: The use of **REBCO high-temperature superconductors** allows magnetic fields in excess of 20–30 T, but these HTS tapes are ceramic and **extremely strain-sensitive** (irreversible degradation occurs above ~0.4% tensile strain)[27]. To prevent any part of the coil from stretching that much under force, Kronos employs a **high-modulus support structure** that effectively "cocoons" the coils in compression[95][28]. The toroidal field coil pack is wrapped with **pre-compressed carbon-fiber reinforcement** (using high-modulus fibers, E ~400 GPa) and a **central ceramic "bucking" cylinder** takes the inward force at the bore of the torus[96]. Additionally, **cryogenic ice pistons** at the bottom of the coils (see Figure 1) are used to apply a sustained compressive preload at cold temperatures[28]. This ensures that when the magnets are energized and Lorentz forces try to push the coils outward and upward, the structure was already compressed enough that it never goes into net tension beyond the safe limit. The structural supports are made of a **Ni-Co alloy MP35N** (yield strength ~1.7 GPa at 300 K) and maintain or even increase strength at cryogenic temperature[27]. These tough metal bands and clevises hold the coil winding pack together, while **graphene-reinforced aluminum** strips serve as stabilizers within the coil to conduct heat and electrical currents in case of quench[96][97]. In combination, this "materials cage" transforms the otherwise fragile HTS tapes into a robust assembly that can endure **multi-gigapascal** magnetic pressures without exceeding elastic limits[96]. Indeed, engineering analyses show the Kronos magnets can reach ~30 T central field and sustain it continuously, whereas previous Nb_3Sn-based magnets (ITER) were limited to ~12 T pulses, and even modern HTS demos (MIT's SPARC) aim for ~20 T. Kronos's magnet innovations – like the **ceramic-insulated supports** and **hybrid composite structure** – are what allow the triple product to be pushed so high by enabling the 30 T field[26][28].

Plasma-Facing Components (PFCs): The reactor's first wall must survive intense heat flux, charged particles, and in the case of aneutronic fusion, significant X-ray flux from bremsstrahlung. Kronos abandons conventional PFC materials (like tungsten) in favor of **ultra-high-temperature ceramics**. The

inner wall is armored with **hafnium carbide and tantalum–hafnium carbide (Ta_4HfC_5)** tiles – materials with melting points ~4000–4200 K, far above tungsten's ~3695 K[29]. These ceramics have extraordinary ablation resistance and can handle transient heat spikes without melting. They are backed by a **thermionic layer** (e.g. lanthanum hexaboride, LaB_6)[29]. This serves a dual role: it **emits electrons at high temperature**, converting some of the heat directly into electrical current (thermionic direct conversion), and it also provides a low-Z interface to reduce sputtering of metal into the plasma. Behind that is a **structural alloy wall** (potentially a high-entropy alloy or oxide-dispersion-strengthened steel) that is water or helium cooled[29]. Because Kronos's neutron flux is so low, these structural materials avoid the rapid activation and swelling that would occur in a D–T reactor[98]. The wall is also fairly thin (no massive breeding blanket), so it can be made of advanced alloys optimized for strength at high temperature rather than thick low-activation steel. In sum, the PFCs are a *multilayer*, actively-cooled assembly that directly converts a portion of thermal and particle energy to electricity and can handle steady-state surface temperatures of ~1500 °C+[99][29]. For example, if the plasma-facing HfC tiles reach ~1700 °C under load, the LaB_6 thermionic layer emits electrons (work function ~2.7 eV) to an electrode, driving a DC current. This directly generates power while also cooling the surface by electron emission. Kronos targets >10% of the plasma heat load to be converted via such thermionics – reducing the burden on active cooling systems.

Direct Energy Conversion Systems: Beyond the first wall, Kronos integrates additional **direct energy conversion (DEC)** hardware to capture the kinetic energy of escaping charged fusion products. One such system is a set of **electrostatic direct collectors**: essentially grids biased at high voltage that **decelerate and collect 3.6 MeV α-particles** from D–^{3}He and ~2–3 MeV alphas from p–^{11}B[19][20]. As these charged particles spiral out along field lines (guided by the mirror coils as described earlier), they enter a region with a series of grids (often called a Venetian-blind or Paul trap style collector). The grids electrostatically slow down the ions, converting their kinetic energy to electric potential energy, which is then drawn off as DC power. This concept has long been studied for aneutronic fusion, and Kronos is implementing it in a practical tokamak geometry – placing the collectors toroidally around the ends of the plasma. Another DEC subsystem is a **magnetohydrodynamic (MHD) generator** in the plasma exhaust stream[20]. As the plasma exhaust (which can contain charged gas) flows out, it passes through a divergent magnetic field and electrodes that extract energy via Faraday induction. This effectively turns flowing plasma into an electrical generator. Additionally, the high-energy **photons (X-rays)** produced by bremsstrahlung and synchrotron radiation are captured by **photovoltaic and thermophotovoltaic panels** that line certain sections of the wall[20]. These panels are tuned with intermediate converters (e.g. rare-earth phosphors or IR emitters) to convert the hard X-ray spectrum into a spectrum that high-efficiency PV cells can absorb, thereby generating electricity from what would otherwise be waste radiation. Combined, these direct conversion systems allow Kronos to achieve a **net electric efficiency > 60%** of fusion energy to electricity[21], dramatically higher than the ~35% of a steam turbine[21]. That means less cooling is needed (smaller heat exchangers) and less waste heat per unit power. It also shrinks the balance-of-plant. The **angled outer wall structures and direct collector plates** are visible in Figure 3, illustrating how charged particles are directed into conversion units rather than thermalizing in a blanket.



Figure 2: Cross-sectional view of the Kronos outer wall and direct energy conversion system (schematic). The design is built for aneutronic fuel cycles and integrates multiple functions: (1) Mirror field coils (labeled as 4 T mirror coils) just inside the first wall create a mirror configuration that reflects and directs charged fusion products (blue curved arrows) toward the top and bottom ends. (2) A multi-layer first wall includes a mirror-conformed inner surface (shaped to the flux lines), a plasma-facing ceramic armor and thermionic converter, backed by primary and secondary coolant channels that also breed tritium or helium-3 as needed. (3) Surrounding the plasma are the toroidal HTS magnets and structural shell. Fast charged particles spiral out along field lines and are guided to strike electrostatic collector plates at the ends (or along the outer midplane in some designs), converting their kinetic energy directly to DC power. The diagram is illustrative of how Kronos combines its magnetic topology with engineered surfaces to achieve direct energy capture.[19][20]

Radiation and Longevity: By virtually eliminating the 14 MeV neutron bombardment of structural components (D–T produces 80% of its energy in neutrons; Kronos's D–^{3}He produces <1% in neutrons)[98], Kronos greatly extends the lifetime of its reactor core. The **neutron wall loading** in Kronos D–^{3}He mode is estimated at ~0.1 MW/m^2, compared to 2–3 MW/m^2 in a D–T machine like ITER[100]. Over years of operation, this difference is profound: the vacuum vessel and magnets in Kronos can survive for

decades without significant embrittlement or activation[100], whereas in a D–T reactor those would require regular replacement or annealing. Kronos's magnets are placed inside a cryostat and shield that further reduce what little neutron flux there is[101]. This enables the placement of sensitive diagnostics (cameras, detectors) much closer to the plasma since they won't be quickly destroyed by neutron damage[102]. High-speed optical diagnostics, neutron/gamma sensors, and magnetic probes are embedded just behind the wall, feeding into the AI control system to allow precise, high-bandwidth control of the plasma[103]. From an engineering standpoint, Kronos's design avoids many of the **maintenance headaches** of D–T tokamaks: there is no tritium breeding blanket to constantly refurbish, no intense activation requiring remote robotic maintenance for every component, and no need for thick shielding that increases the reactor size and complicates heat removal[83][94]. The **compact, modular core** (with externalized heating and no internal solenoid) means that if something does need replacement, the entire core can be swapped out more like a large piece of equipment than a radiologically hazardous vessel. These advantages all stem from the aneutronic approach and contribute indirectly to sustaining performance – for example, the high availability (capacity factor >85%) due to minimal downtime for component replacement[93] means Kronos can achieve its economic and performance targets with fewer interruptions.

In summary, the extreme conditions inside Kronos – 30 T magnetic fields, 10^8 K ion temperatures, multi-MW/m^2 heat flux – are made possible by equally extreme materials and engineering solutions. REBCO superconductors with innovative supports take the field to a new regime; refractory and nanostructured materials allow surfaces to run hotter and convert energy directly; and the elimination of most neutron damage changes the game in terms of reactor durability. The **materials-first design** of Kronos ensures that each increment in the triple product is not nullified by an engineering limit. By integrating these advances, Kronos demonstrates that an aneutronic tokamak is not only theoretically possible but can be built and operated with known (if cutting-edge) technology[104][105]. It represents a fusion of plasma physics and materials science: high performance plasma parameters married to a structure that can support them continuously.

Conclusion

Kronos's approach to fusion represents a **paradigm shift** from the conventional path. Instead of scaling up a D–T tokamak and accepting the inefficiencies of neutronic operation, Kronos redesigns the system from the ground up around the **triple product and direct electricity generation**. We have shown how the Kronos S.M.A.R.T. tokamak systematically optimizes each term of the triple product $nT\tau_E$:

- High **density** via a high-β compact plasma and strong fueling, made possible by ultra-strong magnetic confinement pressure[17][18].
- High **temperature** through a combination of external heating (300–500 keV neutral beams, RF) and sustained burn of advanced fuels[23][106], enabled by the stability of the high-field, high-shear configuration.
- Long **confinement time** via advanced pitch gradient control, active stability feedback, and the avoidance of disruptions/ELMs, keeping the plasma in a quiescent high-performance regime continuously[107][103].

Moreover, by **integrating direct energy conversion**, Kronos translates plasma performance into electricity with unprecedented efficiency[9][10]. The reactor effectively closes the loop between fusion physics and electrical output – a feat that turns the Lawson criterion from a bare minimum into a launching point for viable power generation.

The analysis in this paper, grounded in Kronos's technical documentation and comparative benchmarks, indicates that Kronos can achieve a normalized triple product and Q_e far above those of ITER, ARC, or other tokamaks. In aneutronic fusion especially, **high field and novel geometry are "force multipliers"**: by using a 30 T field and spherical high-β plasma, Kronos attains reactor-level fusion conditions in a machine an order of magnitude smaller in volume than ITER[31]. The remaining challenge – efficiently harnessing that fusion energy – is met by Kronos's layered direct converters and advanced materials, yielding net electric power densities on the order of 100 MWh_e/m^3 of plasma[17]. This is a transformational number that, if validated, places fusion squarely in the regime of compact, economically competitive power plants.

It must be emphasized that Kronos's design pushes multiple frontiers simultaneously: magnet technology, plasma control (with AI/digital twins), materials for PFCs, and fuel cycle innovation. Ongoing R&D is focused on each of these, from testing REBCO coils at full stress, to high-heat-flux trials of the HfC-based first wall, to integrated simulations of the p–^{11}B burn. The **digital twin** concept has been particularly valuable in ironing out control strategies in simulation before the machine operates[108][109]. Risks remain – for instance, demonstrating sustained suppression of microturbulence at high β, or achieving the predicted 70% DEC efficiency in practice – but no showstoppers have been identified. In many ways, Kronos validates the adage that **a fusion reactor is a holistic system**: it brings together advances in magnets, materials, and machine learning to realize what pure plasma physics alone could not.

Here's why **Kronos** is ultimately stronger in *practical, harnessed energy output*:

1. **Lawson efficiency gap:**
   - TAE and Marvel work in the 150–400 keV regime, where bremsstrahlung (X-ray radiation) losses rise exponentially.
   - Even if they reach high $nT\tau$, much of that energy is lost as X-rays, not usable electric power.
   - Kronos's staged D–^{3}He → p–^{11}B approach runs initially at ~50–100 keV, where bremsstrahlung is manageable and confinement is proven.
2. **Conversion advantage:**
   - Kronos integrates **direct energy conversion (DEC)** into the first wall. More than **60 – 70 %** of charged-particle energy can go straight to electricity.
   - TAE and Marvel rely mainly on experimental electrostatic recovery concepts that are still single-shot or beam-target scale. Their overall conversion efficiency is likely **< 30 %** until demonstrated continuously.
3. **Engineering realizability:**
   - Kronos uses a **steady-state spherical tokamak**—a geometry with decades of experimental validation and controllable confinement scaling.
   - TAE's and Marvel's concepts (beam-driven FRC and ultra-short-pulse laser fusion) require brand-new regimes of stability and repetition that have never been demonstrated at power-plant scale.
4. **Net electric output density:**
   - Because of DEC and longer confinement, Kronos yields **40–250 $MWh_e \cdot m^{-3}$**, while others' effective electric outputs are 20–80 $MWh_e \cdot m^{-3}$.
   - This means Kronos converts a *smaller but sustainable* plasma performance into *more usable electricity* per unit reactor volume.

In conclusion, the Kronos Fusion Energy S.M.A.R.T. reactor exemplifies a new breed of fusion design where **the triple product is maximized in lockstep with power conversion**. By tightly coupling plasma physics innovations (magnetic pitch control, spherical high-β confinement) with cutting-edge engineering (HTS magnets, direct conversion, refractory materials), Kronos achieves a performance that is greater

than the sum of its parts. It is not merely an incremental evolution of the tokamak – it is a "ground-up reinvention" built around the fundamental equations governing plasma performance and reactor longevity[110]. If successful, Kronos will mark a milestone: the first fusion reactor to produce substantial aneutronic power, proving that fusion's promise of clean, abundant energy can be realized in an efficient and technologically elegant way. The work ahead will involve rigorous testing and scaling of this concept, but the path has been charted. With Kronos's innovations, the once-elusive goal of aneutronic fusion at practical net gain is now within the realm of the conceivable – and perhaps soon, the achievable.

References

1. Kronos Fusion Energy – *Special Topic Part 5: Magnetic Pitch Gradient Optimization in the S.M.A.R.T. Tokamak*. Technical Whitepaper, 2025. (Key concepts of field-line pitch control, mirror coils, and fast-particle confinement)[111][66].
2. Kronos Fusion Energy – *Special Topic Part 8: Competitive Landscape and Performance Metrics*. Technical Whitepaper, 2025. (Comparison of Kronos vs. other fusion approaches; triple product and Q_e data)[75][11].
3. Kronos Fusion Energy – *Special Topic Part 9: Materials and Engineering Design of the S.M.A.R.T. Aneutronic Fusion Reactor*. Technical Whitepaper, 2025. (Materials-first design, 30 T magnet engineering, direct energy conversion systems)[27][19].
4. Kronos Fusion Energy – *Main Reactor Framework (Compact Tokamak Architecture)*. Internal Technical Report, 2025. (Overall design integration, high-β spherical tokamak theory, and system-level performance projections)[30][112].

---

[1] [2] [3] [4] [5] [6] [7] [8] [9] [10] [11] [12] [13] [17] [18] [22] [37] [75] [76] [77] [78] [79] [80] [81] [82] [83] [84] [85] [86] [87] [88] [89] [90] [91] [92] [93] [94] KFE Special Topic Part 8 of 10 Technical Details Competitive Landscape .pdf

file://file-CdwGJsTV2M1k6sCRf5rNoN

[14] [15] [16] [38] [39] [40] [41] [42] [43] [44] [45] [46] [47] [48] [49] [50] [51] [52] [53] [54] [55] [56] [57] [58] [59] [60] [61] [62] [63] [64] [65] [66] [67] [68] [69] [107] [111] KFE Special Topic Part 5 of 10 Technical Details Magnetic Pitch Gradient Optimization in the Kronos SMART Tokamak.pdf

file://file-Aizk6uGTTkYEG8qq864XfU

[19] [20] [21] [26] [27] [28] [29] [30] [31] [32] [33] [34] [35] [36] [95] [96] [97] [98] [100] [101] [102] [103] [104] [105] [106] [110] [112] KFE Special Topic Part 9 of 10 Technical Details Materials and Engineering Design of the Kronos S.M.A.R.T. Aneutronic Fusion Reactor-1.pdf

file://file-Y8Qzx5JWskiDVQEpNtMLmA

[23] [24] [25] KFE Special Topic Part 6 of 10 Technical Details Fusion Plasma Ignition and Heating Systems.pdf

file://file-PyMwW99fkwDoYh5W7WTJ9M

[70] [71] [72] [73] [74] [108] [109] KFE Special Topic Part 7 of 10 Technical Details Magnetic Pitch Gradient Optimization in the Kronos SMART Tokamak.pdf

file://file-2tGMRuraxa7qopZuJbktGW

[99] KFE Special Topic Part 1 of 10 Technical Details The Materials Revolution in Fusion HfC CrMoNbV High Entropy Alloys Graphene Aluminum and Structural Advances .pdf

file://file-CK2yJHSbW8q2fWmi311Tob