



h-p Adjoint-based Error Estimation for Thermo-acoustic Coupling in Turbulent Premixed Flames

Christopher Ngigi

*University of Toronto Institute for Aerospace Studies
4925 Dufferin Street, Toronto, Ontario, M3H 5T6, Canada*

Doctoral Examination Committee Report

January 2015

1 Introduction and Motivation

Computational Fluid Dynamics (CFD) was developed to reduce the cost of fluid flow experiments whose lifecycle spanning from conception to testing involved numerous design iterations and modifications. The initial applications of CFD focused on aerodynamic and hydrodynamic flows within the engineering industry. At the present time, its role has grown to include a vast spectrum of modern day industries. This is due to the ever-increasing power of computers as predicted by Gordon Moore, namely, that computing power would double approximately every two years. [1]

Since the 1960's, the role of CFD in the aerospace industry has grown to involve more complex design configurations and modelling of physics. Quite naturally, this has been extended to aircraft powerplants: Engine performance software was used to design Compressor maps for the purpose of estimating power outputs; Specialty softwares such as *CHEMKIN*, *CANTERA* are used to calculate combustion rates and products for given reactants and conditions at the lab level; CFD is being applied to simulate the combustion of fuels in laminar and turbulent conditions.

Turbulent combustion is a very complex physics phenomenon. Up to the 90's, researchers were still working on accurate mathematical models that would be capable of predicting to some extent the interaction and behavior of non-laminar fluid flow regimes. Naturally, computers have been employed as tools to simulate these models and results are validated against experiments.

Because of the huge discrepancy in scales when it comes to turbulence, ranging from the Integral scales to the Kolmogorov scales, vast computational resources would be required to model the entire turbulent regime. This high-fidelity branch of CFD is known as Direct Numerical Simulation (DNS), and is only achievable on Supercomputers, such as was recently demonstrated by Kaneda and Ishihara. [2] DNS remains very expensive in terms of computational and time resources: in reality, complex simulations are impossible, some requiring solution time on the order of 10^8 years.

Large Eddy Simulation (LES) is a branch of CFD has been successfully applied to combustion simulation in the last two decades. It serves as a compromise to model Turbulent scales up to a given specific scale (which we call the filter size): any scale smaller than this is modelled.

Within a Gas Turbine combustion chamber, heat release and pressure are a coupled phenomenon, and any sporadic fluctuations in heat release or pressure will affect the other. This is the field of study for *Thermoacoustics*. Higher temperatures within the combustion chamber raise the pressure which in turn increase the temperature even further, leading to a cycle where heat feeds off pressure and vice versa. It often results in structural damage to components within the combustion chamber and the turbine blades,

and these pose huge safety risks and result in very high maintenance costs.

Notice the several stages at which inaccuracies can be introduced into the simulation: one is at the algorithm level due to both the meshing of the geometry and the discretization of the governing equations, and the other at the modelling level due to the selection of turbulence models and filter sizes.

2 Scope of Research

The present work intends to address a two-pronged technique to reduce the computational error arising from discretization and meshing. The technique will involve implementation of the adjoint-based error estimation method to be implemented for mesh refinement. Adjoints will be used for sensitivity analysis, namely, monitoring the computational cells to which the functional outputs of the CFD analysis are most sensitive.

The second part involves the use of high-order finite volume discretization of the governing equations: Favre-Averaged Navier Stokes (FANS). The higher the order of discretization, the higher the accuracy of the solution. This minimizes error and is often desired since for a coarser level of mesh refinement, a higher solution accuracy can be achieved, thus this can be viewed as reducing the computational cost.

As discussed in section 1, it is the intention to ensure that the modifications to the CFFC algorithm will be remain parallelizable, taking advantage of the multiprocessing resources that exist at SCINET. Parallelization is achieved by domain decomposition, such that processors can compute smaller sections of the mesh with the corresponding governing equations all the while communicating and linking to each other through the Message Parsing Interface (MPI). Parallelization is the modern-day approach to increase speed while allowing computationally complex simulations.

The present work will focus on implementing adjoint-based error estimation for mesh refinement and high-order finite volume discretization and attempt to address thermoacoustic phenomenon within turbulent premixed combustion

3 CFD Techniques to Model Combustion

3.1 The Finite Volume Method

3.2 Favre Averaged Navier Stokes Equations

3.3 High Order schemes

3.4 Large Eddy Simulation

3.5 Explicit Filtering and Commutation Errors

4 Adjoint Method for Error Estimation

4.1 Introduction

4.2 Derivation

4.3 Solution of Linear Systems

5 Anisotropic Mesh Refinement

5.1 Techniques

5.2 Benefits of Parallelization

6 Summary of Progress to Date and Future Work

6.1 Progress to Date

| Task | Completion Date |
|---|------------------------|
| Literature Review | September-October 2014 |
| Trelis Meshing Software | November 2014 |
| CFFC Group Code Flux Jacobian Analysis | December 2014 |
| Trilinos Package solution for example Poisson Problem in serial and parallel configurations | December 2014 |

6.2 Future Work

| Task | Completion Date |
|--|-----------------|
| Implementing the approximate Adjoint Derivative to the Flux Jacobians testing on Euler Equations | April 2015 |
| Extension to Mesh adaptation | May 2015 |
| Application of Adjoint Problem to Navier Stokes | June 2015 |
| Explicit Filters for High Order FVM implementation | October 2015 |
| Conference Paper I draft | November 2015 |
| Coupling of High Order method with Adjoint-based AMR | December 2015 |
| CFD simulation of Cold Flow | January 2016 |
| CFD simulation of Laminar Non-Premixed Flame | February 2016 |
| CFD simulation of Laminar Diffusion Flame | February 2016 |
| Journal Paper I | April 2016 |
| Conference Paper II draft | April 2016 |
| CFD simulation of Turbulent Non-Premixed Flame | May 2016 |
| Journal Paper II | July 2016 |
| Conference Paper I Presentation | July 2016 |
| Conference Paper II draft | October 2016 |
| Journal Paper III | October 2016 |
| CFD simulation of Full Thermo-coupling | October 2016 |
| Conference Paper III draft | November 2016 |
| Thesis write-up | September 2017 |

References

- [1] “Excerpts from A Conversation with Gordon Moore: Moore’s Law,” Video Transcript 0305/TSM/LAI/XX/PDF 306959-001US, Intel Corporation, September 2005.

- [2] Kaneda, Y. and Ishihara, T., “High-Resolution Direct Numerical Simulation of Turbulence,” *Journal of Turbulence*, Vol. 7, No. 20, 2006.