

```

#include <stdio.h>
#include <iostream>
#include <stddef.h>
#include <string>
#include <cstdlib>
#include <cstdarg>
#include <cmath>
#include <fstream>
#include <vector>
#include <cstdio>
#include <fstream>
#include <stdlib.h>
#include <sstream>
#include <algorithm>
#include <utility>

using std::cout;
using std::endl;
using std::ios;

// Function
prototypes=====
=
double Evaluate_dUdy_Plus(double lmix_plus, double y_pl, double R_pl, double ymax, double Fmax, double Udif);

std::vector <double> getUplus(double ymax, double Fmax, double Udif, double R_pl, int filewrite);

std::vector <double> evalFunc(double ymax, double Fmax, double Udif, double R_pl, int filewrite);

//=====

// Main function
int main(){

    // variables
    std::vector <double> f_a(4);
    std::vector <double> f_b(4);
    std::vector <double> f_c(4);
    std::vector <double> f_fin(4);

    double Fmax_new=0,          ymax_new=0,          Udif_new = 0,          U_ave_new =0;
    double Fmax_prev=0,        ymax_prev=0,          Udif_prev=0,        U_ave_prev=0;
    // From Question 2
    double ymax = 59.6, Fmax = 2.31695, Udif = 23.0412, U_ave = 18.2401;
    double delt_init =30;
    int coun = 0, iter=0;
    double Re_D = 40000, Re_D_est = 0;
    double c = 0;
    double a= 1;
    double b = 10000;
    double root = 0;

    double check_a = 0;
    double check_b = 0;
    double check_c = 0;

    double damp = 0.3;
    double tol = 1e-5; double toler = 1e-5;

    /*===== BISECTION METHOD ===== */

    f_a = evalFunc(ymax, Fmax, Udif, a, 0);
    f_b = evalFunc(ymax, Fmax, Udif, b, 0);

```

```

check_a = (2*f_a[3]*a - Re_D);
check_b = (2*f_b[3]*b - Re_D);

/* Check that that neither end-point is a root and if f(a) and f(b) have the same sign, throw an exception.
*/
if ( check_a == 0 ){
    root = a;
    std::cout<<"root is "<<root<<endl;
} else if ( check_b == 0 ){
    root = b;
    std::cout<<"root is "<<root<<endl;
} else if ( check_a * check_b > 0 ){
    std::cout<<"f(a) and f(b) do not have opposite signs"<<endl;
}

// Begin the iterations-----

double del1;

del1 = del1_init;

while ( fabs(Re_D_est - Re_D) > tol ){

//    std::cout<<"Outer iteration number: "<<iter<<endl;
    c = 0.5*(a + b);
    f_a = evalFunc(y_max, F_max, U_dif, a, 0);
    f_b = evalFunc(y_max, F_max, U_dif, b, 0);

    check_a = (2*f_a[3]*a - Re_D);
    check_b = (2*f_b[3]*b - Re_D);

    //=====
    // iterate for a converged y_max, F_max, U_dif
    //===== BALDWIN LOMAX MODEL =====

    while ( del1 > tol){
//        std::cout<<"Inner iteration number: "<<count<<endl;
        // Update from previous timestep
        F_max_prev = F_max;
        y_max_prev = y_max;
        U_dif_prev = U_dif;
        U_ave_prev = U_ave;
        //=====
        // new values for new n plus update for U+
        f_c = evalFunc(y_max_prev, F_max_prev, U_dif_prev, c, 0);

        check_c = (2*f_c[3]*c - Re_D);

        // Update new variable values
        y_max_new = f_c[0];
        F_max_new = f_c[1];
        U_dif_new = f_c[2];
        U_ave_new = f_c[3];
        //=====
        // Applying a damping factor before re-plugging in the values
        F_max = 0; y_max = 0; U_dif = 0; U_ave = 0;
        F_max = F_max_prev + damp*(F_max_new - F_max_prev);
        y_max = y_max_prev + damp*(y_max_new - y_max_prev);
        U_dif = U_dif_new;
        U_ave = U_ave_new;

        double del1 = fabs(y_max - y_max_prev);
        double del2 = fabs(F_max - F_max_prev);

```

```

    if (delt1 <=tol && delt2 <=tol ){
        break;
    }
    coun = coun + 1;
}
std::cout<<"    ymax = "<<ymax<<"    Fmax = "<<Fmax<<endl;
std::cout<<" Number of ymax iterations is =    "<< coun<<endl;
//=====

if (check_c == 0){
    //    break;
} else if (check_a * check_c < 0){
    b = c;
} else{
    a = c;
}

if ( b - a < tol ){
    if ( fabs(check_a) < fabs(check_b) && fabs(check_a) < tol ){
        root = a;
        std::cout<<"root is "<<root<<endl;
    }
    else if ( fabs(check_b) < tol ){
        root = b;
        std::cout<<"root is "<<root<<endl;
    }
}

// Break the iterations if convergence tolerance has been met
if (check_a < toler && check_b < toler && check_c < toler){
    break;
}

iter = iter + 1;
Re_D_est = 2*U_ave*c;
}
std::cout<<" Final results Re_D = "<<2*U_ave*c<<endl;
std::cout<<" Final results R+ = "<<c<<endl;
std::cout<<" Final U_ave = "<<U_ave<<endl;
std::cout<<"Number of bisection iterations = "<<iter<<endl;
f_fin = evalFunc(ymax, Fmax, Udif, c, 1);

return 0;
}

std::vector<double> evalFunc(double ymax, double Fmax, double Udif, double R_pl, int filewrite){

    std::vector<double> ReturnVals;
    //evaluate function!
    ReturnVals = getUplus(ymax, Fmax, Udif, R_pl, filewrite);

    return ReturnVals;
}

double Evaluate_dUdy_Plus(double lmix_plus, double y_pl, double R_pl, double ymax, double Fmax, double Udif){

    double dU_dy = 0.0;
    double lmix_plus_fourth = lmix_plus*lmix_plus*lmix_plus*lmix_plus;
    double y_over_R = (1 - y_pl/R_pl);
    double alpha = 0.0168;
    double Ccp = 1.6;
    double FKleb, Fwake, CKleb = 0.3, Cwk = 1;
    double visc=0, eddyIN, eddyOUT;

```

```

if (y_pl <= 1){ // as it was!
    dU_dy = y_over_R - (y_over_R*y_over_R)*(lmix_plus*lmix_plus) +
    2*(y_over_R*y_over_R*y_over_R)*(lmix_plus_fourth);
}

else{
    eddyIN = lmix_plus*lmix_plus * ( std::sqrt(4*lmix_plus*lmix_plus*y_over_R + 1) - 1)
    /(2*lmix_plus*lmix_plus);

    double kleb_6 = (y_pl* CKleb/ymax) * (y_pl* CKleb/ymax) * (y_pl* CKleb/ymax) * (y_pl* CKleb/ymax) *
    (y_pl* CKleb/ymax) * (y_pl* CKleb/ymax);
    FKleb = 1/( 1 + 5.5 * kleb_6);

    if ( ymax*Fmax <= Cwk*ymax*Udif*Udif/Fmax){
        Fwake = ymax*Fmax;
    }
    else{
        Fwake = Cwk*ymax*Udif*Udif/Fmax;
    }
    eddyOUT = alpha * Ccp * Fwake * FKleb;

    if (eddyIN <= eddyOUT){ // maybe compare directly
        visc = eddyIN; // inner layer
        dU_dy = y_over_R / (1 + visc);
    }
    if (eddyIN > eddyOUT){
        visc = eddyOUT; // outer layer
        dU_dy = y_over_R / (1 + visc);
    }
}

return dU_dy;
}

```

```

std::vector <double> getUplus(double ymax, double Fmax, double Udif, double R_pl, int filewrite){

```

```

    double dU_dy0, dU_dy1, dU_dy2, dU_dy3, dU_dy;
    std::vector <double> U_pl_profile;
    std::vector <double> Y_pl_profile;
    std::vector <double> Reynolds;
    std::vector <double> ymax_profile;
    std::vector <double> Results(4);
    double summ = 0.0;    int counter = 0;
    double A0_pl = 26.0;    double K = 0.4;
    double y_pl = 0;    double lmix_pl, delta_y_pl;
    double U_n1=0, U_n2=0;
    double U_ave=0;

    double alpha = 0.0168;
    double Ccp = 1.6;
    double FKleb, Fwake, CKleb = 0.3, Cwk = 1;
    double visc=0, eddyIN, eddyOUT;

    double aa = 2e-1;
    double bb= 1e-1;

```

```

//    std::cout<<"Stuck here.... "<<endl;

```

```

// Build the Velocity

```

```

Profile=====
while (y_pl <= R_pl){

```

```

if (y_pl <= 2){
    delta_y_pl = aa;
}
if (y_pl > 2){
    delta_y_pl = bb;
}

lmix_pl = K*y_pl*(1 - exp(-y_pl/A0_pl) );
double lmix_plus_fourth = lmix_pl*lmix_pl*lmix_pl*lmix_pl;

/* ===== RK4 Scheme ===== */
dU_dy0 = Evaluate_dUdy_Plus(lmix_pl, y_pl, R_pl,ymax, Fmax, Udif);
dU_dy1 = Evaluate_dUdy_Plus(lmix_pl + 0.5*delta_y_pl*dU_dy0, y_pl + 0.5*delta_y_pl, R_pl,ymax, Fmax,
Udif);
dU_dy2 = Evaluate_dUdy_Plus(lmix_pl + 0.5*delta_y_pl*dU_dy1, y_pl + 0.5*delta_y_pl, R_pl,ymax, Fmax,
Udif);
dU_dy3 = Evaluate_dUdy_Plus(lmix_pl + 0.5*delta_y_pl*dU_dy2, y_pl + delta_y_pl, R_pl,ymax, Fmax, Udif);

if (y_pl > 0){
    U_n2 = U_n1 + (delta_y_pl/6)*(dU_dy0 + 2*dU_dy1 + 2*dU_dy2 + dU_dy3);
}

// update vectors to store these values
U_pl_profile.push_back(U_n2);
Y_pl_profile.push_back(y_pl);
ymax_profile.push_back(dU_dy0 * lmix_pl);

double y_over_R = (1 - y_pl/R_pl);

// a build for the Reynold's Stress
if (y_pl <= 1){
    dU_dy = y_over_R - (y_over_R*y_over_R)*(lmix_pl*lmix_pl) +
2*(y_over_R*y_over_R*y_over_R)*(lmix_plus_fourth);
    Reynolds.push_back(lmix_pl*lmix_pl * dU_dy*dU_dy);
}
if (y_pl > 1){
    eddyIN = lmix_pl*lmix_pl * ( std::sqrt(4*lmix_pl*lmix_pl*y_over_R + 1) - 1)/(2*lmix_pl*lmix_pl);
    double kleb_6 = pow((y_pl* CKleb/ymax),6);
    FKleb = 1/( 1 + 5.5 * kleb_6);

    if ( ymax*Fmax <= Cwk*ymax*Udif*Udif/Fmax){
        Fwake = ymax*Fmax;
    }
    else{
        Fwake = Cwk*ymax*Udif*Udif/Fmax;
    }
    eddyOUT = alpha * Ccp * Fwake * FKleb;

    if (eddyIN <= eddyOUT){
        visc = eddyIN; // inner layer
        dU_dy = y_over_R / (1 + visc);
    }
    if (eddyIN > eddyOUT){
        visc = eddyOUT; // outer layer
        dU_dy = y_over_R / (1 + visc);
    }
    Reynolds.push_back(visc * dU_dy);
}

summ = summ + U_n2 * (1 - y_pl/R_pl ) * delta_y_pl;
counter = counter + 1;
y_pl = y_pl + delta_y_pl;
if (fabs(y_pl - R_pl) < 1){
    break;
}

```

```

    }
    U_n1 = U_n2;
}
//===== known and complete =====
U_ave = (2/R_pl) * summ;

double val_max = 0, Rmax = 0, val_Rmax=0;
// now evaluate the new max values: these can only be evaluated once we know the entire velocity profile,
// hence why we initialize at start
for (int i=0; i< counter; i++){
    double ypl = Y_pl_profile[i];
    if (ymax_profile[i] > val_max){
        val_max = ymax_profile[i];
        if (ypl <= 2){
            delta_y_pl = aa;
        }
        if (ypl > 2){
            delta_y_pl = bb;
        }
        ymax = i * delta_y_pl;
        Fmax = (1/K)*val_max;
    }
    if (Reynolds[i] > Rmax){
        Rmax = Reynolds[i];
    }
}

double num_elem = U_pl_profile.size();
Udif = U_pl_profile[num_elem]; // - U_pl_profile[counter * ymax/R_pl];

Results[0] = ymax;
Results[1] = Fmax;
Results[2] = Udif;
Results[3] = U_ave;

//===== now write results to file (Tecplot!)=====

if (fwrite == 1){
    //      std::cout<<"U_max is "<<U_pl_profile[counter-1]<<endl;

    std::stringstream stream1, stream3, stream4, stream5, stream6, stream7;
    stream1 << "U_plus_two-layer_mixing_model.dat";
    stream3 << "i="<<num_elem;
    stream4<<"title = "<<" "<<stream1.str()<<" ";
    std::string var1 = stream3.str();
    std::string var2 = stream4.str();
    std::string fileName1 = stream1.str();

    FILE* fout = fopen(fileName1.c_str(), "w");

    fprintf(fout, "%s", var2.c_str() ); fprintf(fout, "\n");
    fprintf(fout, "%s", "variables = 'U+/U+max' 'y+/R+' 'y+' 'U+' 'normalized_Reynolds_Shear_Stress' ");
    fprintf(fout, "\n"); // 'Reynolds Shear Stress'
    fprintf(fout, "%s %s %s", "zone",var1.c_str(),"f=point"); fprintf(fout, "\n"); //

    summ = 0;
    for (int j = 0; j <= num_elem; j++){
        fprintf(fout, "%e\t %e\t %e\t %e\t %e\t", U_pl_profile[j]/U_pl_profile[num_elem], Y_pl_profile[j]/
        Y_pl_profile[num_elem], Y_pl_profile[j], U_pl_profile[j], Reynolds[j]/Rmax);
        fprintf(fout, "\n");
    }
    fclose(fout);
    std::cout<<" "<<endl; std::cout<<"U_plus results file successfully written"<<endl;

    //=====

```

```
stream5 << "Laufer Experimental Data.dat";
stream6 <<"i="<<11;
stream7<<"title = "<<" "<<stream5.str()<<" ";
var1 = stream6.str();
var2 = stream7.str();
std::string fileName2 = stream5.str();
fout = fopen(fileName2.c_str(), "w");
fprintf(fout, "%s", var2.c_str() ); fprintf(fout, "\n");
fprintf(fout, "%s", "variables = 'U+/U+max' 'y+/R+' "); fprintf(fout, "\n");
fprintf(fout, "%s %s %s", "zone", var1.c_str(), "f=point"); fprintf(fout, "\n"); //
fprintf(fout, "%e\t %e\t ", 0.333, 0.010); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.696, 0.095); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.789, 0.210); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.833, 0.280); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.868, 0.390); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.902, 0.490); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.931, 0.590); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.961, 0.690); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.975, 0.800); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 0.999, 0.900); fprintf(fout, "\n");
fprintf(fout, "%e\t %e\t ", 1.000, 1.000); fprintf(fout, "\n");
fclose(fout);
std::cout<<"Laufer results successfully written"<<endl;
}

return Results;
}
```