	Customers									
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description				
customer_id	PK		SERIAL							
first_name			VARCHAR(50)	NOT NULL						
last_name			VARCHAR(50)							
email			VARCHAR(100)	NOT NULL; UNIQUE						
phone_number			VARCHAR(20)	NOT NULL; UNIQUE						
customer_type			ENUM	NOT NULL		Like home,business or other				

	address_type									
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description				
address_id	PK		SERIAL							
customer_id	FK		INT	NOT NULL	Customers.customer_id					
address_type			ENUM	NOT NULL						
street_address			TEXT	NOT NULL						
city			VARCHAR(50))	NOT NULL						
state			VARCHAR(50)							
post_code			CHAR(8)	NOT NULL						

Orders

Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description
order_id	PK		SERIAL			
customer_id	FK		INT	NOT NULL	Customers.customer_id	
order_date			TIMESTAMP			
total_amount			DECIMAL(10,2))	NOT NULL		
status			ENUM			
priority_delivery			BOOLEAN			By default its FALSE

Customer_Feedback									
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description			
feedback_id	PK		SERIAL						
customer_id	FK		INT	NOT NULL	Customers.customer_id				
order_id	FK		INT		Orders.order_id				
rating			DECIMAL(2,1)	CHECK(BETWEEN 1 AND 5)					
comments			VARCHAR(20)	TEXT					
feedback_date			ENUM	TIMESTAMP					

	Products								
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description			
product_id	PK		SERIAL						
product_name			VARCHAR(100)	NOT NULL					

price		DECIMAL(10,2)	NOT NULL	
1'		` ' '		

	Order_Details									
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description				
order_detail_id	PK		SERIAL							
order_id	FK		INT	NOT NULL	Orders.order_id					
product_id	FK		INT	NOT NULL	Products.product_id					
quantity			INT	NOT NULL						
price_at_order			DECIMAL(10,2)	NOT NULL						
subtotal			DECIMAL(10,2)	ALWAYS AS (quantity * price_at_order)						

	Driver_status									
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description				
driver_id	PK		SERIAL							
first_name			VARCHAR(50)	NOT NULL						
last_name			VARCHAR(50)	NOT NULL						
phone_number			VARCHAR(20)	NOT NULL; UNIQUE						
night_shift			BOOLEAN	DEFAULT FALSE						
driver_status			ENUM							

Vehicle_status									
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description			
vehicle_id	PK		SERIAL						
license_no			VARCHAR(100)						
vehicle_type			VARCHAR(100)	NOT NULL					
vehicle_status			ENUM						

	Driver_Vehicle								
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description			
driver_vehicle_id	PK		SERIAL						
driver_id	FK		INT	NOT NULL	Drivers.driver_id				
vehicle_id	FK		INT	NOT NULL	Vehicles.vehicle_id				

	Routes								
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description			
route_id	PK		SERIAL						
destination_start_end			VARCHAR(100)	NOT NULL					
distance_km			INT						
fuel_cost_estimate			DECIMAL(10,2)	ALWAYS AS ((distance_km * 1.402) / 8)					

Shipment_status									
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description			
shipment_id	PK		SERIAL						
driver_vehicle_id			INT	NOT NULL	Driver_Vehicle.driver_vehicle_id				
order_id			INT		Orders.order_id				
route_id			INT	NOT NULL	Routes.route_id				
status			ENUM	NOT NULL					

Incidents							
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description	
incident_id	PK		SERIAL				
shipment_id	FK		INT		Shipments.shipment_id		
Shipment_type			ENUM				
resolution			TEXT				

SpecialCargoDetails							
Attribute_Name	KEY	INDEX	Data Type & Size	Domains & Constraints	FK Reference	Description	
special_cargo_id	PK		SERIAL				
shipment_id	FK		INT		Shipments.shipment_id		
temperature_range			VARCHAR(20)				

hazardous_class		VARCHAR(50)		
security_required		BOOLEAN		