ktauction.in — EC2 update guide

Docker Hub + EC2 checklist. Pre-built images only on the server. Generated from LiveAuction deploy runbook.

> **Happy path:** PC: build/push → EC2: `docker compose pull && docker compose up -d` → Browser: hard refresh ktauction.in

Quick checklist

Step	Where	Action
1	Your PC (IntelliJ)	Change code, test locally if you can
2	Your PC (Docker)	Build + push backend and/or frontend images
3	EC2 (SSH)	docker compose pull then docker compose up -d
4	Browser	Hard refresh ktauction.in; smoke-test one upload if needed

> **Do not** delete ~/docker-compose.yml or run `docker compose down -v` unless you mean to wipe the database.

Part 1 — On your PC

Prerequisites

- Start Docker Desktop before build.
- `docker login` (Docker Hub account with push access).

Backend (Java changes only)

```
cd backend
docker build -t krushnathakare/cricket-auction-backend:latest .
docker push krushnathakare/cricket-auction-backend:latest
```

Frontend (React/UI changes)

```
cd frontend
docker build --build-arg VITE_API_URL=https://ktauction.in/api \
  -t krushnathakare/cricket-auction-frontend:latest .
docker push krushnathakare/cricket-auction-frontend:latest
```

Wait 1–2 minutes after push before pulling on EC2.

Part 2 — On EC2

Connect

```
ssh -i /path/to/your-key.pem ubuntu@13.200.88.0
```

If SSH times out: AWS Console → EC2 → instance must be **Running**.

Deploy (safe routine)

```
cd ~
ls -la docker-compose.yml
docker compose pull
docker compose up -d
docker ps
```

Keeps MySQL (`mysql_data`) and uploads (`cricket_uploads`, `cricket_images`) when compose mounts volumes on backend.

Health check

```
curl -s -o /dev/null -w "%{http_code}\n" http://localhost:8080/api/tournaments
curl -s -o /dev/null -w "%{http_code}\n" http://localhost:3000/
```

Never do this (unless you accept the risk)

Action	Risk
sudo rm ~/docker-compose.yml	Missing volumes → broken logo URLs (404)
docker compose down -v	Deletes MySQL + uploads
up -d without pull	Old images; site unchanged
Only nginx edit inside container	Lost on recreate; push new frontend image instead

Troubleshooting

- **Site unchanged:** pull + up -d, hard refresh browser.
- **413 upload:** use frontend image with client_max_body_size 12m in nginx.conf.
- **Broken logos:** restore compose volumes, up -d, re-upload files.
- **Edit compose:** sudo nano /home/ubuntu/docker-compose.yml (Ctrl+O, Enter, Ctrl+X).

Backup docker-compose.yml (EC2 home)

```
services:
  mysql:
    image: mysql:8.0
    container_name: cricket-auction-mysql
    restart: unless-stopped
    environment:
      MYSQL_ROOT_PASSWORD: root
      MYSQL_DATABASE: cricket_auction
    ports:
      - "3306:3306"
    volumes:
      - mysql_data:/var/lib/mysql
    healthcheck:
      test: ["CMD", "mysqladmin", "ping", "-h", "localhost", "-uroot", "-proot"]
      interval: 10s
      timeout: 5s
      retries: 5

  backend:
    image: krushnathakare/cricket-auction-backend:latest
    container_name: cricket-auction-backend
    restart: unless-stopped
    depends_on:
      mysql:
        condition: service_healthy
    environment:
      DB_USERNAME: root
      DB_PASSWORD: root
      SPRING_DATASOURCE_URL: jdbc:mysql://mysql:3306/cricket_auction?
createDatabaseIfNotExist=true&useSSL=false&allowPublicKeyRetrieval=true&serverTimezone=UTC
      CORS_ORIGINS: https://ktauction.in,https://www.ktauction.in
    ports:
      - "8080:8080"
    volumes:
      - cricket_uploads:/tmp/cricket-auction-uploads
      - cricket_images:/tmp/cricket-auction-images

  frontend:
    image: krushnathakare/cricket-auction-frontend:latest
    container_name: cricket-auction-frontend
    restart: unless-stopped
    depends_on:
      - backend
    ports:
      - "3000:80"

volumes:
  mysql_data:
```

```
  cricket_uploads:
  cricket_images:
```

Cloudflare tunnel

Usually no restart needed for app deploys. If public site is down: `sudo systemctl status cloudflared`
