

Security Review of TypeScript - A02_CVE-2024-31206

Here is a snippet of code written in TypeScript. I want to check for any potential security vulnerabilities.

```
import { Buffer } from 'node:buffer';
import { URL, URLSearchParams } from 'node:url';

/**
 * @param text The text to send to the aeiou Dectalk API
 * @returns A buffer containing wav-encoded binary output
 * @throws If text is empty or only whitespace
 * @throws If the API returns a non-200 response
 */
export default async function dectalk(text: string):
Promise<Buffer> {
    // The API does not like empty prompts
    text = text.trim();
    if (text.length === 0) {
        throw new TypeError('Text cannot be empty or only
whitespace');
    }

    // Format request URL
    const url = new URL('http://tts.cyzon.us/tts');
    url.search = new URLSearchParams({ text }).toString();

    // Send request
    const response = await fetch(url);

    // TODO look into custom behavior for aeiou's error
codes
    //
https://github.com/calzoneman/aeiou/blob/master/docs/usage-guidelines.md
    if (!response.ok) {
        throw new Error(`${response.status}
${response.statusText}, { cause: response });
    }
}
```

```
// Parse and return response
const binaryData = await response.arrayBuffer();
return Buffer.from(binaryData);
}
```

Here is an analysis of your TypeScript snippet for potential **security vulnerabilities** and **improvements**:

Security Review:

1. Unvalidated User Input (Text Field) - Risk of Injection:

- **Risk:** Although the code trims the input text, it doesn't sanitize it before embedding it into a query parameter.
- **Impact:** If the remote API has weak validation, this might allow for **injection attacks**, especially if special characters are allowed.
- **Mitigation:** Use proper encoding for the query parameters to ensure malicious input does not affect the API.

typescript

```
const params = new URLSearchParams({ text: encodeURIComponent(text)
}).toString();
url.search = params;
```

2. Insecure HTTP Request (No HTTPS):

- **Risk:** The code sends a request over HTTP, which is insecure. This can expose sensitive data to **man-in-the-middle (MITM)** attacks.
- **Impact:** Intercepted data can be manipulated, or the user's response can be altered.

- **Mitigation:** Use `https://` wherever possible, or ensure the external service supports secure communication.

typescript

```
const url = new URL('https://tts.cyzon.us/tts'); // Switch to HTTPS if available
```

3. Error Handling Disclosure (Detailed Errors):

- **Risk:** Throwing the raw error message with `response.status` and `response.statusText` might leak information about the API or its behavior to an attacker.
- **Impact:** Attackers could use error responses to gain insight into the API's internals or structure attacks based on known status codes.
- **Mitigation:** Limit error exposure and provide more generic error messages.

typescript

```
if (!response.ok) {
    console.error('API Request failed', { status: response.status, message:
response.statusText });
    throw new Error('An unexpected error occurred. Please try again later.');
```

4. Uncontrolled Buffer Allocation:

- **Risk:** Creating a `Buffer` from the response without size checks can lead to **memory exhaustion** or **DoS** if the response is unexpectedly large.
- **Impact:** A malicious API response could exhaust server memory, leading to a denial of service.
- **Mitigation:** Add a size limit check before creating the buffer.

typescript

```
const MAX_SIZE = 10 * 1024 * 1024; // 10 MB limit for example
const binaryData = await response.arrayBuffer();
if (binaryData.byteLength > MAX_SIZE) {
    throw new Error('Response size exceeds the limit.');
```

```
}
```

```
return Buffer.from(binaryData);
```

5. Lack of Timeout Handling:

- **Risk:** The `fetch` request has no timeout configured, which can leave the application hanging indefinitely if the API becomes unresponsive.
- **Mitigation:** Use a **timeout wrapper** around the `fetch` call to prevent this.

typescript

```
function fetchWithTimeout(url: URL, timeout: number = 5000): Promise<Response> {
    return Promise.race([
        fetch(url),
        new Promise((_, reject) => setTimeout(() => reject(new Error('Request
timed out')), timeout))
    ]);
}
```

```
const response = await fetchWithTimeout(url);
```

6. Missing Input Length Validation:

- **Risk:** There is no upper limit on the input size. Very long inputs could overwhelm the API or cause performance issues.
- **Mitigation:** Add a **maximum length constraint** for input text.

typescript

```
const MAX_TEXT_LENGTH = 500; // Example max length
if (text.length > MAX_TEXT_LENGTH) {
    throw new Error(`Text exceeds the maximum length of ${MAX_TEXT_LENGTH}
characters.`);
}
```

Final Revised Code with Security Improvements:

typescript

```
import { Buffer } from 'node:buffer';
import { URL, URLSearchParams } from 'node:url';

const MAX_TEXT_LENGTH = 500;
const MAX_SIZE = 10 * 1024 * 1024; // 10 MB size limit

function fetchWithTimeout(url: URL, timeout: number = 5000): Promise<Response> {
    return Promise.race([
        fetch(url),
        new Promise((_, reject) => setTimeout(() => reject(new Error('Request timed
out')), timeout))
    ]);
}

/**
 * @param text The text to send to the aeiou Dectalk API
 * @returns A buffer containing wav-encoded binary output
 * @throws If `text` is empty, only whitespace, or too long
 * @throws If the API returns a non-200 response or times out
 */
export default async function dectalk(text: string): Promise<Buffer> {
    // Validate input
    text = text.trim();
    if (text.length === 0) {
        throw new TypeError('Text cannot be empty or only whitespace');
    }
}
```

```
}
if (text.length > MAX_TEXT_LENGTH) {
    throw new Error(`Text exceeds the maximum length of ${MAX_TEXT_LENGTH}
characters.`);
}

// Format request URL
const url = new URL('https://tts.cyzon.us/tts'); // Ensure HTTPS
url.search = new URLSearchParams({ text: encodeURIComponent(text) }).toString();

// Send request with timeout
const response = await fetchWithTimeout(url);

if (!response.ok) {
    console.error('API Request failed', { status: response.status, message:
response.statusText });
    throw new Error('An unexpected error occurred. Please try again later.');
```

```
}

// Parse and return response with size validation
const binaryData = await response.arrayBuffer();
if (binaryData.byteLength > MAX_SIZE) {
    throw new Error('Response size exceeds the limit.');
```

```
}
return Buffer.from(binaryData);
}
```

Summary of Changes:

1. **Input encoding** for query parameters to prevent injection.
2. **HTTPS** used instead of HTTP for secure communication.
3. **Generic error messages** to avoid exposing API details.
4. **Buffer size check** to prevent memory exhaustion.
5. **Timeout handling** for the `fetch` request.

6. Text length validation to avoid excessively large inputs.

These improvements address potential vulnerabilities and make the code more resilient to malicious inputs and network issues.

Provide the exact part of the code along with line numbers that are vulnerable or have security issues.

Here is the **exact code with line numbers** highlighting the vulnerable or risky sections and explaining the specific issues:

Code with Line Numbers and Vulnerabilities Highlighted:

typescript

```

1  import { Buffer } from 'node:buffer';
2  import { URL, URLSearchParams } from 'node:url';
3
4  /**
5   * @param text The text to send to the aeiou Dectalk API
6   * @returns A buffer containing wav-encoded binary output
7   * @throws If `text` is empty or only whitespace
8   * @throws If the API returns a non-200 response
9   */
10 export default async function dectalk(text: string): Promise<Buffer> {
11     // The API does not like empty prompts
12     text = text.trim();
13     if (text.length === 0) {
14         throw new TypeError('Text cannot be empty or only whitespace');
15     }
16
17     // Format request URL
18     const url = new URL('http://tts.cyzon.us/tts'); // (1) Insecure HTTP usage
19     url.search = new URLSearchParams({ text }).toString(); // (2) Unvalidated
    input
20
21     // Send request

```

```

22     const response = await fetch(url); // (3) No timeout or retry handling
23
24     // TODO look into custom behavior for aeiou's error codes
25     // https://github.com/calzoneman/aeiou/blob/master/docs/usage-guidelines.md
26     if (!response.ok) { // (4) Leaks status code and API behavior
27         throw new Error(`${response.status} ${response.statusText}`, { cause:
response });
28     }
29
30     // Parse and return response
31     const binaryData = await response.arrayBuffer(); // (5) Unchecked response
size
32     return Buffer.from(binaryData); // (6) Potential memory exhaustion
33 }

```

Vulnerabilities Identified with Line Numbers and Issues:

1. Line 18: Insecure HTTP Usage

- **Issue:** Using `http://` makes the request vulnerable to **man-in-the-middle (MITM)** attacks.
- **Mitigation:** Change the URL to `https://` if the API supports it.

Vulnerable Code:

typescript

```
const url = new URL('http://tts.cyzon.us/tts'); // (1)
```

2. Line 19: Unvalidated Input

- **Issue:** The input text is directly embedded into the query parameter without proper **sanitization or encoding**.

- **Impact:** This can lead to **injection attacks** if the remote API does not handle special characters safely.
- **Mitigation:** Use `encodeURIComponent` for the input.

Vulnerable Code:

```
typescript

url.search = new URLSearchParams({ text }).toString(); // (2)
```

3. Line 22: No Timeout or Retry Handling

- **Issue:** If the API is unresponsive, the `fetch` call can hang indefinitely, leading to a **denial of service (DoS)**.
- **Mitigation:** Implement a **timeout** for the request.

Vulnerable Code:

```
typescript

const response = await fetch(url); // (3)
```

4. Line 26-27: Leaks Status Code and API Behavior

- **Issue:** Exposing the raw status code and message from the API can give **attackers insights** into how the API works, potentially enabling further attacks.
- **Mitigation:** Replace detailed error messages with more generic ones.

Vulnerable Code:

```
typescript
```

```
if (!response.ok) { // (4)
    throw new Error(`${response.status} ${response.statusText}`, { cause:
response });
}
```

5. Line 31: Unchecked Response Size

- **Issue:** The code does not check the size of the response, which can lead to **memory exhaustion** if a large payload is returned.
- **Mitigation:** Add a **size limit check** before creating the buffer.

Vulnerable Code:

typescript

```
const binaryData = await response.arrayBuffer(); // (5)
```

6. Line 32: Potential Memory Exhaustion

- **Issue:** Creating a **Buffer** from an unchecked **ArrayBuffer** can **exhaust memory**, leading to a **denial of service (DoS)**.
- **Mitigation:** Add a **size limit validation** before this step.

Vulnerable Code:

typescript

```
return Buffer.from(binaryData); // (6)
```

Summary of Vulnerabilities:

Line Number	Issue	Risk	Solution
18	Insecure HTTP Usage	MITM Attack	Use HTTPS
19	Unvalidated Input	Injection Attack	Use <code>encodeURIComponent</code>
22	No Timeout or Retry Handling	Denial of Service (DoS)	Implement Timeout
26-27	Leaks API Behavior via Errors	Information Disclosure	Use Generic Error Messages
31	Unchecked Response Size	Memory Exhaustion / DoS	Add Size Limit Check
32	Potential Memory Exhaustion	Denial of Service (DoS)	Validate Response Size

By addressing these issues, your code will become more secure, reducing the chances of being vulnerable to attacks or performance issues.

Please analyze the code for common security vulnerabilities if present and map them to OWASP Top 10 Web Application Security Risk category/categories.

Below is the detailed security analysis of your **TypeScript code** snippet, identifying the relevant **OWASP Top 10 Web Application Security Risks (2021)**:

OWASP Top 10 Security Risk Mapping and Analysis

1. Insecure HTTP Usage (Line 18)

OWASP Category: A02:2021 - Cryptographic Failures

- **Issue:** Using **HTTP** for communication can lead to **man-in-the-middle (MITM)** attacks, where an attacker can intercept or modify the data in transit. This exposes sensitive information or allows attackers to manipulate the request/response.
- **Mitigation:** Use `https://` if the API supports it.

Vulnerable Code:

typescript

```
const url = new URL('http://tts.cyzon.us/tts'); // Insecure HTTP usage
```

2. Unvalidated Input in Query Parameters (Line 19)

OWASP Category: A01:2021 - Broken Access Control

- **Issue:** If user input is directly passed into query parameters without encoding or validation, it could be used for **injection attacks**. Although this isn't a classic SQL or XSS injection example, **parameter tampering** could still manipulate the API behavior.
- **Mitigation:** Use `encodeURIComponent` to properly encode query parameters.

Vulnerable Code:

typescript

```
url.search = new URLSearchParams({ text }).toString(); // Unvalidated input
```

3. No Timeout or Retry Handling (Line 22)

OWASP Category: A09:2021 - Security Logging and Monitoring Failures

- **Issue:** Without a **timeout mechanism**, the request can hang indefinitely, leading to a **Denial of Service (DoS)** situation, either intentionally or due to API unavailability.

- **Mitigation:** Implement a **timeout** wrapper around the `fetch` request to fail gracefully and log such incidents.

Vulnerable Code:

typescript

```
const response = await fetch(url); // No timeout handling
```

4. Exposing Detailed Error Information (Lines 26-27)

OWASP Category: A01:2021 - Broken Access Control

OWASP Category: A05:2021 - Security Misconfiguration

- **Issue:** Returning or logging the **status code** and **status text** from the API gives attackers insights into the system's internal behavior, making it easier to exploit vulnerabilities.
- **Mitigation:** Use generic error messages for external exposure, and limit the error information to logs meant for internal monitoring.

Vulnerable Code:

typescript

```
if (!response.ok) {
    throw new Error(`${response.status} ${response.statusText}`, { cause: response }); // Leaks API behavior
}
```

5. Unchecked Response Size (Line 31)

OWASP Category: A04:2021 - Insecure Design

- **Issue:** If the **response size** from the API is not limited, it could result in **memory exhaustion**, potentially leading to a **Denial of Service (DoS)** attack.

- **Mitigation:** Add a **size limit check** before processing the response to ensure it doesn't exceed a safe threshold.

Vulnerable Code:

```
typescript

const binaryData = await response.arrayBuffer(); // Unchecked response size
```

6. Potential Memory Exhaustion from Buffer Allocation (Line 32)

OWASP Category: A06:2021 - Vulnerable and Outdated Components

- **Issue:** Creating a **Buffer** from a potentially large or malformed response without checks could lead to **memory exhaustion** and **Denial of Service (DoS)**.
- **Mitigation:** Check the response size before creating the buffer to prevent allocating more memory than necessary.

Vulnerable Code:

```
typescript

return Buffer.from(binaryData); // Potential memory exhaustion
```

Summary of Vulnerabilities Mapped to OWASP Top 10 Categories

Line Number	Issue	OWASP Category	Description
18	Insecure HTTP Usage	A02:2021 - Cryptographic Failures	Use HTTPS to prevent MITM attacks.

Line Number	Issue	OWASP Category	Description
19	Unvalidated Input in Query Parameters	A01:2021 - Broken Access Control	Input validation is critical to avoid tampering.
22	No Timeout or Retry Handling	A09:2021 - Security Logging and Monitoring Failures	Prevent indefinite hanging by adding timeouts.
26-27	Exposing Detailed Error Information	A01:2021 - Broken Access Control / A05:2021 - Security Misconfiguration	Leaking system information helps attackers.
31	Unchecked Response Size	A04:2021 - Insecure Design	Large responses can cause memory exhaustion.
32	Potential Memory Exhaustion from Buffer Allocation	A06:2021 - Vulnerable and Outdated Components	Avoid excessive memory allocation with size checks.

Final Recommendations

1. **Switch to HTTPS** to avoid exposing the data in transit to MITM attacks.
2. **Sanitize and encode input** parameters to prevent query injection or tampering attacks.
3. **Implement timeouts** for the `fetch` request to avoid hanging or DoS issues.
4. **Limit error information exposure** by logging detailed errors internally but showing generic messages externally.
5. **Add response size validation** to avoid memory exhaustion attacks.
6. **Check memory allocation carefully** to ensure safe buffer creation and prevent DoS attacks.

By addressing these vulnerabilities, your code will align better with security best practices and mitigate several risks listed under the OWASP Top 10.