

ChatGPT - A03_CVE-2021-41232

Here is a snippet of code written in go. I want to check for any potential security vulnerabilities.

```
package main

import (
    "crypto/tls"
    "errors"
    "fmt"
    "log"
    "net/http"

    "github.com/StevenWeathers/thunderdome-planning-
    poker/pkg/database"
    ldap "github.com/go-ldap/ldap/v3"
    "github.com/spf13/viper"
)

func (s *server) createCookie(userID string) *http.Cookie {
    encoded, err :=
s.cookie.Encode(s.config.SecureCookieName, userID)
    var NewCookie *http.Cookie

    if err == nil {
        NewCookie = &http.Cookie{
            Name:    s.config.SecureCookieName,
            Value:   encoded,
            Path:    s.config.PathPrefix + "/",
            HttpOnly: true,
            Domain:  s.config.AppDomain,
            MaxAge:  86400 * 30, // 30 days
            Secure: s.config.SecureCookieFlag,
            SameSite: http.SameSiteStrictMode,
        }
    }
    return NewCookie
}
```

```
func (s *server) authUserDatabase(UserEmail string,
UserPassword string) (*database.User, error) {
    AuthedUser, err := s.database.AuthUser(UserEmail,
UserPassword)
    if err != nil {
        log.Println("Failed authenticating user", UserEmail)
    } else if AuthedUser == nil {
        log.Println("Unknown user", UserEmail)
    }
    return AuthedUser, err
}

// Authenticate using LDAP and if user does not exist,
// automatically add user as a verified user
func (s *server) authAndCreateUserLdap(Username string,
UserPassword string) (*database.User, error) {
    var AuthedUser *database.User
    l, err := ldap.DialURL(viper.GetString("auth.ldap.url"))
    if err != nil {
        log.Println("Failed connecting to ldap server at",
viper.GetString("auth.ldap.url"))
        return AuthedUser, err
    }
    defer l.Close()
    if viper.GetBool("auth.ldap.use_tls") {
        err = l.StartTLS(&tls.Config{InsecureSkipVerify: true})
        if err != nil {
            log.Println("Failed securing ldap connection", err)
            return AuthedUser, err
        }
    }

    if viper.GetString("auth.ldap.bindname") != "" {
        err = l.Bind(viper.GetString("auth.ldap.bindname"),
viper.GetString("auth.ldap.bindpass"))
        if err != nil {
            log.Println("Failed binding for authentication:", err)
            return AuthedUser, err
        }
    }
```

```
}

searchRequest :=
ldap.NewSearchRequest(viper.GetString("auth.ldap.basedn"
),
    ldap.ScopeWholeSubtree, ldap.NeverDerefAliases, 0, 0,
false,
    fmt.Sprintf(viper.GetString("auth.ldap.filter"),
UserName),
    []string{"dn", viper.GetString("auth.ldap.mail_attr"),
viper.GetString("auth.ldap.cn_attr")},
    nil,
    )

sr, err := l.Search(searchRequest)
if err != nil {
    log.Println("Failed performing ldap search query for",
UserName, ":", err)
    return AuthedUser, err
}

if len(sr.Entries) != 1 {
    log.Println("User", UserName, "does not exist or too
many entries returned")
    return AuthedUser, errors.New("user not found")
}

userdn := sr.Entries[0].DN
useremail :=
sr.Entries[0].GetAttributeValue(viper.GetString("auth.ldap.m
ail_attr"))
usercn :=
sr.Entries[0].GetAttributeValue(viper.GetString("auth.ldap.cn
_attr"))

err = l.Bind(userdn, UserPassword)
if err != nil {
    log.Println("Failed authenticating user ", UserName)
    return AuthedUser, err
}
```

```

    AuthedUser, err = s.database.GetUserByEmail(useremail)
    if AuthedUser == nil {
        log.Println("User", useremail, "does not exist in
database, auto-recruit")
        newUser, verifyID, err :=
s.database.CreateUserRegistered(usercn, useremail, "", "")
        if err != nil {
            log.Println("Failed auto-creating new user", err)
            return AuthedUser, err
        }
        err = s.database.VerifyUserAccount(verifyID)
        if err != nil {
            log.Println("Failed verifying new user", err)
            return AuthedUser, err
        }
        AuthedUser = newUser
    }

    return AuthedUser, nil
}

```

Your Go code contains several sections with potential security issues. Let's go through them systematically, with a focus on areas where security vulnerabilities could arise.

1. Insecure LDAP Configuration (`InsecureSkipVerify: true`)

```

go

err = l.StartTLS(&tls.Config{InsecureSkipVerify: true})

```

- **Issue:** Using `InsecureSkipVerify: true` disables TLS certificate validation, exposing the LDAP connection to man-in-the-middle (MITM) attacks.
- **Recommendation:** Avoid using `InsecureSkipVerify: true`. If you need to ignore self-signed certificates for development purposes, ensure it is disabled in production. Alternatively:

```
go

tlsConfig := &tls.Config{
    InsecureSkipVerify: false, // Ensure certificate is verified
}
```

2. Hardcoded Cookie Max-Age (Session Management)

```
go

MaxAge: 86400 * 30, // 30 days
```

- **Issue:** A 30-day cookie expiration may be too long and could increase exposure to session hijacking.
- **Recommendation:** Use shorter session expiration times and consider using **refresh tokens** to extend sessions securely. Additionally, monitor and rotate sessions more frequently.

3. Missing Error Handling in Cookie Encoding

```
go

if err == nil {
    NewCookie = &http.Cookie{
        ...
    }
}
```

- **Issue:** If cookie encoding fails, the function silently returns `nil`. This could lead to inconsistent behavior without providing a proper error response.
- **Recommendation:** Handle the error gracefully:

```
go

if err != nil {
    log.Println("Failed to encode cookie:", err)
    return nil
}
```

4. Improper Error Logging (Sensitive Information Leakage)

```
go

log.Println("Failed authenticating user", userEmail)
```

- **Issue:** Logging the user email on failed authentication attempts could expose sensitive information in logs. This can become an attack vector if the logs are accessed by unauthorized users.
- **Recommendation:** Log only generic error messages and avoid logging sensitive data.

```
go

log.Println("Authentication failed for a user")
```

5. LDAP Injection Risk in User Input

```
go

searchRequest := ldap.NewSearchRequest(viper.GetString("auth.ldap.basedn"),
    ldap.ScopeWholeSubtree, ldap.NeverDerefAliases, 0, 0, false,
    fmt.Sprintf(viper.GetString("auth.ldap.filter"), UserName),
    ...
)
```

- **Issue:** User-supplied input (i.e., `UserName`) is directly inserted into the LDAP query without proper sanitization, exposing the application to **LDAP injection attacks**.
 - **Recommendation:** Ensure the user input is sanitized and avoid direct string concatenation in LDAP filters. Use placeholders or safe APIs to construct queries.
-

6. Weak Password Binding Logic

```
go

err = l.Bind(userdn, UserPassword)
if err != nil {
    log.Println("Failed authenticating user ", UserName)
    return AuthedUser, err
}
```

- **Issue:** The password is directly used to bind without rate-limiting or account lockout after multiple failed attempts. This may allow brute-force attacks.
 - **Recommendation:** Implement **rate limiting** and **account lockout** mechanisms after a set number of failed attempts.
-

7. Missing Secure HTTP Headers

- **Issue:** While you are setting the `Secure` and `HttpOnly` flags on the cookie, there's no enforcement of additional headers like `Content-Security-Policy` (CSP) or `Strict-Transport-Security` (HSTS), which are critical for securing web applications.
 - **Recommendation:** Ensure the server sends appropriate headers, like:
 - `Strict-Transport-Security: max-age=63072000; includeSubDomains`
 - `Content-Security-Policy: default-src 'self';`
-

8. Potential User Enumeration in Error Messages

```
go

if len(sr.Entries) != 1 {
    log.Println("User", UserName, "does not exist or too many entries returned")
    return AuthedUser, errors.New("user not found")
}
```

- **Issue:** The message indicates if the user does not exist, making the system vulnerable to **user enumeration attacks**.
- **Recommendation:** Always respond with generic error messages for authentication-related functions:

```
go

return nil, errors.New("invalid credentials")
```

9. Potential Race Conditions in Auto-User Creation

```
go

newUser, verifyID, err := s.database.CreateUserRegistered(usercn, useremail, "", "")
if err != nil {
    log.Println("Failed auto-creating new user", err)
    return AuthedUser, err
}
```

- **Issue:** If two concurrent requests are made with the same user email, it could lead to **race conditions** and inconsistent user creation behavior.
- **Recommendation:** Use **mutexes** or **database constraints** to prevent duplicate entries.

10. Plaintext Password Handling in LDAP Authentication

```
go
```

```
AuthedUser, err := s.database.AuthUser(UserEmail, UserPassword)
```

- **Issue:** Storing or handling plaintext passwords directly in memory is risky. Even though you are passing it temporarily, passwords should be handled securely throughout their lifecycle.
- **Recommendation:** Use **password hashing** libraries (like bcrypt) for password comparison instead of storing plaintext passwords. If using LDAP, consider token-based authentication where possible.

Summary of Recommendations:

1. **Avoid insecure TLS settings:** Do not use `InsecureSkipVerify`.
2. **Sanitize user input in LDAP filters** to prevent LDAP injection.
3. **Avoid exposing sensitive data** in logs and error messages.
4. **Implement rate-limiting** and **account lockouts** to prevent brute-force attacks.
5. **Secure cookie management:** Use shorter expiration and refresh tokens.
6. **Harden session and authentication management** with proper headers and handling.
7. **Prevent user enumeration** with generic authentication error messages.
8. **Handle race conditions** in auto-user creation logic properly.

Addressing these points will make the code significantly more secure and reduce the risk of common vulnerabilities.

Provide the exact part of the code along with line numbers that are vulnerable or have security issues.

Below is a list of the exact sections in your Go code with line numbers assigned for each identified security issue.

1. Insecure TLS Configuration (`InsecureSkipVerify`)

Issue: Disabling TLS verification exposes the connection to MITM attacks.

Code:

```
go

46: err = l.StartTLS(&tls.Config{InsecureSkipVerify: true})
```

2. Hardcoded Cookie Expiration

Issue: A 30-day cookie expiration is too long and increases session hijacking risks.

Code:

```
go

21: MaxAge: 86400 * 30, // 30 days
```

3. Silent Error Handling in Cookie Encoding

Issue: If encoding fails, it returns `nil` without handling the error properly.

Code:

```
go

17: if err == nil {
18:     NewCookie = &http.Cookie{
```

Fix: Handle the error explicitly:

```
go

17: if err != nil {
18:     log.Println("Failed to encode cookie:", err)
19:     return nil
20: }
```

4. Logging Sensitive User Information

Issue: Logs expose email addresses, enabling sensitive data leakage.

Code:

```
go

29: log.Println("Failed authenticating user", userEmail)
31: log.Println("Unknown user", userEmail)
```

5. LDAP Injection Vulnerability

Issue: Using `fmt.Sprintf` to insert user input in the LDAP filter can lead to LDAP injection.

Code:

```
go

61: fmt.Sprintf(viper.GetString("auth.ldap.filter"), username),
```

Fix: Use a safe method for constructing LDAP filters, avoiding direct user input concatenation.

6. Missing Rate-Limiting and Lockout Mechanism

Issue: No lockout mechanism or rate limiting allows brute-force attacks.

Code:

```
go

79: err = l.Bind(userdn, UserPassword)
```

7. Exposing User Enumeration through Error Messages

Issue: Error message reveals whether a user exists, allowing user enumeration attacks.

Code:

```
go

69: if len(sr.Entries) != 1 {
70:     log.Println("User", UserName, "does not exist or too many entries returned")
71:     return AuthedUser, errors.New("user not found")
```

Fix: Use a generic error message:

```
go

71: return nil, errors.New("invalid credentials")
```

8. Race Condition in User Creation Logic

Issue: Concurrent requests may cause duplicate user creation without proper locking.

Code:

```
go
```

```
92: newUser, verifyID, err := s.database.CreateUserRegistered(usercn, useremail, "",  
    "")
```

9. Handling Plaintext Passwords Directly

Issue: Passwords are handled directly without secure hashing or tokenization.

Code:

```
go  
  
29: AuthedUser, err := s.database.AuthUser(UserEmail, UserPassword)
```

Fix: Use a password hashing library (like bcrypt) and verify passwords securely.

10. Missing Secure Headers for HTTP Cookies

Issue: Though some cookie flags are used, additional security headers (e.g., HSTS) are missing.

Code:

```
go  
  
21: Secure:    s.config.SecureCookieFlag,  
22: SameSite: http.SameSiteStrictMode,
```

Summary of Issues with Line Numbers

Line Number	Issue	Recommendation
17-20	Silent error handling in cookie encoding	Handle the error properly
21	Long cookie expiration (30 days)	Shorten expiration, use refresh tokens
29, 31	Logging sensitive user info	Log generic error messages
46	Insecure TLS (<code>InsecureSkipVerify: true</code>)	Enable certificate verification
61	LDAP injection risk	Sanitize input properly
69-71	User enumeration through error messages	Use generic errors
79	No rate-limiting on password binding	Add rate-limiting or lockout
92	Race condition in user creation logic	Use mutexes or DB constraints
21-22	Missing secure headers	Add HSTS and CSP headers

This detailed breakdown with line numbers will help you locate and fix the security vulnerabilities efficiently.

Please analyze the code for common security vulnerabilities if present and map them to OWASP Top 10 Web Application Security Risk category/categories.

Below is a detailed analysis of your Go code, mapping identified vulnerabilities to relevant categories in the **OWASP Top 10 Web Application Security Risks**.

1. Insecure TLS Configuration (`InsecureSkipVerify`)

Location:

```
go

46: err = l.StartTLS(&tls.Config{InsecureSkipVerify: true})
```

- **Risk:** Disabling TLS verification exposes connections to **Man-in-the-Middle (MITM)** attacks.
- **OWASP Mapping: A03:2021 – Injections**
Disabling TLS certificate validation leaves the connection vulnerable to attack, which can allow malicious actors to manipulate queries, intercept authentication, or inject data.

Recommendation: Enable proper TLS certificate validation:

```
go

err = l.StartTLS(&tls.Config{InsecureSkipVerify: false})
```

2. LDAP Injection Vulnerability

Location:

```
go

61: fmt.Sprintf(viper.GetString("auth.ldap.filter"), UserName)
```

- **Risk:** Untrusted user input is injected directly into the LDAP query. This allows attackers to manipulate LDAP queries to retrieve unauthorized data or escalate privileges.
- **OWASP Mapping: A03:2021 – Injections**

Recommendation: Use parameterized queries or sanitize user input to avoid injections.

3. Logging Sensitive Data (Information Leakage)

Location:

```
go
```

```
29: log.Println("Failed authenticating user", userEmail)
31: log.Println("Unknown user", userEmail)
```

- **Risk:** Exposing sensitive data (e.g., user emails) in logs can aid attackers in reconnaissance efforts.
- **OWASP Mapping: A01:2021 – Broken Access Control**
Exposing sensitive user information can allow attackers to understand valid accounts, facilitating further attacks such as brute force or phishing.

Recommendation: Use generic log messages to avoid exposing sensitive information:

```
go

log.Println("Authentication failed")
```

4. Missing Rate Limiting on Password Authentication

Location:

```
go

79: err = l.Bind(userdn, UserPassword)
```

- **Risk:** Without rate limiting, the system is vulnerable to **brute-force** attacks where attackers repeatedly try passwords.
- **OWASP Mapping: A04:2021 – Insecure Design**
Lack of proper defense mechanisms such as rate limiting or account lockout makes the application prone to brute force attacks.

Recommendation: Implement rate limiting or account lockout:

```
go
```

```
if failedAttempts > threshold {  
    log.Println("Account locked due to too many failed attempts")  
    return nil, errors.New("account locked")  
}
```

5. User Enumeration Through Error Messages

Location:

```
go  
  
69: if len(sr.Entries) != 1 {  
70:     log.Println("User", UserName, "does not exist or too many entries returned")  
71:     return AuthedUser, errors.New("user not found")
```

- **Risk:** Distinct error messages reveal whether a user exists, allowing **user enumeration** through login attempts.
- **OWASP Mapping:** A01:2021 – Broken Access Control

Recommendation: Use generic error messages:

```
go  
  
log.Println("Invalid credentials")  
return nil, errors.New("invalid credentials")
```

6. Hardcoded Long Cookie Expiration

Location:

```
go
```

```
21: MaxAge: 86400 * 30, // 30 days
```

- **Risk:** A 30-day cookie expiration increases exposure to **session hijacking** if the session token is compromised.
- **OWASP Mapping: A02:2021 – Cryptographic Failures**
Long session lifetimes without proper token rotation expose the system to session hijacking risks.

Recommendation: Use shorter expiration times and implement **refresh tokens**.

7. Inadequate Error Handling in Cookie Creation

Location:

```
go

17: if err == nil {
    NewCookie = &http.Cookie{ ... }
}
```

- **Risk:** If encoding fails, the code silently returns `nil` without notifying the caller or handling the error properly.
- **OWASP Mapping: A05:2021 – Security Misconfiguration**
Improper error handling can cause unexpected behavior and make debugging more difficult.

Recommendation: Log the error and handle it properly:

```
go

if err != nil {
    log.Println("Cookie encoding failed:", err)
}
```

```
    return nil  
}
```

8. Race Condition in Auto-User Creation

Location:

```
go  
  
92: newUser, verifyID, err := s.database.CreateUserRegistered(usercn, useremail, "",  
    "")
```

- **Risk:** If two requests are processed concurrently, it could result in the same user being created multiple times, leading to **inconsistent states**.
- **OWASP Mapping: A04:2021 – Insecure Design**
Failure to implement concurrency controls leads to potential inconsistencies in user data.

Recommendation: Use **database constraints** or **mutexes** to prevent duplicate user creation.

9. Missing Secure HTTP Headers

Location:

```
go  
  
21: Secure:    s.config.SecureCookieFlag,  
22: SameSite: http.SameSiteStrictMode,
```

- **Risk:** While some cookie security flags are used, additional **security headers** such as **HSTS** and **CSP** are missing, which leaves the application exposed to **man-in-the-middle**

attacks or XSS attacks.

- OWASP Mapping: A05:2021 – Security Misconfiguration

Recommendation: Add these headers:

```
go

w.Header().Set("Strict-Transport-Security", "max-age=63072000; includeSubDomains")
w.Header().Set("Content-Security-Policy", "default-src 'self'")
```

10. Handling Plaintext Passwords in Memory

Location:

```
go

29: AuthedUser, err := s.database.AuthUser(UserEmail, UserPassword)
79: err = l.Bind(userdn, UserPassword)
```

- **Risk:** Passwords are handled directly in memory without hashing. This increases the risk of password leakage.
- OWASP Mapping: A02:2021 – Cryptographic Failures

Recommendation: Use **bcrypt** or a similar password hashing library for secure password management:

```
go

import "golang.org/x/crypto/bcrypt"

hashedPassword, _ := bcrypt.GenerateFromPassword([]byte(UserPassword),
bcrypt.DefaultCost)
```

Summary of OWASP Mappings

Issue	OWASP Category	Relevant Code Section
Insecure TLS Configuration	A03:2021 – Injections	Line 46
LDAP Injection Vulnerability	A03:2021 – Injections	Line 61
Logging Sensitive Data	A01:2021 – Broken Access Control	Lines 29, 31
Missing Rate Limiting	A04:2021 – Insecure Design	Line 79
User Enumeration Through Error Messages	A01:2021 – Broken Access Control	Lines 69-71
Long Cookie Expiration	A02:2021 – Cryptographic Failures	Line 21
Inadequate Error Handling in Cookie Creation	A05:2021 – Security Misconfiguration	Line 17
Race Condition in User Creation	A04:2021 – Insecure Design	Line 92
Missing Secure HTTP Headers	A05:2021 – Security Misconfiguration	Lines 21-22
Handling Plaintext Passwords in Memory	A02:2021 – Cryptographic Failures	Lines 29, 79

Conclusion

The code contains several vulnerabilities that map to multiple **OWASP Top 10 categories**, including **Injections**, **Broken Access Control**, **Insecure Design**, and **Cryptographic Failures**. To secure this application, address the issues outlined above with appropriate mitigations like input validation, secure password handling, proper error handling, and the use of secure headers.