

smiRk: New R package for microRNA-mRNA data analysis

Krutik Patel, Carole Proctor, David Young and Daryl Shanley

Newcastle University
k.patel5@newcastle.ac.uk

1. Rationale

Introduction

- MicroRNAs (miRs) control over 60% of mammalian protein coding genes [1].
- Large time course mRNA and miRNA data sets are being generated.
- I have created an R package to integrate and functionally analyse this type of data.**
- Output of the R package can help generate hypothesis for further systems or experimental work.




Fig. 1: miRs regulate target mRNA expression levels

Mouse Kidney Fibrosis data [2]

- mRNAseq and small non-coding RNAseq data were located respectively in GSE65267 and GSE61328. Data was processed using standard tools.
- Measurements taken prior to injection of Folic acid and 1, 2, 3, 7 and 14 days after.
- This is a commonly used mouse model for chronic kidney disease experiments.

3. Time course GSEA

Building upon functions from rWikiPathways and clusterProfiler a user can see which pathways their data is most associated with, per time point [3, 4].




Fig. 3: Time point specific pathway enrichment

- Tryptophan Metabolism and Amino Acid Metabolism are found in all time point enrichment's.
- Genes related to Lung Fibrosis, TY-ROBP Causal Network and Complement related pathways found later on in kidney fibrosis data.
- Users can further investigate the pathways of interest.

6. Pathvisio and Model creation




Fig. 7: Pathvisio visualisation of miR integrated Complement and Coagulation Cascades




Fig. 8: GRN of a Complement model in Cell Designer

- Pathvisio output can be simplified to build gene regulatory networks (GRNs) on Cell Designer [5].
- smiRk package utilises big multi omic data for model hypothesis generation.
- Supplements primary use of literature or existing models for model generation.**

2. smiRk package pipeline




Fig. 2: smiRk package overview

- Input = differential expression.**
- WikiPathways used for GSE and cluster analysis to identify pathways of interest [6].
- Databases: TargetScans, miRTarBase and miRDB assess potential miR-mRNA interactions [7-9].
- Graphical networks of filtered miR-mRNA interactions can be made in R.
- miR-mRNA interactions found in the pathways of interest can be exported into Pathvisio or Cytoscape [10, 11].
- Output = Hypothesis generation for further systems or wet lab enquiries.**

4. Pathway Clustering




Fig. 4: Pathway soft clustering

- Clustering by Mfuzz [12].
- The number of genes found in pathways are clustered by temporal changes.
- Four pathways fitted with cluster 1 at > 0.8 confidence, e.g. Inflammatory Response Pathway.

5. miR-mRNA networks




Fig. 5: miR-mRNA interactions in Complement and Coagulation Cascades

Fig. 6: miR-mRNA interactions in Inflammatory Response Pathway

- Displayed using the igraph package [13].
- User can customise which interactions to view.
- Interactions:
 - negative average correlation
 - In miRDB
 - In TargetScans

Conclusions

Conclusions

- smiRk package integrates, analyses and generates networks from time series miR-mRNA expression data.
- Output can lead to hypothesis generation for systems modelling or experimental work.
- smiRk will be accessible from bioconductor in 2020.

References

- Robin C Friedman et al. "Most mammalian mRNAs are conserved targets of microRNAs". In: *Genome research* 19.1 (2009), pp. 92-105.
- Mira Pavkovic et al. "Multi omics analysis of fibrotic kidneys in two mouse models". In: *Scientific data* 6.1 (2019), p. 92.
- Denise N Sienter et al. "WikiPathways: a multifaceted pathway database bridging metabolomics to other omics research". In: *Nucleic acids research* 46.D1 (2017), pp. D661-D667.
- Guanghuang Yu et al. "WikiPathways: an R package for comparing biological themes among gene clusters". In: *Omics: a journal of integrative biology* 16.5 (2012), pp. 284-287.
- Akira Funahashi et al. "CellDesigner 3.5: a versatile modeling tool for biochemical networks". In: *Proceedings of the IEEE* 96.8 (2008), pp. 1254-1265.
- Alexander R Pico et al. "WikiPathways: pathway editing for the people". In: *PLoS biology* 6.7 (2008), e184.
- Vikram Agarwal et al. "Predicting effective microRNA target sites in mammalian mRNAs". In: *Life* 4 (2015), e05005.
- Nathan Wong and Xiaowei Wang. "miRDB: an online resource for microRNA target prediction and functional annotations". In: *Nucleic acids research* 43.D1 (2014), pp. D146-D152.
- Chih-Hung Chou et al. "miRTarBase update 2018: a resource for experimentally validated microRNA-target interactions". In: *Nucleic acids research* 46.D1 (2017), pp. D396-D392.
- Martijn P van Iersel et al. "Presenting and exploring biological pathways with PathVisio". In: *BMC bioinformatics* 9.1 (2008), p. 399.
- Paul Shannon et al. "Cytoscape: a software environment for integrated models of biomolecular interaction networks". In: *Genome research* 13.11 (2003), pp. 2498-2504.
- Matthias E Futschik and Lokes Kumar. "Introduction to Mfuzz package and its graphical user interface". In: (2013).
- Gabor Csardi, Tamas Nepusz, et al. "The igraph software package for complex network research". In: *InterJournal, Complex Systems* 1695.5 (2006), pp. 1-9.