


Types of HMM


Objectives

- To understand the differences between types of HMM
- Notes: pp 38-43

HMM taxonomy



Types of Conventional HMM



Multimodal Interaction Lab

b s m i g a m

EE4R Automatic Spoken Language Processing




Front-End Processing Re-Visited

Vectors in d -dimensional (continuous) space

Vectors in d -dimensional (continuous) space

Symbols from a **finite** set



Multimodal Interaction Lab

b s m i g a m

EE4R Automatic Spoken Language Processing



Discrete HMMs

- If VQ is used, then a state output PDF b_i is defined by a **list** of probabilities-

$$b_i(m) = \text{Prob}(y_t = z_m \mid x_t = s_i)$$

- The resulting HMM is a **discrete HMM**
- Common in mid-1980/ early-1990s
- Computational advantages
- Disadvantages
 - VQ may introduce non-recoverable errors
 - Choice of metric d for VQ?
- Outperformed by Continuous HMM

Multimodal Interaction Lab


b s m i g a m

EE4R Automatic Spoken Language Processing



Continuous HMMs

- Without VQ, $b_i(y)$ must be defined for any y in the (continuous) observation set S
- Hence discrete state output PDFs no longer viable
- Use parametric continuous state output PDFs - **Continuous HMMs**
- Choice of PDF restricted by mathematical tractability and computational usefulness (see “HMM training & recognition” later)
- Most people begin with Gaussian PDFs
- Resulting HMMs called **Gaussian HMMs**



EE4R Automatic Spoken Language Processing




Gaussian HMMs

- State output PDFs are multivariate Gaussian

$$b_i(y) = \frac{1}{\sqrt{(2\pi)^d |C_i|}} \exp \left\{ -\frac{1}{2} (y - m_i)' C_i^{-1} (y - m_i) \right\}$$


- m_i and C_i are the mean vector and covariance matrix which define b_i



EE4R Automatic Spoken Language Processing



Gaussian PDF



Gaussian PDF with $m_i = 0$ and $C_i = 20$



EE4R Automatic Spoken Language Processing



Gaussian HMMs - Issues

- Significant computational savings if covariance matrix can be assumed to be diagonal
- In general, Gaussian PDFs are **not** flexible enough to model speech pattern variability accurately
 - In many applications (e.g. modelling speech from multiple speakers) a unimodal PDF is inadequate
 - Even if unimodal PDF is basically OK there may be more subtle inadequacies

Multimodal Interaction Lab


b s m i g a m

EE4R Automatic Spoken Language Processing




Gaussian Mixture Densities

Example - 2 component Gaussian mixture



$$f(y) = N_{(0,1)}(y)$$

$$g(y) = N_{(2,2)}(y)$$



$$m(y) = w \cdot f(y) + (1-w) \cdot g(y)$$

Multimodal Interaction Lab

b s m i g a m

EE4R Automatic Spoken Language Processing



Gaussian Mixture HMMs

- Any PDF can be approximated arbitrarily closely by a Gaussian mixture PDF with sufficient components
- But...
 - More mixture components require more data for robust model parameter estimation
 - Parameter smoothing and sharing needed (e.g. 'tied mixtures', 'grand variance', ...)
- Gaussian mixture HMMs widely used in systems in research laboratories.

Multimodal Interaction Lab

b s m i g a m

EE4R Automatic Spoken Language Processing



Relationship with Neural Networks

- ‘Classical’ HMM training methods focus on fitting state output PDFs to data (modelling), rather than minimizing overlap between PDFs (discrimination).
- NNs are good at discrimination
- **But** NNs poor at coping with time-varying data
- Research interest in ‘hybrid’ systems which use NNs to relate the observations to the states of the underlying Markov model.

Multimodal Interaction Lab



EE4R Automatic Spoken Language Processing



Summary

- Types of HMM
- Discrete HMMs
- Continuous HMMs
- Gaussian HMMs
- Gaussian Mixture HMMs

Multimodal Interaction Lab



EE4R Automatic Spoken Language Processing

