

Experiment 6

Aim:

- A. To perform a simple k-mean clustering algorithm on any data set(at least 1500 instant and 6 classes).
- B. To Implement k mean clustering algorithm in python.

Theory: K-means clustering is a method of vector quantization, originally from signal processing, that is popular for cluster analysis in data mining. k-means clustering aims to partition 'n' observations into k clusters in which each observation belongs to the cluster with the nearest mean, serving as a prototype of the cluster. This results in a partitioning of the data space into Voronoi cells. The problem is computationally difficult (NP-hard); however, efficient heuristic algorithms converge quickly to a local optimum. These are usually similar to the expectation-maximization algorithm for mixtures of Gaussian distributions via an iterative refinement approach employed by both k-means and Gaussian mixture modelling. They both use cluster centres to model the data; however, k-means clustering tends to find clusters of comparable spatial extent, while the expectation-maximization mechanism allows clusters to have different shapes.

The algorithm has a loose relationship to the k-nearest neighbour classifier, a popular machine learning technique for classification that is often confused with k-means due to the name. Applying the 1-nearest neighbour classifier to the cluster centres obtained by k-means classifies new data into the existing clusters. To process the learning data, the K-means algorithm in data mining starts with the first group of randomly selected centroids, which are used as the beginning points for every cluster, and then performs iterative (repetitive) calculations to optimize the positions of the centroids. It halts creating and optimizing clusters when either:

- The centroids have stabilized—there is no change in their values because the clustering has been successful.
- The defined number of iterations has been achieved.

Algorithm:

- A. Initialize k means with random values
- B. For a given number of iterations:
 - a. Iterate through items:
 - i. Find the mean closest to the item
 - ii. Assign item to mean
 - iii. Update mean


Part A

To perform a simple k-mean clustering algorithm on any data set.

Procedure:

1. Go to Weka Explorer.
2. Choose dataset in weka/data
3. Go to cluster tab
4. Choose cluster algorithm, in this case k-means
5. Click start.
6. Visualize the results

Output:



Weka Explorer

Preprocess Classify Cluster Associate Select attributes Visualize

Clusterer

Choose: SimpleKMeans -init 0 -max-candidates 100 -periodic-pruning 10000 -min-density 2.0 -t1 -1.25 -t2 -1.0 -N 3 -A "weka.core.EuclideanDistance -R first-last" -i 500 -num-slots 1 -S 10

Cluster mode

☒ Use training set
☐ Supplied test set Set...
☐ Percentage split % 66
☐ Classes to clusters evaluation (None) class
☒ Store clusters for visualization

Ignore attributes

Start Stop

Result list (right-click for options)

- 02:07:17 - SimpleKMeans
- 02:08:28 - SimpleKMeans
- 02:09:09 - SimpleKMeans

Cluster output

Initial starting points (random):

Cluster 0: 1,126,16,29,152,28.7,0.881,21,tested_negative
Cluster 1: 0,95,72,0,0,36.8,0.485,57,tested_negative
Cluster 2: 1,97,66,15,140,23.2,0.487,22,tested_negative

Missing values globally replaced with mean/mode

Final cluster centroids:

Attribute	Full Data (768.0)	Cluster# 0 (132.0)	1 (268.0)	2 (368.0)
preg	3.0451	6.8561	4.8657	2.0217
plas	128.8945	118.6136	141.2575	106.8832
pres	85.1055	75.7197	78.6246	65.481
skin	28.5365	14.9545	22.1642	21.3533
linsu	79.7995	40.7727	100.3558	78.8424
mass	31.9926	30.5152	35.1425	30.2285
pedi	0.4719	0.4172	0.5505	0.4342
age	33.2409	46.9091	37.0672	25.5516
class		tested_negative	tested_positive	tested_negative

Time taken to build model (full training data) : 0.07 seconds


== Model and evaluation on training set ==

Clustered Instances

Cluster	Count	Percentage
0	132	(17%)
1	268	(35%)
2	368	(48%)

Status

OK Log x 0



Findings and Learnings :

1. K-means is one of the simplest unsupervised learning algorithms that solve the well known clustering problem.
2. Weka software makes the implementation and visualization of K-means algorithms very simple and efficient.
3. It makes K-means easily available to non-programmer users as well.

Part B

To Implement k mean clustering algorithm in python.

Source Code:

```
from copy import deepcopy
import numpy as np
import pandas as pd
from matplotlib import pyplot as plt


center_1 = np.array([1,1])
center_2 = np.array([5,5])
center_3 = np.array([8,1])
# Generate random data and center it to the three centers
data_1 = np.random.randn(200, 2) + center_1
data_2 = np.random.randn(200,2) + center_2
data_3 = np.random.randn(200,2) + center_3
data = np.concatenate((data_1, data_2, data_3), axis = 0)
plt.scatter(data[:,0], data[:,1], s=7)
plt.show()
# Number of clusters
k = 3
# Number of training data
n = data.shape[0]
# Number of features in the data
c = data.shape[1]
# Generate random centers, here we use sigma and mean to ensure it represent the whole data
mean = np.mean(data, axis = 0)
std = np.std(data, axis = 0)
centers = np.random.randn(k,c)*std + mean
# Plot the data and the centers generated as random
plt.scatter(data[:,0], data[:,1], s=7)
plt.scatter(centers[:,0], centers[:,1], marker='*', c='g', s=150)
plt.show()
centers_old = np.zeros(centers.shape) # to store old centers
centers_new = deepcopy(centers) # Store new centers
print(data.shape)
clusters = np.zeros(n)
distances = np.zeros((n, k))
error = np.linalg.norm(centers_new - centers_old)
# When, after an update, the estimate of that center stays the same, exit loop
```


```

while error != 0:
    for i in range(k):
        distances[:, i] = np.linalg.norm(data - centers[i], axis=1)
        # Assign all training data to closest center
    clusters = np.argmin(distances, axis=1)
    centers_old = deepcopy(centers_new)
    # Calculate mean for every cluster and update the center
    for i in range(k):
        centers_new[i] = np.mean(data[clusters == i], axis=0)
    error = np.linalg.norm(centers_new - centers_old)
print(centers_new)
# Plot the data and the centers generated as random
plt.scatter(data[:,0], data[:,1], s=7)
plt.scatter(centers_new[:,0], centers_new[:,1], marker='*', c='g', s=150)
plt.show()


```

Output:





Final cluster assignment



Findings and Learnings :

1. K-means is one of the simplest unsupervised learning algorithms that solve the well known clustering problem.
2. We have successfully implemented k-means clustering in Python