

1 Identification of the substance/mixture and of the company/undertaking**· Product identifier****· Trade name:*****Herculan PU 302 TM Safe { A }*****· Article number:***HE_703285/13***· Relevant identified uses of the substance or mixture and uses advised against****ATTENTION! DO NOT SPRAY!****· Application of the substance / the mixture***Component or ready-mix for in-situ creation of flooring / roofing / adhesives / resins - materials.
The final product is created only upon curing - Chemical properties of the starting materials in section 3.***· Details of the supplier of the safety data sheet****· Manufacturer/Supplier:****HERCULAN B.V.**
*c/o EPUTAN Kunststofftechnik B.V.
Energieweg 6
4231 DJ Meerkerk
The Netherlands
Phone +31 183 354700
Fax: +31 183 354740
e-mail: info@herculan.com***· Further information obtainable from:***Environmental Department***· Emergency telephone number:***+49 (0) 6131 19240 [24 h - 365 d] - Giftinformationszentrale Mainz
or
+31 (0) 183 354 700 [Mo - Fr. 8 - 17 o'clock] - HERCULAN***2 Hazards identification****· Classification of the substance or mixture***Acute Tox. 4 H332 Harmful if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.
Aquatic Acute 3 H402 Harmful to aquatic life.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.***· Label elements****· GHS label elements****· Hazard pictograms***The product is classified and labelled according to the Globally Harmonised System (GHS).***GHS07****· Signal word****Warning****· Hazard-determining components of labelling:***Hexamethylene diisocyanate, oligomer (biuret type)
hexamethylene-di-isocyanate***· Hazard statements***H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.***· Precautionary statements***P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 2)

Trade name: **Herculan PU 302 TM Safe { A }**

(Contd. of page 1)

Other hazards

-

Contains microplastics - Do not discharge into the environment!

More information in section 15

Handling and/or processing this material may generate dust particles that may cause mechanical irritation of the eyes, skin, nose and throat.

Results of PBT and vPvB assessment

541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclotetrasiloxane
556-67-2	octamethylcyclotetrasiloxane
540-97-6	Dodecamethylcyclotetrasiloxane

PBT: This product contains no substances assessed as PBT at concentrations of 0.1% or higher.

vPvB: This product contains no substances rated as vPvB at concentrations of 0.1% or higher.

3 Composition/information on ingredients

Chemical characterisation: Mixtures

Description: There are no additional ingredients present which are classified as hazardous to health or the environment and on this basis need to be mentioned in this section.

Dangerous components:

28182-81-2	Hexamethylene diisocyanate, oligomer (biuret type)	25-100%
	⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	
104810-48-2	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy-	≥0,25-<1%
	⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317; Aquatic Acute 2, H401	
104810-47-1	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	≥0,25-<1%
	⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317; Aquatic Acute 2, H401	
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≥0,25-≤0,5%
	⚠ Repr. 2, H361; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	
82919-37-7	methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate	≥0,25-≤0,5%
	⚠ Repr. 2, H361; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	
822-06-0	hexamethylene-di-isocyanate	≥0,1-≤0,15%
	⚠ Acute Tox. 1, H330; ⚠ Resp. Sens. 1, H334; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	

SVHC

Additional information:

Acute toxicity estimates

	Oral	Inhalative	Dermal
CAS 112945-52-5	5000 mg/kg	5,010 mg/l	5000 mg/kg
CAS 822-06-0	746 mg/kg	0,124 mg/l	mg/kg
CAS 28182-81-2	mg/kg	1,5 mg/l	mg/kg

For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.



Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Seek medical treatment.

Medical supervision for at least 48 hours.

(Contd. on page 3)

Trade name: **Herculan PU 302 TM Safe { A }**

(Contd. of page 2)

Show this safety data sheet to the doctor on duty.

Protection of first aiders: No action should be taken if there is a risk of personal accidents or in case of insufficient training. This can be dangerous for the person applying mouth-to-mouth resuscitation.

If the possibility of exposure exists, consult section 8 for specific personal protective equipment.

First-aiders should remember to protect themselves and wear the recommended protective clothing.

No action should be taken if there is a risk of personal accidents or in case of insufficient training.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment.

Use a respiratory bag or breathing device.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

Seek medical treatment.

· **After eye contact:**

Protect unharmed eye.

As far as easy to do, remove any contact lenses.

· **After swallowing:**

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

Clean carefully or rinse mouth with water.

Keep breathing passages clear.

Never allow an unconscious person to drink (or eat).

Take patient to a hospital immediately.

· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures· **Extinguishing media**· **Suitable extinguishing agents:**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

· **Advice for firefighters**· **Protective equipment:**

Mount respiratory protective device.

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

PSA 52 / PSA 55 / PSA 56 / PSA 57

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures· **Personal precautions, protective equipment and emergency procedures**

Remove persons from danger area.

(Contd. on page 4)

Trade name: Herculan PU 302 TM Safe { A }

(Contd. of page 3)

· Environmental precautions:*Wear protective equipment. Keep unprotected persons away.**Keep people at a distance and stay on the windward side.**Wear protective clothing.**Do not allow product to reach sewage system or any water course.**Inform respective authorities in case of seepage into water course or sewage system.**In case of seepage into the ground inform responsible authorities.**Do not allow to enter sewers/ surface or ground water.**Prevent further leaks and spills if safe to do so. In case of significant leaks that cannot be contained, inform the local authorities.**If the product contaminates rivers, lakes or sewers, notify the respective authorities.***· Methods and material for containment and cleaning up:***Let reaction take place at least 30 minuten.**Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Dispose contaminated material as waste according to section 13.**Ensure adequate ventilation.**Scoop up into lidded drums and render harmless.**Store in suitable and closed containers for disposal.***· Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.**** 7 Handling and storage****· Handling:***Use according to accepted rules and practices related to industrial hygiene and safety. After working with this product, wash face, hands and exposed skin thoroughly. Remove contaminated clothing and protective equipment before going to the canteen. Do not eat, drink or smoke during use. Do not allow contaminated work clothing to leave the workplace. Wash hands before each work break and immediately after using the product. Wash hands before each work break and at the end of the working day.***· Precautions for safe handling***Provide eyewash facilities and safety showers close to the workplace.**Ensure good ventilation/exhaustion at the workplace.**Prevent formation of aerosols.***· Information about fire - and explosion protection:***No special measures required.***· Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:***No special requirements.***· Information about storage in one common storage facility:***Store away from oxidising agents.**Store away from foodstuffs.***· Further information about storage conditions:***Protect from frost.**Keep container tightly sealed.**Store in dry conditions.**Store in a cool place.***· Specific end use(s)***No further relevant information available.**** 8 Exposure controls/personal protection****· Additional information about design of technical facilities:***No further data; see section 7.***· Control parameters****· Ingredients with limit values that require monitoring at the workplace:***The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

(Contd. on page 5)

Trade name: Herculan PU 302 TM Safe { A }

(Contd. of page 4)

· DNELs**28182-81-2 Hexamethylene diisocyanate, oligomer (biuret type)**

Dermal	Shortterm value	mg/kg (Worker local) mg/kg (Worker system-related)
	Longterm value	mg/cm ² (Worker local) mg/cm ² (Worker system-related)
Inhalative	Shortterm value	1 mg/m ³ (Worker local) mg/m ³ (Worker system-related)
	Longterm value	0,5 mg/m ³ (Worker local) mg/m ³ (Worker system-related)

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Oral	DNEL CHRONIC / LONG	0,5 mg/kg Ig/d (Consumer system-related)
Dermal	DNEL CHRONIC / LONG	1 mg/kg Ig/d (Consumer system-related) 2 mg/kg Ig/d (Worker system-related)
Inhalative	Longterm value	0,87 mg/m ³ (Consumer system-related) 3,53 mg/m ³ (Worker system-related)

822-06-0 hexamethylene-di-isocyanate

Dermal	Shortterm value	mg/kg (Worker local)
	Longterm value	mg/cm ² (Worker local)
Inhalative	Shortterm value	1 mg/m ³ (Worker local)
	Longterm value	0,5 mg/m ³ (Worker local)

· PNECs**28182-81-2 Hexamethylene diisocyanate, oligomer (biuret type)**

Soil	1,33 mg/kg (PNEC Freshwater Sediment)
	0,066 mg/kg (PNEC Soil)
	0,133 mg/kg (PNEC Seawater Sediment)
Water	0,005 mg/l (PNEC Seawater)
	55,6 mg/l (PNEC Wastewater treatment)
	0,05 mg/l (PNEC Water)

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Soil	1,05 mg/kg (PNEC Freshwater Sediment)
	0,21 mg/kg (PNEC Soil)
	0,11 mg/kg (PNEC Seawater Sediment)
Water	0,00022 mg/l (PNEC Seawater)
	1 mg/l (PNEC Wastewater treatment)
	0,0022 mg/l (PNEC Freshwater)

822-06-0 hexamethylene-di-isocyanate

Soil	266.700 mg/kg (PNEC Freshwater Sediment)
	53.182 mg/kg (PNEC Soil)
	26.670 mg/kg (PNEC Seawater Sediment)
Water	1,27 mg/l (PNEC Intermittent freshwater release)
	0,0127 mg/l (PNEC Seawater)
	38,28 mg/l (PNEC Wastewater treatment)
	0,127 mg/l (PNEC Freshwater)

· Additional information:

The lists valid during the making were used as basis.

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing

(Contd. on page 6)

Trade name: Herculan PU 302 TM Safe { A }

(Contd. of page 5)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

· Respiratory protection:

Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when high concentrations are present.

· Recommended filter device for short term use:

Air concentrations would be kept below exposure guidelines. When airborne concentrations may exceed exposure guidelines, use an approved air-purifying respirator fitted with a filter for organic vapours and particles. In circumstances where the concentration in the air may exceed the level for which an air-purifying respirator is effective, use a compressed air respirator (type: positive pressure) (air hose-fed or self-contained respirator). In emergencies or in conditions where the concentration in air is not known, use an approved compressed air breathing apparatus (type: positive pressure) or air hose-fed respirator (type: positive pressure). Use EC-approved respirator: Filter for organic vapours with a particulate pre-filter for highly toxic substances, type AP3 (must comply with Standard EN 14387).

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Natural rubber, NR

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye protection:

Tightly sealed goggles

· Body protection:

(Protective) work clothing

- Protective work clothing (long trousers, long-sleeved shirt). Avoid exposed skin, even in hot weather.

- Depending on processing: use spray-tight trousers or spray-tight overalls

Overall (preferably thick cotton) or Tyvek-Pro Tech 'C', TyvekPro Tech 'F' fully protective single-use clothing.

· Limitation and supervision of exposure into the environment

Storage of substances in tightly closed packaging

Emissions from ventilation or processing equipment should be monitored to ensure they meet the requirements of environmental protection legislation. In some cases, gas scrubbers, filters or technical modifications to process equipment are needed to reduce emissions to acceptable levels.

(Contd. on page 7)

Trade name: **Herculan PU 302 TM Safe { A }**

(Contd. of page 6)

Avoid spreading spilled material and waste material and prevent it from coming into contact with soil, waterways, drains and sewers.

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:** Fluid**Colour:** Colourless· **Odour:** Characteristic· **Odour threshold:** Not determined· **pH-value:** Mixture is non-polar/aprotic.· **Change in condition****Melting point/freezing point:** No test data available**Initial boiling point and boiling range:** 2.230 °C· **Flash point:** 180 °C· **Flammability** No test data available· **Decomposition temperature:** No test data available· **Ignition temperature:** Product is not selfigniting.· **Explosive properties:** Product does not present an explosion hazard.
No test data available· **Explosion limits:****Lower:** No test data available**Upper:** No test data available· **Vapour pressure:** Not determined· **Density at 20 °C:** 1,16 g/cm³· **Relative density** >> density· **Vapour density** No test data available· **Evaporation rate** No test data available· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** No test data available· **Viscosity:****Dynamic:** No test data available**Kinematic:** No test data available· **Solvent content:****Organic solvents:** 0,0 %**Solids content:** 37,3 %· **Other information** No further relevant information available.**10 Stability and reactivity**· **Reactivity**

No further relevant information available.

· **Chemical stability**

Stable under recommended storage conditions. See Section 7, Storage.

(Contd. on page 8)

Trade name: **Herculan PU 302 TM Safe { A }**

(Contd. of page 7)

· **Thermal decomposition / conditions to be avoided:**

Extreme temperatures and direct sunlight.
Exposure to air or moisture for prolonged periods.

· **Possibility of hazardous reactions**

No dangerous reactions known.

· **Conditions to avoid**

No further relevant information available.

· **Incompatible materials:**

No further relevant information available.

· **Hazardous decomposition products:**

No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity**

ATE values > 2000 mg/kg will have no impact on classification.

· **LD/LC50 values relevant for classification:**

CAS	13463-67-7	>20000 mg/kg	mg/l	>10000 mg/kg
-----	------------	--------------	------	--------------

28182-81-2 Hexamethylene diisocyanate, oligomer (biuret type)

Oral	OECD 401 (LD50)	>5.000 mg / kg (rat)
Dermal	OECD 402 (LD50)	>2.000 mg/kg (rat)
		>2.000 mg/kg (rabbit)
Inhalative	Acute inhalatief toxiciteit	11 mg/l (ATE)
	OECD 403 (LC50)	0,402 mg/l (rat) (04 h)
Irritation of skin	OECD 404	(rabbit) (04 h)
	OECD 406	(marmot (Magnusson-Kligman test))
Irritation of eyes	OECD 405	(rabbit)

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Oral	OECD 423 (LD50)	>3.230 mg/kg (rat)
------	-----------------	--------------------

822-06-0 hexamethylene-di-isocyanate

Oral	Acute orale toxiciteit	746 mg/kg (rat)
Dermal	LD50	>2.000 mg/kg (rat)
	OECD 402 (LD50)	>2.000 mg/kg (rat)
Inhalative	Acute inhalatief toxiciteit	0,124 mg/l (rat)
Irritation of skin	OECD 404	(rabbit)
	OECD 406	(Guinea pig)
		(mouse)
Irritation of eyes	OECD 405	(rabbit)

· **Primary irritant effect:**

· **Skin corrosion/irritation**

No irritant effect.

· **Serious eye damage/irritation**

No irritating effect.

· **Respiratory or skin sensitisation**

Sensitisation possible through skin contact.

28182-81-2 Hexamethylene diisocyanate, oligomer (biuret type)

Irritation of skin	OECD 429	(mouse)
--------------------	----------	---------

822-06-0 hexamethylene-di-isocyanate

Irritation of skin	OECD 429	(mouse)
--------------------	----------	---------

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful
Irritant

WE4

(Contd. on page 9)

Trade name: **Herculan PU 302 TM Safe { A }**

(Contd. of page 8)

* **12 Ecological information**· **Toxicity**· **Aquatic toxicity:****28182-81-2 Hexamethylene diisocyanate, oligomer (biuret type)**

OECD 201 (ErC50/ErL50) >100 mg/l (Desmodesmus subspicatus) (72 h)

>100 mg/l (scenedesmus subspicatus) (72 h)

OECD 202 (EC50/EL50) >100 mg/l (Daphnia Magna) (48 h)

OECD 203 (LC50/LL50) >100 mg/l (Danio rerio) (96 h)

OECD 209 (EC50/EL50) 645,7 mg/l (Activated sludge) (03 h)

OECD 471 (Ames Test (Salmonella/microsome test))

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

NOEC 6,3 mg/l (daphnia) (21 d)

OECD 203 (LC50/LL50) 0,9 mg/l (Brachydanio rerio (zebravis).) (96 h)

OECD 209 (EC50/EL50) 0,22 mg/l (algae) (72 h)

822-06-0 hexamethylene-di-isocyanate

Acute EC50 5.560 mg/L (activated sludge)

>100 mg/L (Daphnia Magna) (48 h)

ErC50 (OECD 201) 50-<100 mg/l (scenedesmus subspicatus) (72 h)· **Persistence and degradability****28182-81-2 Hexamethylene diisocyanate, oligomer (biuret type)**

OECD 301 D 0 % (28 d)

· **Behaviour in environmental systems:**· **Bioaccumulative potential****28182-81-2 Hexamethylene diisocyanate, oligomer (biuret type)**

BCF (BioConcentrationFactor) - Bioaccumulation 9,6

OECD 117 (log Pow) - Bioaccumulation

· **Mobility in soil**

No further relevant information available.

· **Ecotoxicological effects:**· **Remark:**

Harmful to fish

· **Additional ecological information:**· **General notes:**Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

· **Results of PBT and vPvB assessment**

This substance/mixture does not contain any components that can be considered persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

· **PBT:**

-

· **vPvB:**

-

· **Other adverse effects**

No further relevant information available.

* **13 Disposal considerations**· **Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

This product, when disposed of in its unused and uncontaminated state, must be treated as hazardous waste according to EC Directive 2008/98/EC. Disposal practices must comply with all national and provincial laws and any municipal or local bylaws regarding hazardous waste. Additional evaluations may be required for used, contaminated and residual material. Do not discharge into sewers, soil or surface water. Incineration in a licensed incinerator suitable for this

(Contd. on page 10)

Trade name: Herculan PU 302 TM Safe { A }

(Contd. of page 9)

hazardous waste is recommended for this material. Small amounts of waste can be neutralized with e.g. polyol in preference to landfilling. Empty drums should be cleaned first (see Section 6) and then either punctured and scrapped or given to an approved reprocessor.

· **Uncleaned packaging:**· **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14 Transport information· **UN-Number**· **ADR, ADN, IMDG, IATA**

Void

· **UN proper shipping name**· **ADR, ADN, IMDG, IATA**

Void

· **Transport hazard class(es)**· **ADR, ADN, IMDG, IATA**· **Class**

Void

· **Packing group**· **ADR, IMDG, IATA**

Void

· **Environmental hazards:**· **Marine pollutant:**

No

· **Special precautions for user**

Not applicable

· **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable

· **UN "Model Regulation":**

Void

15 Regulatory information· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I**

None of the ingredients is listed.

· **Seveso category**

Specified in regulation: Not applicable

· **National regulations:**· **Breakdown regulations:**

Class	Share in %
	0,1

· **Waterhazard class:**

Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Other regulations, limitations and prohibitive regulations**

General international information on combating damage caused by fire and leakage.
www.ERICARDS.net

· **Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H315 Causes skin irritation.

(Contd. on page 11)

Trade name: **Herculan PU 302 TM Safe { A }**

(Contd. of page 10)

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H361 Suspected of damaging fertility or the unborn child.
H400 Very toxic to aquatic life.
H401 Toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

· **Classification according to Regulation (EC)
No 1272/2008**

The classification of the mixture is based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

The safety data sheet is prepared in accordance with Regulation (EC) No. 1907/2006 (REACH) § 31, taking into account Annex II, which was amended by Commission Regulation (EU) 2020/878.

· **Department issuing SDS:**

Environmental Department

· **Contact:**

Dr. Michael Kissel

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
TSCA: Toxic Substances Control Act
Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version
altered.**