

1 Identification of the substance/mixture and of the company/undertaking**· Product identifier****· Trade name:*****Herculan GLP M { A }*****· Article number:***HE_702700/30***· Relevant identified uses of the substance or mixture and uses advised against***No further relevant information available.***· Application of the substance / the mixture***Component or ready-mix for in-situ creation of flooring / roofing / adhesives / resins - materials.
The final product is created only upon curing - Chemical properties of the starting materials in section 3.***· Details of the supplier of the safety data sheet****· Manufacturer/Supplier:*****HERCULAN B.V.****c/o EPUTAN Kunststoftechniek B.V.**Energieweg 6**4231 DJ Meerkkerk**The Netherlands**Phone +31 183 354700**Fax: +31 183 354740**e-mail: info@herculan.com***· Further information obtainable from:***Environmental Department***· Emergency telephone number:***+49 (0) 6131 19240 [24 h - 365 d] - Giftinformationszentrale Mainz
or
+31 (0) 183 354 700 [Mo - Fr. 8 - 17 o'clock] - HERCULAN***2 Hazards identification****· Classification of the substance or mixture***Flam. Liq. 3 H226 Flammable liquid and vapour.**Repr. 1A H360 May damage fertility or the unborn child.**STOT SE 3 H336 May cause drowsiness or dizziness.***· Label elements****· GHS label elements****· Hazard pictograms***The product is classified and labelled according to the Globally Harmonised System (GHS).*

GHS02



GHS07



GHS08

· Signal word*Danger***· Hazard-determining components of labelling:***2-ethoxy-1-methylethyl acetate**Hexanoic acid, 2-ethyl-, zinc salt, basic***· Hazard statements***H226 Flammable liquid and vapour.**H360 May damage fertility or the unborn child.**H336 May cause drowsiness or dizziness.***· Precautionary statements***P210**Keep away from heat/sparks/open flames/hot surfaces. No smoking.**P241**Use explosion-proof electrical/ventilating/lighting equipment.**P261**Avoid breathing dust/fume/gas/mist/vapours/spray.**P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**P405**Store locked up.**P501**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Other hazards***-
Handling and/or processing this material may generate dust particles that may cause mechanical irritation of the eyes, skin, nose and throat.***· Results of PBT and vPvB assessment****· PBT:***This product contains no substances assessed as PBT at concentrations of 0.1% or higher.**(Contd. on page 2)*

Trade name: **Herculan GLP M { A }**

(Contd. of page 1)

· **vPvB:**

This product contains no substances rated as vPvB at concentrations of 0.1% or higher.

3 Composition/information on ingredients· **Chemical characterisation: Mixtures**· **Description:**

There are no additional ingredients present which are classified as hazardous to health or the environment and on this basis need to be mentioned in this section.

· **Dangerous components:**

54839-24-6	2-ethoxy-1-methylethyl acetate	10-25%
	Flam. Liq. 3, H226; STOT SE 3, H336	
763-69-9	ethyl 3-ethoxypropionate	5-10%
	Flam. Liq. 3, H226	
1308-38-9	dichromium trioxide	≤2,5%
85203-81-2	Hexanoic acid, 2-ethyl-, zinc salt, basic	≥0,3-≤0,5%
	Repr. 1A, H360; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	

· **SVHC**· **Additional information:**

For the wording of the listed hazard phrases refer to section 16.

4 First aid measures· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Seek medical treatment.

Medical supervision for at least 48 hours.

Show this safety data sheet to the doctor on duty.

Protection of first aiders: No action should be taken if there is a risk of personal accidents or in case of insufficient training. This can be dangerous for the person applying mouth-to-mouth resuscitation.

If the possibility of exposure exists, consult section 8 for specific personal protective equipment.

First-aiders should remember to protect themselves and wear the recommended protective clothing.

No action should be taken if there is a risk of personal accidents or in case of insufficient training.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment.

Use a respiratory bag or breathing device.

· **After skin contact:**

Immediately rinse with water.

Seek medical treatment.

· **After eye contact:**

Protect unharmed eye.

As far as easy to do, remove any contact lenses.

· **After swallowing:**

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

Clean carefully or rinse mouth with water.

Keep breathing passages clear.

Never allow an unconscious person to drink (or eat).

Take patient to a hospital immediately.

· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

—WE4—

(Contd. on page 3)

Trade name: **Herculan GLP M { A }**

(Contd. of page 2)

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:**
- **Special hazards arising from the substance or mixture**

Water with full jet

Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide (CO)

- **Advice for firefighters**
- **Protective equipment:**

Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
PSA 52 / PSA 55 / PSA 56 / PSA 57

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Remove persons from danger area.
Wear protective equipment. Keep unprotected persons away.
Keep people at a distance and stay on the windward side.
Wear protective clothing.

- **Environmental precautions:**

Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
In case of seepage into the ground inform responsible authorities.
Do not allow to enter sewers/ surface or ground water.
Prevent further leaks and spills if safe to do so. In case of significant leaks that cannot be contained, inform the local authorities.
If the product contaminates rivers, lakes or sewers, notify the respective authorities.

- **Methods and material for containment and cleaning up:**

Let reaction take place at least 30 minuten.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Scoop up into lidded drums and render harmless.
Store in suitable and closed containers for disposal.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

- **Reference to other sections**

7 Handling and storage

- **Handling:**

Use according to accepted rules and practices related to industrial hygiene and safety. After working with this product, wash face, hands and exposed skin thoroughly. Remove contaminated clothing and protective equipment before going to the canteen. Do not eat, drink or smoke during use. Do not allow contaminated work clothing to leave the workplace. Wash hands before each work break and immediately after using the product. Wash hands before each work break and at the end of the working day.

- **Precautions for safe handling**

Provide eyewash facilities and safety showers close to the workplace.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.

(Contd. on page 4)

Trade name: **Herculan GLP M { A }**

(Contd. of page 3)

· **Information about fire - and explosion protection:**

Prevent formation of aerosols.

Keep respiratory protective device available.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

No special requirements.

· **Information about storage in one common storage facility:**

Store away from oxidising agents.
Store away from foodstuffs.

· **Further information about storage conditions:**

Protect from frost.
Keep container tightly sealed.
Store in dry conditions.
Store in a cool place.

· **Specific end use(s)**

No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:**

Keep respiratory protective device available.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1308-38-9 dichromium trioxide

IOELV (European Union)	Long-term value: 2 mg/m ³ as Cr
------------------------	---

· **DNELs**

54839-24-6 2-ethoxy-1-methylethyl acetate

Oral	DNEL CHRONIC / LONG	13,1 mg/kg Ig/d (Consumer local)
Dermal	DNEL CHRONIC / LONG	62 mg/kg Ig/d (Consumer local)
		103 mg/kg Ig/d (Worker local)
Inhalative	Shortterm value	365 mg/m ³ (Consumer local)
		608 mg/m ³ (Worker local)
	Longterm value	181 mg/m ³ (Consumer local)
		302 mg/m ³ (Worker local)

763-69-9 ethyl 3-ethoxypropionate

Oral	Longterm value	1,2 mg/kg (Consumer system-related)
Dermal	Longterm value	24,2 mg/cm ² (Consumer local)
		24,2 mg/cm ² (Consumer system-related)
		102 mg/cm ² (Worker local)
		102 mg/cm ² (Worker system-related)
Inhalative	Longterm value	72,6 mg/m ³ (Consumer local)
		72,6 mg/m ³ (Consumer system-related)
		610 mg/m ³ (Worker local)
		610 mg/m ³ (Worker system-related)

· **PNECs**

54839-24-6 2-ethoxy-1-methylethyl acetate

Soil	9,2 mg/kg (PNEC Freshwater Sediment)
	1,34 mg/kg (PNEC Soil)

(Contd. on page 5)

Trade name: **Herculan GLP M { A }**

(Contd. of page 4)

Water	0,92 mg/kg (PNEC Seawater Sediment)
	0,13 mg/l (PNEC Seawater)
	62,5 mg/l (PNEC Wastewater treatment)
	1,3 mg/l (PNEC Freshwater)
763-69-9 ethyl 3-ethoxypropionate	
Soil	0,419 mg/kg (PNEC Freshwater Sediment)
	0,048 mg/kg (PNEC Soil)
	0,0419 mg/kg (PNEC Seawater Sediment)
Water	0,00609 mg/l (PNEC Seawater)
	50 mg/l (PNEC Wastewater treatment)
	0,0609 mg/l (PNEC Freshwater)

· **Additional information:**

The lists valid during the making were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Do not eat, drink, smoke or sniff while working.

· **Respiratory protection:**

Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when high concentrations are present.

· **Recommended filter device for short term use:**

Combination filter AX-P2

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Natural rubber, NR

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong material gloves

· **Eye protection:**

Tightly sealed goggles

· **Body protection:**

(Protective) work clothing

- Protective work clothing (long trousers, long-sleeved shirt). Avoid exposed skin, even in hot weather.

- Depending on processing: use spray-tight trousers or spray-tight overalls

(Contd. on page 6)

Trade name: **Herculan GLP M { A }**

(Contd. of page 5)

Overall (preferably thick cotton) or Tyvek-Pro Tech 'C', TyvekPro Tech 'F' fully protective single-use clothing.

· **Limitation and supervision of exposure into the environment**

Storage of substances in tightly closed packaging

Emissions from ventilation or processing equipment should be monitored to ensure they meet the requirements of environmental protection legislation. In some cases, gas scrubbers, filters or technical modifications to process equipment are needed to reduce emissions to acceptable levels. Avoid spreading spilled material and waste material and prevent it from coming into contact with soil, waterways, drains and sewers.

* **9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Fluid

Colour:

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined

· **pH-value:**

Mixture is non-polar/aprotic.

· **Change in condition****Melting point/freezing point:**

No test data available

Initial boiling point and boiling range:

155 °C

· **Flash point:**

54 °C

· **Flammability**

Flammable.

· **Auto-ignition temperature:**

325 °C

· **Decomposition temperature:**

No test data available

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:****Lower:**

1 Vol %

Upper:

9,8 Vol %

· **Vapour pressure at 20 °C:**

1 hPa

· **Density at 20 °C:**1,486 g/cm³· **Relative density**

>> density

· **Vapour density**

No test data available

· **Evaporation rate**

No test data available

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:**

No test data available

· **Viscosity:****Dynamic:**

No test data available

Kinematic:

No test data available

· **Solvent content:****Organic solvents:**

23,4 %

Solids content:

64,6 %

(Contd. on page 7)

Trade name: Herculan GLP M { A }

(Contd. of page 6)

· Other information

No further relevant information available.

*** 10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under recommended storage conditions. See Section 7, Storage.
- **Thermal decomposition / conditions to be avoided:** Extreme temperatures and direct sunlight.
Exposure to air or moisture for prolonged periods.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*** 11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity** ATE values > 2000 mg/kg will have no impact on classification.
- **LD/LC50 values relevant for classification:**
- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:** The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** Repr. 1A

*** 12 Ecological information****· Toxicity****· Aquatic toxicity:****54839-24-6 2-ethoxy-1-methylethyl acetate**

OECD 202 (EC50/EL50)	100 mg/l (scenedesmus subspicatus)
OECD 203 (LC50/LL50)	140 mg/l (Onchorynchus mykiss) (96 h)
OECD 209 (EC50/EL50)	110 mg/l (Daphnia Magna) (48 h)
	>100 mg/l (scenedesmus subspicatus) (72 h)
OECD 211	>100 mg/l (Daphnia Magna)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment** This substance/mixture does not contain any components that can be considered persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
- **PBT:** -
- **vPvB:** -

(Contd. on page 8)

Trade name: **Herculan GLP M { A }**

(Contd. of page 7)

· **Other adverse effects**

No further relevant information available.

* **13 Disposal considerations**· **Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

This product, when disposed of in its unused and uncontaminated state, must be treated as hazardous waste according to EC Directive 2008/98/EC. Disposal practices must comply with all national and provincial laws and any municipal or local bylaws regarding hazardous waste. Additional evaluations may be required for used, contaminated and residual material. Do not discharge into sewers, soil or surface water. Incineration in a licensed incinerator suitable for this hazardous waste is recommended for this material. Small amounts of waste can be neutralized with e.g. polyol in preference to landfilling. Empty drums should be cleaned first (see Section 6) and then either punctured and scrapped or given to an approved reprocessor.

· **Uncleaned packaging:**· **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

* **14 Transport information**· **UN-Number**· **ADR, IMDG, IATA**

UN1263

· **UN proper shipping name**· **ADR**

1263 PAINT

· **IMDG, IATA**

PAINT

· **Transport hazard class(es)**· **ADR**· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG, IATA**· **Class**

3 Flammable liquids.

· **Label**

3

· **Packing group**· **ADR, IMDG, IATA**

III

· **Environmental hazards:**· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):**

30

· **EMS Number:**

F-E, S-E

(Contd. on page 9)

Trade name: Herculan GLP M { A }

(Contd. of page 8)

· Stowage Category	A
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable
· Transport/Additional information:	<----- aircraft ----->
· ADR	
· Excepted quantities (EQ):	E1
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	-
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I**

None of the ingredients is listed.

· **Seveso category**

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements**

5.000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements**

50.000 t

· **National regulations:**· **Breakdown regulations:**

Class	Share in %
NK	23,4

· **Waterhazard class:**

Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Other regulations, limitations and prohibitive regulations**

General international information on combating damage caused by fire and leakage.

www.ERICARDS.net

ERIC: 3-05

· **Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.

(Contd. on page 10)

Trade name: **Herculan GLP M { A }**

(Contd. of page 9)

· **Classification according to Regulation (EC) No 1272/2008**

H411 Toxic to aquatic life with long lasting effects.

The classification of the mixture is based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

The safety data sheet is prepared in accordance with Regulation (EC) No. 1907/2006 (REACH) § 31, taking into account Annex II, which was amended by Commission Regulation (EU) 2020/878.

· **Department issuing SDS:**

Environmental Department

· **Contact:**

Dr. Michael Kissel

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

TSCA: Toxic Substances Control Act

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 1A: Reproductive toxicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**