DAA Lab-9

Name: Kshitij Kumar Sharma Roll No.: 1905514 Date: 01/10/2021

Q-8.1) Write a menu-based program to implement the priority queue operations.
User Choice:
1 (to insert an element)
2 (to get maximum)
3 (to extract maximum)
4 (to increase the specified key to a given value)
5 (print order-level traversal of queue), and
6 (to exit).
In the beginning as well as after every operation you are supposed to print the options 1-6 to get an (user) input.

Program:

```
/*
Written by: Kshitij Kumar Sharma                    Roll No.: 1905514
Idea of the solution:
        INSERT(S,x): inserts the element x into the set S, which is equivalent to the operation S = S x U
        MAXIMUM(S): returns the element of S with the largest key EXTRACT-MAX(S): removes and
        returns the element of S with the largest key INCREASE-KEY(S,x,k): increases the value of
        element x's key to the new value k, which is assumed to be at least as large as x's current key
        value
*/

#include<bits/stdc++.h>
using namespace std;

void heapMax(int a[])                                   //prints maximum heap element
{
   cout<<a[0];
}
void heapify(int a[], int n, int i)                     //make max heap
{
   int l,r,largest=i;
   l=2*i+1;
   r=2*i+2;
   if (l<n&&a[l]>a[largest])
      largest=l;
   if (r<n&&a[r]>a[largest])
      largest=r;
   if (largest!=i)
   {
      int t=a[i];
```

```
      a[i]=a[largest];
      a[largest]=t;
      heapify(a,n,largest);
   }
}
void heapExtractMax(int a[],int& n)                    //deletes the max element
{
   int l=a[n-1];
  a[0]=l;
  n=n-1;
  heapify(a,n,0);
}
void heapIncreaseKey(int a[],int n,int i)              //increases the key value
{
    int p=(i-1)/2;
   if(a[p]>0)
   {
      if(a[i]>a[p])
      {
         swap(a[i],a[p]);
         heapIncreaseKey(a,n,p);
      }
   }
}
void maxHeapInsert(int a[],int& n, int k)
{
   n=n+1;
   a[n-1]=k;
   heapIncreaseKey(a,n,n-1);
}
void print(int a[],int n)
{
   int i;
   for(i=0;i<n;i++)
      cout<<a[i]<<" ";
}
void increaseKey(int a[],int i,int k)
{
   if(k<a[i])
      {
         cout<<"Error \n";
         return;
      }
   a[i]=k;
```

```
   while(i>1 && a[(i-1)/2]<a[i])
   {
      swap(a[i],a[(i-1)/2]);
      i=(i-1)/2;
   }
}
int main()                                                    //driver code
{
   int n;
   cout<<"Enter size : ";
   cin>>n;
   int i,a[n],ch;
   cout<<"Enter elements : \n";
   for(i=0;i<n;i++)
      cin>>a[i];
   sort(a,a+n,greater<int>());
   do
   {
      cout<<"\n";
      cout<<"MENU \n";
      cout<<"1-Insert       \t\t 2-Maximum \t\t 3-Extract maximum \n";
      cout<<"4-Increase key \t\t 5-Print   \t\t 6-Exit \n";
      cout<<"Enter the choice : ";
      cin>>ch;
      if(ch==1)
      {
         int k;
         cout<<"Enter key to insert : ";
         cin>>k;
         maxHeapInsert(a,n,k);
      }
      if(ch==2)
         heapMax(a);
      if(ch==3)
         heapExtractMax(a,n);
      if(ch==4)
      {
         int k,j;
         cout<<"Enter index : ";
         cin>>j;
         cout<<"Enter key : ";
         cin>>k;
         increaseKey(a,j,k);
      }
```

```
    if(ch==5)
        print(a,n);
  }while(ch<6);
}
```

Output: