

DAA Lab-10

Name: Kshitij Kumar Sharma

Roll No.: 1905514

Date: 08/10/2021

Q-10.1) Write a program to solve the matrix chain multiplication problem following dynamic programming approach.

Program:

/*

Written by: Kshitij Kumar Sharma

Roll No.: 1905514

Idea of the solution:

Matrix chain multiplication is an optimization problem concerning the most efficient way to multiply a given sequence of matrices. The problem is not actually to perform the multiplications, but merely to decide the sequence of the matrix multiplications involved. The problem is solved using dynamic programming as it can be divided into shared sub problems.

*/

```
#include <bits/stdc++.h>
```

```
using namespace std;
```

```
int dp[100][100],a[100][100];
```

```
void optimalParents(int i,int j)
```

```
//Prints optimal parents
```

```
{
```

```
    if(i==j)
```

```
        cout<<"A"<<i;
```

```
    else
```

```
    {
```

```
        cout<<"(";
```

```
        optimalParents(i,a[i][j]);
```

```
        optimalParents(a[i][j]+1,j);
```

```
        cout<<")";
```

```
    }
```

```
}
```

```
int matrixChain(int* p, int i, int j)
```

```
//Calculates matrix chain multiplication
```

```
{
```

```
    int q;
```

```
    if(i==j)
```

```
        return 0;
```

```
    if (dp[i][j] != -1)
```

```
        return dp[i][j];
```

```
    dp[i][j]=INT_MAX;
```

```
    for (int k=i;k<j;k++)
```

```

    {
        q=matrixChain(p,i,k)+matrixChain(p,k+1,j)+p[i-1]*p[k]*p[j];
        if(q<dp[i][j])
        {
            dp[i][j]=q;
            a[i][j]=k;
        }
    }
    cout<<dp[i][j]<<endl;
    return dp[i][j];
}

int MatrixChainOrder(int* p, int n)                                //calls matrixChain()
{
    int i=1,j=n-1;
    return matrixChain(p,i,j);
}

int main()                                                        //Driver code
{
    int n,i;
    cin>>n;
    int arr[n];
    for(i=0;i<n;i++)
        cin>>arr[i];
    memset(dp, -1, sizeof dp);
    memset(a, -1, sizeof a);
    int s=MatrixChainOrder(arr, n);
    cout<<endl;
    optimalParents(1,n-1);
    cout<<endl;
    cout << "Minimum number of multiplications is "<< s<<endl;
}

```

Output:

```
kshiti@kshiti: ~/Documents/DAA/lab10
kshiti@kshiti:~/Documents/DAA/lab10$ g++ max_chain_multiplication.cpp
kshiti@kshiti:~/Documents/DAA/lab10$ ./a.out
7
30
35
15
5
10
20
25
5000
1000
3500
750
2500
5375
2625
4375
7125
10500
15750
7875
9375
11875
15125

((A1(A2A3))((A4A5)A6))
Minimum number of multiplications is 15125
kshiti@kshiti:~/Documents/DAA/lab10$
```