

Calculator code:

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <title>
      Calculator
    </title>
  </head>
  <body>
    <div align="center">
      Calculator
    </div>
    <form name="Calculator">
      <table border="2" align="center" cellpadding="15" cellspacing="12"
        bgcolor="#c0c0c0">
        <tr>
          <td>
            <input type="text" name="Input" Size="35" id="display">
            <br>
          </td>
        </tr>
        <tr>
          <td>
            <input type="button" name = "one" style="font-size:30px" value=" 1 "
              OnClick="Calculator.Input.value += '1'">
            <input type="button" name = "two" style = "font-size:30px" value=" 2 "
              OnCLick="Calculator.Input.value += '2'">
            <input type="button" name = "three" style="font-size:30px" value=" 3 "
              OnClick="Calculator.Input.value += '3'">
            <input type="button" name="add" style="font-size:30px" value=" + "
              OnClick="Calculator.Input.value += ' + '">
            <br>
            <input type="button" name = "four" style="font-size:30px" value=" 4 "
              OnClick="Calculator.Input.value += '4'">
            <input type="button" name = "five" style="font-size:30px" value=" 5 "
              OnCLick="Calculator.Input.value += '5'">
            <input type="button" name = "six" style="font-size:30px" value=" 6 "
              OnClick="Calculator.Input.value += '6'">
            <input type="button" name = "minus" style="font-size:30px" value=" - "
              OnClick="Calculator.Input.value += ' - '">
            <br>
          </td>
        </tr>
      </table>
    </form>
  </body>
</html>
```

```

<input type="button" name = "seven" style="font-size:30px" value=" 7 "
OnClick="Calculator.Input.value += '7'">
<input type="button" name = "eight" style="font-size:30px" value=" 8 "
OnClick="Calculator.Input.value += '8'">
<input type="button" name = "nine" style="font-size:30px" value=" 9 "
OnClick="Calculator.Input.value += '9'">
<input type="button" name = "mul" style="font-size:30px" value=" * "
OnClick="Calculator.Input.value += ' * '">
<br>
<input type="button" name = "clear" style="font-size:30px" value=" c "
OnClick="Calculator.Input.value = "">
<input type="button" name="zero" style="font-size:30px" value=" 0 "
OnClick="Calculator.Input.value += '0'">
<input type="button" name="Dolt" style="font-size:30px" value=" = "
OnClick="Calculator.Input.value = eval(Calculator.Input.value)">
<input type="button" name="div" style="font-size:30px" value=" / "
OnClick="Calculator.Input.value += ' / '">
<br>
</td>

</tr>
</table>
</form>
</body>
</html>

```

List code:

```

<!DOCTYPE html>
<html>
<body>

```

```

<h2>An Unordered HTML List</h2>

```

```

<ul>
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ul>

```

```

<h2>An Ordered HTML List</h2>

```

```

<ol>
  <li>Coffee</li>

```

```
<li>Tea</li>
<li>Milk</li>
</ol>
```

```
</body>
</html>
```

Combobox code:

```
<!DOCTYPE html>
<html>
<body>
```

```
<h1>The select element</h1>
```

```
<p>The select element is used to create a drop-down list.</p>
```

```
<form action="/action_page.php">
  <label for="cars">Choose a car:</label>
  <select name="cars" id="cars">
    <option value="volvo">Volvo</option>
    <option value="saab">Saab</option>
    <option value="opel">Opel</option>
    <option value="audi">Audi</option>
  </select>
  <br><br>
  <input type="submit" value="Submit">
</form>
```

```
<p>Click the "Submit" button and the form-data will be sent to a page on the
server called "action_page.php".</p>
```

```
</body>
</html>
```

Checkbox code:

```
<!DOCTYPE html>
<html>
<body>
```

```
<h1>Show Checkboxes</h1>
```

```
<form action="/action_page.php">
```

```
<input type="checkbox" id="vehicle1" name="vehicle1" value="Bike">
<label for="vehicle1"> I have a bike</label><br>
<input type="checkbox" id="vehicle2" name="vehicle2" value="Car">
<label for="vehicle2"> I have a car</label><br>
<input type="checkbox" id="vehicle3" name="vehicle3" value="Boat">
<label for="vehicle3"> I have a boat</label><br><br>
<input type="submit" value="Submit">
</form>

</body>
</html>
```

Radiobutton code:

```
<!DOCTYPE html>
<html>
<body>

<h1>Display Radio Buttons</h1>

<form action="/action_page.php">
  <p>Please select your favorite Web language:</p>
  <input type="radio" id="html" name="fav_language" value="HTML">
  <label for="html">HTML</label><br>
  <input type="radio" id="css" name="fav_language" value="CSS">
  <label for="css">CSS</label><br>
  <input type="radio" id="javascript" name="fav_language" value="JavaScript">
  <label for="javascript">JavaScript</label>

  <br>

  <p>Please select your age:</p>
  <input type="radio" id="age1" name="age" value="30">
  <label for="age1">0 - 30</label><br>
  <input type="radio" id="age2" name="age" value="60">
  <label for="age2">31 - 60</label><br>
  <input type="radio" id="age3" name="age" value="100">
  <label for="age3">61 - 100</label><br><br>
  <input type="submit" value="Submit">
</form>

</body>
</html>
```