DEVELOPER ROLE

SET D — ANSWER KEY

Administrator answer key. Keep separate from the candidate question paper.

D — Atomicity

A — Collection

D — O(1)

D — Return large result sets in manageable chunks

B — Trie

A — Same name with different parameter lists

C — Cross-origin browser requests

A — Speed up selected reads at storage/write trade-off

B — O(1)

A — SELECT

A — Cache results of repeated function calls

A — Stack

B — HashSet

B — Groups rows for aggregation

C — TLS transport security

D — GET

C — Queue

A — Redundancy and update anomalies

B — Stack

C — Version control and collaboration

D — String

D — Inorder

D — Rows in the result set

D — Referential integrity

A — Disjoint-set union

D — Persist transaction changes

B — Resolve domain names to IP addresses

B — A class-level member shared by instances

D — Logical unit of work committed or rolled back

A — public

C — final

D — Encapsulation

D — Fetches and integrates remote changes

B — 500

C — Data access operations

A — BFS

B — Database transaction boundaries

A — application/json

A — Transfer data across application boundaries

A — PATCH

D — O(log n)

A — 201

B — O(log n)

A — UPDATE

D — A class can implement multiple interfaces

C — volatile

D — HAVING

A — 0

A — BFS

C — @RestController

D — throw

A — Overlapping with reusable results

C — Secret manager/protected environment

D — Priority queue

C — Controller

C — Initializing a new object

A — Compile-time type safety

D — Salted slow hash such as BCrypt/Argon2

D — finally

D — FileNotFoundException

C — HashMap

A — Architectural style for networked applications

D — Greedy

D — Parameterized queries

D — Logical equality

C — Versioning and applying database schema changes

B — Primary key

A — ArrayList

B — Grant only necessary permissions

A — O(V + E)

C — Kruskal's algorithm

D — O(1)

A — Merge sort

D — $O(n^2)$

B — TRUNCATE

A — INNER JOIN

A — B-tree/B+ tree

B — git switch -c branch-name

D — StringBuilder

D — @GetMapping

B — WHERE

B — O(n)

D — Service/business

B — NOT NULL

B — application.properties

A — IN

C — Graph traversal

C — Java Virtual Machine

B — 401

D — Attack manipulating SQL via untrusted input

D — Subclass implementation of an inherited method

D — ALTER TABLE

D — Automatically close AutoCloseable resources

C — public static void main(String[] args)

D — Supplying an object's dependencies externally

C — Floyd slow/fast pointers

C — this

D — Integrity and authenticity verification

A — HashMap

B — TCP