DEVELOPER ROLE

SET C — ANSWER KEY

Administrator answer key. Keep separate from the candidate question paper.

C — IN

A — Subclass implementation of an inherited method

A — Java Virtual Machine

B — Primary key

D — O(n²)

C — FileNotFoundException

D — 201

B — Collection

C — UPDATE

B — TLS transport security

D — Service/business

C — O(log n)

B — Queue

A — Attack manipulating SQL via untrusted input

C — A class-level member shared by instances

C — Encapsulation

C — Logical unit of work committed or rolled back

D — Cache results of repeated function calls

B — Grant only necessary permissions

D — Compile-time type safety

A — BFS

B — HashSet

A — Redundancy and update anomalies

C — Automatically close AutoCloseable resources

C — 500

D — Version control and collaboration

C — HashMap

C — Data access operations

B — TRUNCATE

A — BFS

A — 0

C — A class can implement multiple interfaces

B — String

A — Overlapping with reusable results

D — Rows in the result set

A — Controller

B — Groups rows for aggregation

D — HashMap

B — throw

B — Resolve domain names to IP addresses

C — SELECT

A — StringBuilder

D — Initializing a new object

D — NOT NULL

C — 401

B — B-tree/B+ tree

A — O(1)

B — Fetches and integrates remote changes

A — Transfer data across application boundaries

B — O(log n)

C — Speed up selected reads at storage/write trade-off

B — Integrity and authenticity verification

C — application.properties

D — Graph traversal

C — Return large result sets in manageable chunks

B — ALTER TABLE

C — INNER JOIN

A — public

A — finally

B — Referential integrity

C — PATCH

A — final

D — GET

C — Cross-origin browser requests

C — Kruskal's algorithm

B — O(1)

B — @RestController

C — Versioning and applying database schema changes

A — O(1)

C — O(V + E)

C — Same name with different parameter lists

A — @GetMapping

B — Supplying an object's dependencies externally

D — Disjoint-set union

C — Atomicity

C — Logical equality

B — Salted slow hash such as BCrypt/Argon2

A — Database transaction boundaries

B — Architectural style for networked applications

A — ArrayList

A — Parameterized queries

B — Secret manager/protected environment

D — git switch -c branch-name

A — TCP

B — Priority queue

D — O(n)

D — Floyd slow/fast pointers

A — Stack

B — WHERE

A — this

B — HAVING

C — public static void main(String[] args)

D — Greedy

C — application/json

D — Inorder

C — Trie

A — Persist transaction changes

B — volatile

B — Stack

D — Merge sort