DEVELOPER ROLE

SET B — ANSWER KEY

Administrator answer key. Keep separate from the candidate question paper.

C — Overlapping with reusable results

A — this

B — O(log n)

B — O(log n)

A — HashMap

B — Parameterized queries

D — O(1)

B — 401

A — Graph traversal

C — O(1)

C — Priority queue

C — Kruskal's algorithm

B — Groups rows for aggregation

A — SELECT

D — Database transaction boundaries

B — Controller

C — $O(n^2)$

B — git switch -c branch-name

C — Greedy

D — INNER JOIN

A — HAVING

C — final

C — finally

C — Salted slow hash such as BCrypt/Argon2

D — StringBuilder

B — Cache results of repeated function calls

B — Initializing a new object

D — NOT NULL

B — Speed up selected reads at storage/write trade-off

C — BFS

A — application.properties

A — Redundancy and update anomalies

C — application/json

C — A class can implement multiple interfaces

C — Rows in the result set

B — @RestController

D — Referential integrity

D — Compile-time type safety

C — TRUNCATE

C — 0

A — Supplying an object's dependencies externally

B — Stack

B — PATCH

D — FileNotFoundException

D — public static void main(String[] args)

D — Integrity and authenticity verification

D — WHERE

D — ArrayList

A — Stack

A — Disjoint-set union

B — @GetMapping

D — TLS transport security

C — Java Virtual Machine

A — Primary key

A — Persist transaction changes

B — Collection

B — Version control and collaboration

C — Merge sort

B — Architectural style for networked applications

B — Grant only necessary permissions

C — Attack manipulating SQL via untrusted input

A — Logical unit of work committed or rolled back

B — HashSet

B — Atomicity

C — Service/business

D — 201

A — ALTER TABLE

B — Fetches and integrates remote changes

D — B-tree/B+ tree

D — O(n)

C — Logical equality

A — O(1)

C — 500

D — Versioning and applying database schema changes

C — UPDATE

A — TCP

A — Queue

A — String

B — IN

A — throw

D — Transfer data across application boundaries

D — A class-level member shared by instances

A — Cross-origin browser requests

C — Return large result sets in manageable chunks

C — Floyd slow/fast pointers

A — Automatically close AutoCloseable resources

C — volatile

B — Subclass implementation of an inherited method

A — public

B — GET

B — Encapsulation

B — Secret manager/protected environment

C — BFS

D — Inorder

D — Same name with different parameter lists

D — HashMap

D — O(V + E)

D — Resolve domain names to IP addresses

B — Trie

A — Data access operations