

Test Report — Folding a section of Browse flashcards

PR: kuantorflow#289 + kuantorflow_automation#82 · Issue: kuantorflow#288 · Date: 2026-08-16

Summary

A section of *Browse flashcards* now folds by clicking its heading and stays folded. The panel was the tallest thing on the front page; folding both sections takes it from 1,322px to 83px. 16 new tests, and the suite is green at 973.

What changed

- `templates/index.html` — a section with topics is a `<details class="topic-fold">` whose `<summary>` holds the existing `<h3>`, with the tile grid inside. A section with no topics (#218 keeps its heading) stays a plain heading: a disclosure that reveals nothing is a promise the page cannot keep.
- `static/js/browse_folds.js` — the only part `<details>` does not do: remembering. Per device in `localStorage`, storing what is **closed**, so an untouched or newly created section is open by default rather than arriving folded over cards just added.
- `templates/base.html` — `refreshBrowseTopics()` builds the same markup after a chat save (#53) **and** calls back into the module to restore the folds. With only the first half, saving a card from the chat springs every section open.
- `static/css/style.css` — the summary carries the heading's spacing and is the press target; the disclosure marker is redrawn as a chevron that turns.

Automated tests

- **Added:** `tests/test_browse_folds.py` — 16 cases across the markup, the twin renderer and the storage rules. Deliberately absent: whether a click folds the section, which is `<details>` doing its job.
- **Against unpatched `main`** (a worktree): **14 of 16 fail**. The two that pass assert #218 behaviour the change preserves.
- **Suite result:** `pytest -m "not live"` — **973 passed** (was 957), 74 skipped (opt-in db). No existing test needed changing: the `<h3 class="topic-section">` the older section tests match survives inside the summary.

Manual & browser verification

Driven against the local app at 1280×720 and 375×812. Screenshots are unavailable in this environment, so every figure below is measured from the DOM rather than looked at.

- **Fresh visit, no stored state** → both sections open, panel 1,322px, 31 tiles visible. The page a first-time visitor gets is the page that existed before.

- **Click a heading** → panel 1,294px → 478px, heading still visible, its 26 tiles report `checkVisibility() === false`. Fold both → 83px. The five activity tiles in *Practise your words*, which share the `.topic-tile` class, are untouched.
- **Reload** → the folded section comes back folded, the other open; `kf_browse_folds_v1` holds `["B2-C1 Conversational Topics"]`.
- **Chevron** → `rotate(-45deg)` closed, `rotate(45deg)` open, read with the transition suppressed (the pane does not composite, so an in-flight transition reads as its start value — the first measurement was misleading and the rule is correct).
- **Press target** → 36px on the first row, 47px on the rest, up from the heading's 21px line. `<summary>` is focusable at `tabIndex 0`.
- **Rebuild path** → rebuilding the panel in JavaScript and calling `kfBrowseFolds.apply()` restores `[closed, open]` from storage and re-binds, so a click on a rebuilt heading persists.
- **Phone (375px)** → folding takes the panel from 2,666px to 868px, no horizontal overflow, the rule line survives beside the long section name.
- No console errors, no server errors.

Result

Pass. Every acceptance criterion in `kquantorflow#288` is met. One number worth stating plainly: fully expanded, the panel is **28px taller** than before, because a disclosure box stops the old heading margins collapsing and the press target is real padding. Folded — the state the ticket exists for — it is 1,239px shorter.