

Test Report — Automatic chat restart after a break

PR: kuantorflow#156 (+ ai_agent#60, kuantorflow_automation#26) · Issue: ai_agent#54 · Date: 2026-07-27

Summary

A conversation left idle longer than the learner's `restart_chat_interval` (hours; **2** by default, `0` = never) is restarted when they return: Mykola reviews their last three exchanges, welcomes them back, and a new chat-log file is opened. Verified end-to-end against the running app with a real Claude recap; 30 new offline tests. Suite: **180 passed**, was 150.

What changed

Three repos, because the feature straddles them.

- **ai_agent** — `recap(..., away_hours=None)`. Given the gap, the prompt tells Mykola the learner has been away *about 5 hours* and asks him to open by acknowledging it in one warm sentence. `build_recap_prompt()` and `describe_gap()` are module level so the wording is checkable without an API call. The parameter is optional, so an older KuantorFlow keeps working.
- **kuantorflow**
 - `settings_store` — `restart_chat_interval`: 2, validated through a new RANGES table (0–24, whole numbers only; booleans and fractions rejected).
 - `POST /mykola/restart-check` — the decision endpoint. Reads the user's threshold, measures the break, and on a restart mints a chat id, asks Mykola for a recap of the last three exchanges, opens the new log file and returns all of it. Every failure path answers `{"restart": false}`.
 - `_last_exchanges(3)` splits chat logs on their timestamp headers, so the restart reviews the last three *messages* rather than the last three log *files* the welcome-back recap uses.
 - `_agent_kwargs(method, away_hours=...)` — feature-detected, like the existing `user_name / hidden_languages` kwargs.
 - Widget: asks the server on load whenever a conversation was restored, sending its own last-message stamp; on a restart it wipes the thread, adopts the new chat id and shows the recap. `newChat()` now shares the same `startFreshChat()` helper.
 - Settings popup: full-width fieldset with the 1–24 slider, a live N h readout and the **Never restart chat automatically** checkbox that greys the slider out.

Automated tests

- **Added:** `tests/test_chat_restart.py` — 30 tests: the setting's default and validation table, saving 0 through `POST /settings`, the endpoint's five answers (within interval, past it,

disabled, no history, Mykola unavailable), a clock-skewed future stamp being ignored, only the last three exchanges reaching the agent, the new log file's content, the break being measured from the newest log for signed-in users, a failing recap still restarting, anonymous restarts without a recap, feature detection against an older `recap()`, and the Settings markup at 0 / 9 hours.

- **Added (ai_agent):** `check_recap_prompt()` in `test_agent_prompt.py` — `describe_gap()` wording and that the break sentence appears only with `away_hours`.
- **Fixed a pre-existing leak:** the suite's chat tests were writing real files into the kuantorflow checkout's `mykola_logs/`. A new autouse `chat_logs` fixture redirects `app.LOG_DIR` to a temp directory, like `settings_dir` and `action_logs` already do. 17 stray files from today's runs were removed.
- **Suite result:** `pytest -m "not live"` — **180 passed**, 1 skipped, 6 deselected (was 150).

Manual & browser verification

Dev server + local MySQL. Server-side flow driven as a signed-in user (session cookie signed with the app's own key), with a five-hour-old chat log seeded for the probe user:

Check	Outcome
Last message 10 minutes ago	<code>{"restart": false, "away_hours": 0.17}</code>
Last message 5 hours ago (threshold 2)	<code>restart: true, away_hours: 5.0, new chat_id</code>
The recap itself (real Claude call)	<i>"Welcome back, Restart — good to see you again after your little interlude. When last we spoke, you saved the splendid word resilient..."</i> — covers exactly the last three exchanges, opens with the break
New chat-log file	created, starting --- Chat restarted automatically after 5.0h away --- followed by the recap
Interval set to 0	<code>{"restart": false, "reason": "disabled"}</code>
Browser: stale conversation in localStorage (3 messages, 5h old), page reloaded	thread wiped to Mykola's greeting, new <code>chat_id</code> adopted, history cleared, <code>lastMessageAt</code> reset
Browser: second page load	no second restart — the chat id stayed put
Settings popup (anonymous)	slider min 1 / max 24 / value 2, readout "2 h", full-width row, everything disabled by the #102 read-only freeze

The probe user's log directory and config file were deleted afterwards, and the anonymous restart's marker file removed from the shared log dir.

Result

Pass. Deploy note: both repos should be pulled, but either order works — `away_hours` is feature-detected, so a new KuantorFlow against an old `ai_agent` simply gets a recap without the break sentence.