

# STATIC IN C++

---

CLASS VARIABLES, OBJECTS, MEMBER FUNCTIONS

# STATIC KEYWORD

---

- Static keyword has different meanings when used with different types.
- We can use static keyword with:
- **Static Variables** : Variables in a function, Variables in a class  
**Static Members of Class** : Class objects and Functions in a class

# STATIC VARIABLES

---

- **Static variables in a Function:** When a variable is declared as static, space for it gets allocated for the lifetime of the program.
- Even if the function is called multiple times, space for the static variable is allocated only once and the value of variable in the previous call gets carried through the next function call.
- This is useful for implementing application where previous state of function needs to be stored.

// C++ program to demonstrate the use  
of static variables in a Function

Output: 0 1 2 3 4

```
#include <iostream>
#include <string>
using namespace std;
void demo()
{
    // static variable
    static int count = 0;
    cout << count << " ";

    // value is updated and
    // will be carried to next
    // function calls
    count++;
}
int main()
{
    for (int i=0; i<5; i++)
        demo();
    return 0; }
```

---



# STATIC VARIABLES

---

- **Static variables in a class:** As the variables declared as static are initialized only once as they are allocated space in separate static storage so, the static variables **in a class are shared by the objects.**
- There can not be multiple copies of same static variables for different objects. Also because of this reason static variables can not be initialized using constructors.



```
// C++ program to demonstrate static variables inside a class
```

```
#include<iostream>
```

```
using namespace std;
```

```
class GfG
```

```
{
```

```
public:
```

```
static int i;
```

---

```
    GfG()
```

```
    {
```

```
        // Do nothing
```

```
    };
```

```
};
```

```
int main()
```

```
{
```

```
GfG obj1;
```

```
GfG obj2;
```

```
obj1.i = 2;
```

```
obj2.i = 3;
```

```
// prints value of i
```

```
cout << obj1.i<<" "<<obj2.i; }
```

in this program we have tried to create multiple copies of the static variable i for multiple objects. But this didn't happen. So, a static variable inside a class should be initialized explicitly by the user using the class name and scope resolution operator outside the class

// C++ program to demonstrate static variables inside a class

```
#include<iostream>
using namespace std;
```

Output: 1

```
class GfG
{
public:
    static int i;

    GfG()
    {
        // Do nothing
    };
};
```

```
int GfG::i = 1;
```

```
int main()
{
    GfG obj;
    // prints value of i
    cout << obj.i; }
```

# STATIC MEMBERS OF CLASS

---

- **Class objects as static:** Just like variables, objects also when declared as static have a scope till the lifetime of program.  
Consider the below program where the object is non-static.



```
// CPP program to illustrate
// when not using static keyword
#include<iostream>
using namespace std;
```

```
class GfG
{
    int i;
public:
    GfG()
    {
        i = 0;
        cout << "Inside Constructor\n";
    }
    ~GfG()
    {
        cout << "Inside Destructor\n";
    }
};

int main()
{
    int x = 0;
    if (x==0)
    {
        GfG obj;
    }
    cout << "End of main\n";
}
```

## Output:

```
Inside Constructor
Inside Destructor
End of main
```

- 
- In the above program the object is declared inside the if block as non-static. So, the scope of variable is inside the if block only. So when the object is created the constructor is invoked and soon as the control of if block gets over the destructor is invoked as the scope of object is inside the if block only where it is declared.

```
// CPP program to illustrate
// class objects as static
#include<iostream>
using namespace std;
```

# LET US NOW SEE THE CHANGE IN OUTPUT IF WE DECLARE THE OBJECT AS STATIC.

---

```
class GfG
{
    int i = 0;

    public:
    GfG()
    {
        i = 0;
        cout << "Inside Constructor\n";
    }

    ~GfG()
    {
        cout << "Inside Destructor\n";
    }
};

int main()
{
    int x = 0;
    if (x==0)
    {
        static GfG obj;
    }
    cout << "End of main\n";
}
```

Output:

```
Inside Constructor
End of main
Inside Destructor
```

- 
- **Static functions in a class:** Just like the static data members or static variables inside the class, static member functions also does not depend on object of class. We are allowed to invoke a static member function using the object and the '.' operator but it is recommended to invoke the static members using the class name and the scope resolution operator.

**Static member functions are allowed to access only the static data members or other static member functions,** they can not access the non-static data members or member functions of the class.

```
// C++ program to demonstrate static  
// member function in a class  
#include<iostream>  
using namespace std;
```

```
class GfG
```

```
{
```

```
public:
```

```
    // static member function
```

```
    static void printMsg()
```

```
    {
```

```
        cout<<"Welcome to GfG!";
```

```
    }
```

```
};
```

```
// main function
```

```
int main()
```

```
{
```

```
    // invoking a static member function
```

```
    GfG::printMsg();
```

```
}
```

Output:

```
Welcome to GfG!
```