

Planned Turbomachinery Cases: Not Yet Validated

Geometry, physics, boundary conditions, rotation model and validation data for each case

OpenFOAM v2412 turbomachinery programme

5 October 2026

- ▶ 19 cases: every planned case not yet compared with experiment. The 4 validated cases (ERCOFTAC pump, FDA blood pump, PPTC open water, single-channel pump) are not repeated.
- ▶ One slide per case, same rows on every slide: geometry, domain and mesh, fluid, physics and solver, rotation model, boundary conditions, operating point, validation data, references, status.
- ▶ Rig facts (geometry, operating point, data) were checked on 5 Oct 2026 against the primary sources listed on each slide and in the reference list at the end. Set-up values for built cases come from the case dictionaries and logs. Set-ups not yet built are marked *planned*: they are proposals, not facts.

Status		Validation data	
Ran, not validated	solver ran, no comparison yet solver crashed or did not converge dictionaries only, no mesh or run in the plan, nothing built	data in hand	on this machine
Ran, did not finish		public, to download	open, to download
Setup only		not available	not public or none
Planned, not started			

Overview of the 19 cases

#	Case	Machine	Physics	Rotation model	Validation data
1	Francis-99	Francis turbine	incompr. RANS	MRF + mixingPlane	data in hand public, to download data in hand data in hand public, to download (paper)
2	NREL Phase VI	HAWT wind turbine	incompr. RANS	MRF	
3	VKI LS89	transonic turbine vane	compressible	none (cascade)	
4	NASA Rotor 37	transonic compressor	compressible	MRF	
5	Timisoara swirl generator	swirl gen. / runner	incompr. URANS	sliding mesh (AMI)	
6	axialTurbine (6 variants)	axial hydro stage	incompr. RANS/URANS	SRF, MRF, mixingPlane, AMI	not available (no experiment)
7	Turbine-99	Kaplan draft tube	incompr. RANS	none (rotating cone wall)	not available (raw data offline)
8	Aachen 1.5-stage	axial gas turbine	compressible	MRF + mixingPlane	not available (SU2 result only)
9	Pelton (NTNU)	impulse turbine	VOF two-phase	sliding mesh (ACMI)	efficiency only, CAD on request
10	Mini-ORC (TU Delft)	radial-inflow turbine	real-gas compressible	MRF + mixingPlane	not available (no measurements)
11	PPTC cavitating	propeller	cavitation (VOF)	MRF or sliding mesh	data in hand
12	SHF impeller	centrifugal pump (air model)	incompr. RANS	MRF or frozen rotor	published (PIV, wall pressure)
13	NASA Stage 35	axial compressor stage	compressible	MRF + mixingPlane	public, to download
14	Radiver	centrifugal compressor	compressible	MRF + mixingPlane	public, to download
15	Krain impeller	centrifugal compressor	compressible	MRF	published, geometry incomplete
16	NASA HECC	centrifugal compressor	compressible	MRF + mixingPlane	public, to download
17	NASA SDT R4	turbofan fan	compressible	MRF + mixingPlane	data public, CAD not
18	MEXICO rotor	HAWT wind turbine	incompr. RANS	MRF	consortium access
19	Wells turbine / OWC	wave-energy air turbine	oscill. flow, VOF chamber	sliding mesh or MRF	per chosen rig

1. Francis-99 (NTNU model Francis turbine, 2nd workshop)

Status: **Ran, did not finish**: 1000 iterations, residuals $\sim 10^{-2}$; serial only

Validation data: **data in hand**



Geometry	NTNU Waterpower Lab model: 1:5.1 model of the Tokke prototype: spiral casing, 14 stay vanes, 28 guide vanes, runner 15 blades + 15 splitters, draft tube. Mesh used: guide-vane angle 6.72°
Domain and mesh	Single passage of guide vane and runner (periodic) + full draft tube; workshop mesh 1.89M cells, 141 patches; non-orth. 72.6° , skewness 3.94
Fluid	Water, incompressible, Newtonian
Physics and solver	Steady RANS, <code>simpleFoam</code> , standard $k-\varepsilon$; PBiCGStab for p , relaxation 0.1, upwind U
Rotation model	MRF runner, case value $\omega = -35.123$ rad/s (335.4 rpm; measured at PL: 34.87 rad/s); mixingPlane at GV–runner and runner–draft tube; 8 periodic <code>ggi</code> pairs (TurboWG libraries)
Boundary conditions	Inlet (GV inflow): prescribed velocity, radial -1.428 , tangential -2.14 m/s, axial 0; outlet: static pressure; walls: no-slip with wall functions
Operating point	Part load : workshop data give $\alpha = 6.72^\circ$ for PL (BEP 9.84° , HL 12.46°); PL $H \approx 11.87$ m, $Q \approx 0.14$ m ³ /s
Validation data	NTNU 2nd-workshop data, downloaded: steady pressure at VL2 (vaneless space), DT5, DT6 (draft tube); steady velocity; PIV on 3 draft-tube lines (<code>f99w2-exp-*</code>)
References	Trivedi, Cervantes, Gandhi, Dahlhaug (2013) <i>J. Fluids Eng.</i> 135(11):111102; Francis-99 2nd workshop data (NTNU, Dec 2016)
Gap / next step	Continue to convergence (ε and <code>mixingPlane</code> flux still oscillate), set ω to the PL value, then compare pressure and PIV

2. NREL Phase VI (Unsteady Aerodynamics Experiment, wind turbine)

Status: **Ran, not validated**: 7 wind speeds, 2000 iterations each

Validation data: **public, to download**

Geometry	2-bladed stall-regulated HAWT, S809 airfoil, $D = 10.058$ m, tip pitch 3° , NASA Ames 24.4×36.6 m tunnel; lofted in Python from the chord/twist tables of TP-500-29955 (root transition, rounded tip cap)
Domain and mesh	Full rotor in a box; STL $\rightarrow$ snappyHexMesh, 1.31M cells; 1 checkMesh test failed (146 skewed faces, max 10.8)
Fluid	Air, incompressible, $\nu = 1.5 \times 10^{-5} \text{ m}^2/\text{s}$
Physics and solver	Steady RANS, simpleFoam, $k-\omega$ SST, TI 1% (assumed)
Rotation model	MRF rotor zone, $\omega = 7.54 \text{ rad/s}$ (72 rpm)
Boundary conditions	Inlet: fixed velocity 5–25 m/s; outlet: $p = 0$, inletOutlet U; far field: slip; blades: no-slip
Operating point	Sequence S (upwind, rigid, 3° tip pitch, 5–25 m/s), 0° yaw subset; 72 rpm; $U_\infty = 5, 7, 10, 13, 15, 20, 25 \text{ m/s}$
Validation data	Shaft torque, root flap moment; C_p from 22 taps at each of 30, 46.6, 63.3, 80, 95% span, integrated to C_n , C_t ; only TP-500-29955 is here, measured data (TP-500-29494, DOE Wind Data Hub) to download
References	Hand et al. (2001) NREL/TP-500-29955; Simms et al. (2001) NREL/TP-500-29494
Gap / next step	5 m/s torque has the wrong sign; fix mesh quality, then compare torque and C_p



3. VKI LS89 (highly loaded transonic turbine guide-vane cascade)

Status: **Ran, did not finish**: 7 conditions, all crashed at 63–93% of target time Validation data: **data in hand**

Geometry	Linear cascade of the VKI LS89 vane: chord 67.647 mm, pitch 57.5 mm, stagger 55° ; 2D section
Domain and mesh	One blade passage, periodic; 7-block Plot3D grid converted (Python 3 rewrite of p3d2gmsh), 56,844 hex cells, 16 stitched interfaces, front/back empty
Fluid	Air, perfect gas, <code>hePsiThermo</code> , Sutherland viscosity
Physics and solver	Compressible, transient, density-based <code>rhoCentralFoam</code> ; run laminar (SST block present but inactive). <code>rhoSimpleFoam</code> failed on 13 μm trailing-edge cells
Rotation model	None (stationary cascade); <code>cyclic</code> pitchwise periodicity
Boundary conditions	Inlet: total pressure 1.435 MPa (MUR43) and total temperature 420 K; outlet: static pressure 0.904 MPa; blade: no-slip, adiabatic
Operating point	MUR43–MUR49: P_0 1.433–1.608 MPa, $T_0 = 420$ K, $M_{2,is} = 0.84, 0.875, 1.02$, $Re_2 = 10^6$
Validation data	Blade-surface isentropic Mach number and pressure (digitised <code>mach.lay</code> , <code>pressure.lay</code>); heat-transfer data in TN 174
References	Arts, Lambert de Rouvroit, Rutherford (1990) VKI Technical Note 174; AboutFlow benchmark test case 2 (QMUL)
Gap / next step	Restart from checkpoints, fix the floating-point crash in the thermo library, add SST, compare surface Mach

4. NASA Rotor 37 (isolated transonic axial compressor rotor)

Status: **Ran, did not finish**: crashes after $\sim 10^{-6}$ s

Validation data: **data in hand**

Geometry	36 MCA blades, tip speed 454 m/s, rig tip clearance 0.356 mm (0.45% span; case uses 0.35 mm); blade rebuilt from the MERIDL geometry file (own parser)
Domain and mesh	Single passage, 10° periodic; 214–258k cells; 42 skewed faces (max 7.3)
Fluid	Air, perfect gas
Physics and solver	Compressible, rhoPimpleFoam; run laminar (SST block present but inactive), ramped ω
Rotation model	MRF , 17,188.7 rpm (1800 rad/s); periodic sides as cyclicAMI pair
Boundary conditions	Inlet: total pressure 101,325 Pa, total temperature 288.15 K; outlet: static pressure 213,391 Pa (estimated from design PR); hub, shroud, blade: no-slip
Operating point	Design: PR 2.106, adiabatic efficiency 0.889, 20.19 kg/s; speedline from choke to near stall
Validation data	Speedline (PR, efficiency vs mass flow), radial total pressure/temperature and flow angle at stations 1 and 4, laser anemometry; Excel archive Rotor37_exp.zip downloaded
References	Reid & Moore (1978) NASA TP-1337; Suder & Celestina (1996) <i>J. Turbomach.</i> 118(2):218–229; Denton (1997) <i>J. Therm. Sci.</i> 6:1–13; Dunham (1998) AGARD-AR-355
Gap / next step	Improve tip and periodic mesh, start at low back-pressure and ramp, turn on SST, then run a speedline

5. Timisoara swirl generator (Politehnica Univ. Timisoara)

Status: **Ran, did not finish**: stable to $t = 0.238$ s, then SIGFPE Validation data: **public, to download** (paper)


Geometry	4 leaned struts → 13 guide vanes → free 10-blade runner → convergent–divergent test section (reproduces the vortex rope of a Francis draft tube at part load)
Domain and mesh	Full 360°; shipped mesh 2.70M hex cells, 18 patches; rotating zone 708,050 cells; max non-orth. 75° at AMI faces
Fluid	Water, incompressible, $\nu = 10^{-6} \text{ m}^2/\text{s}$
Physics and solver	Transient URANS, pimpleFoam, RNG $k-\varepsilon$
Rotation model	Sliding mesh : dynamicMotionSolverFvMesh (solid-body rotation), 3 cyclicAMI interfaces; $\omega = 96.342 \text{ rad/s}$ (920 rpm). Ported from foam-extend GGI
Boundary conditions	Inlet: axial velocity 1.69765 m/s; outlet: fixedMean $p = 0$; runner: movingWallVelocity; other walls: no-slip
Operating point	30 L/s; free runner measured at 920 rpm (design 870 rpm)
Validation data	LDV mean velocity profiles in the cone (used by Petit et al. 2011) and unsteady wall pressure (Bosioc et al. 2012); not on this machine
References	Susan-Resiga et al. (2006) <i>J. Fluids Eng.</i> 128:177–189; Bosioc et al. (2012) <i>J. Fluids Eng.</i> 134(8):081104; Petit et al. (2011) <i>IJFMS</i> 4(1):199–208
Gap / next step	Restart from checkpoint, run several rope periods (1–4 days on 10 cores), average and compare LDV



6. axialTurbine (TurboWG teaching case, 6 rotor–stator methods)

Status: **Ran, not validated**: all 6 methods agree within 1.7% at the runner outlet Validation data: **not available**

Geometry	Synthetic axial hydro stage: guide vanes → 5-blade runner → draft tube
Domain and mesh	Single passage (cases 1–5) or full 5-blade annulus (case 6); 1,400 / 3,700 / 18,500 cells
Fluid	Incompressible, $\nu = 10^{-5} \text{ m}^2/\text{s}$ (non-dimensional teaching set-up)
Physics and solver	Steady (SRFSimpleFoam, simpleFoam) and transient (SRFPimpleFoam, pimpleFoam); standard $k-\varepsilon$
Rotation model	All of them : SRF steady and transient; MRF + cyclicPeriodicAMI; MRF + mixingPlane; rotating mesh with AMI, 1 blade and 5 blades; $\omega = -10 \text{ rad/s}$
Boundary conditions	Inlet: axial velocity 1 m/s; outlet: zero-gradient U, fixed p ; walls: no-slip
Operating point	Single design point
Validation data	No experiment exists for this geometry; method-vs-method comparison only (axial U within 1.7%, flow angle within 4.3°)
References	Nilsson, H., rotating-machinery training, OpenFOAM Workshops OFW7 (2012) and OFW10 (2015); Beaudoin et al. (2014) mixingPlane, IOP Conf. Ser.
Gap / next step	Cannot be validated; keep as a verification case for the rotation models



7. Turbine-99 (Hölleforsen Kaplan draft tube, Vattenfall)

Status: **Setup only**: dictionaries, no mesh

Validation data: **not available** (raw data offline)

Geometry	1:11 model of the Hölleforsen sharp-heel elbow draft tube, runner $D = 0.5$ m: runner cone, elbow, rectangular diffuser. CAD file not downloadable (host dead since 2010)
Domain and mesh	<i>Planned</i> : draft tube only, from the inlet section below the runner to the outlet; hex mesh to be built from the KBwiki geometry description
Fluid	Water, incompressible
Physics and solver	<i>Planned</i> : steady RANS, simpleFoam, $k-\omega$ SST (skeleton present)
Rotation model	None for the flow; rotating runner-cone wall (595 rpm)
Boundary conditions	<i>Planned</i> : inlet = measured LDV axial and tangential mean/RMS profiles at section Ia (radial component missing, to be modelled); outlet: static pressure; cone: rotating wall; walls: no-slip
Operating point	Case T (on-cam, 60% load): $H = 4.5$ m, 595 rpm, $Q = 0.522\text{--}0.528$ m ³ /s, $Re_D \approx 1.75M$
Validation data	Wall pressure recovery and LDV velocity at sections Ia, Ib, II, III; only described in ERCOFTAC KBwiki AC6-07, raw files not public
References	Andersson (2000) Turbine 99 workshop proceedings, ISSN 1402-1536; ERCOFTAC KBwiki AC6-07 (Karlsson); Nilsson & Page (2005), Turbine-99 III, Porjus
Gap / next step	Obtain CAD and inlet/validation data from Vattenfall or Luleå; otherwise not feasible

8. Aachen 1.5-stage axial turbine (RWTH Aachen, IST)

Status: **Setup only**: 3 meshes converted from SU2, not run Validation data: **not available** (SU2 result only)

Geometry	Stator 1 → rotor → stator 2; modified VKI stator vanes, Traupel rotor profile; untwisted, constant hub/tip; for CFD the stator count is raised from 36 to 41 so every row has 41
Domain and mesh	Single passage per row, 8.78° ($360^\circ/41$) periodic; 3 OpenFOAM meshes converted from the SU2 coarse mesh
Fluid	Air, ideal gas ($\gamma = 1.4$, $R = 287.058$), Sutherland viscosity
Physics and solver	<i>Planned</i> : steady compressible RANS, rhoSimpleFoam, SA or $k-\omega$ SST (SU2 used SA + wall functions)
Rotation model	MRF rotor, $\omega = -366.52$ rad/s (3500 rpm); mixingPlane between the 3 rows (compressible + mixingPlane untested in v2412)
Boundary conditions	Inlet: total pressure 158,245 Pa, total temperature 308.26 K, axial; outlet: static pressure 110,051 Pa; TI 2.5%, $\nu_t/\nu = 100$; walls: no-slip
Operating point	Total-to-static PR ≈ 1.44 , motion Mach 0.35
Validation data	RWTH measurements not public; converged SU2 mixing-plane solution available for code-to-code comparison
References	Gallus, Zeschky & Hah (1995) <i>J. Turbomach.</i> 117(4):562–570; SU2 Aachen turbine tutorial; Oliani et al. (2022), new OpenFOAM turbomachinery solver applied to a 1.5-stage turbine
Gap / next step	Test compressible + mixingPlane; request IST data or accept code-to-code comparison only

9. Pelton turbine (NTNU Waterpower Lab reference design)

Status: **Setup only:** dictionaries, no mesh

Validation data: efficiency published; CAD on request

Geometry	Horizontal single-jet Pelton: runner $D = 513$ mm (pitch radius 256.7 mm), 23 buckets, bucket width 114.2 mm, jet diameter 35 mm; geometry and data "available upon request"
Domain and mesh	<i>Planned:</i> nozzle + jet region (static) and runner sector or full runner (rotating), casing
Fluid	Water and air, two-phase, immiscible, isothermal
Physics and solver	<i>Planned:</i> transient VOF, <code>interFoam</code> , $k-\omega$ SST
Rotation model	Sliding mesh with <code>cyclicACMI</code> (jet crosses the interface); <code>overset overInterDyMFoam</code> as fallback. MRF not suitable
Boundary conditions	<i>Planned:</i> nozzle inlet $\alpha = 1$, jet velocity $\sqrt{2gH} \approx 37$ m/s; casing outlets atmospheric total pressure; buckets: moving walls; $\omega \approx 65$ rad/s (placeholder, not sourced)
Operating point	$H = 70$ m, best-efficiency speed to be confirmed
Validation data	Measured efficiency at $H = 70$ m (max 77.75%) and visual inspection (Solemslie & Dahlhaug 2014); NTUA casing data as a cross-check
References	Solemslie & Dahlhaug (2012) IOP EES 15:032005, (2014) IOP EES 22:012004; Petley & Aggidis (2019) <i>IJFMS</i> 12(4); Rygg (2013) NTNU MSc thesis, <code>interDyMFoam</code> + AMI
Gap / next step	Request bucket geometry from NTNU; highest compute cost of all cases (several revolutions at VOF Courant limit)

10. Mini-ORC radial-inflow turbine (TU Delft, ORCHID)

Status: **Setup only**: draft dictionaries only

Validation data: **not available** (no measurements yet)



Geometry	Single-stage radial-inflow turbine, 12 nozzle vanes, rotor $D_2 = 51.5$ mm, 12 kW; meanline and CFD design published, no 3D blade coordinates
Domain and mesh	<i>Planned</i> : one nozzle passage + one rotor passage, periodic
Fluid	Siloxane MM (hexamethyldisiloxane), non-ideal (dense) gas
Physics and solver	<i>Planned</i> : compressible RANS with a real-gas equation of state (Peng–Robinson or CoolProp tables); no validated NICFD solver in v2412, needs a new solver family
Rotation model	MRF rotor + mixingPlane (or frozen rotor) at the nozzle–rotor interface; 98,000 rpm
Boundary conditions	<i>Planned</i> : inlet total pressure 1810 kPa, total temperature 573 K; outlet static pressure 44.3 kPa
Operating point	Volume ratio 48, nozzle exit angle 78° , design η_{ts} 83% (meanline); ORCHID rig limit 25 bar, 300°C
Validation data	No published turbine measurements; only the design-method CFD of de Servi et al.
References	de Servi, Burigana, Pini, Colonna (2019) <i>J. Eng. Gas Turbines Power</i> 141(9):091021; Head et al. (2016) ORCHID preliminary design
Gap / next step	Not feasible until a real-gas solver is built and measurements are published

11. PPTC VP1304 cavitating propeller (SVA Potsdam, SMP'11)

Status: **Planned, not started**: open water validated; cavitation templates only

Validation data: **data in hand**

Geometry	5-blade right-handed CPP VP1304, $D = 0.25$ m, $P_{0.7}/D = 1.635$, $A_E/A_0 = 0.779$; cavitation-tunnel hub cap (differs from open-water rig)
Domain and mesh	<i>Planned</i> : K15A tunnel section 600×600 mm or open domain; reuse the validated M3 snappyHexMesh set-up (1.16M cells) with tip refinement
Fluid	Water + vapour (Schnerr–Sauer); measured $\rho = 997.5$ kg/m ³ , $\nu = 9.4 \times 10^{-7}$ m ² /s, $p_v \approx 2.8$ kPa
Physics and solver	<i>Planned</i> : interPhaseChangeFoam, VOF + Schnerr–Sauer, $k-\omega$ SST
Rotation model	MRF for the first pass; sliding mesh (cyclicAMI) for transient cavity shapes
Boundary conditions	<i>Planned</i> : inlet velocity from J ; outlet pressure set from σ_n ; propeller: rotating no-slip; tunnel walls: slip
Operating point	SVA test cases 2.3.1/2.3.2/2.3.3: $J = 1.019 / 1.269 / 1.408$, $\sigma_n = 2.024 / 1.424 / 2.000$, $n = 25$ s ⁻¹
Validation data	Cavity sketches, photos and videos; cavitating K_T , K_Q ; LDV planes (report 3754); all in references/
References	SVA reports 3752, 3753, 3754 (Potsdam, 2011); Gaggero & Villa (2018) <i>J. Mar. Sci. Appl.</i> 17(1):1–20
Gap / next step	Strongest new case: geometry, mesh and data are ready



12. SHF centrifugal pump impeller (Société Hydrotechnique de France, air model)

Status: **Planned, not started**: correction, this is *not* the ERCOFTAC U3 rig Validation data: published (PIV, wall pressure)

Geometry	Radial pump impeller, 7 blades, outlet radius 0.2566 m, outlet height 38.5 mm, outlet blade angle 22.5° ; tested with a vaneless diffuser, vaned diffusers (8 channel-type or 11 cascade-type vanes) and an industrial volute
Domain and mesh	<i>Planned</i> : full 360° impeller + diffuser (rotor–stator interaction is not periodic)
Fluid	Air at 25°C (low-speed, treated as incompressible)
Physics and solver	<i>Planned</i> : steady RANS (simpleFoam), then transient sliding mesh for blade-position-resolved comparison
Rotation model	MRF (frozen rotor at fixed blade position) or sliding mesh (cyclicAMI)
Boundary conditions	<i>Planned</i> : inlet flow rate; outlet static pressure; walls: no-slip
Operating point	1710 rpm, design flow $Q_n = 0.337 \text{ m}^3/\text{s}$, tip speed 45.95 m/s; tests at 0.30–1.63 Q_n
Validation data	2D PIV of impeller outlet and vaneless diffuser (Wuibaut et al. 2001); mean and unsteady wall pressure at 114 taps in one blade passage (Godinho Patricio 1999); directional-probe traverses with vaned diffuser and volute (El Hajem et al. 1998)
References	Wuibaut et al. (2001) <i>Proc. IMechE A</i> 215(6); Godinho Patricio (1999) PhD thesis, Univ. Lille; El Hajem et al. (1998) <i>La Houille Blanche</i> 7; Atif, Benmansour, Bois (2010) <i>Int. J. Rotating Mach.</i> 706043
Gap / next step	Earlier “duplicate” decision was wrong; full blade geometry availability to be confirmed with Arts et Métiers / Lille (LML)

13. NASA Stage 35 (single-stage transonic axial compressor)

Status: **Planned, not started**: backlog

Validation data: **public, to download**

Geometry	Rotor 35 (36 blades, tip solidity 1.3, aspect ratio 1.19) + stator 35 (46 blades, aspect ratio 1.26); one of four inlet stages (35–38) of NASA TP-1337
Domain and mesh	<i>Planned</i> : single passage per row, periodic; structured blade mesh
Fluid	Air, perfect gas
Physics and solver	<i>Planned</i> : steady compressible RANS, rhoSimpleFoam, $k-\omega$ SST
Rotation model	MRF rotor + mixingPlane to the stator
Boundary conditions	<i>Planned</i> : inlet standard total pressure and temperature; outlet static pressure swept along the speedline
Operating point	Design: 17,188.7 rpm, tip speed 455 m/s, 20.19 kg/s, stage PR 1.82, stage adiabatic efficiency 0.828
Validation data	Overall performance maps and radial surveys of total pressure, temperature and flow angle (NASA TP-1337, TP-1338)
References	Reid & Moore (1978) NASA TP-1337; Reid & Moore (1978) NASA TP-1338 (blade-element data)
Gap / next step	Do after Rotor 37: same speed, flow and tip speed, so set-up and blade parser carry over

14. Radiver (centrifugal compressor with vaned diffuser, RWTH Aachen / MTU)

Status: **Planned, not started**: backlog

Validation data: **public, to download** (open test case)

Geometry	Semi-open impeller with 15 backward-curved blades (no splitters); wedge vaned diffuser with 23 vanes, adjustable in two degrees of freedom; rig commissioned by MTU, run at RWTH IST
Domain and mesh	<i>Planned</i> : one impeller passage + one diffuser passage (non-matching pitch handled by the interface)
Fluid	Air, perfect gas
Physics and solver	<i>Planned</i> : steady compressible RANS, rhoSimpleFoam, $k-\omega$ SST
Rotation model	MRF impeller + mixingPlane at the impeller–diffuser gap (frozen rotor as a check)
Boundary conditions	<i>Planned</i> : inlet total pressure and temperature; outlet static pressure or mass flow
Operating point	Design speed 35,200 rpm, design pressure ratio 4; several diffuser vane settings
Validation data	Steady and unsteady measurements (performance, PIV, unsteady pressure) for several diffuser configurations; geometry and data released to the public domain (RWTH IST open test cases)
References	Ziegler, Gallus & Niehuis (2003) <i>J. Turbomach.</i> 125(1):173–182 (Part I) and 183–192 (Part II); RWTH IST “Open Testcases” page
Gap / next step	Request the open-test-case package from RWTH IST

15. Krain impeller (high-pressure-ratio centrifugal compressor, DLR)

Status: **Planned, not started**: backlog

Validation data: published; geometry incomplete

Geometry	Unshrouded impeller, 24 full blades, 30° backsweep at exit, vaneless diffuser; published geometry does not fully define the blade (reconstruction needed)
Domain and mesh	<i>Planned</i> : one blade passage with tip clearance + vaneless diffuser, periodic
Fluid	Air, perfect gas
Physics and solver	<i>Planned</i> : steady compressible RANS, rhoSimpleFoam, $k-\omega$ SST
Rotation model	MRF impeller (single rotating passage)
Boundary conditions	<i>Planned</i> : inlet total pressure and temperature; outlet mass flow or static pressure
Operating point	Design 22,363 rpm, 4.0 kg/s, total rotor pressure ratio 4.7
Validation data	Laser-two-focus (L2F) velocity measurements upstream, along the passage and downstream of the impeller; performance data
References	Krain (1988) "Swirling impeller flow", <i>J. Turbomach.</i> 110(1):122–128; Eisenlohr, Krain, Richter, Tiede (2002) ASME GT2002-30394
Gap / next step	Geometry reconstruction risk; lower priority than Radiver and HECC

16. NASA HECC (High-Efficiency Centrifugal Compressor, NASA Glenn CE-18)

Status: **Planned, not started**: backlog

Validation data: **public, to download** (public archive)

Geometry	Impeller with 15 main/splitter blade pairs (backswEEP 32–42°), exit diameter 17.0 in; vaned diffuser with 20 main/splitter vane pairs; 90° bend; 60 exit guide vanes
Domain and mesh	<i>Planned</i> : one impeller, one diffuser and one EGV passage, periodic, tip clearance 0.012 in
Fluid	Air, perfect gas
Physics and solver	<i>Planned</i> : steady compressible RANS, rhoSimpleFoam, $k-\omega$ SST
Rotation model	MRF impeller + mixingPlane at impeller–diffuser and diffuser–EGV interfaces
Boundary conditions	<i>Planned</i> : inlet total pressure 11 psia (rig), total temperature; outlet static pressure swept to the map
Operating point	Design corrected speed 21,789 rpm, $U_2 = 1615$ ft/s; design-intent PR 4.85 (14.7 psia) / 4.80 (11 psia), measured 4.68; inlet corrected flow 10.85 lbm/s measured; work factor 0.79 design, 0.81 measured
Validation data	Public data archive: stage and subcomponent performance maps, static pressures, 3-hole probe surveys at diffuser exit
References	Braunscheidel, Welch, Skoch, Medic, Sharma (2014) AIAA paper, NTRS 20140016535; Harrison et al. (2024) NASA/TM-20240003692/REV1, NTRS 20250000831
Gap / next step	Best open centrifugal-compressor data set; download the archive first

17. NASA SDT fan R4 (Source Diagnostic Test)

Status: **Planned, not started**: backlog

Validation data: data public, CAD not

Geometry	1/5-scale high-bypass fan, 22 in diameter, 22 blades, designed by GE Aircraft Engines; OGV sets: Baseline 54 vanes, Low Count 26 vanes, Low Noise; blade CAD not public
Domain and mesh	<i>Planned</i> : one rotor passage + one OGV passage, periodic, with tip clearance
Fluid	Air, perfect gas
Physics and solver	<i>Planned</i> : steady compressible RANS, rhoSimpleFoam, $k-\omega$ SST
Rotation model	MRF rotor + mixingPlane to the OGV (rotor-alone case: MRF only)
Boundary conditions	<i>Planned</i> : inlet total conditions of the 9×15 ft tunnel; bypass outlet static pressure
Operating point	Design corrected speed 12,657 rpm, corrected tip speed 1,215 ft/s, design stage PR 1.47; approach, cutback and takeoff points
Validation data	Rotor-alone and stage performance, LDV flow measurements (NASA Glenn 9×15 ft Low Speed Wind Tunnel)
References	Hughes, Jeracki, Woodward, Miller (2005) NASA/TM-2005-211681 (AIAA-2002-2426); Van Zante et al., SDT LDV report, NTRS 20030066234
Gap / next step	Not feasible without the blade geometry; confirm access with NASA Glenn / GE

18. MEXICO rotor (EU project MEXICO, IEA Wind Task 29 Mexnext)

Status: **Planned, not started**: backlog

Validation data: consortium access

Geometry	3-bladed rotor, $D = 4.5$ m, DU91-W2-250, RISØ-A1-21 and NACA 64-418 sections, with nacelle; DNW LLF 9.5×9.5 m open test section
Domain and mesh	<i>Planned</i> : full rotor (or 120° periodic) in the open-jet test section
Fluid	Air, incompressible
Physics and solver	<i>Planned</i> : steady RANS, simpleFoam, $k-\omega$ SST
Rotation model	MRF rotor for axial flow (sliding mesh for yawed cases)
Boundary conditions	<i>Planned</i> : inlet uniform velocity; outlet static pressure; open-jet / far-field boundary; blades: no-slip
Operating point	Axial flow, 424.5 rpm, pitch -2.3° , $U_\infty = 10, 15, 24$ m/s (tip speed ratio 10, 6.7, 4.2)
Validation data	148 Kulite pressure sensors at 25, 35, 60, 82, 92% radius; rotor loads; PIV wake data
References	Schepers & Snel (2007) ECN-E-07-042 (MEXICO final report); Schepers, Boorsma, Munduate (2014) <i>J. Phys. Conf. Ser.</i> 555:012089
Gap / next step	Confirm data access with IEA Wind Task 29/47

19. Wells turbine / oscillating water column (wave energy)

Status: **Planned, not started**: backlog

Validation data: depends on chosen rig

Geometry	Self-rectifying axial air turbine with symmetric (typically NACA 00xx) blades set in the plane of rotation, above an OWC chamber; no single canonical open rig
Domain and mesh	<i>Planned</i> : turbine passage (periodic); optional OWC chamber with wave flume
Fluid	Air (turbine); water + air for the chamber
Physics and solver	<i>Planned</i> : turbine: transient incompressible RANS, <code>pimpleFoam</code> , $k-\omega$ SST, oscillating inflow; chamber: VOF (<code>interFoam</code>)
Rotation model	MRF for quasi-steady characteristic curves; sliding mesh for the oscillating cycle
Boundary conditions	<i>Planned</i> : inlet time-varying (sinusoidal) velocity or pressure; outlet static pressure; blades: no-slip
Operating point	Flow-coefficient sweep at constant speed (rig-specific)
Validation data	Torque and pressure-drop coefficients vs flow coefficient from the chosen rig (see reviews)
References	Raghunathan (1995) <i>Prog. Aerosp. Sci.</i> 31(4):335–386; Shehata et al. (2017) <i>Int. J. Energy Res.</i> 41:6–38; 16 kW Wells/OWC design for Ecuador (2025) <i>Processes</i> 13:2349 (waves in OpenFOAM)
Gap / next step	Choose a rig with open geometry and measurements first

Data in hand or open

- ▶ Francis-99 (part load)
- ▶ PPTC cavitating
- ▶ VKI LS89
- ▶ NREL Phase VI
- ▶ NASA Rotor 37
- ▶ Stage 35, HECC, Radiver

Possible, with cost or access

- ▶ Timisoara (1–4 days compute)
- ▶ SHF impeller (geometry access)
- ▶ Aachen (code-to-code only)
- ▶ MEXICO (consortium data)
- ▶ Krain (geometry rebuild)
- ▶ Wells (choose rig)

Blocked

- ▶ axialTurbine (no experiment)
- ▶ Turbine-99 (CAD, data offline)
- ▶ Pelton (geometry on request)
- ▶ Mini-ORC (no solver, no data)
- ▶ SDT R4 (CAD proprietary)

1. Trivedi C., Cervantes M.J., Gandhi B.K., Dahlhaug O.G. (2013). Experimental and numerical studies for a high head Francis turbine at several operating points. *J. Fluids Eng.* 135(11):111102. doi:10.1115/1.4024805
2. NTNU Waterpower Lab. Francis-99 2nd workshop data (14–15 Dec 2016), files f99w2-exp-*;
www.ntnu.no/wiki/display/vkl/Second+workshop
3. Hand M.M. et al. (2001). Unsteady Aerodynamics Experiment Phase VI: Wind tunnel test configurations and available data campaigns. NREL/TP-500-29955.
4. Simms D., Schreck S., Hand M., Fingersh L.J. (2001). NREL Unsteady Aerodynamics Experiment in the NASA-Ames wind tunnel: a comparison of predictions to measurements. NREL/TP-500-29494.
5. Arts T., Lambert de Rouvroit M., Rutherford A.W. (1990). Aero-thermal investigation of a highly loaded transonic linear turbine guide vane cascade. VKI Technical Note 174.
6. AboutFlow (QMUL). Test Case 2: VKI LS89. www.aboutflow.sems.qmul.ac.uk/events/munich2016/benchmark/testcase2/
7. Reid L., Moore R.D. (1978). Design and overall performance of four highly loaded, high speed inlet stages for an advanced high-pressure-ratio core compressor. NASA TP-1337.
8. Suder K.L., Celestina M.L. (1996). Experimental and computational investigation of the tip clearance flow in a transonic axial compressor rotor. *J. Turbomach.* 118(2):218–229.
9. Denton J.D. (1997). Lessons from rotor 37. *J. Therm. Sci.* 6:1–13. doi:10.1007/s11630-997-0010-9
10. Dunham J. (ed.) (1998). CFD validation for propulsion system components. AGARD-AR-355.
11. Susan-Resiga R., Ciocan G.D., Anton I., Avellan F. (2006). Analysis of the swirling flow downstream a Francis turbine runner. *J. Fluids Eng.* 128:177–189.
12. Bosioc A.I., Susan-Resiga R., Muntean S., Tanasa C. (2012). Unsteady pressure analysis of a swirling flow with vortex rope and axial water injection in a discharge cone. *J. Fluids Eng.* 134(8):081104.
13. Petit O., Bosioc A.I., Nilsson H., Muntean S., Susan-Resiga R.F. (2011). Unsteady simulations of the flow in a swirl generator, using OpenFOAM. *Int. J. Fluid Mach. Syst.* 4(1):199–208.

14. Nilsson H. Rotating machinery training (SRF, MRF, moving mesh, coupling interfaces). 7th (2012) and 10th (2015) OpenFOAM Workshops.
15. Andersson U. (2000). Turbine 99 – experiments on draft tube flow (test case T). Proc. Turbine 99 Workshop, ISSN 1402-1536.
16. ERCOFTAC Knowledge Base Wiki. Application Challenge AC6-07: Draft tube (contributor R. Karlsson, Vattenfall Utveckling AB).
17. Nilsson H., Page M. (2005). OpenFOAM simulation of the flow in the Hölleforsen draft tube model. Turbine-99 III, Porjus, 8–9 Dec 2005.
18. Gallus H.E., Zeschky J., Hah C. (1995). Endwall and unsteady flow phenomena in an axial turbine stage. *J. Turbomach.* 117(4):562–570. doi:10.1115/1.2836568
19. SU2. Aachen turbine stage with mixing plane (tutorial). su2code.github.io/tutorials/Aachen_Turbine/
20. Oliani S. et al. (2022). A new solver for turbomachinery simulations in OpenFOAM: development and application to a 1.5 axial turbine stage. Conference paper, Univ. Ferrara.
21. Solemslie B.W., Dahlhaug O.G. (2012). A reference Pelton turbine design. *IOP Conf. Ser.: Earth Environ. Sci.* 15:032005.
22. Solemslie B.W., Dahlhaug O.G. (2014). A reference Pelton turbine – design and efficiency measurements. *IOP Conf. Ser.: Earth Environ. Sci.* 22:012004.
23. Petley S., Aggidis G.A. (2019). Estimating the energy loss in Pelton turbine casings by transient CFD and experimental analysis. *Int. J. Fluid Mach. Syst.* 12(4).
24. Rygg J.R. (2013). CFD analysis of a Pelton turbine in OpenFOAM. MSc thesis, NTNU.
25. de Servi C.M., Burigana M., Pini M., Colonna P. (2019). Design method and performance prediction for radial-inflow turbines of high-temperature mini-organic Rankine cycle power systems. *J. Eng. Gas Turbines Power* 141(9):091021.
26. Head A.J., De Servi C., Casati E., Pini M., Colonna P. (2016). Preliminary design of the ORCHID: a facility for studying non-ideal compressible fluid dynamics and testing ORC expanders. ASME Turbo Expo.
27. SVA Potsdam (2011). PPTC open water tests (report 3752); cavitation tests (report 3753); LDV velocity measurements (report 3754).

28. Gaggero S., Villa D. (2018). Cavitating propeller performance in inclined shaft conditions with OpenFOAM: PPTC 2015 test case. *J. Mar. Sci. Appl.* 17(1):1–20. doi:10.1007/s11804-018-0008-6
29. Wuibaut G., Bois G., Caignaert G., Dupont P., Stanislas M. (2001). Analysis of flow velocities within the impeller and the vaneless diffuser of a radial flow pump. *Proc. IMechE A* 215(6).
30. Godinho Patricio O. (1999). Experimental analysis of the mean and fluctuating pressures inside a single inter-blade passage of a centrifugal pump impeller. PhD thesis, Univ. Lille.
31. El Hajem M., Morel R., Spettel F., Bois G. (1998). Étude de l'écoulement moyen en sortie de roue d'une pompe centrifuge (roue SHF). *La Houille Blanche* 7.
32. Atif A., Benmansour S., Bois G. (2010). Numerical investigation of velocity flow field inside an impeller air model of a centrifugal pump with vaned diffuser interactions and comparison with PIV measurements. *Int. J. Rotating Mach.* 2010:706043; and Atif et al., CFM 2017, Lille (rig data table).
33. Reid L., Moore R.D. (1978). Stage 35 single-stage performance and blade-element data (companion to TP-1337). NASA TP-1338.
34. Ziegler K.U., Gallus H.E., Niehuis R. (2003). A study on impeller–diffuser interaction, Parts I and II. *J. Turbomach.* 125(1):173–182, 183–192.
35. RWTH Aachen IST. Open Testcases: Radiver. www.ist.rwth-aachen.de
36. Krain H. (1988). Swirling impeller flow. *J. Turbomach.* 110(1):122–128.
37. Eisenlohr G., Krain H., Richter F.-A., Tiede V. (2002). Investigations of the flow through a high pressure ratio centrifugal impeller. ASME GT2002-30394.
38. Braunscheidel E.P., Welch G.E., Skoch G.J., Medic G., Sharma O.P. (2014). Aerodynamic performance of a compact, high work-factor centrifugal compressor at the stage and subcomponent level. NTRS 20140016535.
39. Harrison et al. (2024). User's guide for the NASA High Efficiency Centrifugal Compressor data archive. NASA/TM-20240003692/REV1, NTRS 20250000831.

- 40. Hughes C.E., Jeracki R.J., Woodward R.P., Miller C.J. (2005). Fan Noise Source Diagnostic Test – rotor alone aerodynamic performance results. NASA/TM-2005-211681.
- 41. Schepers J.G., Snel H. (2007). Model experiments in controlled conditions (MEXICO), final report. ECN-E-07-042.
- 42. Schepers J.G., Boorsma K., Munduate X. (2014). Final results from Mexnext-I. *J. Phys. Conf. Ser.* 555:012089.
- 43. Raghunathan S. (1995). The Wells air turbine for wave energy conversion. *Prog. Aerosp. Sci.* 31(4):335–386.
- 44. Shehata A.S., Xiao Q., Saqr K.M., Alexander D. (2017). Wells turbine for wave energy conversion: a review. *Int. J. Energy Res.* 41:6–38. doi:10.1002/er.3583
- 45. A dynamic analysis of oscillating water column systems: design of a 16 kW Wells turbine for coastal energy generation in Ecuador (2025). *Processes* 13:2349. doi:10.3390/pr13082349