src/pages/ProfilePage.jsx JSX

```jsx
import { useState, useEffect } from 'react';
import { useUser } from '../contexts/UserContext';
import { useAddresses } from '../contexts/AddressContext';
import { motion } from 'framer-motion';
import Toast from '../components/Toast';
import { detectUserLocation } from '../utils/locationUtils';

export default function ProfilePage() {
  const { user, profile, updateProfile, fetchProfile, getActiveTime } = useUser();
  const { addresses, createAddress, updateAddress, deleteAddress } = useAddresses();
  const [activeTab, setActiveTab] = useState('profile');
  const [isEditing, setIsEditing] = useState(false);
  const [isAddingAddress, setIsAddingAddress] = useState(false);
  const [formData, setFormData] = useState({});
  const [addressForm, setAddressForm] = useState({
    recievers_name: '',
    recievers_phone: '',
    address_type: 'Home',
    address_line: '',
    city: '',
    state: '',
    pincode: '',
    is_default: false
  });
  const [loading, setLoading] = useState(true);
  const [detectingLocation, setDetectingLocation] = useState(false);
  const [activeTime, setActiveTime] = useState(null);
  const [toast, setToast] = useState({ message: '', type: 'info' });

  const tabs = [
    { id: 'profile', label: 'PROFILE', icon: '👤' },
    { id: 'addresses', label: 'ADDRESSES', icon: '📍' },
    { id: 'orders', label: 'ORDERS', icon: '📦' }
  ];

  useEffect(() => {
    const loadProfileData = async () => {
      if (user) {
        try {
          if (!profile) {
            await fetchProfile();
          }
          const timeData = await getActiveTime();
          setActiveTime(timeData.active_time);
        } catch (error) {
          console.log('Profile or active time not available');
        }
      }
      setLoading(false);
    };

    loadProfileData();
  }, [user, profile, fetchProfile, getActiveTime]);

  useEffect(() => {
    if (profile) {
      setFormData({
        name: profile.name || '',
        address: profile.address || '',
        phone: profile.phone || ''
      });
    }
  }, [profile]);

  const handleInputChange = (e) => {
    const { name, value } = e.target;
    setFormData(prev => ({ ...prev, [name]: value }));
  };

  const handleAddressInputChange = (e) => {
    const { name, value, type, checked } = e.target;
    setAddressForm(prev => ({
      ...prev,
      [name]: type === 'checkbox' ? checked : value
    }));
  };

  const handleProfileUpdate = async (e) => {
    e.preventDefault();

    try {
      await updateProfile(formData);
      setToast({ message: 'PROFILE UPDATED SUCCESSFULLY!', type: 'success' });
      setIsEditing(false);
    } catch (error) {
      setToast({ message: 'FAILED TO UPDATE PROFILE. PLEASE TRY AGAIN.', type: 'error' });
    }
  };

```

```
    const handleDetectLocation = async () => {
      setDetectingLocation(true);
      try {
        const locationData = await detectUserLocation();
        setAddressForm(prev => ({
          ...prev,
          address_line: locationData.address_line,
          city: locationData.city,
          state: locationData.state,
          pincode: locationData.pincode
        }));
        setToast({ message: 'LOCATION DETECTED SUCCESSFULLY!', type: 'success' });
      } catch (error) {
        setToast({ message: 'FAILED TO DETECT LOCATION. PLEASE ENTER MANUALLY.', type: 'error' });
      } finally {
        setDetectingLocation(false);
      }
    };

    const handleAddAddress = async (e) => {
      e.preventDefault();
      try {
        await createAddress(addressForm);
        setToast({ message: 'ADDRESS ADDED SUCCESSFULLY!', type: 'success' });
        setIsAddingAddress(false);
        setAddressForm({
          recievers_name: '',
          recievers_phone: '',
          address_type: 'Home',
          address_line: '',
          city: '',
          state: '',
          pincode: '',
          is_default: false
        });
      } catch (error) {
        setToast({ message: 'FAILED TO ADD ADDRESS. PLEASE TRY AGAIN.', type: 'error' });
      }
    };

    const handleDeleteAddress = async (addressId) => {
      if (window.confirm('ARE YOU SURE YOU WANT TO DELETE THIS ADDRESS?')) {
        try {
          await deleteAddress(addressId);
          setToast({ message: 'ADDRESS DELETED SUCCESSFULLY!', type: 'success' });
        } catch (error) {
          setToast({ message: 'FAILED TO DELETE ADDRESS.', type: 'error' });
        }
      }
    };

    if (loading) {
      return (
        <div className="min-h-screen bg-[#FFFDF5] p-4">
          <div className="max-w-7xl mx-auto">
            <div className="text-center py-20">
              <div className="w-16 h-16 border-4 border-black bg-white mx-auto mb-4 animate-spin"></div>
              <p className="font-black uppercase tracking-widest text-sm">LOADING PROFILE...</p>
            </div>
          </div>
        </div>
      );
    }

    // Generate profile image from user's name
    const profileImageUrl = `https://api.dicebear.com/7.x/initials/svg?seed=${profile?.name || user?.email || 'User'}`;

    return (
      <>
        <Toast message={toast.message} type={toast.type} />

        <motion.div
          initial={{ opacity: 0, y: 20 }}
          animate={{ opacity: 1, y: 0 }}
          className="min-h-screen bg-[#FFFDF5]"
        >
          {/* Background Pattern */}
          <div
            className="absolute inset-0 opacity-5"
            style={{
              backgroundImage: 'radial-gradient(#000 1.5px, transparent 1.5px)',
              backgroundSize: '20px 20px'
            }}
          ></div>

          <div className="relative z-10 max-w-7xl mx-auto p-4 sm:p-8">
            {/* Header */}
            <div className="text-center mb-8">
              <h1 className="text-3xl sm:text-5xl md:text-7xl font-black uppercase tracking-tight mb-4 -rotate-1">
                MY PROFILE
              </h1>
              <div className="bg-[#FFD93D] border-4 border-black shadow-[6px_6px_0px_0px_#000] p-4 rotate-1 inline-block">
                <p class="font-bold uppercase tracking-wide">MANAGE YOUR ACCOUNT SETTINGS</p>
              </div>
```

```
            </div>

            {/* Profile Header Card */}
            <div className="bg-black border-4 border-black shadow-[8px_8px_0px_0px_#000] mb-8 overflow-hidden">
              <div className="p-6 sm:p-8">
                <div className="flex flex-col sm:flex-row items-center sm:items-start gap-6">
                  <div className="relative">
                    <div className="w-24 h-24 sm:w-32 sm:h-32 border-4 border-white shadow-[4px_4px_0px_0px_#fff] overflow-hidden">
                      <img src={profileImageUrl} alt="Profile" className="w-full h-full object-cover" />
                    </div>
                    <button className="absolute -bottom-2 -right-2 bg-[#FFD93D] border-4 border-white w-10 h-10 flex items-center justify-center shadow-[2px_2px_0px_0px_#fff]">
                      <svg className="w-5 h-5 stroke-[3px]" fill="none" stroke="currentColor" viewBox="0 0 24 24">
                        <path strokeLinecap="round" strokeLinejoin="round" strokeWidth="3" d="M15.232 5.232l3.536 3.536m-2.036-5.036a2.5 2.5 0 113.536 3.536L6.5 21.036H3v-3.536L16.732 3.732z" />
                      </svg>
                    </button>
                  </div>

                  <div className="text-center sm:text-left text-white">
                    <h2 className="text-2xl sm:text-3xl font-black uppercase tracking-tight mb-2">
                      {profile?.name || 'NOT SET'}
                    </h2>
                    <p className="font-bold text-lg mb-2">{user?.email}</p>
                    {activeTime && (
                      <div className="bg-[#C4B5FD] border-2 border-white px-3 py-1 inline-block">
                        <p className="font-black uppercase tracking-widest text-xs text-black">
                          ACTIVE TIME: {activeTime.hours}H {activeTime.minutes}M
                        </p>
                      </div>
                    )}
                  </div>
                </div>
              </div>
            </div>

            {/* Tab Navigation */}
            <div className="bg-white border-4 border-black shadow-[8px_8px_0px_0px_#000] mb-8 overflow-hidden">
              <div className="flex overflow-x-auto">
                {tabs.map((tab) => (
                  <button
                    key={tab.id}
                    onClick={() => setActiveTab(tab.id)}
                    className={`flex-shrink-0 flex items-center gap-3 px-6 py-4 font-black uppercase tracking-widest text-sm border-r-4 border-black last:border-r-0 transition-colors duration-100 ${
                      activeTab === tab.id
                        ? 'bg-black text-white'
                        : 'hover:bg-[#FFD93D]'
                    }`}
                  >
                    <span className="text-lg">{tab.icon}</span>
                    {tab.label}
                  </button>
                ))}
              </div>
            </div>

            {/* Tab Content */}
            <div className="bg-white border-4 border-black shadow-[8px_8px_0px_0px_#000] overflow-hidden">
              {/* Profile Tab */}
              {activeTab === 'profile' && (
                <div>
                  <div className="bg-[#C4B5FD] border-b-4 border-black p-4 sm:p-6">
                    <h3 className="font-black uppercase tracking-widest text-sm">PROFILE INFORMATION</h3>
                  </div>

                  <div className="p-6 sm:p-8">
                    {!isEditing ? (
                      <div className="space-y-6">
                        <div className="grid grid-cols-1 sm:grid-cols-2 gap-6">
                          <div className="bg-[#FFFDF5] border-4 border-black p-4">
                            <label className="font-black uppercase tracking-widest text-xs mb-2 block">FULL NAME</label>
                            <p className="font-bold text-lg">{profile?.name || 'NOT SET'}</p>
                          </div>
                          <div className="bg-[#FFFDF5] border-4 border-black p-4">
                            <label className="font-black uppercase tracking-widest text-xs mb-2 block">EMAIL</label>
                            <p className="font-bold text-lg">{user?.email}</p>
                          </div>
                          <div className="bg-[#FFFDF5] border-4 border-black p-4">
                            <label className="font-black uppercase tracking-widest text-xs mb-2 block">PHONE</label>
                            <p className="font-bold text-lg">{profile?.phone || 'NOT SET'}</p>
                          </div>
                          <div className="bg-[#FFFDF5] border-4 border-black p-4">
                            <label className="font-black uppercase tracking-widest text-xs mb-2 block">ADDRESS</label>
                            <p className="font-bold text-lg">{profile?.address || 'NOT SET'}</p>
                          </div>
                        </div>

                        <button
                          onClick={() => setIsEditing(true)}
                          className="bg-[#FF6B6B] border-4 border-black font-black uppercase tracking-widest
                            text-sm px-6 py-4 h-14 w-full sm:w-auto
                            shadow-[6px_6px_0px_0px_#000]
                            hover:shadow-[3px_3px_0px_0px_#000] hover:translate-x-[3px] hover:translate-y-[3px]
```

```
                        active:shadow-none active:translate-x-[6px] active:translate-y-[6px]
                        transition-all duration-100"
                      >
                        EDIT PROFILE
                      </button>
                    </div>
                  ) : (
                    <form onSubmit={handleProfileUpdate} className="space-y-6">
                      <div className="grid grid-cols-1 sm:grid-cols-2 gap-6">
                        <div>
                          <label htmlFor="name" className="block font-black uppercase tracking-widest text-xs mb-2">FULL NAME</label>
                          <input
                            type="text"
                            name="name"
                            id="name"
                            value={formData.name || ''}
                            onChange={handleInputChange}
                            className="w-full border-4 border-black bg-white font-bold text-base h-14 px-4
                              focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                              focus-visible:outline-none focus-visible:ring-0
                              transition-all duration-100"
                          />
                        </div>
                        <div>
                          <label htmlFor="phone" className="block font-black uppercase tracking-widest text-xs mb-2">PHONE</label>
                          <input
                            type="text"
                            name="phone"
                            id="phone"
                            value={formData.phone || ''}
                            onChange={handleInputChange}
                            className="w-full border-4 border-black bg-white font-bold text-base h-14 px-4
                              focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                              focus-visible:outline-none focus-visible:ring-0
                              transition-all duration-100"
                          />
                        </div>
                      </div>
                      <div>
                        <label htmlFor="address" className="block font-black uppercase tracking-widest text-xs mb-2">ADDRESS</label>
                        <input
                          type="text"
                          name="address"
                          id="address"
                          value={formData.address || ''}
                          onChange={handleInputChange}
                          className="w-full border-4 border-black bg-white font-bold text-base h-14 px-4
                            focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                            focus-visible:outline-none focus-visible:ring-0
                            transition-all duration-100"
                        />
                      </div>
                      <div className="flex flex-col sm:flex-row gap-4">
                        <button
                          type="submit"
                          className="bg-[#FFD93D] border-4 border-black font-black uppercase tracking-widest
                            text-sm px-6 py-4 h-14 w-full sm:w-auto
                            shadow-[6px_6px_0px_0px_#000]
                            hover:shadow-[3px_3px_0px_0px_#000] hover:translate-x-[3px] hover:translate-y-[3px]
                            active:shadow-none active:translate-x-[6px] active:translate-y-[6px]
                            transition-all duration-100"
                        >
                          SAVE CHANGES
                        </button>
                        <button
                          type="button"
                          onClick={() => { setIsEditing(false); setFormData({...profile}); }}
                          className="bg-white border-4 border-black font-black uppercase tracking-widest
                            text-sm px-6 py-4 h-14 w-full sm:w-auto
                            shadow-[6px_6px_0px_0px_#000]
                            hover:bg-[#C4B5FD] hover:shadow-[3px_3px_0px_0px_#000] hover:translate-x-[3px] hover:translate-y-[3px]
                            active:shadow-none active:translate-x-[6px] active:translate-y-[6px]
                            transition-all duration-100"
                        >
                          CANCEL
                        </button>
                      </div>
                    </form>
                  )}
                </div>
              </div>
            )}

            {/* Addresses Tab */}
            {activeTab === 'addresses' && (
              <div>
                <div className="bg-[#FFD93D] border-b-4 border-black p-4 sm:p-6 flex flex-col sm:flex-row justify-between items-start sm:items-center gap-4">
                  <h3 className="font-black uppercase tracking-widest text-sm">MY ADDRESSES</h3>
                  <button
                    onClick={() => setIsAddingAddress(true)}
                    className="bg-black border-4 border-black font-black uppercase tracking-widest
                      text-xs px-4 py-3 h-12 w-full sm:w-auto text-white
                      shadow-[4px_4px_0px_0px_#000]
```

```
                hover:shadow-[2px_2px_0px_0px_#000] hover:translate-x-[2px] hover:translate-y-[2px]
                active:shadow-none active:translate-x-[4px] active:translate-y-[4px]
                transition-all duration-100"
            >
              ADD NEW ADDRESS
            </button>
          </div>

          <div className="p-6 sm:p-8">
            {/* Add Address Form */}
            {isAddingAddress && (
              <motion.div
                initial={{ opacity: 0, height: 0 }}
                animate={{ opacity: 1, height: 'auto' }}
                className="bg-[#C4B5FD] border-4 border-black shadow-[6px_6px_0px_0px_#000] p-6 mb-8 overflow-hidden"
              >
                <div className="bg-black border-b-4 border-black p-4 -m-6 mb-6">
                  <h4 className="font-black uppercase tracking-widest text-sm text-white">ADD NEW ADDRESS</h4>
                </div>

                <form onSubmit={handleAddAddress} className="space-y-4">
                  <div className="grid grid-cols-1 sm:grid-cols-2 gap-4">
                    <div>
                      <label className="block font-black uppercase tracking-widest text-xs mb-2">RECEIVER'S NAME *</label>
                      <input
                        type="text"
                        name="recievers_name"
                        value={addressForm.recievers_name}
                        onChange={handleAddressInputChange}
                        className="w-full border-4 border-black bg-white font-bold text-base h-12 px-4
                          focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                          focus-visible:outline-none focus-visible:ring-0
                          transition-all duration-100"
                        required
                      />
                    </div>
                    <div>
                      <label className="block font-black uppercase tracking-widest text-xs mb-2">PHONE NUMBER *</label>
                      <input
                        type="tel"
                        name="recievers_phone"
                        value={addressForm.recievers_phone}
                        onChange={handleAddressInputChange}
                        className="w-full border-4 border-black bg-white font-bold text-base h-12 px-4
                          focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                          focus-visible:outline-none focus-visible:ring-0
                          transition-all duration-100"
                        required
                      />
                    </div>
                  </div>

                  <div className="grid grid-cols-1 sm:grid-cols-3 gap-4">
                    <div>
                      <label className="block font-black uppercase tracking-widest text-xs mb-2">ADDRESS TYPE</label>
                      <select
                        name="address_type"
                        value={addressForm.address_type}
                        onChange={handleAddressInputChange}
                        className="w-full border-4 border-black bg-white font-bold text-base h-12 px-4
                          focus-visible:bg-[#FFD93D] focus-visible:outline-none transition-colors duration-100"
                      >
                        <option value="Home">HOME</option>
                        <option value="Office">OFFICE</option>
                        <option value="Other">OTHER</option>
                      </select>
                    </div>
                    <div>
                      <label className="block font-black uppercase tracking-widest text-xs mb-2">CITY *</label>
                      <input
                        type="text"
                        name="city"
                        value={addressForm.city}
                        onChange={handleAddressInputChange}
                        className="w-full border-4 border-black bg-white font-bold text-base h-12 px-4
                          focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                          focus-visible:outline-none focus-visible:ring-0
                          transition-all duration-100"
                        required
                      />
                    </div>
                    <div>
                      <label className="block font-black uppercase tracking-widest text-xs mb-2">PINCODE *</label>
                      <input
                        type="text"
                        name="pincode"
                        value={addressForm.pincode}
                        onChange={handleAddressInputChange}
                        className="w-full border-4 border-black bg-white font-bold text-base h-12 px-4
                          focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                          focus-visible:outline-none focus-visible:ring-0
                          transition-all duration-100"
                        required
                      />
```

```
                    </div>
                  </div>

                  <div>
                    <div className="flex justify-between items-center mb-2">
                      <label className="block font-black uppercase tracking-widest text-xs">ADDRESS LINE *</label>
                      <button
                        type="button"
                        onClick={handleDetectLocation}
                        disabled={detectingLocation}
                        className="bg-[#FF6B6B] border-4 border-black font-black uppercase tracking-widest
                          text-xs px-4 py-2 h-10 disabled:opacity-50 disabled:cursor-not-allowed
                          shadow-[4px_4px_0px_0px_#000]
                          hover:shadow-[2px_2px_0px_0px_#000] hover:translate-x-[2px] hover:translate-y-[2px]
                          active:shadow-none active:translate-x-[4px] active:translate-y-[4px]
                          transition-all duration-100"
                      >
                        {detectingLocation ? 'DETECTING...' : 'DETECT LOCATION'}
                      </button>
                    </div>
                    <input
                      type="text"
                      name="address_line"
                      value={addressForm.address_line}
                      onChange={handleAddressInputChange}
                      className="w-full border-4 border-black bg-white font-bold text-base h-12 px-4
                        focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                        focus-visible:outline-none focus-visible:ring-0
                        transition-all duration-100"
                      required
                    />
                  </div>

                  <div>
                    <input
                      type="text"
                      name="state"
                      value={addressForm.state}
                      onChange={handleAddressInputChange}
                      placeholder="STATE"
                      className="w-full border-4 border-black bg-white font-bold text-base h-12 px-4
                        placeholder:text-black/40 placeholder:font-bold placeholder:uppercase
                        focus-visible:bg-[#FFD93D] focus-visible:shadow-[4px_4px_0px_0px_#000]
                        focus-visible:outline-none focus-visible:ring-0
                        transition-all duration-100"
                      required
                    />
                  </div>

                  <div className="flex items-center gap-3">
                    <div className="relative">
                      <input
                        type="checkbox"
                        name="is_default"
                        checked={addressForm.is_default}
                        onChange={handleAddressInputChange}
                        className="sr-only"
                      />
                      <div className={`w-6 h-6 border-4 border-black ${
                        addressForm.is_default ? 'bg-[#FF6B6B]' : 'bg-white'
                      } transition-colors duration-100 cursor-pointer`}
                        onClick={() => setAddressForm(prev => ({ ...prev, is_default: !prev.is_default }))}
                      >
                        {addressForm.is_default && (
                          <svg className="w-4 h-4 text-white stroke-[3px] absolute inset-0" fill="none" stroke="currentColor" viewBox="0 0 24 24">
                            <path strokeLinecap="round" strokeLinejoin="round" strokeWidth="3" d="M5 13l4 4L19 7" />
                          </svg>
                        )}
                      </div>
                    </div>
                    <label className="font-bold uppercase tracking-wide text-sm cursor-pointer"
                      onClick={() => setAddressForm(prev => ({ ...prev, is_default: !prev.is_default }))}
                    >
                      SET AS DEFAULT ADDRESS
                    </label>
                  </div>

                  <div className="flex flex-col sm:flex-row gap-4 pt-4">
                    <button
                      type="submit"
                      className="bg-[#FFD93D] border-4 border-black font-black uppercase tracking-widest
                        text-sm px-6 py-4 h-14 w-full sm:w-auto
                        shadow-[6px_6px_0px_0px_#000]
                        hover:shadow-[3px_3px_0px_0px_#000] hover:translate-x-[3px] hover:translate-y-[3px]
                        active:shadow-none active:translate-x-[6px] active:translate-y-[6px]
                        transition-all duration-100"
                    >
                      SAVE ADDRESS
                    </button>
                    <button
                      type="button"
                      onClick={() => setIsAddingAddress(false)}
                      className="bg-white border-4 border-black font-black uppercase tracking-widest
```

```
                                text-sm px-6 py-4 h-14 w-full sm:w-auto
                                shadow-[6px_6px_0px_0px_#000]
                                hover:bg-[#C4B5FD] hover:shadow-[3px_3px_0px_0px_#000] hover:translate-x-[3px] hover:translate-y-[3px]
                                active:shadow-none active:translate-x-[6px] active:translate-y-[6px]
                                transition-all duration-100"
                            >
                              CANCEL
                            </button>
                          </div>
                        </form>
                      </motion.div>
                    )}

                    {/* Address List */}
                    <div className="grid grid-cols-1 md:grid-cols-2 gap-6">
                      {addresses.map(address => (
                        <div key={address.id} className="bg-white border-4 border-black shadow-[6px_6px_0px_0px_#000] overflow-hidden relative">
                          {address.is_default && (
                            <div className="absolute -top-3 -right-3 bg-[#FFD93D] border-4 border-black font-black uppercase tracking-widest text-xs px-3 py-1 shadow-[4px_4px_0px_0px_#000] rotate-12 z-10">
                              DEFAULT
                            </div>
                          )}

                          <div className="bg-[#C4B5FD] border-b-4 border-black p-4">
                            <div className="flex items-center justify-between">
                              <span className="bg-black border-2 border-black text-white font-black uppercase tracking-widest text-xs px-3 py-1">
                                {address.address_type}
                              </span>
                            </div>
                          </div>

                          <div className="p-4">
                            <h4 className="font-black text-lg uppercase tracking-tight mb-2">{address.recievers_name}</h4>
                            <p className="font-bold mb-1">{address.address_line}</p>
                            <p className="font-bold mb-1">{address.city}, {address.state} - {address.pincode}</p>
                            <div className="bg-[#FFFDF5] border-2 border-black px-3 py-1 inline-block mb-4">
                              <p className="font-bold text-sm">PHONE: {address.recievers_phone}</p>
                            </div>

                            <div className="flex gap-2">
                              <button
                                onClick={() => handleDeleteAddress(address.id)}
                                className="bg-[#FF6B6B] border-4 border-black font-black uppercase tracking-widest
                                  text-xs px-4 py-2 h-10 flex-1
                                  shadow-[4px_4px_0px_0px_#000]
                                  hover:shadow-[2px_2px_0px_0px_#000] hover:translate-x-[2px] hover:translate-y-[2px]
                                  active:shadow-none active:translate-x-[4px] active:translate-y-[4px]
                                  transition-all duration-100"
                              >
                                DELETE
                              </button>
                            </div>
                          </div>
                        </div>
                      )}
                    </div>

                    {addresses.length === 0 && !isAddingAddress && (
                      <div className="text-center py-16">
                        <div className="bg-[#C4B5FD] border-4 border-black shadow-[8px_8px_0px_0px_#000] p-8 inline-block -rotate-1">
                          <div className="w-16 h-16 bg-white border-4 border-black mx-auto mb-4 flex items-center justify-center">
                            <svg className="w-8 h-8 stroke-[4px]" fill="none" stroke="currentColor" viewBox="0 0 24 24">
                              <path strokeLinecap="round" strokeLinejoin="round" strokeWidth="4" d="M17.657 16.657L13.414 20.9a1.998 1.998 0 01-2.827 0l-4.244-4.243a8 8 0 1111.314 0z" />
                              <path strokeLinecap="round" strokeLinejoin="round" strokeWidth="4" d="M15 11a3 3 0 11-6 0 3 3 0 016 0z" />
                            </svg>
                          </div>
                          <p className="font-black uppercase tracking-tight text-lg mb-4">NO ADDRESSES ADDED YET</p>
                          <button
                            onClick={() => setIsAddingAddress(true)}
                            className="bg-[#FF6B6B] border-4 border-black font-black uppercase tracking-widest
                              text-sm px-6 py-4 h-14
                              shadow-[6px_6px_0px_0px_#000]
                              hover:shadow-[3px_3px_0px_0px_#000] hover:translate-x-[3px] hover:translate-y-[3px]
                              active:shadow-none active:translate-x-[6px] active:translate-y-[6px]
                              transition-all duration-100"
                          >
                            ADD YOUR FIRST ADDRESS
                          </button>
                        </div>
                      </div>
                    )}
                  </div>
                </div>
              )}

              {/* Orders Tab */}
              {activeTab === 'orders' && (
                <div>
                  <div className="bg-[#FF6B6B] border-b-4 border-black p-4 sm:p-6">
                    <h3 className="font-black uppercase tracking-widest text-sm text-white">MY ORDERS</h3>
                  </div>

```

```
                  <div className="p-6 sm:p-8 text-center">
                    <div className="bg-[#FFD93D] border-4 border-black shadow-[8px_8px_0px_0px_#000] p-8 inline-block rotate-1">
                      <div className="w-16 h-16 bg-black border-4 border-black mx-auto mb-4 flex items-center justify-center">
                        <svg className="w-8 h-8 stroke-[4px] text-white" fill="none" stroke="currentColor" viewBox="0 0 24 24">
                          <path strokeLinecap="round" strokeLinejoin="round" strokeWidth="4" d="M16 11V7a4 4 0 00-8 0v4M5 9h14l1 12H4L5 9z" />
                        </svg>
                      </div>
                      <p className="font-black uppercase tracking-tight text-lg mb-4">VIEW YOUR ORDER HISTORY</p>
                      <a
                        href="/orders"
                        className="bg-black border-4 border-black font-black uppercase tracking-widest
                          text-sm px-6 py-4 h-14 inline-block text-white
                          shadow-[6px_6px_0px_0px_#000]
                          hover:shadow-[3px_3px_0px_0px_#000] hover:translate-x-[3px] hover:translate-y-[3px]
                          active:shadow-none active:translate-x-[6px] active:translate-y-[6px]
                          transition-all duration-100"
                      >
                        GO TO ORDERS
                      </a>
                    </div>
                  </div>
                </div>
              )}
            </div>
          </div>
        </motion.div>
      </>
    );
  }
```