

Full Stack Development Summary

- ✓ **IF conditions**
- ✓ **IF-ELSE conditions**
- ✓ **ELSE-IF Ladder conditions**
- ✓ **SWITCH-CASE statements**
- ✓ **“FOR” Loop**
- ✓ **“WHILE” Loop**
- ✓ **“DO-WHILE” Loop**
- ✓ **ENHANCED “FOR” Loop**

IF CONDITIONS

The if statement is used to execute a block of code only when a condition is true.

SYNTAX

```
If (condition) {  
    // code to be executed.  
}
```

IF ELSE CONDITION

- The if-else statement is used to execute one block of code .
- If the condition is true and another block if the condition is false.

SYNTAX

```
If (condition) {  
    //code if condition is true  
} else {  
    // code if condition is false  
}
```

ELSE IF LADDER CONDITIONS

- The else – if ladder is used when there are multiple conditions to check.
- The program executes the block of the first condition that is true.

SYNTAX

```
If(condition1) {  
    //code  
}  
else if { condition2){  
    // code  
}  
else if { condition3) {  
    // code  
}  
  
Else {  
    // code  
}
```

SWITCH CASE STATEMENT

- A switch – case statement is a control structure used to execute one block of code .
- The multiple options based on the value of an expression.

SYNTAX

```
switch (expression) {  
    case value1:  
        // Code block  
        break;  
    case value2:  
        // Code block  
        break;  
    case value3:  
        // Code block  
        break;  
    default:  
        // Default code block  
}  

```

FOR LOOP

A for loop is used to execute a block of code repeatedly for a specific number of times.

SYNTAX

```
For(initialization; condition;( increament / decreament) {  

```

WHILE LOOP

A while loop is used to execute a block of code repeatedly as long as a specific condition is true.

SYNTAX

```
While (condition) {  
    // code to be executed  
}
```

DO WHILE LOOP

A do while loop executes the code block at least once, then checks the condition.

SYNTAX

```
do {  
    }while (condition);
```

ENHANCED “FOR “LOOP

The enhanced for loop is used to iterate through arrays or

collections without using an index.

SYNTAX

For (data type variable: collections) {

// code to execute

}