


# Network Science

2019. november 18.



**THE HIDDEN VARIABLE MODEL**

# The hidden variable model

## Network models

### Hidden variable model

- How to generate a random graph with degree correlations?

→ With the hidden variable model!

# The hidden variable model

## Network models

### Hidden variable model

#### Definition of the hidden variable model

- We define a distribution  $\rho(h)$  for the hidden variables, and a joint distribution  $r(h, h')$  for the linking probabilities.

# The hidden variable model

## Network models

### Hidden variable model

#### Definition of the hidden variable model

- We define a distribution  $\rho(h)$  for the hidden variables, and a joint distribution  $r(h, h')$  for the linking probabilities.
- We take  $N$  nodes, and for each we draw its hidden variable from  $\rho(h)$ .

# The hidden variable model

## Network models

### Hidden variable model

#### Definition of the hidden variable model

- We define a distribution  $\rho(h)$  for the hidden variables, and a joint distribution  $r(h, h')$  for the linking probabilities.
- We take  $N$  nodes, and for each we draw its hidden variable from  $\rho(h)$ .
- Every node pair  $i$  and  $j$  are connected with a probability

$$P(i - j) = r(h_i, h_j).$$

# The hidden variable model

Network models

Hidden variable  
model

- Let  $P(k | h)$  denote the conditional probability that a node has degree  $k$  given its hidden variable is  $h$ .

# The hidden variable model

Network models

Hidden variable  
model

- Let  $P(k | h)$  denote the conditional probability that a node has degree  $k$  given its hidden variable is  $h$ .
- Based on that the degree distribution can be written as

$$p(k) = \sum_h P(k | h) \rho(h)$$



# The hidden variable model

## Network models

### Hidden variable model

- Let  $P(k | h)$  denote the conditional probability that a node has degree  $k$  given its hidden variable is  $h$ .
- Based on that the degree distribution can be written as

$$p(k) = \sum_h P(k | h) \rho(h)$$

- Normalisation:

$$\sum_k P(k | h) = 1$$

for all  $h$ .

# The hidden variable model

Network models

Hidden variable  
model

- Let  $P(k | h)$  denote the conditional probability that a node has degree  $k$  given its hidden variable is  $h$ .
- Based on that the degree distribution can be written as

$$p(k) = \sum_h P(k | h) \rho(h)$$

- Normalisation:

$$\sum_k P(k | h) = 1$$

for all  $h$ .

- The average degree of nodes with a given  $h$  can be written as

$$\overline{k(h)} = \sum_k k P(k | h)$$

# The hidden variable model

## Network models

### Hidden variable model

- Let  $P(k | h)$  denote the conditional probability that a node has degree  $k$  given its hidden variable is  $h$ .
- Based on that the degree distribution can be written as

$$p(k) = \sum_h P(k | h) \rho(h)$$

- Normalisation:

$$\sum_k P(k | h) = 1$$

for all  $h$ .

- The average degree of nodes with a given  $h$  can be written as

$$\overline{k(h)} = \sum_k k P(k | h)$$

and the overall average degree as

$$\langle k \rangle = \sum_k k p(k) = \sum_k k \sum_h P(k | h) \rho(h) = \sum_h \overline{k(h)} \rho(h).$$

# The hidden variable model

Network models

Hidden variable  
model

- Let us unfold  $P(k | h)$  as

$$P(k | h) = \sum_{k_1, \dots, k_c} P_1^{(h)}(k_1, h_1) P_2^{(h)}(k_2, h_2) \dots P_c^{(h)}(k_c, h_c) \delta_{k_1 + k_2 + \dots + k_c, k},$$

where  $P_i^{(h)}(k_i, h_i)$  denotes the probability that a node with hidden variable  $h$  is connected altogether with  $k_i$  links to other nodes with hidden variable  $h_i$ , and  $h_c$  is the maximal value of  $h$ .

# The hidden variable model

## Network models

### Hidden variable model

- Let us unfold  $P(k | h)$  as

$$P(k | h) = \sum_{k_1, \dots, k_c} P_1^{(h)}(k_1, h_1) P_2^{(h)}(k_2, h_2) \dots P_c^{(h)}(k_c, h_c) \delta_{k_1 + k_2 + \dots + k_c, k},$$

where  $P_i^{(h)}(k_i, h_i)$  denotes the probability that a node with hidden variable  $h$  is connected altogether with  $k_i$  links to other nodes with hidden variable  $h_i$ , and  $h_c$  is the maximal value of  $h$ .

- Since links are introduced independent of each other,

$$P_i^{(h)}(k_i, h_i) = \binom{N_i}{k_i} r(h_i, h)^{k_i} [1 - r(h_i, h)]^{N_i - k_i},$$

where  $N_i = N\rho(h_i)$  is the number of nodes with hidden variable  $h_i$ .

# The hidden variable model

## Network models

### Hidden variable model

- Let us unfold  $P(k | h)$  as

$$P(k | h) = \sum_{k_1, \dots, k_c} P_1^{(h)}(k_1, h_1) P_2^{(h)}(k_2, h_2) \dots P_c^{(h)}(k_c, h_c) \delta_{k_1 + k_2 + \dots + k_c, k},$$

where  $P_i^{(h)}(k_i, h_i)$  denotes the probability that a node with hidden variable  $h$  is connected altogether with  $k_i$  links to other nodes with hidden variable  $h_i$ , and  $h_c$  is the maximal value of  $h$ .

- Since links are introduced independent of each other,

$$P_i^{(h)}(k_i, h_i) = \binom{N_i}{k_i} r(h_i, h)^{k_i} [1 - r(h_i, h)]^{N_i - k_i},$$

where  $N_i = N\rho(h_i)$  is the number of nodes with hidden variable  $h_i$ .

- The **generating function** of this binomial distribution is

$$G_i^{(h)}(z) = \sum_{k_i} \binom{N_i}{k_i} r(h_i, h)^{k_i} [1 - r(h_i, h)]^{N_i - k_i} z^{k_i} = [1 - (1 - z)r(h_i, h)]^{N_i}.$$

# The hidden variable model

Network models

Hidden variable  
model

- Since  $k = k_1 + k_2 + \cdots + k_c$  and  $P(k | h)$  is given by the convolution of the  $P_i^{(h)}(k_i, h_i)$  distributions, the generating function of  $P(k | h)$ , denoted by  $G(z)$  is simply

$$G(z) = \prod_i G_i^{(h)}(z) = \prod_i [1 - (1 - z)r(h_i, h)]^{N_i}.$$

# The hidden variable model

Network models

Hidden variable  
model

- Since  $k = k_1 + k_2 + \dots + k_c$  and  $P(k | h)$  is given by the convolution of the  $P_i^{(h)}(k_i, h_i)$  distributions, the generating function of  $P(k | h)$ , denoted by  $G(z)$  is simply

$$G(z) = \prod_i G_i^{(h)}(z) = \prod_i [1 - (1 - z)r(h_i, h)]^{N_i}.$$

- If we take the logarithm of the generating function, we get

$$\begin{aligned} \ln G(z) &= \sum_i N_i \ln [1 - (1 - z)r(h_i, h)] = \\ &N \sum_{h'} \rho(h') \ln [1 - (1 - z)r(h', h)]. \end{aligned}$$



# The hidden variable model

## Network models

### Hidden variable model

- Since  $k = k_1 + k_2 + \dots + k_c$  and  $P(k | h)$  is given by the convolution of the  $P_i^{(h)}(k_i, h_i)$  distributions, the generating function of  $P(k | h)$ , denoted by  $G(z)$  is simply

$$G(z) = \prod_i G_i^{(h)}(z) = \prod_i [1 - (1 - z)r(h_i, h)]^{N_i}.$$

- If we take the logarithm of the generating function, we get

$$\begin{aligned} \ln G(z) &= \sum_i N_i \ln [1 - (1 - z)r(h_i, h)] = \\ &N \sum_{h'} \rho(h') \ln [1 - (1 - z)r(h', h)]. \end{aligned}$$

- The average degree of a node with hidden variable  $h$  is given by  $G'(z)|_{z=1}$ .

# The hidden variable model

## Network models

### Hidden variable model

- Since  $k = k_1 + k_2 + \dots + k_c$  and  $P(k | h)$  is given by the convolution of the  $P_i^{(h)}(k_i, h_i)$  distributions, the generating function of  $P(k | h)$ , denoted by  $G(z)$  is simply

$$G(z) = \prod_i G_i^{(h)}(z) = \prod_i [1 - (1 - z)r(h_i, h)]^{N_i}.$$

- If we take the logarithm of the generating function, we get

$$\begin{aligned} \ln G(z) &= \sum_i N_i \ln [1 - (1 - z)r(h_i, h)] = \\ &N \sum_{h'} \rho(h') \ln [1 - (1 - z)r(h', h)]. \end{aligned}$$

- The average degree of a node with hidden variable  $h$  is given by  $G'(z)|_{z=1}$ . However, since  $G(1) = 1$ , this is also equal to

$$\begin{aligned} \overline{k(h)} &= G'(z)|_{z=1} = [\ln G(z)]'|_{z=1} = N \sum_{h'} \frac{\rho(h')r(h', h)}{1 - (1 - z)r(h', h)} \Big|_{z=1} = \\ &N \sum_{h'} \rho(h')r(h', h). \end{aligned}$$

# The hidden variable model

Network models

Hidden variable  
model

- Let us assume that we want to generate **sparse** networks, where  $\overline{k(h)}$  **is independent of  $N$** .

# The hidden variable model

Network models

Hidden variable  
model

- Let us assume that we want to generate **sparse** networks, where  $\overline{k(h)}$  is independent of  $N$ .
- If  $\rho(h)$  is size independent as well (which is a quite natural assumption), then  $r(h', h)$  must behave as

$$r(h', h) = \frac{C(h', h)}{N},$$

where  $C(h', h)$  is a size independent "nice" function.

# The hidden variable model

## Network models

## Hidden variable model

- Let us assume that we want to generate **sparse** networks, where  $\overline{k(h)}$  is independent of  $N$ .
- If  $\rho(h)$  is size independent as well (which is a quite natural assumption), then  $r(h', h)$  must behave as

$$r(h', h) = \frac{C(h', h)}{N},$$

where  $C(h', h)$  is a size independent "nice" function.

- Based on that, the logarithm of the generating function can be written as

$$\begin{aligned}\ln G(z) &= N \sum_{h'} \rho(h') \ln \left[ 1 - (1 - z) r(h', h) \right] = \\ &= N \sum_{h'} \rho(h') \ln \left[ 1 - (1 - z) \frac{C(h', h)}{N} \right] \simeq \\ &= N \sum_{h'} \rho(h') \left[ (z - 1) \frac{C(h', h)}{N} \right],\end{aligned}$$

# The hidden variable model

Network models

Hidden variable  
model

- Let us assume that we want to generate **sparse** networks, where  $\overline{k(h)}$  is **independent of  $N$** .
- If  $\rho(h)$  is size independent as well (which is a quite natural assumption), then  $r(h', h)$  must behave as

$$r(h', h) = \frac{C(h', h)}{N},$$

where  $C(h', h)$  is a size independent "nice" function.

- Based on that, the logarithm of the generating function can be written as

$$\begin{aligned}\ln G(z) &= N \sum_{h'} \rho(h') \ln \left[ 1 - (1-z)r(h', h) \right] = \\ &= N \sum_{h'} \rho(h') \ln \left[ 1 - (1-z) \frac{C(h', h)}{N} \right] \simeq \\ &= N \sum_{h'} \rho(h') \left[ (z-1) \frac{C(h', h)}{N} \right],\end{aligned}$$

yielding for the generating function itself

$$G(z) \simeq \exp \left[ (z-1) \sum_{h'} \rho(h') C(h', h) \right] = \exp \left[ (z-1) \overline{k(h)} \right].$$

# The hidden variable model

## Network models

### Hidden variable model

- The probability mass function corresponding to an exponential generating function is the Poisson distribution, thus,

$$P(k \mid h) = \frac{\overline{k(h)}^k e^{-\overline{k(h)}}}{k!},$$
$$\overline{k(h)} = N \sum_{h'} \rho(h') r(h', h) = \sum_{h'} \rho(h') C(h', h).$$

# The hidden variable model

Network models

Hidden variable  
model

- What about the **degree correlations**?



# The hidden variable model

Network models

Hidden variable  
model

- What about the **degree correlations**?
- Let's start with defining  $P(h' | h)$  as the conditional probability that a link is connecting to a node with hidden variable  $h'$ , given that the node at the other end has  $h$ .

# The hidden variable model

Network models

Hidden variable  
model

- What about the **degree correlations**?
- Let's start with defining  $P(h' | h)$  as the conditional probability that a link is connecting to a node with hidden variable  $h'$ , given that the node at the other end has  $h$ .
- Since the number of such links is proportional to both the number of nodes with  $h'$  and the connection probability  $r(h', h)$ , we can write

$$P(h' | h) = \frac{\rho(h')r(h', h)}{\sum_{h''} \rho(h'')r(h'', h)} = \frac{N\rho(h')r(h', h)}{\overline{k(h)}}.$$

# The hidden variable model

Network models

Hidden variable  
model

- What about the **degree correlations**?
- Let's start with defining  $P(h' | h)$  as the conditional probability that a link is connecting to a node with hidden variable  $h'$ , given that the node at the other end has  $h$ .
- Since the number of such links is proportional to both the number of nodes with  $h'$  and the connection probability  $r(h', h)$ , we can write

$$P(h' | h) = \frac{\rho(h')r(h', h)}{\sum_{h''} \rho(h'')r(h'', h)} = \frac{N\rho(h')r(h', h)}{k(h)}.$$

- Based on  $P(h' | h)$  we can write the conditional probability  $P(k' | k)$  that a link connects to a node with degree  $k$ , given that it started on a node with degree  $k$  as

$$P(k' | k) = \sum_{h', h} P(k' | h')P(h' | h)P(h | k),$$

where the last factor  $P(h | k)$  can be given according to Bayes theorem as

$$P(h | k) = \frac{P(k | h)\rho(h)}{\sum_k P(k | h)\rho(h)} = \frac{P(k | h)\rho(h)}{p(k)}.$$

# The hidden variable model

Network models

Hidden variable  
model

- By substituting back we obtain

$$P(k' | k) = \frac{1}{p(k)} \sum_{h', h} P(k' | h') P(h' | h) P(k | h) \rho(h).$$

# The hidden variable model

Network models

Hidden variable  
model

- By substituting back we obtain

$$P(k' | k) = \frac{1}{p(k)} \sum_{h', h} P(k' | h') P(h' | h) P(k | h) \rho(h).$$

- Thus, the ANND can be written as

$$\begin{aligned} k_{\text{nn}}(k) &= \sum_{k'} k' P(k' | k) = \frac{1}{p(k)} \sum_{k', h', h} \underbrace{k' P(k' | h')}_{\overline{k'(h')}} P(h' | h) P(k | h) \rho(h) \\ &= \frac{1}{p(k)} \sum_{h', h} \underbrace{\overline{k'(h')} P(h' | h)}_{k_{\text{nn}}(h)} P(k | h) \rho(h), \end{aligned}$$

where we introduced

$$k_{\text{nn}}(h) = \sum_{h'} \overline{k'(h')} P(h' | h)$$

as the average nearest neighbours degree of nodes with parameter  $h$ .

# The hidden variable model

## Network models

### Hidden variable model

- By substituting back we obtain

$$P(k' | k) = \frac{1}{p(k)} \sum_{h', h} P(k' | h') P(h' | h) P(k | h) \rho(h).$$

- Thus, the ANND can be written as

$$\begin{aligned} k_{\text{nn}}(k) &= \sum_{k'} k' P(k' | k) = \frac{1}{p(k)} \sum_{k', h', h} \underbrace{k' P(k' | h')}_{\overline{k'(h')}} P(h' | h) P(k | h) \rho(h) \\ &= \frac{1}{p(k)} \sum_{h', h} \underbrace{\overline{k'(h')} P(h' | h)}_{k_{\text{nn}}(h)} P(k | h) \rho(h), \end{aligned}$$

where we introduced

$$k_{\text{nn}}(h) = \sum_{h'} \overline{k'(h')} P(h' | h)$$

as the average nearest neighbours degree of nodes with parameter  $h$ . Thus, the ANND can be formulated as

$$k_{\text{nn}}(k) = \frac{1}{p(k)} \sum_h k_{\text{nn}}(h) P(k | h) \rho(h).$$

# The hidden variable model

Network models

Hidden variable  
model

- OK, but how to generate a random graph with prescribed degree correlations?

# The hidden variable model

Network models

Hidden variable  
model

- OK, but how to generate a random graph with prescribed degree correlations?
- We can use the method of **hidden degrees**.



# The hidden variable model

Network models

Hidden variable  
model

- OK, but how to generate a random graph with prescribed degree correlations?
- We can use the method of **hidden degrees**.
- Let us go back to the complete statistical description of degree correlations:

# The hidden variable model

Network models

Hidden variable  
model

- OK, but how to generate a random graph with prescribed degree correlations?
- We can use the method of **hidden degrees**.
- Let us go back to the complete statistical description of degree correlations:
  - The matrix  $E_{k',k}$  gives the number of connections between nodes of degree  $k$  and  $k'$ ,

# The hidden variable model

## Network models

### Hidden variable model

- OK, but how to generate a random graph with prescribed degree correlations?
- We can use the method of **hidden degrees**.
- Let us go back to the complete statistical description of degree correlations:
  - The matrix  $E_{k',k}$  gives the number of connections between nodes of degree  $k$  and  $k'$ ,
  - The matrix  $e_{k',k} = E_{k',k}/2M$  gives the probability for finding a link between nodes of degree  $k$  and  $k'$ , and can be treated as a **joint probability mass function** between  $k$  and  $k'$ .

# The hidden variable model

## Network models

### Hidden variable model

- OK, but how to generate a random graph with prescribed degree correlations?
- We can use the method of **hidden degrees**.
- Let us go back to the complete statistical description of degree correlations:
  - The matrix  $E_{k',k}$  gives the number of connections between nodes of degree  $k$  and  $k'$ ,
  - The matrix  $e_{k',k} = E_{k',k}/2M$  gives the probability for finding a link between nodes of degree  $k$  and  $k'$ , and can be treated as a **joint probability mass function** between  $k$  and  $k'$ .
  - The degree distribution can be calculated from  $e_{k',k}$  as

$$q_k = \sum_{k'} e_{k',k} = \frac{k p(k)}{\langle k \rangle} \longrightarrow p(k) = \frac{\langle k \rangle}{k} q_k = \frac{\langle k \rangle}{k} \sum_{k'} e_{k',k}.$$

# The hidden variable model

## Network models

### Hidden variable model

- OK, but how to generate a random graph with prescribed degree correlations?
- We can use the method of **hidden degrees**.
- Let us go back to the complete statistical description of degree correlations:
  - The matrix  $E_{k',k}$  gives the number of connections between nodes of degree  $k$  and  $k'$ ,
  - The matrix  $e_{k',k} = E_{k',k}/2M$  gives the probability for finding a link between nodes of degree  $k$  and  $k'$ , and can be treated as a **joint probability mass function** between  $k$  and  $k'$ .
  - The degree distribution can be calculated from  $e_{k',k}$  as

$$q_k = \sum_{k'} e_{k',k} = \frac{k p(k)}{\langle k \rangle} \longrightarrow p(k) = \frac{\langle k \rangle}{k} q_k = \frac{\langle k \rangle}{k} \sum_{k'} e_{k',k}.$$

- Analogously, if we specify a **joint probability mass function**  $P(h', h)$ , the distribution of the hidden variables can be written as

$$\rho(h) = \frac{\langle h \rangle}{h} \sum_{h'} P(h', h).$$

# The hidden variable model

Network models

Hidden variable  
model

- Since the number of nodes with  $h$  is  $N_h = N\rho(h)$ , it is natural to set the connection probabilities as

$$r(h', h) = \frac{\langle h \rangle P(h', h)}{N\rho(h)\rho(h')}.$$

# The hidden variable model

Network models

Hidden variable  
model

- Since the number of nodes with  $h$  is  $N_h = N\rho(h)$ , it is natural to set the connection probabilities as

$$r(h', h) = \frac{\langle h \rangle P(h', h)}{N\rho(h)\rho(h')}.$$

- This way, the average degree of nodes with  $h$  is

$$\overline{k(h)} = N \sum_{h'} r(h', h) \rho(h') = \langle h \rangle \sum_{h'} \frac{P(h', h)}{\rho(h)} = h,$$

# The hidden variable model

Network models

Hidden variable  
model

- Since the number of nodes with  $h$  is  $N_h = N\rho(h)$ , it is natural to set the connection probabilities as

$$r(h', h) = \frac{\langle h \rangle P(h', h)}{N\rho(h)\rho(h')}.$$

- This way, the average degree of nodes with  $h$  is

$$\overline{k(h)} = N \sum_{h'} r(h', h) \rho(h') = \langle h \rangle \sum_{h'} \frac{P(h', h)}{\rho(h)} = h,$$

- and therefore

$$P(k | h) = \frac{h^k e^{-h}}{k!}.$$



# The hidden variable model

## Network models

## Hidden variable model

- Since the number of nodes with  $h$  is  $N_h = N\rho(h)$ , it is natural to set the connection probabilities as

$$r(h', h) = \frac{\langle h \rangle P(h', h)}{N\rho(h)\rho(h')}.$$

- This way, the average degree of nodes with  $h$  is

$$\overline{k(h)} = N \sum_{h'} r(h', h) \rho(h') = \langle h \rangle \sum_{h'} \frac{P(h', h)}{\rho(h)} = h,$$

- and therefore

$$P(k | h) = \frac{h^k e^{-h}}{k!}.$$

- Thus, the degree distribution and the ANND are

$$p(k) = \sum_h \frac{h^k e^{-h}}{k!} \rho(h),$$

$$k_{\text{nn}}(k) = \frac{1}{p(k)} \sum_{h'} k_{\text{nn}}(h) \frac{h^k e^{-h}}{k!} \rho(h),$$

where

$$k_{\text{nn}}(h) = \sum_{h'} \overline{k'(h')} P(h' | h) = \sum_{h'} h' P(h' | h).$$

# The hidden variable model

Network models

Hidden variable  
model

- The  $P(h' | h)$  conditional probability can be obtained from the joint distribution  $P(h', h)$  as

$$P(h' | h) = \frac{e_{h',h}}{\sum_{h'} e_{h',h}} = \frac{e_{h',h}}{q_h} = \frac{\langle h \rangle P(h', h)}{h \rho(h)}.$$

# The hidden variable model

## Network models

### Hidden variable model

- The  $P(h' | h)$  conditional probability can be obtained from the joint distribution  $P(h', h)$  as

$$P(h' | h) = \frac{e_{h',h}}{\sum_{h'} e_{h',h}} = \frac{e_{h',h}}{q_h} = \frac{\langle h \rangle P(h', h)}{h \rho(h)}.$$

- Since the Poisson distribution is a narrow distribution around its mean, in the large degree regime

$$\begin{aligned} p(k) &\sim \rho(h = k), \\ k_{nn}(k) &\sim k_{nn}(h = k) \end{aligned}$$