





Comment	Description	Designator	Footprint	LibRef	Quantity
1128	SMT Holder for CR123A Battery w/ coil spring	BT1	BAT_1128	1128	1
22uF	CL21 Series 0805 22uF 16V ±20% Tolerance X5R Multilayer Ceramic Chip Capacitor	C1	FP-CL21-IPC_C	CMP-13271-002990-1	1
CC0805KRX7R7BB104	CAP CER 0.1UF 16V X7R 0805	C2	FP-CC0805-0_85-MFG	CMP-1036-04402-6	1
1uF		C3	CAPC2013X140X50LL2 0T25	CMP-2007-04674-1	1
ESP32-S3-WROOM-1	Integrated Circuit	IC1	ESP32S3WROOM1	ESP32-S3-WROOM-1	1
B6B-PH-K-K(LF)(SN)	PH Series 6 Position 2 mm Pitch Through Hole Top Entry Shrouded Header	J1	FP-B6B-PH-K- K_LF_SN-MFG	CMP-17439-000495-1	1
22-28-4060	Connector	J2	HDRV6W66P0X254_1 X6_1524X249X838P	22-28-4060	1
B2B-PH-K-S(LF)(SN)	Male Header, Pitch 2 mm, 1 x 2 Position, Height 6 mm, Tail Length 3.4 mm, -25 to 85 degC, RoHS, Bulk	J3	JST-B2B-PH-K-S_V	CMP-2000-05162-1	1
10K	Resistor	R1	RESC2012X60N	CMP0805AFX-1002ELF	1