

Inapproximability of NPO problems



Let Π be a problem in NPO that is NP-hard

- We seek results of the form: if $P \neq NP$ then Π cannot be approximated within a factor of c for some constant c
 - i.e. if $P \neq NP$ then Π has no approximation algorithm with performance guarantee d , for any $1 \leq d \leq c$
 - Gives an indication of the limit to how well Π can be approximated

Example 1: Minimum Graph Colouring

- **Instance:** Graph $G=(V,E)$
- **Feasible solutions:** Any colouring of V
- **Measure:** Number of colours
- **Goal:** min

Min Graph Colouring is NP-hard



Inapproximability of Min Graph Colouring

The problem of deciding whether a graph can be coloured with **3** colours is known to be **NP-complete**

Suppose that there is an approximation algorithm **A** for **Min Graph Colouring** with performance guarantee $c < 4/3$

Let **G** be any graph

- (i) If **G** is **3-colourable**, then $m^*(G) \leq 3$ so **A** returns a colouring using $\leq 3c < 4$ colours, i.e. **3** colours
- (ii) If **G** is not **3-colourable**, then $m^*(G) \geq 4$ so **A** returns a colouring using ≥ 4 colours

So the existence of **A** would decide the **3-colourability** of **G** in polynomial time


Theorem: If $P \neq NP$ then **Minimum Graph Colouring** has no **c**-approximation algorithm with $c < 4/3$

Example 2: Minimum Bin Packing


- **Instance:** Collection **C** of **n** objects, of sizes **a_i** ($1 \leq i \leq n$) and a bin capacity **b**
- **Feasible solutions:** Any partition of **C** into **k** bins such that the sum of sizes of the objects in each bin does not exceed **b**
- **Measure:** Number of bins **k**
- **Goal:** **min**

Example instance: bin capacity **4**; object sizes **3,2,1,4,2**

(i)
4 bins



(ii)
3 bins



Minimum Bin Packing is NP-hard

Inapproximability of Minimum Bin Packing

Recall the **Partition** problem (known to be NP-complete):

- **Instance:** a collection **S** of positive integers
- **Question:** can **S** be partitioned into two sub-collections of equal sum?

Example: $a_1=7, a_2=4, a_3=11, a_4=4, a_5=9, a_6=7$ - answer is **no**

Change a_6 to **5** - answer is **yes** since

$$a_3 + a_5 = 11 + 9 = 7 + 4 + 4 + 5 = a_1 + a_2 + a_4 + a_6$$

Suppose that there is a polynomial-time approximation algorithm **A** for **Minimum Bin Packing** with performance guarantee $c < 3/2$

Let **S** be a collection of **n** integers in an instance of **Partition**. Define an instance **x** of **Minimum Bin Packing** with **n** objects with sizes given by **S** and define the capacity of each bin to be $b = \frac{1}{2} \sum \{a_i : a_i \text{ is in } S\}$

Inapproximability of Minimum Bin Packing (continued)

- (i) If **S** has a partition into two sets of equal sum, then $m^*(x) = 2$ so **A** returns a packing into $2c < 3$ bins, i.e. 2 bins
- (ii) If **S** does not have a partition into two sets of equal sum, then **A** returns a packing into $\geq m^*(x) \geq 3$ bins

Therefore the existence of **A** would decide the whether **S** has a partition into two sets of equal sum in polynomial time


Theorem: If $P \neq NP$ then **Minimum Bin Packing** has no c -approximation algorithm with $c < 3/2$

(NB **Minimum Bin Packing** is approximable within $3/2$)

Example 3: TSP

- **Instance:** Set **S** of **n** cities, distance $d(c_i, c_j)$ between each pair of cities $c_i, c_j \in S$
- **Feasible solutions:** Any travelling salesman tour of **S**, i.e. a permutation of **1, ..., n**
- **Measure:** Total length of the tour
- **Goal:** **min**

Example instance:




- Tour **1-2-4-3** is a feasible solution of measure **14**
- Tour **1-2-3-4** is an optimal solution - measure is **12**

TSP is **NP-hard**

Inapproximability of TSP

Problem of deciding whether a graph **G** has a Hamiltonian Cycle is **NP-complete** (**HC**)



Inapproximability of TSP

Problem of deciding whether a graph G has a Hamiltonian Cycle is **NP-complete** (**HC**)

Suppose that there is an approximation algorithm A for **TSP** with performance guarantee $c \geq 1$

Let $G=(V,E)$ be a graph in an instance of **HC**, where $n=|V|$

Define an instance x of **TSP** by letting V be the set of cities in x with distance function $d : V \times V \rightarrow \mathbb{N}$ as follows:

$$\begin{aligned} d(u,v) &= 1, & \text{if } \{u,v\} \in E \\ d(u,v) &= 1+nc, & \text{if } \{u,v\} \notin E \end{aligned}$$

- (i) If G has a Hamiltonian Cycle then $m^*(x)=n$ so A returns a tour of length $\leq nc$
- (ii) If G does not have a Hamiltonian Cycle, then A returns a tour of length $\geq m^*(x) \geq (n-1) + (1+nc) = (c+1)n > nc$

Inapproximability of TSP (continued)

Therefore the existence of **A** would decide the whether **G** has a Hamiltonian Cycle in polynomial time

Theorem: If **P \neq NP** then **TSP** has no **c**-approximation algorithm with **c \geq 1**

Approximation algorithms have been the subject of much recent research

- Recall **PO \subseteq FPTAS \subseteq PTAS \subseteq APX \subseteq NPO**
- Each of these inclusions is strict (if **P \neq NP**)
- A major research aim has been to classify problems within this hierarchy

Some **NPO** problems – what is known

- Not in **APX**
 - Minimum Graph Colouring, Maximum Clique, Travelling Salesman, Longest Common Subsequence
- In **APX** but not in **PTAS** (with bounds on best guarantee)
 - Max SAT ($c \leq 1.2551$)
 - Vertex cover ($1.1666 \leq c \leq 2$)
 - Bin Packing ($c = 1.5$)
 - Shortest common superstring ($c \leq 2.4783$)
 - Maximum 3D-matching ($c \leq 1.5 + \varepsilon$)
 - Max Cut ($1.0624 \leq c \leq 1.1383$)
- In **PTAS** but not in **FPTAS**
 - Geometric TSP
- In **FPTAS** but not in **PO**
 - Subset Sum Optimization
 - Knapsack
- (All of the above under the assumption that **P** \neq **NP**)