

More Bayes

CS4061 / CS5014 Machine Learning

Paul Henderson
University of Glasgow

`paul.henderson@glasgow.ac.uk`

*Based on previous material by
Simon Rogers & Ke Yuan*

Bayesian Probability

- ▶ what does $p(\text{head}) = 0.5$ **mean**?

Bayesian Probability

- ▶ what does $p(\text{head}) = 0.5$ **mean**?
- ▶ **frequentist** view: if I flip the coin infinitely many times, it shows heads 50% of the time

Bayesian Probability

- ▶ what does $p(\text{head}) = 0.5$ **mean**?
- ▶ **frequentist** view: if I flip the coin infinitely many times, it shows heads 50% of the time
- ▶ **Bayesian** view: I have 50% confidence that if I flip the coin **once**, it'll show heads
- ▶ probability = **degree of belief**

Bayesian Linear Regression

- ▶ model parameters \mathbf{w} are a random variable
 - ▶ we're uncertain what values they take
 - ▶ **prior** $p(\mathbf{w})$ represents our assumptions about 'sensible' models

Bayesian Linear Regression

- ▶ model parameters \mathbf{w} are a random variable
 - ▶ we're uncertain what values they take
 - ▶ **prior** $p(\mathbf{w})$ represents our assumptions about 'sensible' models
- ▶ we have training data (\mathbf{X}, \mathbf{t})
 - ▶ **likelihood** $p(\mathbf{t} | \mathbf{X}, \mathbf{w})$ says how probable it is for given model \mathbf{w}

Bayesian Linear Regression

- ▶ model parameters \mathbf{w} are a random variable
 - ▶ we're uncertain what values they take
 - ▶ **prior** $p(\mathbf{w})$ represents our assumptions about 'sensible' models
- ▶ we have training data (\mathbf{X}, \mathbf{t})
 - ▶ **likelihood** $p(\mathbf{t} | \mathbf{X}, \mathbf{w})$ says how probable it is for given model \mathbf{w}
- ▶ want a density $p(\mathbf{w} | \mathbf{X}, \mathbf{t})$ that combines these
- ▶ it should give high probability to outcomes consistent with **both** data **and** prior


Bayesian Linear Regression

- ▶ model parameters \mathbf{w} are a random variable
 - ▶ we're uncertain what values they take
 - ▶ **prior** $p(\mathbf{w})$ represents our assumptions about 'sensible' models
- ▶ we have training data (\mathbf{X}, \mathbf{t})
 - ▶ **likelihood** $p(\mathbf{t} | \mathbf{X}, \mathbf{w})$ says how probable it is for given model \mathbf{w}
- ▶ want a density $p(\mathbf{w} | \mathbf{X}, \mathbf{t})$ that combines these
- ▶ it should give high probability to outcomes consistent with **both** data **and** prior
- ▶ called the **posterior**; given by Bayes' rule:


$$p(\mathbf{w} | \mathbf{X}, \mathbf{t}) = \frac{p(\mathbf{t} | \mathbf{X}, \mathbf{w}) p(\mathbf{w})}{p(\mathbf{t} | \mathbf{X})}$$

Bayesian Linear Regression

prior




data & model




Bayesian Linear Regression


prior




likelihood




data & model




Bayesian Linear Regression




Bayesian Linear Regression



data & model



Bayesian Linear Regression



Computing the posterior

- ▶ Bayes rule:

$$p(\mathbf{w}|\mathbf{X}, \mathbf{t}) = \frac{p(\mathbf{t}|\mathbf{X}, \mathbf{w})p(\mathbf{w})}{p(\mathbf{t}|\mathbf{X})}$$

- ▶ Unfortunately, computing the posterior is hard...
- ▶ ...because marginal likelihood $p(\mathbf{t}|\mathbf{X})$ is hard to compute:

$$p(\mathbf{t}|\mathbf{X}) = \int p(\mathbf{t}|\mathbf{w}, \mathbf{X})p(\mathbf{w}) d\mathbf{w}$$

- ▶ Sometimes we can do it (e.g. everything Gaussian)
- ▶ Usually we can't and need some trick/alternative

Example – Olympic data

- ▶ Model predictions are Gaussian

$$\mathbf{t} \sim \mathcal{N}(\mathbf{X}\mathbf{w}, \sigma^2\mathbf{I})$$

- ▶ \mathbf{t} is a vector containing all the t_n
- ▶ \mathbf{X} is a matrix containing all the \mathbf{x}_n

Example – Olympic data

- ▶ Model predictions are Gaussian

$$\mathbf{t} \sim \mathcal{N}(\mathbf{X}\mathbf{w}, \sigma^2\mathbf{I})$$

- ▶ \mathbf{t} is a vector containing all the t_n
- ▶ \mathbf{X} is a matrix containing all the \mathbf{x}_n
- ▶ Joint likelihood is given by

$$p(\mathbf{t}|\mathbf{w}, \mathbf{X}, \sigma^2) = \prod_{n=1}^N p(t_n|\mathbf{w}, \mathbf{x}_n, \sigma^2)$$

Example – Olympic data

- ▶ Model predictions are Gaussian

$$\mathbf{t} \sim \mathcal{N}(\mathbf{X}\mathbf{w}, \sigma^2\mathbf{I})$$

- ▶ \mathbf{t} is a vector containing all the t_n
- ▶ \mathbf{X} is a matrix containing all the \mathbf{x}_n
- ▶ Joint likelihood is given by

$$p(\mathbf{t}|\mathbf{w}, \mathbf{X}, \sigma^2) = \prod_{n=1}^N p(t_n|\mathbf{w}, \mathbf{x}_n, \sigma^2)$$

- ▶ Ignoring a constant, this is

$$p(\mathbf{t}|\mathbf{w}, \mathbf{X}, \sigma^2) \propto \exp \left\{ -\frac{1}{2\sigma^2} (\mathbf{t} - \mathbf{X}\mathbf{w})^\top (\mathbf{t} - \mathbf{X}\mathbf{w}) \right\}$$

Example – Olympic data

- ▶ Choose a Gaussian prior:

$$p(\mathbf{w}) = \mathcal{N}(\mathbf{0}, \mathbf{S}), \quad \mathbf{S} = \begin{bmatrix} 100 & 0 \\ 0 & 5 \end{bmatrix}$$

- ▶ Mean ($\mathbf{0}$) and covariance (\mathbf{S}) are design choices
- ▶ Lets us inject our own knowledge about what \mathbf{w} are likely

Example – Olympic data

- ▶ Choose a Gaussian prior:


$$p(\mathbf{w}) = \mathcal{N}(\mathbf{0}, \mathbf{S}), \quad \mathbf{S} = \begin{bmatrix} 100 & 0 \\ 0 & 5 \end{bmatrix}$$

- ▶ Mean ($\mathbf{0}$) and covariance (\mathbf{S}) are design choices
- ▶ Lets us inject our own knowledge about what \mathbf{w} are likely
- ▶ Density is (ignoring a constant)

$$p(\mathbf{w}) \propto \exp \left\{ -\frac{1}{2} \mathbf{w}^T \mathbf{S}^{-1} \mathbf{w} \right\}$$

Example – Olympic data

- ▶ Rescale Olympic year:
 - ▶ $1896 = 1, 1900 = 2, \dots, 2008 = 27, 2012 = 28$
- ▶ Prior density:



- ▶ Mean (**0**) and covariance (**S**)

Example – Olympic data



- ▶ Ignoring non \mathbf{w} terms, the prior multiplied by the likelihood is:

$$\begin{aligned} & p(\mathbf{t} | \mathbf{w}, \mathbf{X}, \sigma^2) p(\mathbf{w}) \\ \propto & \exp \left\{ -\frac{1}{2\sigma^2} (\mathbf{t} - \mathbf{X}\mathbf{w})^\top (\mathbf{t} - \mathbf{X}\mathbf{w}) \right\} \exp \left\{ -\frac{1}{2} \mathbf{w}^\top \mathbf{S}^{-1} \mathbf{w} \right\} \\ \propto & \exp \left\{ -\frac{1}{2} \left(\mathbf{w}^\top \left[\frac{1}{\sigma^2} \mathbf{X}^\top \mathbf{X} + \mathbf{S}^{-1} \right] \mathbf{w} - \frac{2}{\sigma^2} \mathbf{w}^\top \mathbf{X}^\top \mathbf{t} \right) \right\} \end{aligned}$$

- ▶ Can be rearranged to (yet another) Gaussian
- ▶ It has parameters:

$$\mu = \frac{1}{\sigma^2} \mathbf{\Sigma} \mathbf{X}^\top \mathbf{t} \qquad \mathbf{\Sigma} = \left(\frac{1}{\sigma^2} \mathbf{X}^\top \mathbf{X} + \mathbf{S}^{-1} \right)^{-1}$$

Olympic data – Posterior



- ▶ *Left*: posterior (black) and prior (grey), zoomed in
- ▶ *Right*: functions corresponding to some \mathbf{w} sampled from posterior

Olympic data – Predictions

- Our motivation for being Bayesian was to be able to average predictions (at \mathbf{x}_{new}) over all \mathbf{w} :

$$\mathbb{E}_{p(\mathbf{w}|\mathbf{X},\mathbf{t},\sigma^2)} \{f(\mathbf{w})\} = \int f(\mathbf{w})p(\mathbf{w}|\mathbf{t},\mathbf{X},\sigma^2) d\mathbf{w}$$

Olympic data – Predictions

- Our motivation for being Bayesian was to be able to average predictions (at \mathbf{x}_{new}) over all \mathbf{w} :

$$\mathbb{E}_{p(\mathbf{w}|\mathbf{X},\mathbf{t},\sigma^2)} \{f(\mathbf{w})\} = \int f(\mathbf{w})p(\mathbf{w}|\mathbf{t},\mathbf{X},\sigma^2) d\mathbf{w}$$

- For our model, $f(\mathbf{w})$ is a Gaussian density:

$$f(\mathbf{w}) = f_{\mathcal{N}}(t_{\text{new}}; \mathbf{w}^T \mathbf{x}_{\text{new}}, \sigma^2)$$

Olympic data – Predictions

- ▶ Our motivation for being Bayesian was to be able to average predictions (at \mathbf{x}_{new}) over all \mathbf{w} :

$$\mathbb{E}_{p(\mathbf{w}|\mathbf{X}, \mathbf{t}, \sigma^2)} \{f(\mathbf{w})\} = \int f(\mathbf{w}) p(\mathbf{w}|\mathbf{t}, \mathbf{X}, \sigma^2) d\mathbf{w}$$

- ▶ For our model, $f(\mathbf{w})$ is a Gaussian density:

$$f(\mathbf{w}) = f_{\mathcal{N}}(t_{\text{new}}; \mathbf{w}^T \mathbf{x}_{\text{new}}, \sigma^2)$$


- ▶ We can compute this expectation exactly, to give predictive **density**:

$$p(t_{\text{new}}|\mathbf{X}, \mathbf{t}, \mathbf{x}_{\text{new}}, \sigma^2) = \mathcal{N}(\mathbf{x}_{\text{new}}^T \boldsymbol{\mu}, \sigma^2 + \mathbf{x}_{\text{new}}^T \boldsymbol{\Sigma} \mathbf{x}_{\text{new}})$$

...where posterior parameters were:


$$\boldsymbol{\mu} = \frac{1}{\sigma^2} \boldsymbol{\Sigma} \mathbf{X}^T \mathbf{t} \qquad \boldsymbol{\Sigma} = \left(\frac{1}{\sigma^2} \mathbf{X}^T \mathbf{X} + \mathbf{S}^{-1} \right)^{-1}$$

Olympic data – Predictions



Predictive density for 2012 Olympics

Olympic data – Predictions



Maximum *a posteriori*

- ▶ posterior $p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})$ incorporates observations and prior knowledge
- ▶ posterior \propto likelihood \times prior

Maximum *a posteriori*

- ▶ posterior $p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})$ incorporates observations and prior knowledge
- ▶ posterior \propto likelihood \times prior
- ▶ so far: made predictions by considering entire posterior, i.e.

$$\mathbf{E}_{p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})} \{ \dots \}$$

...called **fully Bayesian** approach

Maximum *a posteriori*

- ▶ posterior $p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})$ incorporates observations and prior knowledge
- ▶ posterior \propto likelihood \times prior
- ▶ so far: made predictions by considering entire posterior, i.e.

$$\mathbf{E}_{p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})} \{ \dots \}$$

...called **fully Bayesian** approach

- ▶ alternative: just consider **mode** of posterior
...called **maximum *a posteriori*** approach

Maximum *a posteriori*

- ▶ posterior $p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})$ incorporates observations and prior knowledge
- ▶ posterior \propto likelihood \times prior
- ▶ for Olympics, posterior was Gaussian with parameters

$$\boldsymbol{\mu} = \frac{1}{\sigma^2} \boldsymbol{\Sigma} \mathbf{X}^T \mathbf{t} \qquad \boldsymbol{\Sigma} = \left(\frac{1}{\sigma^2} \mathbf{X}^T \mathbf{X} + \mathbf{S}^{-1} \right)^{-1}$$

Maximum *a posteriori*

- ▶ posterior $p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})$ incorporates observations and prior knowledge
- ▶ posterior \propto likelihood \times prior
- ▶ for Olympics, posterior was Gaussian with parameters

$$\boldsymbol{\mu} = \frac{1}{\sigma^2} \boldsymbol{\Sigma} \mathbf{X}^T \mathbf{t} \qquad \boldsymbol{\Sigma} = \left(\frac{1}{\sigma^2} \mathbf{X}^T \mathbf{X} + \mathbf{S}^{-1} \right)^{-1}$$

- ▶ mode = mean for Gaussian, hence MAP estimate of \mathbf{w} is

$$\mathbf{w}^* = \frac{1}{\sigma^2} \boldsymbol{\Sigma} \mathbf{X}^T \mathbf{t}$$

Maximum *a posteriori*

$$\begin{aligned}\mathbf{w}^* &= \operatorname{argmax}_{\mathbf{w}} p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) \\ &= \operatorname{argmax}_{\mathbf{w}} \log p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})\end{aligned}$$

Maximum *a posteriori*

$$\begin{aligned}\mathbf{w}^* &= \underset{\mathbf{w}}{\operatorname{argmax}} p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) \\ &= \underset{\mathbf{w}}{\operatorname{argmax}} \log p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})\end{aligned}$$

- ▶ posterior \propto likelihood \times prior
- ▶ for Olympics, chose Gaussian prior and Gaussian likelihood

$$p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) \propto \exp \left\{ -\frac{1}{2\sigma^2} (\mathbf{t} - \mathbf{X}\mathbf{w})^\top (\mathbf{t} - \mathbf{X}\mathbf{w}) \right\} \exp \left\{ -\frac{1}{2} \mathbf{w}^\top \mathbf{S}^{-1} \mathbf{w} \right\}$$

Maximum a posteriori

$$\begin{aligned}\mathbf{w}^* &= \underset{\mathbf{w}}{\operatorname{argmax}} p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) \\ &= \underset{\mathbf{w}}{\operatorname{argmax}} \log p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})\end{aligned}$$

- ▶ posterior \propto likelihood \times prior
- ▶ for Olympics, chose Gaussian prior and Gaussian likelihood

$$\begin{aligned}p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) &\propto \exp \left\{ -\frac{1}{2\sigma^2} (\mathbf{t} - \mathbf{X}\mathbf{w})^\top (\mathbf{t} - \mathbf{X}\mathbf{w}) \right\} \exp \left\{ -\frac{1}{2} \mathbf{w}^\top \mathbf{S}^{-1} \mathbf{w} \right\} \\ \log p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) &= -\frac{1}{2\sigma^2} \sum_{n=1}^N (t_n - \mathbf{w}^\top \mathbf{x}_n)^2 - \frac{1}{2} \mathbf{w}^\top \mathbf{S}^{-1} \mathbf{w} + \text{const.}\end{aligned}$$

Maximum a posteriori

$$\begin{aligned}\mathbf{w}^* &= \operatorname{argmax}_{\mathbf{w}} p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) \\ &= \operatorname{argmax}_{\mathbf{w}} \log p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})\end{aligned}$$

- ▶ posterior \propto likelihood \times prior
- ▶ for Olympics, chose Gaussian prior and Gaussian likelihood

$$\begin{aligned}p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) &\propto \exp \left\{ -\frac{1}{2\sigma^2} (\mathbf{t} - \mathbf{X}\mathbf{w})^\top (\mathbf{t} - \mathbf{X}\mathbf{w}) \right\} \exp \left\{ -\frac{1}{2} \mathbf{w}^\top \mathbf{S}^{-1} \mathbf{w} \right\} \\ \log p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) &= -\frac{1}{2\sigma^2} \sum_{n=1}^N (t_n - \mathbf{w}^\top \mathbf{x}_n)^2 - \frac{1}{2} \mathbf{w}^\top \mathbf{S}^{-1} \mathbf{w} + \text{const.} \\ \therefore \mathbf{w}^* &= \operatorname{argmax}_{\mathbf{w}} \left\{ -\sum_{n=1}^N (t_n - \mathbf{w}^\top \mathbf{x}_n)^2 - \frac{\lambda}{2} \sum_{k=1}^K w_k^2 \right\}\end{aligned}$$


Maximum a posteriori

$$\begin{aligned}\mathbf{w}^* &= \underset{\mathbf{w}}{\operatorname{argmax}} p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) \\ &= \underset{\mathbf{w}}{\operatorname{argmax}} \log p(\mathbf{w} \mid \mathbf{X}, \mathbf{t})\end{aligned}$$

- ▶ posterior \propto likelihood \times prior
- ▶ for Olympics, chose Gaussian prior and Gaussian likelihood

$$\begin{aligned}p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) &\propto \exp \left\{ -\frac{1}{2\sigma^2} (\mathbf{t} - \mathbf{X}\mathbf{w})^\top (\mathbf{t} - \mathbf{X}\mathbf{w}) \right\} \exp \left\{ -\frac{1}{2} \mathbf{w}^\top \mathbf{S}^{-1} \mathbf{w} \right\} \\ \log p(\mathbf{w} \mid \mathbf{X}, \mathbf{t}) &= -\frac{1}{2\sigma^2} \sum_{n=1}^N (t_n - \mathbf{w}^\top \mathbf{x}_n)^2 - \frac{1}{2} \mathbf{w}^\top \mathbf{S}^{-1} \mathbf{w} + \text{const.} \\ \therefore \mathbf{w}^* &= \underset{\mathbf{w}}{\operatorname{argmin}} \left\{ \sum_{n=1}^N (t_n - \mathbf{w}^\top \mathbf{x}_n)^2 + \frac{\lambda}{2} \sum_{k=1}^K w_k^2 \right\}\end{aligned}$$


Regularised Least Squares



$$\mathbf{w}^* = \underset{\mathbf{w}}{\operatorname{argmin}} \sum_{n=1}^N (t_n - \mathbf{w}^T \mathbf{x}_n)^2 + \frac{\lambda}{2} \sum_{k=1}^K w_k^2$$

► 2nd term = **L2 regulariser**


Regularised Least Squares



$$\mathbf{w}^* = \underset{\mathbf{w}}{\operatorname{argmin}} \sum_{n=1}^N (t_n - \mathbf{w}^T \mathbf{x}_n)^2 + \frac{\lambda}{2} \sum_{k=1}^K |w_k|$$

► 2nd term = **L1** regulariser

Regularised Least Squares



$$\mathbf{w}^* = \underset{\mathbf{w}}{\operatorname{argmin}} \sum_{n=1}^N (t_n - \mathbf{w}^T \mathbf{x}_n)^2 + \frac{\lambda}{2} \sum_{k=1}^K |w_k|$$

- ▶ 2nd term = **L1** regulariser
- ▶ encourages **sparsity**
- ▶ many elements of \mathbf{w} will be zero

Summary

- ▶ Saw how predictions could be made by averaging over all possible parameter values \mathbf{w} , conditioned on training data – Bayesian
- ▶ Handles uncertainty in measurements *and* in \mathbf{w} itself
- ▶ Can use marginal likelihood to compare models
- ▶ Maximum *a posteriori* is a simpler alternative to full Bayesian approach

Deep learning for regression

- ▶ linear model: $t = \mathbf{w}^T \mathbf{x}$
 - ▶ \mathbf{w} is a vector

Deep learning for regression

- ▶ linear model: $t = \mathbf{w}^T \mathbf{x}$
 - ▶ \mathbf{w} is a vector
- ▶ deep linear model: $t = \mathbf{W}_1 \mathbf{x}'$ with $\mathbf{x}' = \mathbf{W}_0 \mathbf{x}$
 - ▶ \mathbf{W}_i are matrices
 - ▶ \mathbf{x}' is a vector

Deep learning for regression

- ▶ linear model: $t = \mathbf{w}^T \mathbf{x}$
 - ▶ \mathbf{w} is a vector
- ▶ deep linear model: $t = \mathbf{W}_1 \mathbf{x}'$ with $\mathbf{x}' = \mathbf{W}_0 \mathbf{x}$
 - ▶ \mathbf{W}_i are matrices
 - ▶ \mathbf{x}' is a vector
- ▶ even deeper linear model:

$$\mathbf{x}' = \mathbf{W}_0 \mathbf{x}$$

$$\mathbf{x}'' = \mathbf{W}_1 \mathbf{x}'$$

$$t = \mathbf{W}_2 \mathbf{x}''$$

- ▶ ...etc.

Deep learning for regression

- ▶ deep linear model:

$$\mathbf{x}' = \mathbf{W}_0 \mathbf{x}$$

$$\mathbf{x}'' = \mathbf{W}_1 \mathbf{x}'$$

$$t = \mathbf{W}_2 \mathbf{x}''$$

Deep learning for regression

- ▶ deep ~~linear~~ model:

$$\mathbf{x}' = g(\mathbf{W}_0 \mathbf{x})$$

$$\mathbf{x}'' = g(\mathbf{W}_1 \mathbf{x}')$$

$$t = \mathbf{W}_2 \mathbf{x}''$$

Deep learning for regression

- ▶ deep ~~linear~~ model:

$$\mathbf{x}' = g(\mathbf{W}_0 \mathbf{x})$$

$$\mathbf{x}'' = g(\mathbf{W}_1 \mathbf{x}')$$

$$t = \mathbf{W}_2 \mathbf{x}''$$

- ▶ g is...

- ▶ nonlinear

- ▶ elementwise, i.e. if $\mathbf{y} = \begin{pmatrix} y_1 \\ y_2 \\ \vdots \end{pmatrix}$ then $g(\mathbf{y}) = \begin{pmatrix} g(y_1) \\ g(y_2) \\ \vdots \end{pmatrix}$

Deep learning for regression

- ▶ deep ~~linear~~ model:

$$\mathbf{x}' = g(\mathbf{W}_0 \mathbf{x})$$

$$\mathbf{x}'' = g(\mathbf{W}_1 \mathbf{x}')$$



$$t = \mathbf{W}_2 \mathbf{x}''$$

- ▶ g is...

- ▶ nonlinear

- ▶ elementwise, i.e. if $\mathbf{y} = \begin{pmatrix} y_1 \\ y_2 \\ \vdots \end{pmatrix}$ then $g(\mathbf{y}) = \begin{pmatrix} g(y_1) \\ g(y_2) \\ \vdots \end{pmatrix}$

- ▶ common choices for g :



Deep learning for regression

- ▶ deep nonlinear model:

$$\mathbf{x}' = g(\mathbf{W}_0 \mathbf{x})$$

$$\mathbf{x}'' = g(\mathbf{W}_1 \mathbf{x}')$$

$$t = \mathbf{W}_2 \mathbf{x}''$$

- ▶ this can closely approximate any function $t^*(\mathbf{x})$ if either
 - ▶ two layers, and \mathbf{W}_0 has 'enough' rows/columns
 - ▶ fixed size \mathbf{W}_i (as large as \mathbf{x}), and 'enough' layers
- ▶ can approximate an arbitrarily wiggly line!

Deep learning for regression

- ▶ deep nonlinear model:

$$\mathbf{x}' = g(\mathbf{W}_0 \mathbf{x})$$

$$\mathbf{x}'' = g(\mathbf{W}_1 \mathbf{x}')$$

$$t = \mathbf{W}_2 \mathbf{x}''$$

- ▶ this can closely approximate any function $t^*(\mathbf{x})$ if either
 - ▶ two layers, and \mathbf{W}_0 has 'enough' rows/columns
 - ▶ fixed size \mathbf{W}_i (as large as \mathbf{x}), and 'enough' layers
- ▶ can approximate an arbitrarily wiggly line!
- ▶ still fit by minimising mean square error (or maximising likelihood):

$$\mathbf{W}_0^*, \mathbf{W}_1^*, \mathbf{W}_2^* = \underset{\mathbf{W}_0, \mathbf{W}_1, \mathbf{W}_2}{\operatorname{argmin}} \frac{1}{N} \sum_{n=1}^N (t_n - \mathbf{W}_2 g(\mathbf{W}_1 g(\mathbf{W}_0 \mathbf{x}_n)))^2$$

Deep learning for regression

- ▶ deep nonlinear model:

$$\mathbf{x}' = g(\mathbf{W}_0 \mathbf{x})$$

$$\mathbf{x}'' = g(\mathbf{W}_1 \mathbf{x}')$$

$$t = \mathbf{W}_2 \mathbf{x}''$$

- ▶ this can closely approximate any function $t^*(\mathbf{x})$ if either
 - ▶ two layers, and \mathbf{W}_0 has 'enough' rows/columns
 - ▶ fixed size \mathbf{W}_i (as large as \mathbf{x}), and 'enough' layers
- ▶ can approximate an arbitrarily wiggly line!
- ▶ still fit by minimising mean square error (or maximising likelihood):

$$\mathbf{W}_0^*, \mathbf{W}_1^*, \mathbf{W}_2^* = \underset{\mathbf{W}_0, \mathbf{W}_1, \mathbf{W}_2}{\operatorname{argmin}} \frac{1}{N} \sum_{n=1}^N (t_n - \mathbf{W}_2 g(\mathbf{W}_1 g(\mathbf{W}_0 \mathbf{x}_n)))^2$$

- ▶ use gradient descent!

Deep learning for regression

- ▶ a big enough nonlinear regression model can predict lots of interesting things!

Deep learning for regression

- ▶ a big enough nonlinear regression model can predict lots of interesting things!
- ▶ e.g. image \rightarrow 3D object locations

Deep learning for regression

- ▶ a big enough nonlinear regression model can predict lots of interesting things!
- ▶ e.g. image \rightarrow other viewpoints

Deep learning for regression

- ▶ a big enough nonlinear regression model can predict lots of interesting things!
- ▶ e.g. random noise \rightarrow cats