

Project Report
on
Gaze Tracker

Submitted in the partial fulfillment of the requirements for
the award of Degree of B. Tech

By
Khushi (2100680100186)
Kunal Yadav (2100680100195)
Manav Adhana (2100680100204)
Maneesha (2100680100205)

Under the Supervision of: -

Dr. Satendra Kumar
(Associate Professor, Department of CSE)



Department of Computer Science & Engineering
Meerut Institute of Engineering and Technology,
Meerut – 250005



Dr. A.P.J. Abdul Kalam Technical University, U.P., Lucknow

[Batch: 2021-2025]

DECLARATION

I hereby declare that this submission is my own work and that, to the best of my knowledge and belief, it contains no material previously published or written by another person nor material which to a substantial extent has been accepted for the award of any other degree or diploma of the university or other institute of higher learning, except where due acknowledgment has been made in the text.

Signature:

Name : Khushi

Roll No.: 2100680100186

Date :

Signature:

Name : Kunal Yadav

Roll No.: 2100680100195

Date :

Signature:

Name : Manav Adhana

Roll No.: 2100680100204

Date :

Signature:

Name : Maneesha

Roll No.: 2100680100205

Date :

CERTIFICATE

This is to certify that Project Report entitled — **GAZE TRACKER** which is submitted by Kunal Yadav (2100680100195), Manav Adhana (2100680100204), Maneesha (2100680100205) and Khushi (2100680100186) in partial fulfillment of the requirement for the award of degree B. Tech. in Department of Computer Science and Engineering of Dr. A.P.J. Abdul Kalam Technical University, U.P., Lucknow., is a record of the candidate own work carried out by him/her under my/our supervision. The matter embodied in this Project report is original and has not been submitted for the award of any other degree.

Date:

Supervisor

Dr. Satendra Kumar
(Associate Professor, CSE)

ACKNOWLEDGEMENTS

It gives us a great sense of pleasure to present the report of the B. Tech Project undertaken during B.Tech. Final Year. We owe special debt of gratitude to our guide Dr. Satendra Kumar, Department of Computer Science & Engineering, Meerut Institute of Engineering and Technology, Meerut for his constant support and guidance throughout the course of our work. His sincerity, thoroughness and perseverance have been a constant source of inspiration for us. It is only his cognizant efforts that our endeavors have seen light of the day.

We also do not like to miss the opportunity to acknowledge the contribution of all faculty members of the department for their kind assistance and cooperation during the development of our project. Last but not the least, we acknowledge our friends for their contribution in the completion of the project.

Signature:

Name : Khushi

Roll No. : 2100680100186

Date :

Signature:

Name : Kunal Yadav

Roll No. : 2100680100195

Date :

Signature:

Name : Manav Adhana

Roll No. : 2100680100204

Date :

Signature:

Name : Maneesha

Roll No. : 2100680100205

Date :

ABSTRACT

This research paper describes the implementation of Raspberry Pi technology to build a head-movement and blink-controlled PC system for individuals with physical disabilities. By recognizing head movements and eye blinks, the system allows users to control the computer cursor without the need for traditional input devices. The hardware setup includes a Raspberry Pi 3B for processing, a 720p USB camera to capture video of the user's face, and several infrared (IR) sensors that detect eye blinks. The camera tracks head movements to move the cursor in different directions, while the IR sensors detect intentional blinks that simulate mouse clicks.

The system is built using the Python programming language and Open CV, a powerful computer vision library, to handle face detection and cursor mapping. Through a combination of hardware interfacing and real-time software control, the system provides a smooth and responsive user experience. A key part of the implementation involves calibration and testing to ensure that the system accurately detects user input and avoids errors caused by unintentional movements or blinks.

The ability to differentiate between reflexive and intentional blinks, using IR sensors and debounce logic, significantly enhances the reliability of cursor control. As a result, users can interact with a computer in a more natural and independent manner. This approach highlights how technology can be adapted to serve accessibility needs by focusing on user-friendly and cost-effective solutions.

Looking forward, this system can be improved with more refined blink detection techniques, enhanced camera quality for better head or eye tracking, and additional input methods such as gesture recognition or voice activation. These improvements could further increase usability and extend the system's application to mobile devices and smart home controls. The core goal remains to provide physically challenged individuals with a greater degree of freedom and interaction with digital technology, without relying on complex or expensive tools.

TABLE OF CONTENTS

TITLE	Page No.
Declaration.....	i
Certificate.....	ii
Acknowledgement.....	iii
Abstract.....	iv
List of Table.....	vii
List of Figures.....	viii
 CHAPTER 1 – INTRODUCTION	1
1.1 Overview.....	1
1.2 Feature Extraction	2
1.3 Accessing Models.....	2
1.4 Summary of Result.....	3
1.5 Scope.....	4
1.6 Software development methodology	5
 CHAPTER 2 –LITERATURE REVIEW	7
2.1 Key Factors Influencing	7
2.2 Strategies	8
 CHAPTER 3 – SOFTWARE REQUIREMENTS SPECIFICATIONS	10
3.1 Introduction.....	10
3.2 General architecture of software.....	10
3.3 Requirements Specifications.....	11
3.3.1 Functional Requirements.....	11
3.3.2 Non-Functional Requirements.	12
3.4 System Requirement Study	13

3.4.1 Software Requirements.....	13
3.4.2 Hardware Requirements.....	14
3.5 System Design.....	15
3.5.1 Introduction.....	15
CHAPTER 4–IMPLEMENTATION	18
4.1.1 Code Implementation.....	19
CHAPTER 5– TECHNOLOGY USED.....	21
CHAPTER 6- RESULT AND DISCUSSION	22
CHAPTER 7- CONCLUSION & FUTURE WORK	23
REFERENCES	25
Appendix.....	27
Research Paper1.....	31
Research Paper2.....	37
Project Plagiarism Report.....	53

LIST OF TABLES

Table No.	Description	Page no.
1.1	Expected Accuracy	4
1.2	Features	4
6.1	Testing	22
6.2	Optimal Condition	22

LIST OF FIGURES

Fig. No.	Description	Page no.
3.1	General Architecture	11
3.2	Non-functional Requirement	12
3.3	System Requirement	13
3.4	System Design Diagram	17
4.1	Raspberry Pi setup	18
4.2	Wearable assistive device	18
4.3	Smart glasses prototype	19
4.4	Code Implemented	19
4.5	Code Implemented	20
4.6	Code Implemented	20

CHAPTER 1

INTRODUCTION

1.1 OVERVIEW

Introduction to Head and Blink Tracking

Head and blink tracking is a technique used to monitor and analyse head movements and eye blinks to control computer interfaces, especially for individuals with physical disabilities. It has wide applications in assistive technologies, human-computer interaction (HCI), and accessibility solutions. By tracking head movements and detecting intentional blinks, such systems allow users to control the computer cursor and clicks without traditional input devices. A head and blink tracking system typically consists of a camera that captures real-time video of the user's face and infrared (IR) sensors that detect eye blinks. The system processes these signals to detect facial features (such as eyes, nose, and mouth) and uses these to estimate head orientation and blink events. This technology enables hands-free control of devices, enhancing accessibility for individuals with mobility impairments and improving user experience in assistive applications.

Unlike AI-based gaze tracking systems that require complex machine learning models, traditional head and blink tracking relies on lightweight image processing and sensor-based techniques. These methods are efficient, cost-effective, and suitable for real-time applications with minimal hardware requirements.

How Head and Blink Tracking Works

1. **Face Detection & Head Tracking:** A USB camera captures real-time images of the user's face. Facial landmarks (eyes, nose, mouth) are detected, and head movement is mapped to cursor direction.
2. **Blink Detection:** IR sensors mounted near the eyes detect intentional blinks by sensing quick proximity changes.
3. **Cursor & Click Control:** Head movements control cursor direction, while detected blinks trigger click actions.
4. **Calibration & Real-time Processing:** The system undergoes calibration to fine-tune sensitivity and continuously updates cursor position and click detection in real time.

Applications of Gaze Tracking

- **Assistive Technology:** Enables individuals with physical disabilities to control computers and smart devices using only their eye movements.
- **Human-Computer Interaction (HCI):** Supports hands-free navigation in computers and interactive systems.
- **Virtual Reality:** Enhances user experience by enabling gaze-based interactions.

- **Medical Research:** Used in studies related to vision disorders, cognitive conditions, and neurological diseases.
- **Marketing & Advertising:** Helps analyze user engagement by tracking eye movement on advertisements and digital content.
- **Automotive Safety:** Detects driver fatigue and distraction, reducing accident risks by improving road safety.
- **Smart Home Controls:** Facilitates hands-free control of home devices for users with limited mobility.

1.2 Feature Extraction

Feature Extraction in Gaze Tracking

Feature Extraction in Head and Blink Tracking

Feature extraction in this system involves identifying key face-related and eye-related elements from camera images and sensor signals. The main features extracted include:

- **Facial Landmark Detection:** Using models like dlib or OpenCV, the system detects key points on the face such as eyes, nose, and mouth for head orientation tracking.
- **Head Pose Estimation:** By calculating angles based on landmark positions, the system estimates head direction (up, down, left, right) to move the cursor.
- **Blink Detection (via IR Sensors):** Infrared sensors detect intentional blinks by measuring quick changes in IR reflection when eyes close, differentiating voluntary blinks from natural ones.
- **Cursor Mapping:** Detected head movements and blinks are mapped to cursor movement and mouse click actions on the computer screen.

Implementation in Gaze Tracking:

1. **Data Collection:** Camera captures face video; IR sensors capture blink signals.
2. **Feature Extraction:** Detect face landmarks for head tracking and sensor signals for blink detection.
3. **Movement & Click Estimation:** Head pose estimation algorithms map movements to cursor control; blink signals trigger click actions.
4. **Real-Time Processing:** System continuously processes camera and sensor data to provide smooth, responsive control.

1.3 Accessing Models

This system uses traditional image processing and sensor-based methods rather than AI models, making it lightweight and efficient.

Key Tools and Methods:

- OpenCV Library: Used for face detection, facial landmark tracking, and image processing.
- dlib Library: Provides accurate facial landmark detection models for real-time head pose estimation.
- IR Sensors and GPIO Programming: Hardware-based blink detection using infrared proximity sensors connected to Raspberry Pi GPIO pins.
- Geometric Models: Trigonometric calculations to convert head tilt angles into screen coordinates.
- Custom Algorithms: Rule-based detection and calibration methods for filtering out false positives and tuning sensitivity.

1.4 Summary of Results:

This project implements a head-movement and blink-based control system, providing an alternative interaction method for individuals with physical disabilities. Instead of using full gaze tracking, the system relies on head movement detection and intentional eye blinks to simulate cursor control and clicking. This method avoids complex eye tracking while still offering reliable hands-free operation.

Unlike AI-based gaze tracking, which relies on machine learning to predict gaze direction, this system uses traditional image processing and sensor-based techniques. Head movements are detected by tracking facial landmarks, while blinks are registered through infrared (IR) sensors that capture changes around the eye area.

The system's performance is evaluated based on the following criteria:

1. **Head Movement Detection Accuracy** – The ability to correctly identify directional head tilts using facial landmark tracking and map them to cursor movement.
2. **Blink Detection Reliability** – The system's effectiveness in distinguishing intentional blinks from reflexive ones using IR sensor input and threshold filtering.
3. **Processing Speed** – The responsiveness of the system, ensuring real-time control with minimal delay during operation.

The accuracy and responsiveness depend on several factors, including camera resolution, lighting conditions, and sensor placement. Typically, for systems built with a Raspberry Pi 3B, a 720p USB camera, and IR sensors, the overall accuracy ranges from **85% to 92%** in controlled indoor environments. Proper lighting, stable head positioning, and careful calibration steps are essential for achieving peak performance.

By combining geometric face models and carefully analyzing head position and blink patterns, the system achieves dependable control of cursor movement and clicks. While occasional discrepancies may occur due to rapid head movements, varying facial structures, or light interference, regular recalibration and optimized sensor alignment help maintain consistent performance. This level of accuracy is sufficient for assistive

applications such as menu navigation and basic computer interaction tasks.

Table:1.1 Expected Accuracy

Metric	Expected Accuracy(%)	Expected Response Time (sec)
Head Tracking	80-85%	0.05-0.10
Eye Tracking	75-80%	0.08-0.12
Blink Detection	70-75%	0.05-0.08

Table:1.2 Features

Feature	Existing Eye- Tracking Device	Our Proposed System
Cost	Expensive(40K-80k)	Affordable (Raspberry Pi- based)
Hardware	Special eye-tracking cameras	Standard Webcam & IR Sensors
Ease of use	Complex setups required	Simple & user friendly
Accuracy	High but Costly	Good, need improvements
Input Method	Eye movements Only	Head+ Blink detection

1.5 SCOPE

Scope of Head and Blink Tracking System:

Head and blink tracking technology offers an innovative and accessible method for individuals, especially those with physical and motor impairments, to control digital devices through natural movements. By leveraging simple head tilts and intentional eye blinks, users are empowered to perform complex tasks such as cursor movement and click actions without relying on traditional input devices like a mouse or keyboard. This makes it particularly valuable in creating inclusive technologies that bridge the gap between humans and machines.

In the field of **assistive technology**, this system plays a transformative role. It provides a lifeline for individuals living with conditions such as Amyotrophic Lateral Sclerosis (ALS), cerebral palsy, paralysis, spinal cord injuries, and muscular dystrophy. By enabling cursor control and click simulation solely through head movements and blink detection, the technology restores independence and dignity to users, allowing them to navigate software applications, browse the internet, and communicate with others in a hands-free manner.

In the domain of **gaming and virtual reality (VR)**, head tracking enhances immersive experiences by allowing players to naturally interact with virtual environments. Users can aim, navigate, and make selections simply by moving their heads, providing a more intuitive and engaging gameplay experience. Similarly, in **augmented reality (AR)**, combining head gestures with blink-based selections can further improve user engagement, offering a seamless interaction model where digital elements respond instantly to physical cues.

The **automotive industry** also stands to benefit from this technology. Blink detection and head movement monitoring are increasingly being integrated into advanced driver assistance systems (ADAS) to detect signs of driver fatigue, drowsiness, and distraction. By issuing alerts when drivers show signs of inattention or microsleeps, these systems enhance road safety, reduce

accident rates, and contribute to a safer driving environment for everyone.

In **medical research and healthcare**, analyzing blink rates and head movement patterns provides critical insights into neurological and cognitive conditions. Researchers and clinicians can use this technology to study disorders such as Parkinson's disease, Alzheimer's disease, autism spectrum disorders, and Attention Deficit Hyperactivity Disorder (ADHD). This opens up possibilities for non-invasive diagnostics and continuous patient monitoring, enabling early detection and intervention.

The field of **smart home automation** presents another exciting application. As smart environments evolve, integrating head and blink tracking systems can enable users to control lighting, appliances, entertainment systems, and security devices through simple, hands-free commands. For individuals with limited mobility, this technology offers greater independence, enabling them to interact with their living space in a seamless and intuitive manner.

With the rise of **wearable technologies**, such as smart glasses and head-mounted displays, head and blink tracking systems are being adapted for professional and industrial use. Surgeons in sterile operating rooms can navigate medical imaging systems using only eye gestures, eliminating the need for physical contact. Similarly, engineers, field technicians, and emergency responders can access information, control tools, and communicate while keeping their hands free for critical tasks, improving efficiency and safety in demanding environments. Furthermore, as hardware miniaturization and sensor precision continue to advance, the potential applications of this technology will expand even further. Emerging fields such as **robotics**, **human-computer interaction (HCI)**, and **wearable health monitoring** can benefit from reliable, non-invasive head and blink tracking systems. Future iterations may include gesture recognition, voice control integration, and real-time adaptive interfaces, making digital systems more responsive and accessible to a wider audience.

In conclusion, while the current project primarily focuses on providing cursor control and click simulation for individuals with physical disabilities, the underlying head and blink tracking technology has a broad and evolving scope.

1.6 SOFTWARE DEVELOPMENT METHODOLOGY

The software development process for the gaze tracking system follows an Agile methodology, which emphasizes iterative progress, continuous testing, and user feedback. Agile allows the development team to adapt quickly to changing requirements and ensure a high-quality product.

Each development cycle (or sprint) focuses on implementing specific features such as blink detection, head movement tracking, cursor control, or calibration routines. At the end of each cycle, the software is tested in real-time to validate its performance and identify areas for refinement. This incremental approach not only enhances system stability and reliability but also ensures that user needs are consistently prioritized during development.

Regular user testing plays a crucial role in evaluating the system's usability, responsiveness, and accuracy. Feedback from individuals with physical impairments helps the developers fine-tune features like blink sensitivity, cursor speed, and dwell time for selections. This close loop of feedback and adjustment ensures the final product is intuitive, accessible, and practical for real-world use.

Moreover, Agile's flexibility allows the team to explore improvements in user interface design and system calibration without overhauling the entire application. It also encourages collaboration between software engineers, hardware integrators, and user experience designers,

resulting in a well-rounded, user-friendly solution.

In the future, this development approach makes it easier to introduce additional features—such as voice commands or gesture-based controls—and to adapt the system for use on other platforms, such as tablets, smartphones, or home automation devices. The focus remains on building a reliable, scalable, and maintainable system that can improve digital accessibility for users with mobility limitations.

Key Stages of Software Development

- **Requirement Analysis:** Understanding user needs and defining system functionalities, such as real-time gaze tracking, calibration, and data visualization.
- **Design Phase:** Creating system architecture, selecting appropriate image processing techniques, and designing user interfaces for gaze-based interaction.
- **Implementation:** Developing the software using programming languages like Python , along with libraries such as OpenCV for image processing. Ensuring modular and scalable code.
- **Testing:** Conducting unit tests, integration tests, and performance tests to validate accuracy, response time, and user experience.
- **Deployment & Maintenance:** Deploying the gaze tracker on target platforms, monitoring performance, and providing updates based on user feedback.

CHAPTER 2

LITERATURE REVIEW

Gaze Tracking Technology

Head movement and blink detection technology are key methods used for hands-free computer control, especially for individuals with physical disabilities. These systems track the movement of a user's head to move the mouse cursor and detect intentional eye blinks to simulate mouse clicks. The technology is often implemented with a combination of a camera and infrared (IR) sensors. The camera captures video of the user's face to track head movements, while IR sensors detect the user's blinks, allowing for click actions without using a traditional input device like a mouse.

Unlike traditional gaze tracking, which focuses on eye movement and pupil detection, the system in our project tracks head position through face detection techniques and interprets eye blinks for click actions. This approach provides a straightforward, cost-effective solution that can be deployed using devices like Raspberry Pi and USB cameras. It offers significant value for users with mobility impairments, enabling them to interact with digital interfaces by simply moving their heads and blinking.

The system is relatively simple, yet effective. It does not require complex or expensive tools, and with the right calibration and real-time software control, it can provide reliable and smooth interaction with the computer. The use of IR sensors allows for accurate blink detection, which reduces errors from reflexive blinks and ensures that only intentional blinks are considered as click actions.

2.1 Key Factors Influencing Gaze Tracking

Several key factors influence the accuracy, efficiency, and adoption of gaze tracking systems. These factors impact the reliability of gaze tracking techniques and their practical usability across different domains.

- **Lighting Conditions:** Variations in lighting can significantly affect the visibility of eye features. Low-light environments or excessive glare can interfere with pupil detection, reducing the accuracy of gaze tracking systems.
- **User Variability:** Differences in individual eye structures, blinking frequency, and head movements present challenges in ensuring consistent gaze tracking performance across diverse users.
- **Camera Quality and Resolution:** Higher-resolution cameras provide more accurate gaze tracking but require greater computational power. The frame rate of cameras also affects real-time tracking performance.
- **Real-time Processing Requirements:** Applications such as gaming, assistive technology, and virtual reality demand low-latency gaze tracking for seamless interaction. Efficient image processing algorithms.

2.2 Strategies

Accurate and Reliable Head Movement Tracking

- Use **traditional face detection algorithms** like Haar cascades (as used in OpenCV) to detect and track head position.
- Implement **image processing techniques** to map head movements to screen coordinates, ensuring smooth cursor movement in real-time.
- Calibrate the system to account for variations in user head positions and movement speeds.

Effective Blink Detection

- Use **infrared sensors** to accurately detect eye blinks by identifying changes in light levels near the eyes.
- Implement **debounce mechanisms** to prevent false positives caused by reflexive blinks.
- Fine-tune blink detection sensitivity to distinguish between unintentional and intentional blinks.

Seamless User Experience

- Ensure **low-latency processing** to maintain a responsive system that updates cursor positions in real-time.
- Design **adjustable sensitivity settings** for both head movement tracking and blink detection, allowing users to fine-tune the system to their preferences and reduce false detection.
- Provide **intuitive interface designs** that make interaction easy without requiring extensive training or learning curves.

Personalization Without AI

- Use **rule-based systems** for head tracking and blink detection that rely on pre-programmed thresholds and algorithms.
- Allow **manual customization** for settings like blink dwell time or head movement sensitivity to adapt the system to individual user needs.
- Enable **adjustable click options**, where a user can configure how long to hold the blink to register a click.

Head Movement and Blink-Based Navigation

- Implement **head gestures** (e.g., tilting the head left/right or up/down) to enable navigation through menus or applications.
- Use **blinks** as a trigger for selection, allowing users to open files, click on buttons, or perform other mouse-related actions.
- Enable **multi-screen support** for users to control multiple displays with ease.

Customer Support and Engagement

- Provide **on-screen tutorials** that demonstrate how to use the head movement and blink-based interface, guiding users through the system's features.
- Set up **help menus** that allow users to troubleshoot issues using head movements and blinks.
- Implement **feedback mechanisms**, where users can report any issues or difficulties they encounter while interacting with the system.

Data Security and Privacy Protection

- Ensure that any **head movement data** or **blink logs** are stored securely and are only used for system calibration and improvement.
- Allow users to **control permissions** regarding the use of their data, ensuring that it is

only collected when necessary for system functionality.

- **Encrypt** all sensitive interaction logs and respect user privacy, especially in compliance with relevant privacy laws.

Reward-Based Engagement Strategies

- Develop **reward systems** that encourage users to complete certain tasks using head movement and blink detection, such as interactive tutorials or loyalty programs.
- Create **gamified experiences** where users can earn rewards by completing head-controlled challenges.
- Offer **discounts or rewards** to users who consistently engage with the system, motivating long-term use.

Several prior research efforts have explored assistive technologies leveraging eye and head movements for computer interaction, particularly targeting individuals with physical disabilities. For instance, Álvarez et al. (2013) presented an eye-gaze tracking system for human-computer interaction using low-cost webcams, demonstrating promising accuracy for basic pointer control. Similarly, Villanueva and Cabeza (2007) emphasized vision-based systems for eye tracking that could be implemented in real-time environments using commercial-grade cameras. More recent developments such as the Eye Writer project (Golan et al., 2010) employed open-source hardware and software to enable paralyzed individuals to draw and communicate using eye movements. Furthermore, systems utilizing blink detection for mouse click simulation were studied by Maazaoui et al. (2018), who integrated infrared sensors with a neural network classifier to distinguish intentional blinks. These related studies have laid the foundation for accessible, affordable, and real-time assistive technologies, aligning well with the proposed Raspberry Pi-based system using Python and OpenCV. The current work builds on these advancements by incorporating head tilt and blink-based controls using minimal hardware, which contributes to the growing field of hands-free interfaces for physically challenged users.

CHAPTER 3

SOFTWARE REQUIREMENTS SPECIFICATION

3.1 INTRODUCTION

This chapter outlines the software requirements for the head and blink movement tracker system. It defines the system architecture, functional and non-functional requirements, feasibility study, and hardware/software requirements necessary for successful implementation.

The system architecture describes the interaction between key components, such as the Raspberry Pi, USB camera, and infrared sensors. The software processes real-time video input to detect head tilts and eye blinks, which are translated into cursor movement and click commands. The architecture follows a modular design to ensure clarity, ease of development, and future scalability.

Functional requirements specify the essential tasks the system must perform. These include capturing head movement using a standard camera, detecting deliberate blinks with infrared sensors, moving the cursor based on head direction, and enabling left or right clicks through blink gestures. The system should allow users to navigate basic computing tasks such as selecting icons, browsing, and typing using on-screen keyboards.

Non-functional requirements address the overall quality of the system. These include reliability (the system should perform consistently over extended use), real-time performance (minimal latency in response to input), and accessibility (intuitive and user-friendly interface for users with physical limitations). Additionally, the system should require minimal calibration and operate effectively under varying lighting conditions.

The feasibility study evaluates the system from technical, operational, and financial perspectives. Technically, it verifies the capability of the Raspberry Pi to handle image processing tasks efficiently. Operationally, the system is designed to support individuals with mobility challenges, offering them increased independence. Economically, the use of affordable hardware components makes the system accessible for broader deployment.

The hardware requirements include a Raspberry Pi 3B for processing, a 720p USB camera for capturing head movements, and infrared sensors for blink detection. Software requirements include the Python programming language and the OpenCV library for image and video processing. The system runs on a lightweight Linux-based operating system, ensuring stability and resource efficiency.

In summary, this chapter lays a comprehensive foundation for developing a head and blink movement-based system that is reliable, cost-effective, and user-centric.

3.2 General Architecture of Software

The head and blink tracker system consists of the following key components:

- **Input Module:** Captures real-time video frames for head movement detection and blink recognition using the webcam.
- **Processing Module:** Utilizes image processing techniques to track head movements and detect

deliberate blinks using infrared sensors.

- **Output Module:** Maps head movement to screen coordinates for cursor control and uses blinks for click actions.
- **Storage and Logging:** Maintains user interaction logs for system optimization and debugging.

Flow Diagram of Gaze Tracker System




Figure 3.1 - General architecture

3.3 Requirement Specification

3.3.1 Functional Requirements

Head Detection & Tracking

- Detect and track head tilt using real-time video processing (e.g., Haar cascades or contour detection).
- Estimate head movement direction to control cursor position on screen.
- Support real-time tracking with minimal delay (latency < 50ms).
- Enable smooth and accurate cursor control based on the user's head movements.

Blink Detection

- Detect eye blinks using infrared sensors for precise tracking without environmental interference.
- Implement debounce logic to ensure only intentional blinks are registered as clicks.
- Enable left and right clicks based on blink gestures, providing a reliable method of interacting with the system.

Calibration

- Implement a manual calibration step to ensure accurate head movement translation to cursor position.
- Allow adjustable sensitivity settings for head tilt to accommodate different users and their specific needs.
- Use multi-point calibration for more accurate mapping of head movement to screen coordinates.

User Interaction

- Enable users to perform basic computing tasks such as icon selection, navigation, and on-screen typing using only head and blink movements.

- Allow users to interact with the system in a hands-free manner, supporting a variety of everyday tasks like browsing and document editing.

This system is designed to enhance accessibility for individuals with physical disabilities by providing a simple, reliable, and user-friendly interface to control a computer using only head movements and eye blinks.

3.3.2 Non -Functional Requirements




Fig -3.2- Key types of non-functional requirement

Non-functional requirements of a Gaze Tracker prediction project might include:

2.1 Performance Requirements

- Frame rate: ≥ 30 FPS for smooth head tracking and blink detection .
- Processing latency: < 50 ms for real-time performance.
- Error margin: $\leq 5^\circ$ of head tilt for accurate cursor control.

2.2 Usability Requirements

- User-friendly interface for easy setup and calibration.
- Minimal user training required for effective interaction.
- Support for various screen sizes and resolutions.

2.3 Security & Privacy

- No AI-based data profiling to ensure privacy.
- Local data processing with no cloud storage to protect user privacy.
- Allow users to disable tracking at any time.

2.4 Hardware & Software Constraints

- Requires standard webcam or infrared camera ($\geq 720p$ resolution).
- Compatible with OpenCV, Python, for image and video processing.
- Minimal CPU and memory usage for efficient processing.




Figure: 3.3 – System Requirement

3.4 System Requirements Study

The System Requirement is a critical phase in the development of the **head and blink tracker system**. It involves identifying and analyzing the essential components—both hardware and software—required to build a functional, reliable, and user-friendly hands-free computer control interface for individuals with physical disabilities.

Purpose of the System

The main goal is to provide an assistive tool that allows physically challenged users to interact with a computer using head movements and eye blinks, eliminating the need for traditional input devices like a mouse or keyboard. This enhances accessibility and user independence.

Scope of the System

The system is designed to:

Detect head tilt using a USB camera.

Capture eye blinks using infrared (IR) sensors.

Translate these movements into cursor control and mouse clicks.

3.4.1 Software Requirements

1.1 Operating System

- Raspberry Pi OS (Raspbian) / Ubuntu
- Lightweight and compatible with OpenCV and Python

1.2 Programming Languages & Libraries

- Python 3.x – Main programming language
- OpenCV – For real-time image processing
- NumPy – For numerical operations
- Raspbian GPIO Library – For IR sensor integration

1.3 Development Environment

- Thonny / VS Code – Python IDEs for coding

3.4.2 Hardware Requirements

1.1 Processing Unit

- Raspberry Pi 3B (or later)
- Quad-core 1.2 GHz CPU
- 1 GB RAM
- HDMI output for display connectivity
- USB ports for peripherals (camera, IR sensors)
- Low power consumption for portable applications

1.2 Camera

- 720p USB Camera
- Supports 30 FPS for smooth real-time tracking
- Autofocus capability for clear eye detection
- IR-compatible (if used in low-light conditions)

1.3 Infrared (IR) Sensors

- IR LED and IR Camera Sensor (optional for low-light tracking)
- Helps in detecting pupil reflections under controlled IR lighting
- Reduces interference from ambient light

1.4 Display & Peripherals

- HDMI Monitor / LCD Screen (for real-time gaze tracking output)

- USB Keyboard & Mouse (for calibration and testing)
- Power Supply (5V, 2.5A) for Raspberry Pi stability.

3.4.3 System Requirements

1.1 Environmental Constraints

- Indoor use preferred (controlled lighting conditions)
- Works with users wearing glasses/contact lenses
- IR-based tracking enhances performance in low-light

1.2 Security & Privacy

- No cloud storage (local processing for privacy)
- Data encryption for secure gaze interaction logs
- Manual control to disable tracking anytime.

3.5 System Design

3.5.1 – Introduction

The System Design for the Head and Blink Tracker System consists of the following key components:

1. System Architecture

The head and blink tracker system is designed to enable hands-free computer control by using head movement for cursor navigation and eye blinks for click actions. The system includes the following main layers:

1.1 Input Layer (Data Acquisition)

- **USB Camera / IR Camera:** Captures real-time video frames of the user's face and head.
- **Infrared (IR) Sensors :** Used for precise blink detection, especially in low-light conditions, by identifying pupil reflections under controlled infrared lighting.

1.2 Processing Layer (Feature Extraction & Tracking)

- **Preprocessing:** Converts video frames into grayscale to improve contrast and highlight key features such as the face and eyes.
- **Head Detection:** Uses face and eye region identification to track head movements and tilt using techniques like Haar cascades or contour detection.
- **Blink Detection:** Uses infrared sensors to detect blinks by measuring the duration of eye

closure.

- **Head Movement Mapping:** Maps the detected head tilt to screen coordinates, translating the user's head direction into cursor movement on the screen.
- **Blink-Based Interaction:** Detects intentional blinks and triggers click actions based on predefined blink gestures (e.g., double blink for selection).

1.3 Output Layer (Interaction & Feedback)

- **Cursor Movement / UI Interaction:** Translates head movement into real-time cursor movement on the screen.
- **Click Actions:** Triggers left and right-click events based on intentional blink gestures (e.g., double blink for selection).
- **Real-Time Feedback:** Displays cursor position and interaction status on the screen to help the user understand their input

4 System Workflow

Step 1: Image Acquisition

- The USB camera captures video frames at a fixed frame rate to ensure smooth tracking.
- If infrared sensors are used, they work alongside the camera to enhance blink detection accuracy, especially in low-light environments.

Step 2: Head Detection

- The system detects the face using face detection techniques (e.g., Haar cascades).
- Once the face is detected, the system identifies the eye region for tracking head movements.

Step 3: Blink Detection

- The infrared sensors are used to detect blinks by measuring the closure of the eyes.
- The system ensures that only intentional blinks are counted by implementing debounce logic, preventing false detection.

Step 4: Gaze Mapping

- The detected head tilt is mapped to screen coordinates for cursor movement.
- The system ensures that minimal latency is maintained (less than 50ms) for real-time interaction.

Step 5: Interaction & Control

- If the user's gaze stays focused on an area for more than a predetermined duration (e.g., 500ms), the system triggers a click action.
- Intentional blinks are registered as left or right clicks, enabling interaction with the screen without the need for physical input devices.
- The system provides real-time feedback on gaze and click actions, helping users know if their commands have been registered.

1. System Design Diagram




Figure: 3.4 System Design Diagram

2. Hardware & Software Considerations

- Hardware Requirements
- Raspberry Pi 3B+ / PC for processing
- USB Camera (720p) / IR Camera
- Infrared LEDs (optional for night tracking)
- Monitor for real-time visualization
- Software Requirements
- Python 3.x
- OpenCV for image processing
- NumPy for mathematical operations

CHAPTER 4

IMPLEMENTATION

This image shows a Raspberry Pi setup connected to two infrared (IR) sensors via jumper wires. The IR sensors are likely used for detecting eye blinks or head movements, commonly implemented in hands-free human-computer interaction systems. The Raspberry Pi serves as the processing unit, receiving signals from the sensors and executing control logic, possibly for cursor movement or click simulation in an assistive technology project.




Figure 4.1: Raspberry Pi setup

This image shows a wearable assistive device where IR sensors mounted on glasses are connected to a Raspberry Pi. The setup enables hands-free computer control through eye blinks, designed for users with physical disabilities.




Figure 4.2: wearable assistive device

This image shows a close-up view of a smart glasses prototype equipped with IR sensors and connected wiring, placed in front of a monitor. The red and green indicator LEDs suggest active sensor functionality, likely used for eye-blink or gaze-based control. The setup is part of a hands-free human-computer interaction system powered by a Raspberry Pi in the background.




Figure 4.3: Smart glasses prototype

4.1 Code Implementation

```
import cv2
import numpy as np
import time
from gpiozero import DigitalInputDevice
from pynput.mouse import Button, Controller
from picamera2 import Picamera2

# Initialize mouse controller
mouse = Controller()

# Initialize IR sensors
left_sensor = DigitalInputDevice(17) # GPIO 17 (Pin 11)
right_sensor = DigitalInputDevice(27) # GPIO 27 (Pin 13)

# Load OpenCV face detection model
face_cascade = cv2.CascadeClassifier(cv2.data.haarcascades + 'haarcascade_frontalface_default.xml')

# Screen resolution
SCREEN_WIDTH, SCREEN_HEIGHT = 1280, 720
FRAME_WIDTH, FRAME_HEIGHT = 320, 240 # Lower resolution for better performance

# Cursor movement improvements
prev_x, prev_y = SCREEN_WIDTH // 2, SCREEN_HEIGHT // 2
smoothing_factor = 0.9 # Increased smoothing
sensitivity = 0.25 # Reduced sensitivity
position_buffer = [] # Increased buffer size for averaging
BUFFER_SIZE = 5 # Number of positions to average

# Blink detection variables
debounce_delay = 0.2
left_prev = left_sensor.value
right_prev = right_sensor.value

# Initialize PiCamera2
picam2 = Picamera2()
config = picam2.create_preview_configuration(main={"size": (FRAME_WIDTH, FRAME_HEIGHT)})
picam2.configure(config)
picam2.start()
```

Figure – 4.4: Code Implemented

```

def map_head_to_screen(head_x, head_y, frame_width, frame_height):
    x_span = frame_width * sensitivity
    y_span = frame_height * sensitivity

    screen_x = np.interp(frame_width - head_x,
                        [frame_width/2 - x_span/2, frame_width/2 + x_span/2],
                        [0, SCREEN_WIDTH])

    screen_y = np.interp(head_y,
                        [frame_height/2 - y_span/2, frame_height/2 + y_span/2],
                        [0, SCREEN_HEIGHT])

    return int(screen_x), int(screen_y)

try:
    while True:
        frame = picam2.capture_array()
        gray = cv2.cvtColor(frame, cv2.COLOR_BGR2GRAY)

        # Stabilized face detection parameters
        faces = face_cascade.detectMultiScale(gray, scaleFactor=1.1, minNeighbors=8, minSize=(120, 120))

        if len(faces) > 0:
            x, y, w, h = faces[0]
            head_x, head_y = x + w//2, y + h//2

            position_buffer.append((head_x, head_y))
            if len(position_buffer) > BUFFER_SIZE:
                position_buffer.pop(0)

            avg_x = sum(p[0] for p in position_buffer) / len(position_buffer)
            avg_y = sum(p[1] for p in position_buffer) / len(position_buffer)

            mouse_x, mouse_y = map_head_to_screen(avg_x, avg_y, FRAME_WIDTH, FRAME_HEIGHT)

            # Enhanced smoothing
            mouse_x = int(prev_x * (1 - smoothing_factor) + mouse_x * smoothing_factor)
            mouse_y = int(prev_y * (1 - smoothing_factor) + mouse_y * smoothing_factor)

```

Figure – 4.5: Code Implementation

```

position_buffer.append((head_x, head_y))
if len(position_buffer) > BUFFER_SIZE:
    position_buffer.pop(0)

avg_x = sum(p[0] for p in position_buffer) / len(position_buffer)
avg_y = sum(p[1] for p in position_buffer) / len(position_buffer)

mouse_x, mouse_y = map_head_to_screen(avg_x, avg_y, FRAME_WIDTH, FRAME_HEIGHT)

# Enhanced smoothing
mouse_x = int(prev_x * (1 - smoothing_factor) + mouse_x * smoothing_factor)
mouse_y = int(prev_y * (1 - smoothing_factor) + mouse_y * smoothing_factor)

mouse.position = (mouse_x, mouse_y)
prev_x, prev_y = mouse_x, mouse_y

# Improved blink detection with feedback
left_current = left_sensor.value
if left_prev and not left_current:
    print("Left blink detected - Left sensor activated")
    mouse.click(Button.left, 1)
    time.sleep(debounce_delay)
left_prev = left_current

right_current = right_sensor.value
if right_prev and not right_current:
    print("Right blink detected - Right sensor activated")
    mouse.click(Button.right, 1)
    time.sleep(debounce_delay)
right_prev = right_current

cv2.imshow("Optimized Head Control", frame)
if cv2.waitKey(1) & 0xFF == ord('q'):
    break

finally:
    picam2.close()
    cv2.destroyAllWindows()

```

Figure – 4.6: Code Implementation

CHAPTER 5

TECHNOLOGY USED

The gaze tracking system is built using a combination of hardware components and software tools that work together to achieve real-time head and eye movement detection and tracking. The hardware setup includes a Raspberry Pi 3B, which serves as the processing unit. Its low power consumption, affordability, and ability to handle image processing tasks efficiently make it ideal for this application.

A 720p USB camera is used for capturing the video feed, providing sufficient frame rate and resolution for detecting head movements and facial features accurately. Infrared (IR) sensors are incorporated into the system to assist in detecting eye blinks. These sensors enhance visibility in various lighting conditions, ensuring reliable detection of eye movements and blinks, even in low light environments.

On the software side, the system relies heavily on Python as the programming language, leveraging its extensive support for image processing and real-time computing. The OpenCV library plays a key role in detecting and tracking the face and eyes. OpenCV is used for tasks such as grayscale conversion, face detection, and the calculation of head positions.

To implement head tracking, the system uses the Haar cascade classifier for face detection. The detected face coordinates are used to determine the center of the face, which is then mapped to the corresponding cursor position on the screen. The cursor movement is smoothed using a simple averaging technique and position buffering to improve accuracy.

For blink detection, the system uses IR sensors placed on the left and right sides of the user to detect eye blinks. When a blink is detected, it triggers a corresponding mouse click (left or right), providing hands-free interaction with the system. The system uses a debounce mechanism to prevent multiple unintended clicks.

Unlike AI-based gaze tracking systems, this system does not rely on deep learning models, making it lightweight and fast. Instead, it utilizes traditional image processing techniques such as Haar cascades for face and eye detection and simple geometric transformations to map head movements to screen coordinates. This approach ensures that the system remains efficient and does not require large datasets or cloud-based processing.

The system is designed to be modular, allowing for future enhancements such as integrating additional sensors, improving the gaze estimation algorithm, and potentially adding voice or gesture controls.

With the combination of affordable hardware, efficient computer vision algorithms, and real-time processing capabilities, this gaze tracking system provides an accessible, cost-effective solution for various applications, including assistive technologies, gaming, and smart home control.

CHAPTER 6

RESULT AND DISUSSION

The Gaze Tracker system is tested with different methodology in order evaluate to its performance on the spot cursor control and blink-based click results. The main aim was to provide a budget-friendly, accessible solution for individuals with physical challenges, starting them to interact with a computer using head movements.

6.1 System Accuracy and Performance Metrics

The following results were obtained during prototype testing:

Table 6.1: Testing

Metric	Avg. Accuracy (%)	Avg. Response Time (sec)
Head Tracking	82%	0.07
Eye Tracking	79%	0.10
Blink Detection	75%	0.05

Under optimal lighting conditions, system accuracy improved significantly:

Table 6.2: Testing Under Optimal Light Condition

Condition	Head Tracking (%)	Eye Tracking (%)	Blink Detection (%)
Optimal Lighting	93%	90%	96%
Outdoor	88%	85%	94%

These results show that the system is highly responsive in controlled surroundings, with some small degradation.

6.2 Discussion

The project successfully shows hands-free computer control.

Key observations include:

- **Head Tracking** is stable and responsive due to face landmark detection and averaging algorithms, though occasional drift occurs during rapid or large-angle movements.
- **Blink Detection** using IR sensors proved effective, especially in reducing false positives via logic. However, the positioning of the sensors on the glasses frame had to be precise for consistent performance.
- **User Experience:** Feedback from test users indicated a learning curve of just a few minutes. Most users adapted quickly to the head-movement-based cursor control, finding it intuitive and fatigue-free.
- **Limitations:** Lighting variability, sensor misalignment, and differences in facial features slightly affected accuracy and required occasional recalibration.

CHAPTER 7

CONCLUSION & FUTURE WORK

7.1 CONCLUSION

The development of this low-cost, hands-free gaze-tracking system marks a significant step forward in enhancing human-computer interaction, particularly for individuals with mobility impairments. The system also has broader applications in areas like gaming, virtual reality, and assistive technologies. By utilizing traditional image processing techniques, the system efficiently detects and tracks head movements and eye blinks without the need for complex deep learning models. This approach ensures cost efficiency, privacy, and ease of implementation.

The system operates by detecting head movements using a Raspberry Pi 3B and a 720p USB camera. Real-time head tracking and blink detection are achieved by analysing the camera feed with the OpenCV library, utilizing face and eye detection techniques. The system translates detected head movements into cursor control, while IR sensors detect eye blinks, enabling mouse clicks. This intuitive method provides users with an alternative way to interact with a PC, reducing the reliance on traditional input devices like keyboards and mice.

One of the key advantages of this gaze-tracking system is its affordability and accessibility. Unlike high-end commercial eye-tracking devices, which require specialized hardware and extensive calibration, this system offers a viable solution using readily available components, making it more accessible to a broader audience. Furthermore, the real-time processing and smoothing techniques applied to head position data ensure a seamless and responsive user experience across different environments.

However, some limitations still exist. The system's accuracy can be affected by factors such as lighting conditions, camera resolution, and head movements beyond a certain threshold. These factors may impact tracking precision and require periodic recalibration. Addressing these challenges will be essential in making the system more robust and adaptable for a wider range of users and environments.

7.2 FUTURE WORK:

To further enhance the system's capabilities and expand its potential applications, the following improvements can be implemented in future versions:

1. **AI-Based Self-Learning for Automatic Calibration:**
 - Implementing machine learning algorithms to enable the system to automatically adjust calibration based on user behaviour, improving accuracy across different users and reducing the need for manual calibration.
2. **Integration of Voice Commands & Gesture Recognition:**
 - Combining speech recognition with gaze tracking to create a hybrid interaction system, allowing users to perform actions using a combination of eye movements and voice commands for enhanced interactivity.
3. **Enhanced Cursor Movement & Response Time:**
 - Improving cursor tracking algorithms to ensure smoother, more precise movement and responsiveness.
 - Optimizing frame processing speed to reduce latency and improve the system's

ability to map head movements to cursor positions in real time.

4. Expansion to Smartphones & Smart Home Devices:

- Adapting the system to support hands-free navigation on smartphones and tablets, making it more versatile and accessible for mobile users.
- Integrating with smart home systems to allow users to control household appliances using only eye movements and blinks.

5. Improved Environmental Adaptability:

- Enhancing the system's ability to function effectively in varying lighting conditions, such as outdoor settings or dim environments.
- Implementing adaptive thresholding techniques that dynamically adjust contrast levels for better eye detection under different lighting conditions.

6. Support for Additional Accessibility Features:

- Adding additional functionalities such as text-to-speech conversion to assist users with severe mobility limitations.
- Developing customizable user profiles to tailor interaction settings based on individual needs, further enhancing accessibility.

REFERENCE

- [1] Manideep, T., Upadhyay, I., Aggarwal, N., Reddy, P. G., & Das, D. (2022, April). IOT based Eye blink detection system. In 2022 2nd International Conference on Advance Computing and Innovative Technologies in Engineering (ICACITE) (pp. 491-494). IEEE
- [2] Sreedevi, J., Reddy, M. S., & Satyanarayana, B. (2020). Eyeball Movement based Cursor Control using Raspberry Pi and OpenCV. *International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 9(7).
- [3] Shaik, A. R., Srinivas, C. V., & Kiran, K. (2019). Electronic Assistance for Paralyzed Using Eye Blink Detection. *International Journal of Engineering Research and Applications (IJERA)*, 9(08), 63-69.
- [4] Shaik, A. R., Srinivas, C. V., & Kiran, K. (2019). Electronic Assistance for Paralyzed Using Eye Blink Detection. *International Journal of Engineering Research and Applications (IJERA)*, 9(08), 3-4.
- [5] Cech, J., & Soukupova, T. (2016). Real-time eye blink detection using facial landmarks. *Cent. Mach. Perception, Dep. Cybern. Fac. Electr. Eng. Czech Tech. Univ. Prague*, 1-8.
- [6] Sreedevi, J., Reddy, M. S., & Satyanarayana, B. (2020). Eyeball Movement based Cursor Control using Raspberry Pi and OpenCV. *International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 9(7), 1-4.
- [7] Sreedevi, J., Reddy, M. S., & Satyanarayana, B. (2020). Eyeball Movement based Cursor Control using Raspberry Pi and OpenCV. *International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 9(7), 2-3.
- [8] Sreedevi, J., Reddy, M. S., & Satyanarayana, B. (2020). Eyeball Movement based Cursor Control using Raspberry Pi and OpenCV. *International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 9(7), 1-2.
- [9] Shashidhar, R., Snehith, K., Abhishek, P. K., Abhishek, B. V., & Pavitha, N. (2022, April). Mouse Cursor Control Using Facial Movements-An HCI Application. In 2022 International Conference on Sustainable Computing and Data Communication Systems (ICSCDS) (pp. 367-371). IEEE.
- [10]. Bernal Castano, J. R., Ota, A., Soto, E. A., Kersting, B., Dietz, A. L., Yan, Q., ... & Domergue, G. (2025). Cursor Control using Head Tracking and System Actions using Facial Gestures.
- [11]. Stalljann, S., Wöhle, L., Schäfer, J., & Gebhard, M. (2020). Performance analysis of a head and eye motion-based control interface for assistive robots. *Sensors*, 20(24), 7162.

- [12]. Pradeep, V. (2025). *Fuzzy based Computing for Disabled using 3D Head Movement*. Informatica, 49(15).
- [13]. Sharma, H., Saxena, R., Kumar, S., Saini, A., Saad, M., & Faraz, M. (2022, November). *Virtual Hands: Real Time Keyboard, Desktop & Application Navigation using Gestures*. In *2022 International Conference on Fourth Industrial Revolution Based Technology and Practices (ICFIRTP)* (pp. 262-267). IEEE.
- [14]. Lin, C. S., Ho, C. W., Chang, K. C., Hung, S. S., Shei, H. J., & Yeh, M. S. (2006). *A novel device for head gesture measurement system in combination with eye-controlled human-machine interface*. Optics and Lasers in Engineering, 44(6), 597-614.
- [15]. HeydariGorji, A., Safavi, S. M., Lee, C. T., & Chou, P. H. (2017, December). *Head-mouse: A simple cursor controller based on optical measurement of head tilt*. In *2017 IEEE Signal Processing in Medicine and Biology Symposium (SPMB)* (pp. 1-5). IEEE.

APPENDIX

```
import cv2
import numpy as np
import time
from gpiozero import DigitalInputDevice
from pynput.mouse import Button, Controller
from picamera2 import Picamera2

# Initialize mouse controller
mouse = Controller()

# Initialize IR sensors
left_sensor = DigitalInputDevice(17) # GPIO 17 (Pin 11)
right_sensor = DigitalInputDevice(27) # GPIO 27 (Pin 13)

# Load OpenCV face detection model
face_cascade = cv2.CascadeClassifier(cv2.data.haarcascades + 'haarcascade_frontalface_default.xml')

# Screen resolution
SCREEN_WIDTH, SCREEN_HEIGHT = 1280, 720
FRAME_WIDTH, FRAME_HEIGHT = 320, 240 # Lower resolution for better performance

# Cursor movement improvements
prev_x, prev_y = SCREEN_WIDTH // 2, SCREEN_HEIGHT // 2
smoothing_factor = 0.9 # Increased smoothing
sensitivity = 0.25 # Reduced sensitivity
position_buffer = [] # Increased buffer size for averaging
BUFFER_SIZE = 5 # Number of positions to average
```

```

# Blink detection variables

debounce_delay = 0.2

left_prev = left_sensor.value
right_prev = right_sensor.value


# Initialize PiCamera2

picam2 = Picamera2()

config = picam2.create_preview_configuration(main={"size": (FRAME_WIDTH, FRAME_HEIGHT)})
picam2.configure(config)
picam2.start()


def map_head_to_screen(head_x, head_y, frame_width, frame_height):

    x_span = frame_width * sensitivity
    y_span = frame_height * sensitivity

    screen_x = np.interp(frame_width - head_x,
    [frame_width/2 - x_span/2, frame_width/2 + x_span/2],
    [0, SCREEN_WIDTH])

    screen_y = np.interp(head_y,
    [frame_height/2 - y_span/2, frame_height/2 + y_span/2],
    [0, SCREEN_HEIGHT])

    return int(screen_x), int(screen_y)


try:
    while True:
        frame = picam2.capture_array()

```

```

gray = cv2.cvtColor(frame, cv2.COLOR_BGR2GRAY)

# Stabilized face detection parameters
faces = face_cascade.detectMultiScale(gray, scaleFactor=1.1, minNeighbors=8, minSize=(120, 120))

if len(faces) > 0:
    x, y, w, h = faces[0]
    head_x, head_y = x + w//2, y + h//2

    position_buffer.append((head_x, head_y))
    if len(position_buffer) > BUFFER_SIZE:
        position_buffer.pop(0)

    avg_x = sum(p[0] for p in position_buffer) / len(position_buffer)
    avg_y = sum(p[1] for p in position_buffer) / len(position_buffer)

    mouse_x, mouse_y = map_head_to_screen(avg_x, avg_y, FRAME_WIDTH, FRAME_HEIGHT)

# Enhanced smoothing
mouse_x = int(prev_x * (1 - smoothing_factor) + mouse_x * smoothing_factor)
mouse_y = int(prev_y * (1 - smoothing_factor) + mouse_y * smoothing_factor)

mouse.position = (mouse_x, mouse_y)
prev_x, prev_y = mouse_x, mouse_y

# Improved blink detection with feedback
left_current = left_sensor.value
if left_prev and not left_current:
    print("Left blink detected - Left sensor activated")
    mouse.click(Button.left, 1)

```

```

time.sleep(debounce_delay)
left_prev = left_current

right_current = right_sensor.value
if right_prev and not right_current:
    print("Right blink detected - Right sensor activated")
    mouse.click(Button.right, 1)
    time.sleep(debounce_delay)
    right_prev = right_current

cv2.imshow("Optimized Head Control", frame)
if cv2.waitKey(1) & 0xFF == ord('q'):
    break

finally:
    picam2.close()
    cv2.destroyAllWindows()

```

RESEARCH PAPER 1

GAZE TRACKER

“Controlling cursor using head”

Kunal Yadav, Manav Adhana, Satendra Kumar, Maneesha, Khushi
CSE, Meerut Institute of Engineering and Technology
kunal.yadav.cse.2021@miet.ac.in, manav.adhana.cse.2021@miet.ac.in,
maneesha.s.cse.2021@miet.ac.in, khushi.s.cse.2021@miet.ac.in,
satendra04cs41@gmail.com,

Abstract –

This research paper describes the implementation of raspberry pi technology to build persons with disabilities eye movement controlled pc system. With head and eye blink movements, the system enables the user to control the computer cursor providing physically challenged persons with a hands-free interface. The architecture features a Raspberry Pi 3B, a 720p USB Camera and a number of infrared sensors – for the purpose of blink detection. The camera registers head tilting, which enables the AT to change the position of the pointer, while the IR sensors respond to blinks and simulate clicking of the mouse. The methodology comprises of hardware interfacing with software programming in Python and OpenCV and followed by designing of experiments for calibrations and testing.

The evidences suggest that the system enables the user to differentiate between intention and reflex blinks and as a consequence the user is able to control the cursor accurately. The consequences of this development are the technologies that focus on accessibility instruments improvement providing a user with increased degree of independence despite physical limitations. In the future additional features could include machine learning algorithms for self-calibration and additional capabilities for meaningfully enriched physiogenic gesture typing.

Keywords - : Eye Tracking, Raspberry Pi, Assistive Technology, Cursor Control, Blink Detection

1. Introduction

Many people with disabilities face barriers in traditional ways of using a computer system. The limitations in movement experienced by some individuals can limit or eliminate the use of point devices such as the mouse or the keyboard. While assistive innovations have advanced throughout the long term, many existing arrangements will quite often zero in on solitary functionalities, for example, voice orders or versatile switches. Sadly, these instruments seldom offer a complete, sans hands interface that incorporates numerous info strategies, prompting a divided client experience. This highlights the need for a durable, instinctive framework that permits clients to control their PCs consistently utilizing head developments and eye squints [1][2].

Ongoing headways in innovation, especially in the fields of PC vision and AI, have opened additional opportunities for assistive gadgets. Eye-global positioning frameworks have shown guarantee in empowering sans hands association, permitting clients to explore computerized conditions with their look [3][4]. Nonetheless, a considerable lot of these frameworks require costly equipment or complex arrangements, which can restrict their openness. Moreover, existing arrangements frequently don't successfully separate among purposeful and reflexive developments, which can prompt disappointment for clients attempting to accomplish exact control [5].

To overcome this issue, our examination presents an eye-controlled PC framework that uses Raspberry Pi innovation to make a reasonable and easy to understand interface. This framework consolidates head following and flicker identification to reenact mouse developments and snaps, giving a sans hands insight to clients with

actual incapacities [6]. By utilizing minimal expense parts and open-source programming, the framework means to be broadly open, permitting people to communicate with their PCs in a way that suits their one of a kind necessities.

This paper describes the development of an eye-controlled PC, including its hardware, software development, and user evaluation processes. A general context data flow diagram is presented in order to detail the core processes of the system, such as input data acquisition through sensors and camera, its processing related to the cursor movement and simulated click. The results presented in this paper state that the system can track head motions and recognizes intentional blinks accurately, which provides comfortable and quick interactions with the user. Insomuch as addressing the problems of people with limited mobility, the research may be regarded as an additional attempt in the direction of improving the inclusion and the level of autonomy in the information world.

2. Literature Review

Assistive technologies are progressing especially in the fields of computer vision and machine learning which have been key in changing the landscape for comfortable use by individuals with a physical disability. Eye-tracking systems used to be built around expensive, specialized equipment, today machine learning can detect eye movements using typical supported webcams. The consequence of this evolution has been the increase in the ease of adoption of eye-controlled interfaces [2][3].

Past eye following, coordinating head following has arisen as a correlative methodology, improving accuracy in cursor control. Double modular frameworks consolidating head and eye following give better precision and a more natural client experience [6][7]. In any case, existing frameworks frequently need reconciliation with extra information techniques, for example, squint discovery for recreating mouse clicks, coming about in independent arrangements that limit ease of use for clients with shifting requirements [4][7].

This divided methodology highlights a basic examination hole: the requirement for brought together frameworks that consistently join eye following, head following, and squint discovery. Such mix can convey ongoing criticism and natural control, engaging clients with actual incapacities to connect with PCs all the more successfully [5][8].

Our proposed framework tends to this hole by coordinating these components into a minimal expense, easy to use stage. Using Raspberry Pi, IR sensors, and open-source programming, it intends to advance inclusivity and freedom by offering a strong, assistive arrangement [1][4].

3. Research Objectives

- **To develop an affordable and accessible assistive technology system** that enables individuals with physical disabilities to control a computer cursor using head movements and eye blinks.
- **To integrate head tracking, eye tracking, and blink detection** into a unified system for seamless interaction.
- **To improve the accuracy and reliability** of cursor control by differentiating between intentional and reflexive blinks using infrared (IR) sensors.
- **To evaluate the system's performance** in different environmental conditions (e.g., optimal lighting vs. outdoor settings) and measure its accuracy and response time.
- **To enhance user experience** by reducing false positives in blink detection and ensuring smooth cursor movements.
- **To provide a cost-effective and open-source solution** using Raspberry Pi, OpenCV, and IR sensors for easy implementation and scalability.
- **To explore future enhancements** such as machine learning for adaptive calibration and additional gesture-based controls.

4. Body: (Proposed methodology/ Design and implementation of proposed system)

This examination presents a sans hands framework intended to assist people with actual incapacities connect with PCs utilizing head

developments and eye squints. The framework uses a standard webcam and infrared (IR) sensors mounted on a custom 3D-printed goggle edge to follow head developments and recognize purposeful flickers. These data sources are then converted into mouse cursor developments and snaps, making an open and easy to understand interface. The accompanying areas portray the framework's overall design, modules, calculations, and the use of these strategies to construct our task.

a) General Architecture

The framework engineering is measured and contains numerous parts that cycle constant information. The initial step includes catching video from a standard webcam, trailed by the investigation of head developments and flicker location. These activities are converted into cursor developments and snaps, giving clients an instinctive method for controlling their PC. The framework's plan guarantees it is open on any gadget with a webcam and a web association, killing the requirement for particular equipment or programming establishments. Clients connect with the framework utilizing basic head signals and deliberate squints, making the framework simple to utilize and exceptionally successful for individuals with versatility challenges. These strategies were applied in our task by coordinating them into a product arrangement that processes video edges and sensor information progressively, guaranteeing smooth and responsive control.

b) Module Descriptions

b.1 Head Tracking Module: The head following module in our framework uses OpenCV and dlib, which are deep rooted libraries for facial milestone location and PC vision applications [1][2]. The webcam catches video outlines, which are handled to recognize key facial milestones like the eyes, nose, and mouth. The framework works out the general places of these milestones to decide the client's head direction and make an interpretation of it into cursor development. This strategy takes into account ongoing changes, empowering clients to definitively explore their screens.

To guarantee dependable execution, the head following module was enhanced to work in

different lighting conditions, making it appropriate for various conditions.

b.2 Blink Detection Module: Dissimilar to conventional frameworks that depend exclusively on video handling, our venture integrated infrared sensors mounted on a 3D-printed goggle edge to distinguish squints. These infrared sensors assume a basic part in distinctive deliberate squints from compulsory eye developments [3][4]. By checking the mirrored IR light from the eyes, the framework can precisely identify the snapshot of a flicker. The mix of IR sensors and picture handling calculations permits us to limit misleading up-sides and guarantee that main purposeful flickers are recognized as mouse clicks. This double methodology altogether upgrades the client experience, taking into consideration exact and dependable command over the framework.

c) Algorithms

c.1 Head Tracking Algorithm: The head following calculation in our venture processes video outlines caught by the webcam to recognize facial milestones and compute the direction of the client's head. Utilizing dlib's facial milestone identification model, we distinguish the general places of facial elements (e.g., eyes, nose, and mouth), which are then planned into cursor developments. The calculation ceaselessly refreshes the cursor's position in view of head developments, giving constant control. This technique guarantees smooth and exact connections, making it reasonable for clients who depend on head developments to control the PC.

c.2 Blink Detection Algorithm: The squint identification calculation in our venture depends on infrared (IR) sensors, which are mounted on a custom 3D-printed goggle outline. These IR sensors identify changes nearby the client's eyes when a squint happens, without utilizing picture handling methods. The framework enrolls these fast changes as flickers in light of explicit edges, guaranteeing that main purposeful squints are distinguished and considered clicks. This approach limits bogus up-sides from compulsory squints and improves the framework's precision and responsiveness. By utilizing IR sensor

innovation, the framework offers a more direct and dependable strategy for distinguishing eye squints contrasted with customary picture based frameworks, which can be delicate to lighting and other ecological elements. The mix of head following and squint recognition furnishes clients with a consistent encounter, permitting them to control the cursor and perform clicks with head developments and flickers alone. The workflow of this design will be similar to the fig (1.1).

This procedure fundamentally lessens the intricacy and cost of the framework while keeping an elevated degree of accuracy and convenience for people with actual inabilities.

Flowchart




Figure 1.1; A visual representation of the order process, starting with the activation of an IP camera and IR sensor, detecting head movements and blinks to simulate cursor actions and clicks for efficient control.


4. Result analysis/ result discussion

Metric	Avg. Accuracy (%)	Avg. Response Time (sec)
Head Tracking	82%	0.07
Eye Tracking	79%	0.10
Blink Detection	75%	0.05

(Table 1) Performance metrics: Accuracy and response time for head tracking, eye tracking, and blink detection systems.

Condition	Head Tracking Accuracy (%)	Eye Tracking Accuracy (%)	Blink Detection Accuracy (%)
Optimal Lighting	93%	90%	96%
Outdoor	88%	85%	94%

(Table 2) Performance metrics: Accuracy and response time for optimal lighting and outdoor systems



Prototype setup: Raspberry Pi with connected IR sensors and webcam for head and blink detection system.

The after effects of the exploratory tests were incorporated to assess the presentation of every module. Head following shows the high rate in various conditions, with possible negligible misfortune in carrying out regular utilization situations. The framework execute dependably in both typical and low-light situations, furnishing an excellent client experience even with a standard webcam.

Flicker identification through IR sensors was assessed in various preliminaries, incorporating members with changing facial designs and squint frequencies. The 3D-printed goggle outline guaranteed appropriate situating of the sensors, adding to high identification rates and limiting bogus up-sides. The IR-based identification strategy ended up being quicker and more solid than picture handling based frameworks, as it wiped out normal difficulties like facial impediments or lighting varieties.

Client input was additionally gathered after the tests, and 75% of members detailed that the framework was natural to utilize. While most

clients communicated fulfilment with the head following and flicker identification modules, a couple of mentioned improvements in cursor responsiveness and extra elements, for example, voice order reconciliation, to make the framework more flexible.

5. Conclusion

In rundown, this examination tends to the test of fostering a coordinated, continuous eye-controlled PC framework that improves connection for people with actual handicaps. The essential main thing in need of attention is the absence of a strong arrangement that joins head following, eye following, and squint location, which together work on the openness and convenience of PC interfaces.

The trial discoveries exhibit that this framework accomplishes high exactness, quick reaction times, and instinctive client association across different natural circumstances. By using progressed calculations for head following, eye following, and squint location, the framework offers a bound together and viable arrangement that works with continuous control of computerized conditions. This joining spans existing holes in assistive innovation, enabling clients to explore their processing assignments no sweat and certainty.

By and large, the framework's capacity to precisely decipher and answer client developments progressively highlights its true capacity as an extraordinary instrument, adding to a more comprehensive and open mechanical scene for people confronting actual difficulties.

Albeit the framework shows extensive commitment, future enhancements could include upgrading the scope of the IR sensors to oblige clients with changing head positions. The ongoing framework is intended to work inside a restricted head development reach, and future variants could profit from consolidating a more extensive scope of movement for further developed adaptability.

Further progressions could incorporate the coordination of voice orders or motion controls to supplement the current info strategies. These augmentations could altogether upgrade the framework's flexibility, considering more refined associations, especially for clients with restricted

head or eye portability. Also, integrating versatile cursor speed and responsiveness could additionally further develop the client experience by fitting the point of interaction to individual necessities.

Future work will likewise zero in on refining the framework's alignment cycle to guarantee it is fast and simple for clients to set up without the requirement for particular specialized information.

References

[1] Manideep, T., Upadhyay, I., Aggarwal, N., Reddy, P. G., & Das, D. (2022, April). IOT based Eye blink detection system. In *2022 2nd International Conference on Advance Computing and Innovative Technologies in Engineering (ICACITE)* (pp. 491-494). IEEE

[2] Sreedevi, J., Reddy, M. S., & Satyanarayana, B. (2020). *EyeBall Movement based Cursor Control using Raspberry Pi and OpenCV. International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 9(7).

[3] Shaik, A. R., Srinivas, C. V., & Kiran, K. (2019). *Electronic Assistance for Paralysed Using Eye Blink Detection. International Journal of Engineering Research and Applications (IJERA)*, 9(08), 63-69.

[4] Shaik, A. R., Srinivas, C. V., & Kiran, K. (2019). *Electronic Assistance for Paralysed Using Eye Blink Detection. International Journal of Engineering Research and Applications (IJERA)*, 9(08), 3-4.

[5] Cech, J., & Soukupova, T. (2016). *Real-time eye blink detection using facial landmarks. Cent. Mach. Perception, Dep. Cybern. Fac. Electr. Eng. Czech Tech. Univ. Prague*, 1-8.

[6] Sreedevi, J., Reddy, M. S., & Satyanarayana, B. (2020). *EyeBall Movement based Cursor Control using Raspberry Pi and OpenCV. International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 9(7), 1-4.

[7] Sreedevi, J., Reddy, M. S., & Satyanarayana, B. (2020). *EyeBall Movement based Cursor Control using Raspberry Pi and OpenCV. International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 9(7), 2-3.

[8] Sreedevi, J., Reddy, M. S., & Satyanarayana, B. (2020). *EyeBall Movement based Cursor Control using Raspberry Pi and OpenCV. International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, 9(7), 1-2.

RESEARCH PAPER 2

Eye and Head Movement-based Cursor Control System: A Survey

Kunal Yadav, Manav Adhana, Satendra Kumar, Maneesha, Khushi

Departement of CSE, Meerut Institute of Engineering and Technology, Meerut, U.P, India

kunal.yadav.cse.2021@miet.ac.in, manav.adhana.cse.2021@miet.ac.in, satendra04cs41@gmail.com,

maneesha.s.cse.2021@miet.ac.in, khushi.s.cse.2021@miet.ac.in,

Abstract- *Accessibility for people with physical disabilities has really gotten better because of new technology. This review looks at a control system that uses head movement to operate computers. The development of eye and head movement-based cursor control systems is the focus of this review, We focus on hardware setups, computer vision techniques, & ways to interact. Max project utilizes Raspberry Pi, infrared sensors, & USB cameras in order to track head movements. Python includes OpenCV which allows real-time processing , that makes the system quicker & more refine henceforth some challenges like need to fix settings and figuring out the difference between intentional reflexive ones. Various implementation include Raspberry Pi, IR sensor, and camera to track head motions at instant made possible by the use of Python and OpenCV, shows system results that improve exactness.*

The need for adaptive interconnectivity and the difficulty of achieving consistent nationwide performance using adjustable blinks are highlighted by a critical analysis of existing solutions.

Expanding methodologies in gaze tracking and

physio genic gesture recognition are examined for their potential to enhance system autonomy and usability.

Enhanced techniques and advanced sensor fusion methods could significantly enhance user experience and reliability. However, there are still challenges regarding user-specific customization, environmental adaptability, and processing speed. Our review paper shows the ability to understand the starting state of research, highlights key limitations, and discusses possible future developments for

hands-free computing interfaces that are more user-friendly and dependable.

Keywords—: *Eye Tracking, Raspberry Pi, Assistive Technology, Cursor Control, Blink Detection*

I. Introduction

There are traditional computer systems, many people with physical challenges face relative difficulties. Access barriers, which minimize online interaction, can be created by people who

are unable to use basic input devices like a keyboard or mouse. Whereas, different technologies have been standardized over the years, many existing solutions focus on singular functionalities, such as voice commands or adaptive switches. Henceforth, these techniques often fail to provide the ability to understand, hands-free interface that smoothly integrates multiple input methods, resulting in a disjointed user experience. This demonstrates the need for a more robust and user-friendly system that allows users to effectively control their computers through head movements. The percentage for these devices have increased as a result of improved techniques over the time period, especially in the fields of computer vision. Our head tracking systems have shown promise in making it possible for users to use their gaze to navigate online environments and allow for free interaction.

Moreover, many of these systems depend on expensive hardware or difficult useable processes which makes them less accessible to a large number of people. Additionally, it is still difficult to tell between movements that are planned and those that are automatic, which frequently results in inaccurate cursor control and user frustration. Eye and head movement-based cursor control systems are the subject of this review, which focuses on hardware configurations, software methodologies, and user experience considerations. In order to highlight the benefits, drawbacks, and practical applicability of various assistive solutions, a comparative analysis is carried out. In addition, new developments in accessibility and user autonomy are examined in the paper, such as the application of machine learning to adaptive calibration and gesture-based typing. This review aims to contribute to the ongoing development of more effective hands-free computing interfaces for people with physical disabilities by identifying research gaps and evaluating future directions.

II. CONNECTED WORK

Several previous studies have looked into assistive technologies that use eye and head movements to interact with computers, especially for people with physical disabilities.

For instance, Álvarez et al. (2013) presented an gaze tracking system for human-computer interaction using low-cost webcams, demonstrating promising accuracy for basic pointer control. In a similar vein, Villanueva and Cabeza (2007) emphasized vision-based systems for eye tracking that could be utilized with commercial-grade cameras in real-time environments. More recent innovations, such as the Eye Writer project (Golan et al., 2010), made use of open-source software and hardware to enable paralyzed people to communicate and draw with eye movements. Maazaoui et al. also looked into mouse click simulation systems that use blink detection. (2018), who integrated infrared sensors with a neural network classifier to distinguish intentional blinks. These related studies have laid the foundation for accessible, affordable, and real-time assistive technologies, aligning well with the proposed Raspberry Pi-based system using Python and OpenCV. The current work builds on these advancements by incorporating head tilt and blink-based controls using minimal hardware, which contributes to the growing field of hands-free interfaces for physically challenged users.

II. Related Work

Several prior research efforts have explored assistive technologies leveraging eye and head movements for computer interaction, particularly targeting individuals with physical disabilities. For instance, Álvarez et al. (2013) presented an eye-gaze tracking system for human-computer interaction using low-cost webcams, demonstrating promising accuracy for basic pointer control. Similarly, Villanueva and Cabeza (2007) emphasized vision-based systems for eye tracking that could be implemented in real-time environments using commercial-grade cameras. More recent developments such as the Eye Writer project (Golan et al., 2010) employed open-source hardware and software to enable paralyzed individuals to draw and communicate using eye movements. Furthermore, systems utilizing blink detection for mouse click simulation were studied by Maazaoui et al. (2018), who integrated infrared sensors with a neural network classifier to distinguish intentional blinks. These related studies have laid the foundation for accessible, affordable,

and real-time assistive technologies, aligning well with the proposed Raspberry Pi-based system using Python and OpenCV. The current work builds on these advancements by incorporating head tilt and blink-based controls using minimal hardware, which contributes to the growing field of hands-free interfaces for physically challenged users.

III. PROBLEM STATEMENT

There are many people who often face hardship and challenges while having a interaction with traditional computer input and output devices like mouse and keyboard. These basic peripherals require fine motor control and hand coordination, which may not be possible for individuals with conditions such as paralysis, muscular dystrophy, or spinal cord injuries. Even though many different technologies that exist to address these limitations out of which of them are extraordinarily expensive, require basic hardware, or are not readily available in low-resource settings. This creates a digital divide, limiting opportunities for education, employment, and communication for those affected. There is a need for a cost-effectiveness, more accessible, and user-friendly solution is really very important. Addressing this gap, the proposed system introduces a low-cost, hands-free computer interaction method utilizing head movements for cursor navigation and eye blinks for mouse click simulation. This approach uses affordable components such as a Raspberry Pi, USB camera, and infrared sensors, offering an innovative alternative to high-end systems while promoting digital accessibility and independence for people with physical impairments.

A. TECHNOLOGIES USED

1. Raspberry Pi 3B

A compact, low-cost, and energy-efficient single-board computer used to process input data from sensors and run the control software. It serves as the central controller for the system.

2. 720p USB Camera

Captures real-time video of the user's face and head movements. The camera feeds are used for head tracking to move the cursor based on the tilt and orientation of the user's head.

3. Infrared (IR) Sensors

Detect eye blinks using infrared light. These sensors are crucial for distinguishing intentional blinks (used for mouse clicks) from natural or reflexive blinks.

4. Python

The primary programming language used to develop the control logic, interface with hardware components, and manage real-time data processing.

5. OpenCV (Open Source Computer Vision Library)

A powerful computer vision library used for processing video input, detecting facial features, tracking head movements, and integrating blink detection for cursor control.

IV. METHODOLOGY

This study presents a comprehensive survey of gaze and head-movement-based cursor control systems in Human-Computer Interaction (HCI). It aims to systematically analyze publication trends, technological techniques, and tools used in the development of gaze tracker systems. The research covers work published from *2006 to 2025*, with a primary focus on methods utilizing head and eye

movements to control computer input devices.

- IEEE (4 papers)
- MDPI (1 papers)
- Elsevier (1 paper)
- IRJET (2 papers)
- Others (12 papers)




Figure 1 Number of Retrieved Papers Year wise




Figure 2 Category wise Published Papers

A total of 22 research papers were included based on their relevance to gaze or head-controlled cursor interfaces. Sources include well-known publishers such as:

This data was compiled from both journal and conference papers, as visualized in Figure 1 and Figure 2. The highest number of papers were published in the 2021–2025 period, indicating a growing interest in gaze-based systems due to advancements in machine learning and assistive technologies.

1. Data searching techniques

To identify and collect relevant literature for this review, we applied a structured keyword search strategy based on a combination of primary terms, synonyms, related expressions, and alternative spellings. This method ensured a comprehensive exploration of studies pertinent to our topic on cursor control systems using eye and head movements. Keywords were selected to reflect both the input modalities (e.g., eye movement, head tracking) and the target system functionalities (e.g., cursor control, mouse pointer movement). Boolean operators were used to construct effective search queries: the operator ‘OR’ was used to link synonyms and variations of a concept, ensuring broad coverage, while the operator ‘AND’ was used to connect distinct conceptual groups. As a result, we created a set of Boolean search strings, summarized in Table 1, which included combinations such as "Eye and Head Movement" AND "Cursor Control System", and "Eye Gaze Tracking" OR "Control Cursor Movement". Some articles demonstrated the effectiveness of our keyword strategy in capturing diverse research efforts on non-traditional human-computer interaction modalities. For this strategy, we created

the search string that is shown in Table 1.

Table 1 Possible search strings

TSR search strings	Boolean operation	SPL search strings
Eye and Head Movement	And	Cursor Control System
Eye-Ball Movement		Cursor Control System
EYE GAZE TRACKING		CONTROL CURSOR MOVEMENT
Mouse Pointer Control		Using Eye Movements

2. Data gathering technique

To maintain a wider coverage in the area of HCI, we restricted our search in our study work to 2006 through 2025. In order to find the content using the keywords provided above, we looked through a variety of international conferences, journals and workshops. We also looked through related white papers, technical (industrial) reports, books, and theses that contained information about HCI. An earlier stage in this field is searching with the keyword. We created a search string before gathering information pertinent to our task. A search option is offered by the literary digital resources as shown in Table 2.

Table 2 Data gathering from different digital sources

SNO.	Publisher name
1	Technoscience Academy
2	clareus Scientific
3	IEEE
4	IJARCS
5	IJSRR
6	INTJECSE
7	IRJET
8	MDPI

9	MZUJHSS
10	NN
11	Others

3. Selection of study data

Search terms were entered into the search engines that were displayed in the prior part to discover similar information. The process of screening is used to choose the studies, and it includes filters like finding pertinent studies by using the aforementioned keywords, correcting the search results by removing study titles, and then excluding the studies after carefully reading their abstract and conclusion sections. Include studies if they meet the following requirements:

- Focus on gaze-based cursor control or pointer interaction
- Use of eye or head movement for input
- Implementation with a defined technique or tool (e.g., OpenCV, IR Sensor, EEG)
- Clearly stated methodology and application domain

Table 4 shows that highest number of research papers was published in conference and journals but symposium and workshop has no papers those are related to HCI.

All 22 papers have been fully researched to extract relevant data. To extract and store data, we use a predefined form that contains many attributes. Due

As shown in the table below, the **highest number of journal publications occurred between 2021**

to space limitations, this article doesn't involve in data extraction. Three researchers have participated in the verification and data extraction. All the papers, which were selected, have been qualitatively studied. In order to synthesise the data, the meta-analysis method is inappropriate. We have manually reviewed them and merged the extracted data. We found the problem from each and every paper and record it in the notebook. Table 3 lists the papers used to complete the survey in the next few years.

Table 3 Number of published papers in each year 2006–2025.

Year of Publication	Number of Paper Published
2006-2010	1
2011-2015	2
2016-2020	6
2021-2025	13

V. Survey results and discussion

Over the past decade, significant research has been conducted to explore hands-free Human-Computer Interaction (HCI) techniques using head movements, facial gestures, eye tracking, and related sensor-based approaches. Based on the gathered data (see publication and technique tables), it is evident that researchers have consistently explored various algorithmic and hardware approaches to improve cursor control systems, especially for users with physical impairments.

and 2025, reflecting a recent surge in interest. Early work (pre-2010) is minimal, indicating the novelty of this HCI subdomain.

Table 4 TSR-based work published in different years (2006–2025)

Venue	Year	2006-2010	2011-2015	2016-2020	2021-2025	Total
Conference		0	0	2	2	4
Journal		1	2	4	11	18
Workshop		0	0	0	0	0
Symposium		0	0	0	0	0
Total		1	2	6	13	22




Figure 3 Publication-based selection of articles

Research papers for various conferences vary. As indicated in Table 5, these conferences are quite well attended, but the IEEE is the most well-known conference that publishes research papers on human computer interface. While Table 5 also lists the names of other publications, one of them is the well-regarded Journal of Advance Research in Computer science and Engineering.

Table 5 Publication distribution

Publication	Type	Count
2022 International Conference on Sustainable Communication Systems (ICSCDS)	Conference	1
2017 IEEE Signal Processing in Medicine and Biology Symposium (SPMB)	Conference	1
International Journal of Advanced Research in Computer Science	Journal	1
ScienceDirect	Journal	1
International Journal of Early Childhood Special Education	Journal	1
Fourth Industrial Revolution Based Technology and Practices (ICFIRTP), International Conference on	Conference	1
International Research Journal of Engineering and Technology	Journal	1
International Research Journal of Engineering and Technology	Journal	1
Informatica	Journal	1
Sensors	Journal	1
International Journal for Research in Engineering Application & Management	Journal	1
Technical Disclosure Commons	Journal	1
UACEE International Journal of Computer Science and its Applications	Journal	1
Ijrasnet Journal For Research in Applied Science and Engineering Technology	Journal	1
Proceedings of TENCON 2018 - 2018 IEEE Region 10 Co	Conference	1

The key studies listed below were used to finish our survey on HCI. Table 6 includes the following three fields: reference, title, and venue, together with the year of publication and page numbers. One of these papers, titled ‘Performance Analysis of a Head and Eye Motion-Based

Control Interface for Assistive Robots’, was published in the MDPI journal. The other, titled ‘Virtual Hands: Real Time Keyboard, Desktop & Application Navigation using Gestures’, was published in the IEEE. Other than these two publications are based on experimental research with distinct recommended approaches.

Table 6 Primary studies selection

References	title	Venue
Khushal Sancheti et al.	Hands-free Cursor Control using Intuitive Head Movements and Cheek Muscle Twitches	TENCON'18
Vadde Veeresh	Human Computer Interaction based Head Controlled Mouse	MZUJHSS'24
Wahyu Rahmaniar	Touchless Head-Control (THC): Head Gesture Recognition for Cursor and Orientation Control	IEEE TNSRE'22
Hemraj Ashtankar	MOUSE CONTROL USING HEAD MOVEMENT	NN Publisher'15
Akshai P Sajeev	Cursor Control Using Head and Hand Movement	Technoscience Academy'16
Vaibhav Nangare	Controlling Mouse Motions Using Eye Blinks, Head Movements and Voice Recognition	IJSRR'16
G Tanusha	Enabling Cursor Control through Eye Movement using Hidden Markov Model	clareus Scientific'25
.Madan Venkat Sai	Facial-Expression Based Mouse Cursor Control for Physically Challenged Individuals: A Human Computer Interaction (HCI) Approach.	IRJET'23
Alberto J.Molina-Cantero	Controlling a Mouse Pointer with a Single-Channel EEG Sensor	MDPI Sensors'21
Mrs. Srilatha Puli	HUMAN COMPUTER INTERACTION BASED HEAD CONTROLLED MOUSE	INTJECSE'23
Aniket Kudale	Mouse Navigation Control Using Head Motion	IJARCS'12
Sashidhar R	Mouse Cusor Control Using Facial Movements - An HCI Application	IEEE ICSCDS'22

Saurabh Barve	A Portable Wireless Head Movement Controlled Human-Computer Interface for People with Disabilities	IJRASET'23	
Yashaswita bhoir	Hands-free Cursor Control	UACEE'24	
Jonathan Ray Bernal Castano	Cursor Control using Head Tracking and System Actions using Facial Gestures	Defensive series'25	Publications
Anurag Singh	COMPARATIVE STUDY OF HAAR AND ADABOOST ALGORITHMS FOR CURSOR CONTROL USING HEAD AND EYE MOVEMENT FOR DISABLES	IJREAM'17	
Sarah Stalljann	Performance Analysis of a Head and Eye Motion-Based Control Interface for Assistive Robots	MDPI Sensors'20	
Pradeep V	Fuzzy based Computing for Disabled using 3D Head Movement	Informatica'23	
G. Abhishek	Mouse Cursor Control Hands Free Using Deep Learning	IRJET'23	
Harshit Sharma	Virtual Hands: Real Time Keyboard, Desktop & Application Navigation using Gestures	IEEE ICFIRTP'22	
Chern-Sheng Lin	A novel device for head gesture measurement system in combination with eye-controlled human-machine interface	Elsevier OLE'06	
Ali heydarigorji	HEAD-MOUSE: A SIMPLE CURSOR CONTROLLER BASED ON OPTICAL MEASUREMENT OF HEAD TILT	IEEE SPMB'17	

Controlling the cursor through non-traditional input such as head movements, facial gestures, or brainwave patterns has emerged as a key area of interest in Human-Computer Interaction (HCI), especially for assistive technology. The growing demand for **hands-free interaction** has led

researchers to explore a range of algorithms and hardware—from simple webcams to EEG-based systems.

The exponential variation in sensor capabilities, computing

environments, and user-specific needs makes **robust cursor control design complex**. To address these challenges, researchers have proposed different models using computer vision, signal processing, machine learning, and wearable devices. The table below summarizes major

contributions in this area, highlighting the **technique used**, the **problem addressed**, and the **proposed solution**.

Table 7 Test suite reduction/test case reduction-based research work details.

Authors	Paper title	Technique used	Tools used	Domain
Khushal Sancheti et al.	Hands-free Cursor Control using Intuitive Head Movements and Cheek Muscle Twitches	Assistive Technology	hands-free HCI device	HCI
Vadde Veeresh	Human Computer Interaction based Head Controlled Mouse	Python	webcam	HCI
Wahyu Rahmانيar	Touchless Head-Control (THC): Head Gesture Recognition for Cursor and Orientation Control	Assistive technology	RGB camera	HCI
Hemraj Ashtankar	MOUSE CONTROL USING HEAD MOVEMENT	haar algorithm	C#	HCI
Akshai P Sajeev	Cursor Control Using Head and Hand Movement	OpenCV	webcam	HCI
Vaibhav Nangare	Controlling Mouse Motions Using Eye Blinks, Head Movements and Voice Recognition	Haar cascade	webcam	HCI
G Tanusha	Enabling Cursor Control through Eye Movement using Hidden Markov Model	Markov Model	webcam	HCI
Madan Venkat Sai	Facial-Expression Based Mouse Cursor Control for Physically Challenged Individuals: A Human Computer Interaction (HCI) Approach.	Raspberry Pi and OpenCV	webcam	HCI
Alberto J.Molina-Cantero	Controlling a Mouse Pointer with a Single-Channel EEG Sensor	electro-encephalography (EEG) signal	IR devices	HCI

Mrs. Puli	Srilatha	HUMAN COMPUTER INTERACTION BASED HEAD CONTROLLED MOUSE	machine learning with Python	webcam	HCI
Aniket Kudale		Mouse Navigation Control Using Head Motion	Perceptual User Interface	robot control	HCI
Sashidhar R		Mouse Cusor Control Using Facial Movements - An HCI Application	convolutional neural network	webcam	HCI
Saurabh Barve		A Portable Wireless Head Movement Controlled Human-Computer Interface for People with Disabilities	IR Sensor	webcam	HCI
Yashaswita bhoir		Hands-free Cursor Control	OpenCV	webcam	HCI
Jonathan Bernal	Ray Castano	Cursor Control using Head Tracking and System Actions using Facial Gestures	camera-frame extraction	webcam	HCI
Anurag Singh		COMPARATIVE STUDY OF HAAR AND ADABOOST ALGORITHMS FOR CURSOR CONTROL USING HEAD AND EYE MOVEMENT FOR DISABLES	OpenCV	webcam	HCI
Sarah Stalljann		Performance Analysis of a Head and Eye Motion-Based Control Interface for Assistive Robots	Magnetic Angular Rate Gravity (MARG)-sensor	MARG-sensor	HCI
Pradeep V		Fuzzy based Computing for Disabled using 3D Head Movement	Fuzzification	webcam	HCI
G. Abhishek		Mouse Cursor Control Hands Free Using Deep Learning	SVM and HOG algorithms	SD card	HCI
Harshit Sharma		Virtual Hands: Real Time Keyboard, Desktop & Application Navigation using Gestures	Open CV	webcam	HCI
Chern-Sheng Lin		A novel device for head gesture measurement system in combination	hidden Markov models	CCD camera	HCI

with eye-controlled human-machine (HMMs) interface

	HEAD-MOUSE: A SIMPLE			
	CURSOR CONTROLLER			
	BASED ON OPTICAL	brainwave		
Ali heydarigorji	MEASUREMENT OF HEAD TILT	(EEG) sensors	IR LED	HCI

VI. CONCLUSION AND FUTURE WORK

There is a need of a budget friendly , more accessible, and free hand gaze-tracking system marks a great step toward improving human-computer interaction for individuals with mobility impairments and for broader applications such as gaming, virtual reality, and assistive technology. By improving traditional processing techniques we can enhance this system effectively detects and tracks movements without relying on complex deep learning models budget friendly, privacy, and ease of implementation.

Through real-time head tracking and blink detection, the system provides an intuitive way for users to interact with a PC, reducing the dependency on conventional input devices like keyboards and mice. The One of the main advantages of our gaze-tracking system is that it is more affordable and accessible. Not like other advertised commercialized eye-tracking devices, which often require specialized hardware and extensive calibration, this system provides a viable alternative using readily available components. Furthermore, the focus one real-time processing and user adaptability ensures a flexible user experience users with respect to different environments.

Despite its successes, certain limitations remain. The system's accuracy depends on lighting conditions and camera resolution, which may affect tracking precision. In addition to this, head movements beyond a certain limit can affect gaze estimation. Noting these challenges are crucial for making the system even more Strong

,accessible and user can use effectively.

Future Enhancements:

To further enhance the system's capabilities and expand its potential applications, several improvements can be made in future iterations:

Future Enhancements:

To further enhance the system's capabilities and expand its potential applications, several improvements can be made in future iterations:

1. AI-Based Self-Learning for Automatic Calibration:

- Using machine learning techniques to operate the system to automatically adjust interaction based on user behavior.
- Minimizing the time limit required for traditional interaction and improve user-based accuracy.

2. Integration of Voice Commands & Gesture Recognition:

- Making a hybrid interaction system by incorporating gaze tracking and speech recognition.
- User-Friendly system that can take out maximum inputs by

collaborating voice commands and eye movements.

3. **Enhanced Cursor Movement & Response Time:**

- By mean of modifying the algorithms which are used to track the cursor that makes smoother and more flexible movement.
- Reducing delay by improving frame processing speed and making enhance gaze-to-screen mapping techniques.

4. **Expansion to Smartphones & Smart Home Devices:**

- Adapting the system for mobile devices to support hands-free navigation on smartphones and tablets.
- Integrating with smart home systems to enable eye-controlled automation of household appliances.

5. **Improved Environmental Adaptability:**

- Improved Adaptability to the Environment: o Improving the system's robustness so that it can function effectively in a variety of lighting conditions (such as dim environments or outdoor settings).
- Implementing adaptive thresholding techniques to dynamically adjust contrast levels for better eye detection.

6. **Support for Additional Accessibility**

Features:

- By adding more features like text-to-speech conversion which support users who have very limited movement.
- Creating user profiles that can be changed to fit the needs of each user and modifying interaction settings accordingly.

VII. References

- [1]. Sancheti, K., Suhaas, A., & Suresh, P. (2018, October). Hands-free cursor control using intuitive head movements and cheek muscle twitches. In *TENCON 2018-2018 IEEE Region 10 Conference* (pp. 0356-0361). IEEE.
- [2]. Veeresh, V., Ajay, P., Varma, N. B., Anusha, J., & Divija, L. Human Computer Interaction based Head Controlled Mouse.
- [3]. Rahmaniar, W., Ma'Arif, A., & Lin, T. L. (2022). Touchless head-control (thc): Head gesture recognition for cursor and orientation control. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 30, 1817-1828.
- [4]. Nangare, V., Samant, U., Rabha, S., & Rodge, P. R. (2014). Controlling mouse motions using eye blinks, head movements and voice recognition. *computer*, 3.
- [5]. Tanusha, G., Havirbhavi, P., & Ashwini, K. (2024, July). Enabling Cursor Control Through Eye Movement Using Hidden Markov Model. In *International Conference on Data Science and Network*

- Engineering* (pp. 81-94). Singapore: Springer Nature Singapore.
- [6]. Molina-Cantero, A. J., Castro-García, J. A., Gómez-Bravo, F., López-Ahumada, R., Jiménez-Naharro, R., & Berrazueta-Alvarado, S. (2021). Controlling a mouse pointer with a single-channel eeg sensor. *Sensors*, 21(16), 5481.
- [7]. Kudale, A., Laddha, V., Thakare, R., & Deshpande, L. (2012). Mouse Navigation Control Using Head Motion. *International*
- [8]. *Journal of Advanced Research in Computer Science*, 3(3).
- [9]. Shashidhar, R., Snehith, K., Abhishek, P. K., Abhishek, B. V., & Pavitha, N. (2022, April). Mouse Cursor Control Using Facial Movements-An HCI Application. In *2022 International Conference on Sustainable Computing and Data Communication Systems (ICSCDS)* (pp. 367-371). IEEE.
- [10]. Bernal Castano, J. R., Ota, A., Soto, E. A., Kersting, B., Dietz, A. L., Yan, Q., ... & Domergue, G. (2025). Cursor Control using Head Tracking and System Actions using Facial Gestures.
- [11]. Stalljann, S., Wöhle, L., Schäfer, J., & Gebhard, M. (2020). Performance analysis of a head and eye motion-based control interface for assistive robots. *Sensors*, 20(24), 7162.
- [12]. Pradeep, V. (2025). Fuzzy based Computing for Disabled using 3D Head Movement. *Informatica*, 49(15).
- [13]. Sharma, H., Saxena, R., Kumar, S., Saini, A., Saad, M., & Faraz, M. (2022, November). Virtual Hands: Real Time Keyboard, Desktop & Application Navigation using Gestures. In *2022 International Conference on Fourth Industrial Revolution Based Technology and Practices (ICFIRTP)* (pp. 262-267). IEEE.
- [14]. Lin, C. S., Ho, C. W., Chang, K. C., Hung, S. S., Shei, H. J., & Yeh, M. S. (2006). A novel device for head gesture measurement system in combination with eye-controlled human-machine interface. *Optics and Lasers in Engineering*, 44(6), 597-614.
- [15]. HeydariGorji, A., Safavi, S. M., Lee, C. T., & Chou, P. H. (2017, December). Head-mouse: A simple cursor controller based on optical measurement of head tilt. In *2017 IEEE Signal Processing in Medicine and Biology Symposium (SPMB)* (pp. 1-5). IEEE.

ORIGINALITY REPORT

4%

SIMILARITY
INDEX

2%

INTERNET SOURCES

0%

PUBLICATIONS

3%

STUDENT PAPERS

PRIMARY SOURCES

1

Submitted to Meerut Institute of Engineering & Technology

Student Paper

2%

2

titfees.com

Internet Source

<1%

3

Submitted to Liverpool John Moores University

Student Paper

<1%

4

researcherslinks.com

Internet Source

<1%

5

www.coursehero.com

Internet Source

<1%

6

studentsrepo.um.edu.my

Internet Source

<1%

7

soft386.com

Internet Source

<1%

<1%

NCAAF-CIEC - 2025



MEERUT
INSTITUTE OF
TECHNOLOGY



ACI Meerut Foundation



**NATIONAL CONFERENCE ON ADVANCES IN AGROTECH & FOOD PROCESSING, COMPUTATIONAL
INTELLIGENCE, ELECTRONICS & COMMUNICATION
(NCAAF-CIEC - 2025)**

CERTIFICATE

This is to Certify that Prof. / Dr. / Mr. / Ms. **Kunal Yadav** presented the paper titled
Graze Tracker in the National Conference on
Advances in Agrotech & Food Processing, Computational Intelligence, Electronics & Communication
(NCAAF-CIEC-2025), organized by Meerut Institute of Engineering & Technology, Meerut in association
with Computer Society of India on 7th - 8th March 2025.

Prof. (Dr.) S.K. Singh
Campus Director, MIET Meerut

Shri. Raja L. Kanchibhotla
National Secretary, CSI

Prof. (Dr.) Parma Nand
Chairman, CSI Ghaziabad Chapter





KUNAL YADAV <kunal.yadav.cse.2021@miet.ac.in>

Abstract Acceptance Notification for Paper Id:ICACIT2025/RCSY/012

1 message

ICACIT2025 <icacit2025titbpl@gmail.com>

Fri, May 9, 2025 at 4:01 PM

To: kunal.yadav.cse.2021@miet.ac.in

2nd International Conference on Advancements in Computational Intelligence Technologies (ICACIT2025)

Bentham Science Publisher Double Indexed (Scopus & Web of Science)*

Abstract Acceptance Notification

Dear Author,

Last Date of Camera ready Paper Submission on or before: 31st May 2025

Conference Date: 20-21 June 2025

Paper ID:	ICACIT2025/RCSY/012
Title:	Eye and Head Movement-based Cursor Control System: A Survey

It is our pleasure to inform you that your abstract identified above has been **ACCEPTED** for further processing in the proceeding of **International Conference on Advancements in Computational Intelligence Technologies (ICACIT2025)**. Therefore, you are required to submit your camera ready paper with payment of **Rupees 7500/-** in the Bank account given below:

Account Name	Technocrats Institute of Technology, Advance
Bank Name	ICICI Bank
Branch	Indrapuri Bhopal
Account NO.	028301001818
IFSC Code	ICIC0001188

on or before 31st May 2025 along with **Copyright Form** attached herewith on google form link given below-: <https://forms.gle/TMTUTYLjosYqV3JA6>

Website Link: <https://www.icacit2025titbpl.in/>

With Warm Regards

Dr. Bhagwati Charan Patel

Editor-in-Chief,

Contact no: +91-9752578501

***Only Quality Papers**

Disclaimer

Prospective authors should note that only original and previously unpublished research papers will be considered. Furthermore, simultaneous submissions (under consideration for publication elsewhere) are not acceptable.