

Integration & webhooks — send an event out, receive one in, replay a failed one

WHAT IT IS

The platform talks to the outside world in both directions. Every business event (registration, funding change, viva outcome, etc.) queues into the **outbox**, gets delivered to the right partner adapter, retried with backoff on failure. Every inbound webhook (funder confirms payment, HR confirms employment, etc.) lands on our endpoint, normalises into a business event, and a workflow reacts. In this chapter we watch an outbound event queue and deliver, receive an inbound webhook that updates Priya's arrangement, then simulate a failed delivery and replay it.

THE CLICKS

01 Open Integration

WHERE Sidebar → **Integration** (cable icon, ADMINISTRATION).

DO Show adapters and delivery report tiles at the top.

SEE Counts: ok / retrying / failed in the last 24 hours.

SAY *“Every partner is an adapter. Every message we send is in the outbox. Every message we receive is a row in the inbound log.”*

02 Watch an outbound event queue

WHERE On Priya's record (from earlier) → **Send registration notice to UKRI** button (or trigger by adjusting something on her funding).

DO Click. Back on Integration → **Outbox** tab.

SEE New row: event student . registered, target UKRI adapter, attempt 1, delivered at (timestamp).

SAY *“There it is. Between our click and the partner receiving it, the outbox handles delivery — retries on our side, not on the caller's.”*

03 Simulate an inbound webhook

WHERE Same page → **Inbound** tab → **Simulate webhook** (dev-only button).

DO Pick source UKRI, event payment . confirmed, entity Priya's arrangement, amount 1552. Send.

SEE Row appears in inbound log. A business event fires — one of Priya's stipend rows flips from "Due" to "Paid".

SAY *“Webhook → normalise → business event → workflow reacts. All visible.”*

04 Force a failed delivery, then replay

WHERE **Outbox** tab → **Simulate failure** on a queued row (dev-only).

DO Confirm. Watch the row turn amber "retrying".

SEE Retry timeline: attempts with backoff (1 min, 2 min, 4 min).

SAY *“Nothing is fire-and-forget. If a partner is down for two hours, we retry with backoff and land the message when they come back.”*

THE LINE

“Every message we send and receive is a first-class record — not a console log.”