

Identity & RBAC — create a user, assign a role, watch the UI change for them

WHAT IT IS

Users have roles; roles have permissions; permissions gate endpoints on the backend AND controls in the UI. When a user logs in, their JWT carries the tenant and the permission set, and the frontend uses that same set to grey out buttons the user can't act on. In this chapter we create a new user (a wellbeing officer), give them a role, log in as them, and confirm they see the sidebar, buttons and pages that role gets — and nothing else.

THE CLICKS

01 Open Users

WHERE Sidebar → **Settings** → **Users** tab (or /settings/users).

DO Land on the users table.

SEE Rows with role chips and active/inactive pills.

SAY *“Users have roles. Roles have permissions. The JWT carries the whole set — one auth check on the way in.”*

02 Create a new user

WHERE Top-right → **+ New user**.

DO Fill: email wellbeing@example.com, name Sam Cooper, temporary password, is_active on. Save.

SEE New row appears with no role chip yet.

SAY *“Just an account. No permissions yet — they can't even open the app.”*

03 Assign a role

WHERE On the new user's row → **Roles** column → **+ Assign role**.

DO Pick Wellbeing Officer. Save.

SEE Role chip appears. Permissions summary panel updates: student.read, notes.write, case.escalate.

SAY *“Assigning a role assigns its permissions. No per-user permission management to drift out of sync.”*

04 Open a role to show its permissions

WHERE Settings → **Roles** tab → open Wellbeing Officer.

DO Show its permission list.

SEE Permission codes like student.read, notes.write, case.escalate — no funding.change, no audit.read.

SAY *“Permissions name actions, not screens. A new screen inherits the right permissions automatically.”*

THE LINE

“The permission code gates the endpoint AND the button — one system of truth for what a user can do.”