


TITLE PAGE

- **Problem Statement ID** – [SIH1642](#)
- **Problem Statement Title** – AI/ML-Powered Weather Anomaly Detection, Monitoring, and Explainability Platform
- **Theme** – [Disaster Management & Smart Automation](#)
- **PS Category** – [Software](#)
- **Team ID** – [27113](#)
- **Team Name** – [ILLUMINATI](#)



Detailed Explanation of Proposed Solution

- **Context-Aware Baselines:** Replaces static thresholding (temp > 35°C) with empirical location- and season-specific baseline distributions (μ , σ , IQR) calculated from multi-year NOAA METAR & IMD station data.
- **Dual-Engine Detection Brain:** Combines standardized Z-score deviations ($Z = (X - \mu)/\sigma$) with an unsupervised Scikit-learn Isolation Forest on multivariable feature vectors.
- **Calibrated Anomaly Scoring:** Blends statistical and ML indicators into a continuous [0.00, 1.00] score across 4 operational severities: Normal, Watch, High, and Critical.
- **Automated Explainability Engine:** Quantifies feature contribution percentages (%) and generates human-readable meteorological diagnostic summaries for decision-makers.

How it Addresses the Problem?


- **Eliminates False Alarms:** Understands regional seasonality—35°C in Delhi in May is normal, whereas 35°C in Bengaluru or Shimla in January is an extreme anomaly. Eliminates alarm fatigue.
- **Catches Compound Extremes:** Detects concurrent moderate departures (heat + plunging pressure + surging humidity) that precede cyclones and cloudbursts before single thresholds trigger.
- **Sub-15ms Real-Time Inference:** In-memory O(1) monthly baseline lookup matrix and lightweight inference execute in <15ms, ideal for high-frequency automated weather stations (AWS).
- **Actionable Decision Support:** Replaces black-box percentages with transparent driver rankings, allowing NDMA/SDMA emergency teams to know immediately why an alert fired.

Innovation and Uniqueness of Solution

- **Dual-Engine Parametric + ML Fusion:** Integrates statistical parametric rigor with unsupervised tree isolation—zero manual heuristic tuning needed.
- **Transparent Feature Attribution:** Computes mathematical relative importance ($\text{Contrib}_i = (|Z_i| / \sum |Z_j|) \times 100\%$) paired with plain-language meteorological rationale.
- **Interactive "What-If" Studio:** Live dynamic parameter sliders allow disaster managers and judges to simulate extreme hypothetical conditions on the fly and inspect real-time severity shifts.
- **Physical Domain Sanity Verification:** Meteorological bounds filter (0-100% RH, 870-1085 hPa) rejects faulty sensor telemetry before triggering false emergency alarms.



TECHNICAL APPROACH & SYSTEM ARCHITECTURE



END-TO-END SYSTEM PIPELINE ARCHITECTURE

1. Data Ingestion & Sanitization Engine

NOAA ISD & METAR Automated Feeds → Physical Domain Bounds Validation (0-100% RH, 870-1085 hPa) → Cyclical sin/cos Time Coordinates & Rolling Features.

2. Historical Baseline Knowledge Store

Precomputed Location- & Month-Indexed Norms (μ , σ , Q25, Q75) cached in O(1) in-memory JSON matrix for <1ms sub-millisecond retrieval.

3. Dual-Engine Intelligence Brain

- Statistical Layer: Univariate Standardized Z-Scores $Z = (X - \mu) / \sigma$
- ML Layer: Scikit-learn Isolation Forest on multivariable feature vectors.

4. Calibrated Scoring & Explainability

Blended [0.00, 1.00] Anomaly Score → 4 Operational Severities (Normal / Watch / High / Critical) + Mathematical Contributor % Attribution.

5. Delivery & Visual User Interface

High-Throughput FastAPI REST Microservice (<15ms) → React Dashboard with Leaflet India Map & Interactive Live "What-If" Simulation Studio.

CORE ARCHITECTURAL COMPONENTS


- **Data Hygiene Engine:** Strict physical range filters discard bad sensor telemetry (-999°C, 500% RH) before scoring, preventing false alarms.
- **Baseline Matrix:** Precomputed location-month parameter store enables O(1) mathematical comparisons in under 1 millisecond.
- **Isolation Forest:** Tree ensemble isolates rare anomalous combinations in high-dimensional meteorological space.
- **Explainability Engine:** Dynamic mathematical attribution formula $\text{Contrib}_i = (|Z_i| / \sum |Z_j|) \times 100\%$ paired with plain-language diagnostic rationale.

TECHNOLOGY STACK & INTEGRATIONS

- **Machine Learning & AI:** Scikit-learn (Isolation Forest), NumPy, Pandas, SciPy, Joblib
- **Backend REST Framework:** FastAPI (Asynchronous), Pydantic v2, Uvicorn, SQLAlchemy
- **Frontend Dashboard:** React 18, Vite, Tailwind CSS, Lucide Icons, Recharts, Leaflet GIS
- **Data Feeds & Standards:** NOAA ISD / ICAO METAR Station Telemetry, JSON REST Endpoints



ANALYSIS OF THE FEASIBILITY OF THE IDEA



Technical and Operational Feasibility

- **Lightweight CPU Compute:** Algorithmic pipeline runs on commodity CPU servers with zero costly GPU requirements; inference takes <15ms per station.
- **Zero Sensor Capex:** 100% compatible with existing IMD and NOAA global METAR sensor networks—no costly custom sensors needed.
- **National Scalability:** Precomputed baseline lookups provide O(1) response times, scaling smoothly to 10,000+ national weather stations.

Potential Challenges and Risks

- **Sensor Telemetry Noise:** Hardware malfunctions transmitting corrupted data packets, outliers, or missing sensor parameters.
- **Climate Non-Stationarity:** Long-term decadal climate shifts altering historical seasonal distributions over time.
- **Microclimate Diversity:** Vast meteorological variance across India's distinct geographical zones (coastal, arid, alpine, plateau).

Strategies to Overcome Challenges

- **Physical Domain Sanitization:** Domain bounds filter and forward-fill imputation sanitize bad telemetry before scoring.
- **Dynamic Baseline Recalibration:** Rolling-window baseline updates continuously adapt to evolving climate norms.
- **Granular Partitioning:** Station- and month-indexed baseline matrices ensure localized thresholding.

DEVELOPMENT & DEPLOYMENT ROADMAP

- Phase 1: Ingestion & Sanitization**

Automated METAR/ISD parser, domain bounds sanity verification (0-100% RH, 870-1085 hPa), cyclic temporal encoding.
- Phase 2: Baseline Engine & ML Brain**


Location-month baseline matrix calculation (μ , σ , IQR), multivariable Isolation Forest training, model serialization.
- Phase 3: High-Speed REST API**

FastAPI microservices (<15ms latency), Pydantic v2 schemas, automated contributor ranking & explainability engine.
- Phase 4: Dashboard & Live Studio**

Interactive React dashboard, Leaflet India map, What-If prediction studio, simulated extreme weather drills.



IMPACT AND BENEFITS



MEASURABLE SOCIETAL & OPERATIONAL IMPACT

- **Disaster Preparedness:** Provides critical hours of advance warning before severe cloudbursts, heatwaves, and depressions strike vulnerable regions.
- **Agricultural Resilience:** Early detection of unseasonal precipitation and sudden thermal spikes protects crop yields for millions of farmers.
- **Aviation & Urban Safety:** Real-time runway and stormwater drainage telemetry alerts prevent airport delays and urban flash flooding.
- **Eliminates False Alarms:** Contextual baselines eliminate emergency alarm fatigue for civil defense and municipal authorities.

CORE BENEFITS OF THE SOLUTION

- **Social Benefit:** Saves human lives and reduces emergency displacement in flood-prone and heat-stressed districts.
- **Economic Benefit:** Mitigates multi-crore infrastructure and agricultural damages (\$3B+ annual extreme weather risk averted).
- **Operational Benefit:** Transparent diagnostic explanations enable targeted, immediate emergency resource allocation (pumps, NDRF).
- **Zero-Capex Scalability:** Zero sensor hardware cost; seamlessly interfaces with existing IMD and NOAA telemetry networks.

FOR INSTANCE: REAL-WORLD FIELD SCENARIO

1. Field Telemetry Observed (Bengaluru Airport AWS):

Date: September 10 | Temp: 37.0°C | Rainfall: 145.0mm | Pressure: 994.0 hPa | Humidity: 92% | Wind: 14.5 m/s

2. Historical Baseline Context (Bengaluru September Norm):

Historical Normal: Temp 27.1°C (±1.8) | Rain 18.2mm (±14.5) | Pressure 1008.0 hPa (±2.1) | Humidity 74.0%

3. AeroSense Dual-Engine Intelligence Output:

- Rainfall: +8.74σ (Deluge) | Temp: +5.50σ (Heat Spike) | Pressure: -6.67σ (Deep Depression)
- Calibrated Anomaly Score: 0.94 →  CRITICAL SEVERITY ALERT

4. Transparent Root-Cause Attribution (% Contributor Breakdown):

-  Rainfall: 52.4% contribution (+696% departure from September normal)
-  Temperature: 28.1% contribution (+9.9°C anomalous thermal surge)
-  Pressure: 19.5% contribution (-14.0 hPa dangerous barometric plunge)

5. Life-Saving Operational Outcome:

BBMP Municipal & SDRF response teams receive automated diagnostic alert in <15ms. High-capacity flood dewatering pumps and emergency boats are deployed to vulnerable low-lying zones 4 hours before severe flooding paralyzes the city.

[1] Liu, F. T., Ting, K. M., & Zhou, Z. H. (2008)***"Isolation Forest"***

IEEE International Conference on Data Mining (ICDM), pp. 413-422. Foundational algorithm for unsupervised high-dimensional anomaly isolation.

[2] India Meteorological Department (IMD)***"Climate Normals & Extreme Weather Event Criteria (1991–2020)"***

Ministry of Earth Sciences, Government of India. Official statistical baselines and threshold standards for heatwaves and depressions.

[3] World Meteorological Organization (WMO)***"Multi-Hazard Early Warning Systems & Compound Risk Assessment"***

WMO Guidelines No. 1155. Protocols for concurrent multi-variable meteorological hazard detection.

[4] NOAA & ICAO Standards***"Surface Weather METAR Reporting & ISD Database Manual"***

Federal Meteorological Handbook No. 1 (FMH-1) and NOAA National Centers for Environmental Information.

[5] Ribeiro, M. T., Singh, S., & Guestrin, C. (2016)***"“Why Should I Trust You?”: Explaining the Predictions of Any Classifier"***

ACM SIGKDD International Conference, pp. 1135-1144. Principles of transparent feature attribution in complex ML models.

[6] Pedregosa, F. et al. (2011)***"Scikit-learn: Machine Learning in Python"***

Journal of Machine Learning Research (JMLR), Vol. 12, pp. 2825-2830. Core ML engine powering high-performance Isolation Forest trees.

[7] Tiangolo, S. et al. (2023)***"FastAPI: High-Performance Asynchronous Python Web Framework"***

Production-grade microsecond API server powering typed Pydantic v2 schemas and real-time inference.

[8] National Disaster Management Authority (NDMA)***"National Guidelines on Management of Urban Flooding and Cyclones"***

Government of India. Operational Standard Operating Procedures for early warning alert dissemination.